7

8

9

12 13

15 16

Slope deformation, reservoir variation and meteorological data at the 2 Khoko landslide, Enguri hydroelectric basin (Georgia), during 2016-3 2019 4

Alessandro Tibaldi^{1*}, Federico Pasquaré Mariotto², Paolo Oppizzi³, Fabio Luca Bonali¹, Nino 5 Tsereteli⁴, Levan Mebonia⁵, Johni Chania⁵ 6

¹ Department of Earth and Environmental Sciences, University of Milan Bicocca, 20129 Milan, Italy

² Department of Human and Innovation Sciences, Insubria University, Como, Italy

³ Geolog.ch, Mendrisio, Switzerland 10 11

⁴ Institute of Geophysics, University of Tbilisi, Tbilisi, Georgia

⁵ Enguresi LtD Society, Georgia

14 *Corresponding Author: alessandro.tibaldi@unimib.it

17 Abstract

The Greater Caucasus mountain belt is characterized by deep valleys, steep slopes and frequent 18 seismic activity, the combination of which results in major landslide hazard. Along the eastern side 19 of the Enguri water reservoir lies the active Khoko landslide, whose head scarp zone affects the 20 important Jvari-Khaishi-Mestia road, one of the few connections with the interior of the Greater 21 Caucasus. Here, we present a database of measurement time series taken over a period of 4 years 22 (2016-2019) that enable to compare slope deformation with meteorological factors and man-induced 23 perturbations owing to variations in the water level of the reservoir. The monitoring system we used 24 is composed of two digital extensometers, placed within two artificial trenches excavated across the 25 landslide head scarp. The stations are equipped also with internal and near ground surface 26 thermometers. The data set is integrated by daily measurements of rainfall and lake level. The 27 monitoring system - the first installed in Georgia - was set up in the framework of a NATO-funded 28 project, aimed at assessing different types of geohazards affecting the Enguri artificial reservoir and 29 30 the related hydroelectrical plant. Our results indicate that the Khoko landslide displacements appear to be mainly controlled by variations in hydraulic load, in turn induced by lake level oscillations. 31 Rainfall variations might also have contributed, though this is not always evident for all the studied 32 period. The full databases are freely available online at DOI: 10.20366/unimib/unidata/SI384-1.1 33 34 (Tibaldi et al., 2020).

35

36 **1** Introduction

Landslides are widespread natural hazard sources, affecting most of the world's countries and capable 37 of causing serious economic losses. In fact, they can damage buildings, communication systems and 38

the overall environment. Moreover, these natural events are major cause of loss of life (Froude and 39 Petley, 2018). The monitoring of landslides is a necessary step to implement protective measures, as 40 it allows to recognize possible acceleration in slope deformation rate, alert residents or close road 41 communication systems, where needed. This type of monitoring is also of paramount importance for 42 assessing possible triggering factors (Casagli et al., 2009), determining the level of risk (Spiker and 43 Gori, 2003), and planning land use and risk management (Fell et al., 2005; Bertolini et al., 2005). 44 This activity can be of special relevance in case of complex situations, such as those affecting an 45 artificial water reservoir, where water variations can destabilize (or stabilize) the slopes overlooking 46 47 the basin. In such case, multiparameter data can be crosscut in order to look into possible correlations between lake level variations, meteorological conditions, and slope deformations, which in turn are 48 49 key to effectively managing the filling and emptying of the reservoir.

The database of slope deformation can be derived from a variety of possible monitoring tools, which 50 51 range from on-site instruments to remotely controlled ones. The formers include continuous or intermittent data collection, such as settlement gauges, inclinometers and piezometric groundwater 52 53 measurements (Liu and Wang, 2008). Surveys can be carried out by detecting surface movements of unstable areas through levels, theodolites, Electronic Distance Measurement, and total station GPS 54 measurements (Liu Shao-tang, 2006). Remote control systems include aerial or terrestrial 55 photogrammetry in the visible or radar ranges (Bitelli et al., 2004). Monitoring the distance between 56 two points across the main landslide head scarp is the most effective way to describe the 57 displacements within the landslide, at a site far away from its toe. This is particularly helpful in 58 assessing the susceptibility of the whole landslide body to variations in toe conditions: in fact, a 59 feedback at the head scarp helps to decipher the long range of these effects. 60

In November 2016, an international team of scientists, under the aegis of NATO, set about working 61 in the area of the Enguri artificial water reservoir, on the southwestern foothills of the Greater 62 Caucasus, Georgia (Fig. 1). During the first of several research missions, the team installed, for the 63 64 first time in Georgia, two digital extensometers across the head scarp of the major, active Khoko landslide, located along the eastern mountain slope overlooking the reservoir. The associated 65 66 hydroelectrical plant, built during the Soviet era (Fig. 1c), is responsible for about half of the energy supply to the country (Tibaldi et al. 2018). This monitoring activity is particularly relevant because 67 the study area is located in a region affected by widespread seismicity (Fig. 1a), associated with still 68 active mountain building processes, which have led to the formation of the Greater and Lesser 69 Caucasus, resulting from the continent-continent collision between the African-Arabian and 70 71 Eurasian plates (Reilinger 1997; 2006; Koçyigit et al. 2001; Pasquaré et al. 2011). Seismicity can produce earthquake with Ms of 6-7 (Tsereteli et al., 2016) and macroseismic intensities up to 10 72

(Varazanashvili et al., 2018), as a consequence of active compressional tectonics (Tsereteli et al., 2016; Tibaldi et al., 2017a, b, 2019). As broadly agreed upon in the scientific literature, there is a tight connection between active tectonic processes and the occurrence of landslides (e.g. Tibaldi et al. 2004, 2015; Tibaldi and Pasquaré, 2008; Pasquaré Mariotto and Tibaldi, 2016). As it is beyond doubt that, in the future, a seismic event will happen again in the area, the installed monitoring landslide system will be instrumental in quantitatively assessing the effects of ground shaking on slope deformation rate.

Last but not least, the Jvari-Khaishi-Mestia road cuts across the uppermost portion of the Khoko landslide, along a 2-km-long stretch, at an elevation of 700 m a.s.l. Several field surveys in the area enabled the team to assess the presence of developing cracks, shear planes, opening of holes, and an overall active deformation concentrated along 150-200-m-long road segments, which could pose serious threats to road traffic security. These fractured zones are being continuously repaired by way of asphalt refilling, with the purpose of preventing serious damage and road accidents.

We hereby provide and illustrate the database of measurements gathered by way of the integrated monitoring system installed at the Khoko landslide. The main goals of our research are to identify range and patterns of deformation, and assess possible relations between changes in water level at the artificial Enguri reservoir, meteorological factors (temperature and rain) and slope deformations. The analysis of these multi-temporal datasets is of broad interest, as it can provide a detailed framework for planning the most appropriate actions in the management of major water reservoirs aimed at energy production.



Figure 1. (a) Main historic and instrumental earthquake epicenters in the western Greater Caucasus; the
black rectangle shows the area of Figure (b). White lines are country borders; the main Quaternary faults (red
lines) are from Gulen et al. (2011) and Tsereteli et al. (2016). Reference system: WGS84 / geographic coordinates. (b)
DEM of the Enguri reservoir area, with dam location, © Google Maps. (c) Photo of the Enguri dam.

99

100 2 Site description

101 2.1 Quaternary geology and geomorphology

The study area is characterized by substrate rocks and widespread Quaternary deposits, which have been mapped thanks to a new geological survey, integrated with geological maps compiled prior to the creation of the artificial lake (Fig. 2). The studied slope is marked by landforms that are typical of recent/active gravitational deformation; the total surface area affected by slope instability, which is about 1.2 km², is characterized by debris deposits, colluvium deposits, alluvial deposits, ancient landslide deposits (Fig. 2) and fractured substrate rocks. Debris deposits are widespread in the lower parts of the mountain located in the southern sector of the study area, outside the landslide area. They can be observed also at the head scarp of the landslide. Colluvium deposits mantle the central part of the landslide body and the lowermost slope in the southwestern sector of the study area. Landslide deposits are widespread in the upper portion of the landslide body. Alluvial deposits are located along the trace of the old Enguri river, now below the artificial lake's level.

At an altitude of 720-740 m, a number of scarps can be noticed, facing westward and affecting the 113 Jvari-Khaishi-Mestia road (Figs. 2 and 3). The height of such scarps ranges from 20 m to 70 m. At 114 the foot of the scarps, the topography is either horizontal or gently dipping westward, suggesting a 115 possible uphill tilting of the slope (Fig. 3a). The asphalted surface of the road here is affected by 116 fissures, as wide as a few centimeters, and by westward-facing, 20-cm-high (in 2016) scarps (Fig. 117 118 3d). These structures are parallel to sub-parallel to the morphological high head scarps. As documented by Tibaldi et al. (2019), in the forest across the southern segment of the head scarps, tens 119 120 of meters long, and up to 3.8 m wide fissures were found. Some of the trees, with trunks of about 20 cm in diameter, grew inside the fissures, suggesting that the fissures have a long history, at least 121 122 dating back to several tens of years (Tibaldi et al., 2019).

Downhill from the head scarp, several changes of inclination affect the slope, resulting in a series of downhill-facing scarps. Most are oriented perpendicularly to the local slope dip and can be observed in the upper part of the slope. This suggests the possible presence of secondary landslide slip planes (Tibaldi et al., 2019). Besides, most of the studied slope is characterized by the presence of several tilted trees; moreover, locally all of the trunks are tilted, and this is another indicator of active slope deformation (Fig. 3c).

The arrangement of river streams, as shown Figure 2, is based on the present-day river network and 129 Soviet-era topographic maps compiled before the build-up of the water reservoir. In the slope section 130 131 above the present-day lake, the rivers mostly follow the average slope dip, according to a dendritic pattern. Below the present-day lake level, one single stream was draining the landslide area. Here, at 132 the toe of the slope, this single stream was running parallel to the main Enguri river but with a 133 northward, opposite flow (Tibaldi et al., 2019). This is an anomaly in the stream pattern that can be 134 linked to a disturbance in the average slope topography, suggesting a possible early bulging of the 135 landslide toe. 136



Figure 2. Geological and geomorphological map of the study area, modified after Tibaldi et al. (2019).
Location in Figure 1b.



Figure 3. (a) Oblique view of the studied landslide (© Google Earth); trench locations are shown.
(b) Photo of a segment of the landslide head scarp; it is worth noticing the flat-lying area at the foot
of the scarp, created by the uphill tilting of the slope during rotational movements of the landslide
block. House for scale (left hand side of the flat area). (c) Example of tilted trees along the landslide
slope. (d) Photo of the escarpments cutting the Jvari-Khaishi-Mestia road (white triangles),
representing the surface expression of active landslide slip planes.

150 **2.2 Substrate description**

Around the landslide area, Jurassic volcanic and terrigenous rocks and Cretaceous carbonate deposits 151 crop out (Fig. 2), generally dipping to the south. The inclination of the Cretaceous strata cropping out 152 around the Enguri dam is in the order of 60-70°, whereas the bedding attains a shallower dip 153 northward, becoming sub-horizontal toward the northern part of the reservoir. Below the carbonate 154 layers, Jurassic deposits can be observed, made of sandstones, tuffs, tuff-breccia and gypsum layers 155 that crop out locally along the southeastern slopes of the reservoir. In the landslide area, essentially 156 Jurassic and Quaternary deposits crop put. Here, most of the Jurassic rocks dip to the east, with slight 157 variations (Fig. 4b). Presently, gypsum is excavated from a small mine, for economic purposes. Near 158

the coast of the artificial lake, at the foot of the onshore section of the landslide, there are intenselydeformed gypsum rocks.

The complexity of the geometry of the head scarps as well as the morphology of the slope, and the 161 size of the whole unstable slope, suggest that the landslide slip surface is not unique and probably 162 there are different, partially superimposed slip planes. This interpretation is supported by the analysis 163 of the state of preservation of piezometers located in the landslide body. We checked the instruments 164 and noticed that most of the piezometers installed during 2015 across the landslide, are interrupted at 165 depths between 16 and 42 m (Table 1). Although the a priori hypothesis must be mentioned that these 166 interruptions may have been produced by infiltration of fine material into the piezometers, we made 167 the measurements in May 2017, only two years after their installation, thus the very recent age of the 168 169 piezometers suggests that these may be the depths where the piezometric logs are intersected by the sliding surfaces of active landslides. This is supported by the observation that close piezometers, 170 originally excavated down to different depths, are now interrupted at the same depth, such as BH3 171 and BH4 cut at -16 m, and BH1 and BH2 cut at -35-36 m. The fact that in general these ruptures are 172 173 located at different depths indicates the presence of different slip planes.

Other logs were drilled during the Soviet era to reconstruct the rock distribution in the substrate. An 174 175 analysis of the lithological characteristics of the logs shows that the intact substrate rock is located at deeper levels, in the order of several tens of meters. For example, logs 3261 and 3297 (drilled in 176 1966) (Fig. 4b) show the presence of clastic, unconsolidated deposits, rich in clay and locally gypsum 177 fragments, down to a depth of 57.5 m (log 3297), and/or clastic deposits with a sill to clay matrix 178 179 down to at least 61 m (log 3297) and at least 80 m (log 3261). Log 3291 (also drilled in 1966) shows the presence of clay and gypsum deposits down to a depth of 30 m, and of the substrate at greater 180 depths. The geological survey integrated with the observations of the logs and piezometers enabled 181 us to prepare the geological section of Figure 4b, which extends across the onshore landslide portion 182 and below the lake (Fig. 4a). The section indicates that the intact substrate rock is always deeper than 183 184 30 m, down to 80 m. In this section, we added the head scarps of slip planes as observed in the field (red lines), and the main slip surfaces (dashed black lines) as obtained by a numerical slope analysis 185 performed by Tibaldi et al. (2019). The analysis was carried out considering different levels of the 186 lake reservoir; in the section are represented: i) the deepest slip surface (corresponding to FS < 1) 187 among those obtained with a maximum of 510 m a.s.l. of the reservoir water level (this surface starts 188 at log BH4), ii) the deepest slip surface (corresponding to FS < 1) among those calculated with a 189 minimum of 430 m a.s.l. of the reservoir water level (this surface starts at log BH3), and iii) the 190 shallowest slip surface that is present in both scenarios of lake level. 191



194

Figure 4. (a) Trace (red dashed line) of the geological section and location (red dots) of the 195 piezometers described in Table 1. Black lines are major landslide scarps. (b) Geological section 196 across the slope facing the Enguri reservoir. Black columns represent locations and depth of logs 197 used to construct the cross section. Dashed black lines are the main potential slip surfaces calculated 198 through a static analysis by Tibaldi et al. (2019), red lines with arrows are landslide scarps surveyed 199 in the field. Data of the submerged part are derived from geological surveys made in the Soviet era, 200 201 before the construction of the dam.

203	Table 1. Characteristics of measured piezometers and water table depth; b.g.s. refers to depths
204	below ground surface.

	Site	Easting (dd.ddd)	Northing (dd.ddd)	Elevation (m)	Installed total depth	Measured depth to water (m b.g.s.)	Measured depth to bottom
					(m b.g.s.)		(m b.g.s.)
	BH1	42.049950	42.781550	566.6	45	7,4	35
	BH2	42.050650	42.782500	568.2	50	1,5	36
	BH3	42.049850	42.784583	587	32	1,3	16
	BH4	42.050583	42.784417	652.8	65	1,3	16
	BH5	42.052633	42.787150	679.7	50	0,5	42
	BH6	42.053017	42.779717	725.9	50	12,0	18
	BH7	42.055433	42.781700	721.3	50	5,8	49
	BH8	42.055883	42.786517	704	55	4,8	23
	BH9	42.051800	42.788767	702.6	51	0,2	37
	BH10	42.051800	42.790167	727.9	50	Broken	Broken

3 Methodology and instrumentation

207 In 2016, two trenches were excavated across the main head scarps of the Khoko landslide, separated by about 240 m. The location of the sites selected for trenching is indicated in Figure 3a, and these 208 locations were based upon the presence of clear indicators of active deformation on the road, at the 209 foot of the main landslide scarps. Each of the two trenches was suitable for hosting a horizontal, 210 digital extensometer (Wire Linear Potentiometric Transducer, SF500). The two trenches were opened 211 perpendicularly to the scarp strike, crossing the road at a high angle (Fig. 5a). The instrumentation 212 213 was placed within a protection system aimed at avoiding disturbance or damage from heavy load traffic (Figs. 5b-d). The opening of the trenches was performed in two stages, so as to enable vehicles 214 215 to drive through the area along alternating lanes. The protection of the measurement stations consists of a channel in reinforced concrete, buried down to a depth of at least 50 cm. 216

217 The instrument is composed of a wire, a digital meter, and a recorder system. The stainless steel wire changes its length based on the relative movements of the piercing points to which it is connected. 218 219 The wire was inserted into a pipe, laid down horizontally and protected with sand (Fig. 5c-d). At both ends, steel pipes were positioned, aimed at securing the measurement wire and the electronic 220 221 instrumentation. Each vertical tube was equipped with a steel cover and gasket. The two covers were 222 buried underneath a 15 cm-thick soil layer. These operations were made more difficult by the presence of a pavement in concrete beneath the present-day asphalt layer. The meter is a wire potentiometric 223 position transducer that turns a linear motion into a resistance variation. It is made of a precision 224 rotating potentiometer operated by the winding or unwinding stainless steel wire. 225

Due to the impossibility of transmitting the data directly to a computer at the Enguri dam premises or via internet (due to the remoteness of the site), the measurements have been stored in a digital recorder (data logger THEMIS-USB-GPRS) and downloaded on a 30-day basis. The system is connected to a set of insulated batteries with a life of 6 months.

Extensometer n. 1 was put in operation in November 2016, whereas the second extensometer began
 recording data in May 2017. The instruments include also an internal and external sensor of
 temperature - PT100.

The station for measuring the Enguri lake level is installed at an altitude of 360 m in the dam. It is made of a Multi-Channel Recorder RSG30 Ecograph T, by Endress+Hauser, using the Software ETU00xA, V2.02.xx. The data are transmitted in real-time to the dam administration and stored in local computers.

Rainfall amounts are recorded by a station, situated at an altitude of 540 m near the dam'sadministrative building. The station features the Davis Vantage Pro2 instrument, suitable for

measuring rainfall, wind speed, temperature and humidity, with data updated every 2.5 seconds. It comes with a self-emptying tipping spoon determining rainfall amounts in 0.2 mm increments, and is laser-calibrated for increasing accuracy. The data are transmitted in real-time to the dam administration and stored in local computers.

243



244

Figure 5. (a) Opening of trench n. 1. (b) Installation of the concrete protection for the extensometer.
(c) Section transversal to the extensometer system. (d) Longitudinal section of the extensometer
system. Location of the two measurement stations provided in Figure 3a.

- 248
- 249 **4 Results**

250 4.1 Extensometer data

Figure 6 shows the readings collected over a 35-month interval, between 4 November 2016 and 9 October 2019, by the extensioneter at station n. 1. The overall extension recorded during the 35-

month period is equal to 88.7 mm, corresponding to an average extension rate of 0.08 mm/day (that 253 is 30.8 mm/y). Extension peaked from 16 May 2017 to 8 August 2017, with a total extension of 52 254 mm, corresponding to an average rate of 0.61 mm/day. This documented acceleration in the 255 movement coincided with the opening of new fractures on the road surface at about 700 m of altitude, 256 i.e. 230 m above the average lake level of 470 m a.s.l. 257

From 3 October 2017, extension ceased until 16 January 2018. This date marks the beginning of 258 another period of slight extension, lasting until 6 March 2018. From this date on, another interval of 259 extension rate increase was recorded, although much less pronounced than the previous one. This 260 increase lasted until 22 May 2018, marked by a rate of 0.12 mm/day. From the end of May 2018 to 261 October 2019, extension was linear with a rate of 0.04 mm/day, with a data gap between 262 263 30/12/2018 and 13/8/2019 due to a technical problem. This slower, creep-like movement was 264



266

Figure 6. Graph showing the readings of the incremental extension (in mm), associated with 267 landslide surface displacement, recorded by station n.1 from November 2016 to October 2019. 268

269

Regarding extensometer n. 2, data are shown over a 28.5-month interval (from 18 May 2017 to 30 270 September 2019) (Fig. 7). Here, the total amount of extension was 19.14 mm, with an average 271 extension rate of 0.02 mm/day (that is 8.17 mm/y). From the beginning until 24 October 2017, there 272

was a steady slight extension, followed by a period of high deformation expressed, in the graph, by a line with an upward convexity, indicating firstly a strong increase and later on a gradual decrease in the extension rate. This period lasted until 27 February 2018 and was characterized by an average rate of 0.16 mm/day, followed by another increase for one month, and then by a steady extension until 15 November 2018. Thereafter, until 29 January 2019, a new increase in the extension rate was observed, after which extension ceased.

279



280

Figure 7. Graph showing the readings of the incremental extension (in mm), associated with
landslide surface displacement, and recorded from May 2017 to September 2019 by station n.2.

283

284 4.2 Meteorological data

The amount of rainfall shows important variations (Fig. 8). Rainy days are mostly characterized by amounts within 10-20 mm/day. Peaks of 40-50 mm/day were recorded on 7/9/17, 5/2/18, 12/2/18, 26/9/18, 23/5/20 and 18/6/20. Peaks between 51-60 mm/day occurred on 6/12/17, 5/3/18 and 1/12/19. The highest peaks, above 70 mm/day, took place on 22/10/18 and 25/7/19. Periods of particularly heavy rains were recorded from 19/1/18 to 12/5/18 and from 22/9/18 to 16/1/19. From middle April 2018 to 25 September 2018, there was a gap in the data due to technical problems. As regards temperatures (T), these show a double fluctuation (Fig. 9); the short-term fluctuation took

place within a frequency of 5-20 days, whereas the long-term fluctuation developed each 12 months.

At Trench 1, in the first period of observations, the T at the data logger, near the ground surface,

gradually decreased to 3° on 22/2/17, though there was a gap in data, due to a technical problem, from

mid- December 2017 to mid-February 2017. Then, T increased until it peaked to 22.9° on 15/8/17.

From this date until 2/2/18, there was a gradual decrease, until a minimum of 5.5° was reached. Then T increased again and reached a maximum of 22.4° on 10/8/18. T then decreased down to 0.9° on 27/12/18. At Trench 2 the variations of T were similar to Trench 1, although the absolute values were sometimes higher, in the order of 1°-2°.

300 The T of the wire inside the instrument recorded the same pattern of variations, although smoothed,

with T systematically higher, in the order of $3^{\circ}-4^{\circ}$ at Trench 1, and with a much smaller difference at

Trench 2 (Fig. 9). This different pattern can be due to the fact that in Trench 2 there is a greater circulation of water than in the other trench, and thus the temperature tends to be more balanced due to a better thermal conductivity of water than air.

305



Figure 8. Amount of rainfall recorded near the landslide, from 4 November 2016 to 30 June 2020.

308



309



Figure 9. Temperatures recorded at Trench 1 from November 2016 to December 2018, and at Trench 2 from May 2017 to September 2019. The grey line represents the variations in temperature of the extensometer wire, inside the instrument, whereas the orange line shows temperature variations at the data logger that is near the ground surface.

- 315
- 316
- 317

318 4.3 Lake level data

Since the beginning of our measurements (1 January 2017) until 20 February 2017, there was a 319 continuous emptying of the reservoir, the level of which dropped down to a minimum of 410 m a.s.l. 320 (Fig. 10). Thereafter, the reservoir was filled again, to a maximum of 510 m on 5 August 2017, 321 322 followed by a further increase on 12 September 2017, up to 511 m. From this date on, there was a decrease of the lake level until 29 February 2018, when it reached an altitude of 443 m. Then, it 323 increased again reaching the altitude of 510 m on 30 June 2018. Later on, a new period of level 324 decrease lasted until 31 March 2019, when lake level reached 414 m. Over the next month there was 325 326 an oscillation with an increase of 35 m followed by a decrease. From 23 April 2019, a lake level increase was recorded, which ended on 26 July 2019, reaching an altitude of 507 m. Thereafter, a 327 new period of lake level decrease took place, until 29 April 2020 when it reached 419 m. 328



330

329

Figure 10. Variations of the level of the Enguri artificial water reservoir from 1 January 2017 to 30
June 2020.

333

5 Discussion

5.1 Correlation of slope deformation - lake level - rainfall

Here, we briefly discuss all the data, which we have combined in the graphs of Figure 11, so as to provide a more immediate interpretation. In this graph we also report the rainfall cumulated per month, in order to better quantify its possible influence. At extensometer n. 1, the total amount of

extension has been 88.7 mm in 35 months, yielding an average extension rate of 0.08 mm/day. 339 Extension peaked from 16 May 2017 to 8 August 2017, with a total extension of 52 mm that 340 corresponds to a rate of 0.61 mm/day, about eight times the average extension rate during the whole 341 measurement period. This extension rate increase follows the almost complete drawdown of the lake 342 (which went down to the lowest level on 21 February 2017) and the ensuing period of lake level 343 infilling, with a 100-m water level increase. A delay of about one month can be recognized between 344 the lake level increase and the extension rate increase, but the shape and duration of the period of 345 extension increase mimics exactly the shape and duration of the lake infilling (segments between 346 347 arrows in Fig. 11), suggesting a strong correlation. Another interval of extensional rate increase, although much smoother than the previous one, is recognizable during a period after 6 March 2018, 348 349 at the same time as a 67-m increase of the water level. During the third period of lake filling and refilling, due to technical problems at the extension possible further rate variations were not 350 351 recorded. During periods of water level lowering, instead, the extension rate tends to decrease to the lowest values. 352

353 At extension rate values in the period 11/2016 - 4/2017, during which the extension curve is subhorizontal in spite of rainfall 354 355 variations. Similarly, there is no correlation between rain and extension when there is the strongest extension increase of 5/2017 - 8/2017, because this follows a period of low rain precipitations. On 356 the contrary, this extension rate increase perfectly matches, after one month, the lake level increase. 357 The other period of extension increase from 2/2018 to 5/2018 coincides with the second lake level 358 increase, but it follows also a period of rainfall intensification (11/2017-2/2018). We suggest that, in 359 this case, cumulated rainfall might have contributed to increasing the extension rate owing to water 360 infiltration into the slope, though this is masked by lake level increase and we do not have data on the 361 362 variation of water saturation in the landslide slope.

At extensometer n. 2, the total amount of extension was 19.14 mm in 28.5 months, with an average 363 364 extension rate of 0.02 mm/day. There is no correlation between the amount of rainfall and extension rate values in the period 5/2017 - 10/2017, during which the extension curve is subhorizontal in spite 365 366 of rainfall variations. Extension increased, from 31 October 2017 to 1 April 2018, to 0.13 mm/day, corresponding to a 5-month interval of increased deformation, in a much similar way as at 367 extensometer n. 1, over a three-month period. It is worth noting that the extension curves derived 368 from the two extensometers have a similar shape, but at extensometer n. 2 the curve is shifted onward 369 by four to six months. This period of extension increase coincides with the lake level decrease, but it 370 also coincides with a period of rainfall increase. We suggest that these accelerated movements at 371 372 extensometer n. 2 may have been triggered by the previous movements within the landslide sector

where extensometer n. 1 is located, as it will be highlighted in the following chapter, in possible combination with rain infiltration in the slope. At extensometer n. 2, the extension curve is still steep in the following period until 7/2018, which is coincident with a lake level increase, followed by a further extension rate increase until 1/2019, in correspondence of lake level decrease and strong rainfall.

As documented by Tibaldi et al. (2019), based on the analysis of the Quaternary geological deposits 378 of the area, and by the presence of the high head scarp, the landslide area had already been subject to 379 slope failure events during prehistoric times. As a consequence of this, the processes that have taken 380 381 place along and across the slope during lake level variations, have been affecting an already destabilized slope, which is expected to be more sensitive to variations of the conditions at its toe. In 382 383 general, the presence of artificial lakes can trigger possible seepage process accompanied by an increase in pore water pressure in the slope deposits, with the effect of reducing their shear strength. 384 385 At the same time, the presence of a water basin may lead to a stabilization of the submerged part of the slope (Paronuzzi et al., 2013). In transient conditions, lake filling or drawdown can trigger 386 387 landslides (Schuster, 1979; Kenney, 1992; Zhu et al., 2011). In a similar way to the Enguri case, preexisting, ancient landslides were reactivated during the filling of the water reservoir at the Włocławek 388 389 dam in Poland (Kaczmarek et al., 2015). This cause-effect relation is even more apparent, where bank-forming materials have a high permeability, like in the study area, in which the slope is mostly 390 made of debris and highly fractured materials; within highly permeable deposits, a reservoir level 391 392 increase can trigger a rapid reservoir-induced water inflow that reduces both the strength and the 393 factor of safety. This occurred, for example, at the October 1963 Vajont landslide in NE Italy: as documented by Paronuzzi et al. (2013), among the triggering factors for the disaster, a predominant 394 role was played by reservoir level increase, and by the presence of an already existing landslide. 395 Another example comes from the Byford Creek landslide, located above the Clyde artificial reservoir 396 in New Zealand, where lake filling produced a major increase in extension rate, followed by long-397 398 term creep movements (Macfarlane, 2009).

To summarize the above, our data show that, at least during the first period of extension increase at extensometer n. 1, the slope still has a high sensitivity to water infilling operations more than 40 years after the construction of the Enguri reservoir. The presence of highly-permeable deposits in the lower part of a slope, as is the case at the Khoko landslide, represents a key aspect to be considered for the assessment of hydrogeological hazard. In such a case, during reservoir level increase, the water pore pressure effects on shear strength prevail over the stabilizing and buttressing effects induced by the water body, resulting in an acceleration in slope movements. For the other periods of extension

increase, an effect of rainfall intensification cannot be excluded, whereas extensometer n. 2 may also 406 have reacted to deformation of the slope part where the other extensometer n. 1 is located. 407



Figure 11. Graphs showing the combination of all data collected at trench 1 (A) and trench 2 (B). 410 Note that rainfall is expressed as cumulated month precipitation. The arrows point to the segments 411 of the extension and lake level curves that show similar shape at short time distance. 412

413

5.2 Behaviour of the landslide and slip planes 414

The hypothesis introduced in the previous chapter proposes that during the first and greatest lake level 415 increase, there was an increment in water pore pressure within the slope with a consequent decrease 416 of the shear strength. This seems to have produced an increase in extension at the two trenches with 417

a time offset. Another possibility is that the lake level increase triggered slope deformation only at 418 the landslide sector where extensometer n. 1 is located, whereas the other landslide portion, where 419 extensometer n. 2 is located, initially remained stable but, later on, deformation was triggered also 420 there. The different patterns observed at the two trenches may be explained in terms of the fact that 421 they are located in two different sectors of the general landslide, which can move separately. The 422 possible presence of different sectors within the general landslide body is suggested by underground 423 data and by GPS data. Based on the results summarized in Figure 4, a number of possible slip planes 424 affect the landslide, from shallow to deeper ones. Moreover, the slip planes modeled through our 425 static analysis are of two types: slip planes that initiate at the head scarp and prolong downward to 426 the valley bottom (now covered by the lake), and slip planes that run from the head scarp to half of 427 the slope, reaching the present lake's coastline. The presence of multiple slip planes at different depths 428 is supported also by the documented ruptures of piezometers at different depths. These slip planes 429 430 clearly correspond to different portions of the landslide that might move, at least in part, autonomously from each other. GPS stations were installed in the upper part of the landslide and were 431 432 operational during most of the 2016-2019 observation period (Ospanov and Krivchenko, 2021). Four GPS stations are characterized by motion vectors with the same cumulated magnitude of movement 433 434 (160-183 mm) and the same orientation (the central four arrows in Fig. 12), whereas the other two GPS stations show different magnitude of movement (48 mm the GPS located west, and 80 mm the 435 GPS located east in Fig. 12) and different, opposite orientations. Based on these data and 436 geomorphological evidence, we suggest the possible presence of three main landslide sectors: two 437 438 corresponding to shallower landslides (A and B in Fig. 12) and one deeper (C in Fig. 12).

On the other hand, during the decrease of the lake level, extension increases at both trenches, as is the case, for instance, at the very beginning of 2018. This increase in extension might be due to the debuttressing of the slope toe associated with the emptying of the lake, resulting in a more widespread mobilization of the landslide and probable inception of slip along the deeper planes. As already suggested in the previous chapter, we cannot rule out the possibility that water infiltration due to periods of increased rainfall might also have contributed to increasing the extension rate.



Figure 12. Sketch of the possible different units that compose the general landslide onshore. The
green unit C corresponds to a deeper-seated slope deformation, whereas the orange (A) and the blue
(B) units are shallower bodies. White arrows represent GPS vectors collected by Ospanov and
Krivchenko (2021). Black lines are the main scarps affecting the slope.

451

452 6 Data availability

The databases showcased in this work are available for download from the UniData Repository 453 (Milan, Italy) at https://www.unidata.unimib.it/?indagine=deformation-and-meteorological-data-of-454 the-khoko-landslide-enguri-republic-of-georgia-2016-2020, DOI: 10.20366/unimib/unidata/SI384-455 1.1 (Tibaldi et al., 2020). The extension dataset is provided in two separate files, for Trench 1 and for 456 Trench 2, in tab format (extension data with frequency sampling of 60 min) together with air 457 458 temperature near the ground surface (frequency sampling of 60 min), and temperature of the extensometer wire in the interior of the instrument (frequency sampling of 60 min). At the same web 459 460 link is available the file of meteorological data (frequency sampling of 1 day) and lake level variations (frequency sampling each 5 days until 30/7/17 and then each one day). 461

462

463 7 Conclusions

At the major Khoko landslide, located on the eastern side of the Enguri artificial water reservoir, a 4-464 year-long campaign of measurement, by way of two digital extensometers, enables documenting the 465 activity of the mass movement, at a rate of 8.2 mm/yr to 30.8 mm/yr depending on the site of 466 measurement. During this period, we observed a correlation between the greatest, rapid infilling of 467 the lake and an increase in deformation rate of the slope. Deformation of the landslide at extensometer 468 n. 1, thus, appears to have been controlled by variations in hydraulic load, induced mainly by lake 469 oscillations. There is a systematic delay between man-induced lake oscillation and the response of 470 the landslide mass, quantifiable in about one month at extensometer n. 1. Increase of extension at 471 extensometer n. 2 may, in turn, have been triggered by the previous deformation that occurred in the 472 landslide sector where the other extensometer is located. These results, together with the different 473 slip rates at the two instruments, the presence of different slip planes at various depths, and the 474 different orientations and amounts of movement measured at GPS stations located in the landslide, 475 476 suggest that the Khoko landslide is composed of more than one unstable block, each of which can behave in a different way. Moreover, a possible correlation with heavier rainfall has been observed 477 478 for some periods of increased extension, and thus we cannot rule out the possible contribution of 479 water infiltration in the slope. This overall monitoring effort will help individuate possible future accelerations of deformation at the unstable mass overlooking the Enguri artificial reservoir. 480

481

486

488

482 Author contributions. AT coordinated the research and wrote most of the paper. PO designed and 483 maintained the sensor network. FPM and FB contributed to the geological and geomorphological 484 mapping of the landslide area. NT coordinated and contributed to collecting extension data at the 485 extensometers. LM and JC provided meteorological and lake level data.

487 **Competing interests.** The authors declare they have no conflict of interest.

Acknowledgements. We are indebted to the Ministry of Infrastructure of Georgia that helped us to
 obtain the permission to work along the Jvari-Khaishi-Mestia road. We also wish to thank four
 anonymous reviewers for their precious and helpful comments and suggestions.

Financial support. This research was conducted with the financial help from NATO project SfP G4934 "Georgia Hydropower Security", the International Lithosphere Program - Task Force II, and project 216758 of the Shota Rustaveli National Science Foundation. Satellite images were provided in the framework of the European Space Agency project n. 32309 "Active tectonics and seismic hazard of southwest Caucasus by remotely-sensed and seismological data".

- 498
- 499 **References**

Bertolini, G., Guida, M., & Pizziolo, M. (2005). Landslides in Emilia-Romagna region (Italy):
strategies for hazard assessment and risk management. Landslides, 2(4), 302-312.

Bitelli, G., Dubbini, M., & Zanutta, A. (2004). Terrestrial laser scanning and digital photogrammetry
techniques to monitor landslide bodies. International Archives of Photogrammetry, Remote Sensing
and Spatial Information Sciences, 35(B5), 246-251.

- 505 Casagli, N., Tibaldi, A., Merri, A., Del Ventisette, C., Apuani, T., Guerri, L., Fortuny-Guasch J. &
- Tarchi, D. (2009). Deformation of Stromboli Volcano (Italy) during the 2007 eruption revealed by
 radar interferometry, numerical modelling and structural geological field data. Journal of
 Volcanology and Geothermal Research, 182(3-4), 182-200.
- Fell, R., Ho, K. K., Lacasse, S., & Leroi, E. (2005). A framework for landslide risk assessment and
 management. Landslide risk management, 3-25.
- Froude, M. J. and Petley, D. N., 2018. Global fatal landslide occurrence from 2004 to 2016, Nat.
 Hazards Earth Syst. Sci., 18(8), 2161–2181, doi:10.5194/nhess-18-2161-2018.
- Gulen L., and EMME WP2 Team (2011). Active faults and seismic sources of the Middle East region:
 earthquake model of the Middle East (EMME) project. In: Abstracts of the AGU Fall Meeting, San
- 515 Francisco, California, 5-9 December 2011.
- Kaczmarek, H., Tyszkowski, S., and Banach, M., 2015. Landslide development at the shores of a
 dam reservoir (Włocławek, Poland), based on 40 years of research, Environmental Earth Sciences,
 74(5), 4247-4259.
- 519 Kenney, T.C., 1992. Slope stability in artificial reservoirs: influence of reservoir level, selected cases,
- and possible solutions, In: Semenza, E., Melidoro, G. (Eds.), Proceedings of the meeting on the 1963
- Vajont landslide, 17-19 September 1986, Ferrara, Cansiglio and Vajont. Grafica Ferrarese, Ferrara,
 Italy, 67-85.
- 522 Mary, 07-65.
 - Koçyigit, A., Yılmaz, A., Adamia, S., and Kuloshvili, S. (2001). Neotectonics of East Anatolia
 Plateau (Turkey) and Lesser Caucasus: Implication for transition from thrusting to strike-slip faulting.
 Geodin. Acta, 14, 177-195.
 - Liu Shao-tang 2006. Deformation measurements during the construction of large dam projects.
 Chinese Journal of Underground Space and Engineering 06(Z2): 1346–1348.
 - Liu, S. T., and Wang, Z. W. (2008). Choice of surveying methods for landslides monitoring. In
 Landslides and engineered slopes: from the past to the future. Proceedings of the tenth international
 symposium on landslides and engineered slopes. Taylor & Francis, Xi'an.
 - Macfarlane, D.F., 2009. Observations and predictions of the behaviour of large, slow-moving
 landslides in schist, Clyde Dam reservoir, New Zealand, Engineering Geology, 109(1-2), 5-15.
 - 533 Ospanov N. S., and Krivchenko, A. A., 2021. Description of a 2-Year, High-Resolution Geodetic
 - Monitoring of the Khoko Landslide, Enguri Reservoir, Georgia. In. F. L. Bonali et al. (eds.), Building
 Knowledge for Geohazard Assessment and Management in the Caucasus and other Orogenic
 Regions, NATO Science for Peace and Security Series C: Environmental Security, Springer Nature,
 - 537 301-316, doi.org/10.1007/978-94-024-2046-3_16.
 - Paronuzzi, P., Rigo, E., and Bolla, A., 2013. Influence of filling–drawdown cycles of the Vajont reservoir on Mt. Toc slope stability, Geomorphology, 191, 75-93.
 - Pasquaré Mariotto F., Tibaldi A. (2016). nversion kinematics at deep-seated gravity slope
 deformations revealed by trenching techniques. Nat. Hazards Earth Syst. Sci., 16, 663-674.
 - Pasquaré, F., Tormey, D., Vezzoli, L., Okrostsvaridze, A., Tutberidze, B. (2011). Mitigating the
 consequences of extreme events on strategic facilities: Evaluation of volcanic and seismic risk
 affecting the Caspian oil and gas pipelines in the Republic of Georgia. J. Environ. Man., 92, 1774–
 1782.
 - Reilinger, R. E., McClusky, S. C., Oral, M. B., King, R. W., Toksoz, M. N., Barka, A. A., Kinik, I.,
 Lenk, O., and Sanli, I. (1997). Global Positioning System measurements of present-day crustal
 - movements in the Arabia-Africa-Eurasia plate collision zone. J. Geophys. Res., 102, 9983–9999.

- 549 Reilinger, R. E., McClusky, S. C., Vernant, P., Lawrence, S., Ergintav, S., Cakmak, R., Ozener, H.,
- Kadirov, F., Guliev, I., Stepanian, R., Nadariya, M., Hahubia, G., Mahmoud, S., Sakr, K., Arrajehi,
 A., Paradissis, D., Al-Aydrus, A., Prilepin, M., Guseva, T., Evren, E., Dmirotsa, A., Filikov, S. V.,
- 552 Gomez, F., Al-Ghazzi, R., Karam, G. (2006). GPS constraints on continental deformation in the
- 553 Africa-Arabia-Eurasia continental collision zone and implications for the dynamics of plate
- interactions. J. Geophys. Res., 111, B05411, https://doi.org/10.1029/2005JB004051.
- Schuster, R.L., 1979. Reservoir-induced landslides, Bulletin of the International Association of
 Engineering Geology, 20, 8-15.
- Spiker, E. C., & Gori, P. (2003). National landslide hazards mitigation strategy, a framework for loss
 reduction (No. 1244). US Geological Survey.
- Tibaldi, A., Pasquaré F. (2008). Quaternary deformations along the "Engadine–Gruf tectonic system", Swiss–Italian border. J. Quaternary Sci., 23 475–487.
- Tibaldi, A., Rovida, A., Corazzato C. (2004). A giant deep-seated slope deformation in the Italian
 Alps studied by paleoseismological and morphometric techniques. Geomorphology, 58, 27–47.
- 563 Tibaldi, A., Corazzato, C., Rust, D., Bonali, F. L., Pasquaré Mariotto, F., Korzhenkov, A. M., Oppizzi
- P., and Bonzanigo, L. (2015). Tectonic and gravity-induced deformation along the active Talas-
- 565 Fergana Fault, Tien Shan, Kyrgyzstan. Tectonophysics, 657, 38–62.
- 566 Tibaldi, A., Alania, V., Bonali, F. L., Enukidze, O., Tsereteli, N., Kvavadze, N., Varazanashvili, O.
- (2017a). Active inversion tectonics, simple shear folding and back-thrusting at Rioni Basin, Georgia.
 J. Struct. Geol., 96, 35–53.
- Tibaldi, A., Russo, E., Bonali, F.L., Alania, V., Chabukiani, A., Enukidze, O., Tsereteli, N. (2017b).
 3-D anatomy of an active fault propagation fold: a multidisciplinary case study from Tsaishi (Georgia), western Caucasus. Tectonophysics, 717, 253–269.
- Tibaldi, A., Korzhenkov, A.M., Pasquaré Mariotto, F., Rust, D., Tsereteli, N. (2018). NATO and
 earth scientists: An ongoing collaboration to assess geohazards and contribute to societal security in
 Central Asia and the Caucasus. Episodes, 41, 193-205.
- Tibaldi, A., Oppizzi, P., Gierke, J. S., Oommen, T., Tsereteli, N., Gogoladze, Z. (2019). Landslides
 near Enguri dam (Caucasus, Georgia) and possible seismotectonic effects. Natural Hazards and Earth
 System Sciences, 19, 71.
- Tibaldi, A., Oppizzi, P., Bonali, F., Pasquarè Mariotto, F., Tsereteli, N., Mebonia, L., 2020.
 Deformation and meteorological data of the Khoko landslide, Enguri, Republic of Georgia. UniData
 Bicocca Data Archive, Milan. Study Number SI384, Data file version 1.0 DOI: 10.20366/unimib/unidata/SI384-1.1
- Tsereteli, N., Tibaldi, A., Alania, V., Gventsadse, A., Enukidze, O., Varazanashvili, O., Müller B. I.
 R. (2016). Active tectonics of central-western Caucasus, Georgia. Tectonophysics, 691, 328-344.
- Varazanashvili, O., Tsereteli, N., Bonali, F. L., Arabidze, V., Russo, E., Pasquaré Mariotto, F.,
 Gogoladze, Z., Tibaldi, A., Kvavadze, N., Oppizzi, P. (2018). GeoInt: the first macroseismic intensity
 database for the Republic of Georgia. J. Seismol., 1–43, https://doi.org/10.1007/s10950-017-9726-5.
- Zhu, D., Yan, E., Hu, G., and Lin, Y. 2011. Revival deformation mechanism of Hefeng Landslide in
 the Three Gorges Reservoir based on FLAC3D software, Procedia Engineering, 15, 2847-2851.