Rainfall erosivity mapping over mainland China based on high density hourly rainfall records

Tianyu Yue¹, Shuiqing Yin¹, Yun Xie¹, Bofu Yu², Baoyuan Liu¹

¹State Key Laboratory of Earth Surface Processes and Resource Ecology, Faculty of Geographical Science, Beijing Normal
 ⁵ University, Beijing, 100875, China
 ²Australian Rivers Institute, School of Engineering and Built Environment, Griffith University, Nathan, Queensland, QLD
 4111, Australia

Correspondence to: Shuiqing Yin (yinshuiqing@bnu.edu.cn)

- Abstract. Rainfall erosivity quantifies the effect of rainfall and runoff on the average rate of soil loss. Maps of rainfall erosivity 10 are needed for erosion assessment using the Universal Soil Loss Equation (USLE) and its successors. To improve erosivity maps that are currently available, hourly and daily rainfall data from 2,381 stations for the period 1951-2018 were used to 1-in-10-year event generate newthe R-factor and EI_{30} maps for mainland China (available at https://dx.doi.org/10.12275/bnu.clicia.rainfallerosivity.CN.001; Yue et al., 2020). One-min rRainfall data at a 1 min intervals from 62 stations, of which 18 had a record length > 29 years, were used to compute the 'true' rainfall erosivity against which
- 15 the new R-factor and 1-in-10-year EI₃₀ maps were assessed to quantify the improvement over the existing maps through cross-validation. The results showed that (1) <u>existingcurrentold</u> maps underestimated erosivity for most of the south-eastern part of China and overestimated for most of the western region; (2) the new R-factor map generated in this study had a median absolute relative error of 16% for the western region, compared to 162% for <u>the existingcurrentold</u> maps, and 18% for the rest of China. TAnd the new 1-in-10-year EI₃₀ map had a median absolute relative error of 14% for the central and eastern regions of China.
- 20 <u>compared to 21% for the existing map (-map accuracy was not evaluated for with excluding the western region where the 1-min data were limited) in length not evaluated due to data limitations, compared to 21% for currentold maps; (3) the R-factor map was improved mainly for the western region, because of an increase in the number of stations from 87 to 150 and temporal resolution from daily to hourly-data; (4) the benefit of increased station density for erosivity mapping is limited once the station density reached about 1 station per 10,000 km².</u>

25 1 Introduction

Soil erosion has been <u>the a</u> major threat to soil health, soil and river ecosystem services in many regions of the world (FAO, 2019a). Soil erosion has on-site impacts, such as the reduction of soil and water, the loss of soil nutrients, the decrease of land quality and food production, as well as off-site impacts, such as excessive sedimentation and water pollution.

Soil erosion models are tools to evaluate the rate of soil loss and can provide policymakers useful information for taking measures in soil and water conservation. The Universal Soil Loss Equation (USLE; Wischmeier and Smith, 1965; 1978) and the Revised USLE (RUSLE; Renard et al., 1997; USDA-ARS, 2013) have been widely used to estimate soil erosion in at least 109 countries over the past 40 years (Alewell et al., 2019). Rainfall erosivity is one of the factors in the USLE and RUSLE to represent the potential ability of rainfall and runoff to affect soil erosion.

In the USLE, erosivity of a rainfall event is identified as the EI value, also denoted as EI₃₀, which is the product of the total storm energy (E) and the maximum 30-min intensity (I₃₀) (Wischmeier, 1959). The erosivity factor (R-factor) in the USLE is the mean annual total EI values of all erosive events. To recognize interannual rainfall variability, rainfall data of long periods are required (Wischmeier and Smith, 1978). In the original isoerodent maps generated by Wischmeier and Smith (1965),

stations with rainfall data of at least 22 years were used.

To use the USLE, two additional input parameters are required. One is the seasonal distribution of the R-factor. To compute 40 the soil erodibility factor (K-factor) and cover-management factor (C-factor), seasonal distribution of EI (monthly, Wischmeier and Smith, 1965; or half-month percentage of EI, Wischmeier and Smith, 1978; Renard et al., 1997) is needed. In addition₁-1in-10-year storm EI value (called "10-yr EI" in Renard et al. (1997)) is needed to compute the support practice factor (P-factor) for the contour farming (Renard et al., 1997).

Kinetic energy generated by raindrops can be calculated based on raindrop disdrometer data and estimated based on breakpoint

45 or hyetograph data via KE-I equations, while I_{30} is expected to be prepared using breakpoint or hyetograph data with an observed interval ≤ 30 min. In the original study of event rainfall erosivity, the recording-rain-gauge chart was used (Wischmeier and Smith, 1958). However, these data were usually in shortage not only in the length but also in the spatial coverage.

Methods to estimate rainfall erosivity based on more readily available data have been developed widely, such as daily

- 50 (Richardson et al., 1983; Haith and Merrill, 1987; Sheridan et al., 1989; Selker et al., 1990; Bagarello and D'asaro, 1994; Yu and Rosewell, 1996b, c; Zhang et al., 2002; Capolongo et al., 2008; Angulomart nez and Beguer a, 2009; Xie et al., 2016), monthly (Arnoldus, 1977; Ferro et al., 1991; Renard and Freimund, 1994), and annual rainfall (Yu and Rosewell, 1996a; Ferrari et al., 2005; Bonilla and Vidal, 2011; Lee and Heo, 2011). Yin et al. (2015) evaluated a number of empirical models to estimate the R-factor using rainfall data of temporal resolutions from daily to average annual, and showed that the most accurate prediction was based on data at the highest temporal resolution.
- Once values of the erosivity factor is obtained with site observations, spatial interpolation methods can be used to estimate rainfall erosivity for sites without rainfall data based on surrounding sites to produce the erosivity maps or isoerodent maps. Local values of erosivity can be taken from these maps (Wischmeier and Smith, 1978). Rainfall erosivity maps can also be meaningful in various fields such as soil erosion, sediment yield, environment and ecology. In the original version of the USLE,
- 60 181 stations with breakpoint data plus 1,700 stations with annul averaged precipitation, 1-in-2-year 1-h rainfall amount and 1-in-2-year 24-h amount were used to generate the erosivity map for the eastern part of the US (Wischmeier and Smith, 1965). In the successor of the USLE (Wischmeier and Smith, 1978), the erosivity map for the western part of the US were generated based on 1-in-2-year, 6-h rainfall amount data (P) using the equation of R=27.38P^{2.17}. In Revised USLE (RUSLE), Renard et al. (1997) released the erosivity map using the same data as Wischmeier and Smith (1965) for the eastern part, and 60-min

- 65 rainfall data at 790 stations for the western part in the US. In RUSLE2, monthly erosivity maps based on 15-min data from 3,700 stations were generated (USDA-ARS, 2013). Erosvity maps based on spatial interpolation have been widely produced <u>globally-around the world</u> (Lu and Yu, 2002; Oliveira et al., 2012; Liu et al., 2013; Klik et al., 2015; Panagos et al., 2015a; Panagos et al., 2015b; Borrelli et al., 2016; Qin et al., 2016; Panagos et al., 2017; Sadeghi et al., 2017; Yin et al., 2019; Riquetti et al., 2020; Silva et al., 2020).
- 70 Recently, the Food and Agriculture Organization (FAO) proposed to produce a Global Soil Erosion Map (GSERmap) which encouraged scientists around the worldglobally from all over the world to generate their own national level maps making the most of the country knowledge, locally available methods and input data (FAO, 2019b). Rainfall erosivity maps for China were reviewed and relevant information on how they were generated are presented in Table 1, which shows that current R-factor maps for mainland China typically used readily-available daily rainfall data from about 500-800 stations (e.g. Zhang et al. 2019).
- 75 al., 2003; Liu et al., 2013; Qin et al., 2016; Yin et al., 2019; Liu et al., 2020), which were recorded by simple rain gauges. However, daily rainfall data are not enough to derive sub-daily intensities, which reduced the accuracy of estimated rainfall erosivity (Yin et al., 2015). One-minute data are the finest resolution data measured by automatic tipping bucket rain gauges we can obtain up to now, therefore they are one of the best datasets for deriving precipitation intensity and estimating rainfall erosivity. However, 62 stations with 1-min data collected were inadequate for the spatial interpolation of rainfall erosivity over
- 80 mainland China. Hourly data was believed to reflect the <u>temporal</u> variation of precipitation intensity better than daily data, which can be used to improve the estimation of at-site rainfall erosivity with precipitation observations. In addition, the increase of station density for the interpolation can better describe the spatial variation of rainfall erosivity and improve the estimation of rainfall erosivity for areas without observations together with the improvement of interpolation models and procedures. Therefore hourly and daily data for more than 2,000 stations of hourly and daily data were collected, together with the <u>1-min</u>
- 85 data for 62 of them tostations of 1 min data: (a) to-develop high-quality maps of the R-factor and 1-in-10-year EI₃₀ over the mainland China; (b) to-quantify the improvement of the new erosivity maps using precipitation data in a higher temporal resolution and from more weather stations, and better interpolation techniques compared to those used to generate erosivity maps that are currently available (Yin et al., 2019). New R-factor and 1-in-10-year EI₃₀ maps were produced in this study may improve the estimation of the soil loss in mainland China. The meaning and rationale of the study is to: (1) present and share high-precision maps of the R-factor and 1-in-10-year EI₃₀ over the mainland China with related Eearth system science communities; (2) provide some insights in the improvement of rainfall erosivity maps for other regions-over the world.

Table 1: Studies on the mapping of R-factor for or involving China

Study Area	Period	Temporal resolution of precipitation data	No. of stations for the study area	Interpolation method	Reference
China	1956-1984	Multi-year average of annual, maximum daily and maximum hourly	125	Unknown	Wang et al., 1996
Cinina	1971-1998	Daily	564	Ordinary Kriging	Zhang et al., 2003
	1960-2009	Daily	590	Ordinary Kriging	Liu et al., 2013

Study Area	Period	Temporal resolution of precipitation data	No. of stations -for the study area	Interpolation method	Reference
	1951-2010	Daily	756	Universal co-kriging with the aid of the elevation	Qin et al., 2016
	1961-2016 Daily 774		774	Ordinary Kriging	Yin et al., 2019 *
	1989-2010	Annual average	Gridded (0.5°×0.5°)		Naipal et al., 2015
Global	1998-2012 (in China)	Hourly and sub-hourly	3,625 (387 in China)	Gaussian Process Regression	Panagos et al., 2017
	1980-2017	Daily	30,000+ (~800 in China)	Thin-plate spline smoothing	Liu et al., 2020

*Map of event-1-in-10-year EI₃₀ in China was also generated.

95 2 Data and methods

2.1 Data

2.1.1 Rainfall data

Rainfall data were obtained at the daily, hourly and 1-min intervals.

Daily rainfall data from 2,381 meteorological stations over mainland China (Fig.1) over the period of 1951-2014 was measured with simple rain gauges. The data were collected and quality controlled by the National Meteorological Information Center of China Meteorological Administration. Daily data were collected all year around at these stations. -An effective year of the daily data was defined as a year when there was no missing data for one or more months in the year, and a missing month was defined as a month when there were more than 6 missing days in the month. The missing records in the effective years were input as zero. Based on this definition, the number of effective years ranged from 18 to 54 years. Most of the stations (88%) have data of more

105 than 50 years.

Hourly rainfall data from the same 2,381 stations with daily data (Fig. 1) were collected by siphon rain gauges or tipping bucket rain gauges and also quality controlled by the National Meteorological Information Center of China Meteorological Administration. The period of record for hourly data was from 1951 to 2018. The start year of the data varied because data collection commenced in different years. Observation was suspended in the snowy season, which resulted in some missing months

110 in winter for station in the northern part of China. There were 932 (39%) stations with data for the whole year, 550 (23%) stations from April to October and 421 (18%) stations from May to September.




Figure 1: Spatial distribution of stations with daily and hourly rainfall data and the length of the hourly data. Western, Mid-western, North_eastern and South_eastern regions were abbreviated as W, MW, NE and SE, respectively.

- 115 The missing data were handled according to the following criteria: (a) a day with more than 4 missing hours was defined as a missing day; (b) a month with more than 6 missing days was defined as a missing month; (c) a year with any missing month in its wet-season was defined as a missing year. The wet-season for stations north of 32 N was from May to September, and for those south of 32 N was from April to October. Missing years were removed and missing hours in the remaining effective years were input in two categories: (a) the missing period is followed by a non-zero record, which recorded the accumulated
- 120 rainfall amount in the missing period based on data notes; (b) the missing period is followed by zero. In the first case, each missing hour and the following non-zero hour were assigned the mean value of the non-zero record in these hours. For the second case, the missing hours were input as zero value.

Data at 1-min intervals were collected from 62 stations in mainland China (Fig. 2; and were used in Yue et al., 2020). Data from station No. 1-18 have effective years of 29-40 and cover the period of 1961(1971)-2000. Data from stations No. 19-62 have

125 effective years of 2-12 and cover the period of 2005-2016. The missing data in the effective years were assumed to be zero.




Figure 2: Spatial distribution of the stations with 1-min rainfall data

2.1.2 Published rainfall erosivity maps for China

The existing rainfall erosivity maps were collected and compared with the maps generated in this study. The current national R-factor map and 1-in-10-year EI₃₀ map are based on daily rainfall data only over the period from 1961 to 2016 from 774 stations in China (Yin et al., 2019). Another R-factor map shown in the discussion section of this study (Fig. 12) was based on the global rainfall erosivity dataset published by Joint Research Centre - European Soil Data Centre (ESDAC; Panagos et al., 2017).

2.2 Calculation of rainfall erosivity using 1-min, hourly and daily data

135 One-minute and hourly data were first separated into storm events. A continuous period of >= 6 hours of no-precipitation was used to separate storms (Wischmeier and Smith, 1978). Storms with the amount of >= 12 mm were defined as erosive events (Xie et al., 2000), and were used to calculate the rainfall erosivity factors.

The R-factor was calculated using Eqs. (1-3; USDA-ARS, 2013):

$$\mathbf{R} = \frac{1}{N} \sum_{i=1}^{N} \sum_{j=1}^{m} (EI_{30})_{ij},\tag{1}$$

140
$$\mathbf{E} = \sum_{r=1}^{l} (e_r \cdot P_r),$$
 (2)

$$e_r = 0.29[1 - 0.72exp(-0.082i_r)], \tag{3}$$

where EI_{30} (event rainfall erosivity, MJ mm ha⁻¹ h⁻¹) was the product of the total storm energy E (MJ ha⁻¹) and the maximum 30-min intensity I_{30} (mm h⁻¹); *i*=1, 2, ..., *N*, where *N* is the number of effective years, and *j* = 1, 2, ..., *m* means there are *m* erosive storm events in the *i*th year. For each storm event, rainfall was divided into *l* time intervals depending on the temporal

145 resolution of rainfall data. The total storm energy E was the sum of the energy for each time interval r, which was the unit energy e_r (energy per mm of rainfall, MJ ha⁻¹ mm⁻¹) multiplied by the rainfall amount P_r (mm) for each time interval. And i_r was the intensity (mm h⁻¹) of the r^{th} interval. I₃₀ (mm h⁻¹) was the maximum intensity over 30 consecutive minutes for each storm event. For hourly data, the I₃₀ was assumed to be the same as the maximum 1-hour intensity.

The 1-in-10-year EI₃₀ with 1-min or hourly data was obtained by fitting the generalized extreme value distribution (GEV). The 150 GEV distribution is a family of probability distributions of Gumbel, Fr échet and Weibull, and can be denoted as G (μ , σ , ξ) with parameters μ (location), σ (scale), and ξ (shape) (Coles, 2001):

$$G(z) = exp\left\{-\left[1+\xi\left(\frac{x-\mu}{\sigma}\right)\right]^{-1/\xi}\right\}\left\{x:1+\xi(x-\mu)/\sigma>0\right\},\tag{4}$$

where *x* was the annual maximum storm EI₃₀ (MJ mm ha⁻¹ h⁻¹), $-\infty < \mu < \infty$, $\sigma > 0$ and $-\infty < \xi < \infty$. The extreme quantiles of the annual maximum EI₃₀ (*X_p*) can be obtained by inverting Eq. (4):

155
$$X_{p} = \begin{cases} \mu - \frac{\sigma}{\xi} \left[1 - \{ -\log(1-p) \}^{-\xi} \right], for \xi \neq 0\\ \mu - \sigma \log\{ -\log(1-p) \}, for \xi = 0 \end{cases}$$
(5)

where $G(X_p) = 1 - p$. The 1-in-10-year EI₃₀, was the value of X_p when p was 1/10.

Parameter values for the GEV distribution were estimated using the L-moments method (Hosking, 1990).

Since hourly data aggregation of 1-min data and temporal variation in rainfall intensity is reduced, erosivity factor values computed with hourly data would be underestimated. Therefore, the R-factor and 1-in-10-year EI_{30} values computed with hourly data need to be adjusted by multiplying conversion factors of 1.871 and 1.489 (SI units), which were fitted by 1-min

160 hourly data need to be adjusted by multiplying conversion factors of 1.871 and 1.489 (SI units), which were fitted by 1-min rainfall data from 62 stations over mainland China (Yue et al., 2020). Erosivity factors from daily data were also obtained as described in Section 2.3. The R-factor using daily data was the mean annual daily erosivity. Daily rainfall erosivity was obtained by the following equation developed by Xie et al. (2016):

$$R_{daily} = \alpha P_{daily}^{1.7265},\tag{6}$$

165 where P_{daily} was the daily precipitation (\geq _10_mm), parameter α was 0.3937 in the warm season (May to September), and 0.3101 in the cold season (October to April).

The 1-in-10-year EI₃₀ using daily data was the 1-in-10-year daily erosivity adjusted with a conversion factor of 1.17 based on 1-min data from 18 stations in China (Yin et al., 2019). And the 1-in-10-year daily erosivity was obtained by calibrating the GEV distribution parameters as Eqs. (4-5) and the *x* in the functions was replaced by the annual maximum daily erosivity.

170 2.3 Rainfall erosivity for individual stations

Hourly data from 2,381 stations were used to produce the R-factor and the 1-in-10-year EI_{30} maps. Due to the annual variability of rainfall erosivity, stations with less than 22 effective years should be excluded (Wischmeier and Smith, 1978). However, 133 out of 150 stations in western China have less than 22 effective years (Fig. 1). Once these stations are removed, the western stations would be too sparse, which would reduce the interpolation accuracy of the rainfall erosivity map. To fill the gap due

175 to the insufficient number of years, daily rainfall data with longer periods of record were used to adjust erosivity values based on hourly data at the same station.

When the effective years of hourly data were not less than those of daily data for 871 out of 2,381 station, no adjustment of the R-factor was made. For the remaining 1,510 stations, the R-factor from hourly data was then adjusted by a relationship between the mean annual rainfall and the R-factor computed with hourly data as follows (Zhu and Yu, 2015):

180
$$R_{h_{adj}} = R_{hour} \left(\frac{P_d}{P_h}\right)^{1.481},$$
 (7)

where R_{h_adj} was the adjusted R-factor, R_{hour} was the estimated R-factor using hourly rainfall data, P_d was the mean annual precipitation of longer period (period of the daily data), and P_h was the mean annual precipitation of shorter period (period of the hourly data).

The exponent value of 1.481 was estimated based on a power relationship between the mean annual precipitation and the R-185 factor, and the latter was determined using 1-min and daily rainfall data of 35 stations in China (Fig. 2). All the daily and 1min data shared common periods of record of more than 10 years.

$$R_{min} = 0.156 \cdot P_m^{1.481},\tag{8}$$

where R_{min} was the R-factor (MJ mm ha⁻¹ h⁻¹ a⁻¹), and P_m was the mean annual precipitation (mm) using 1-min data. The coefficient of determination (R²) was 0.776 for Eq. (8).

190 The 1-in-10-year EI_{30} for the stations was adjusted in a similar fashion. No adjustment is needed for 89% of the stations where the effective years of the hourly data were not less than 22 years. For the remaining 11% of the station, the 1-in-10-year EI_{30} was estimated with daily data.

The record length was 22 to 29 years for 16(0.7%) stations, 30 to 39 years for 44(1.8%) stations, 40 to 49 years for 216(9.1%) stations, more than 50 years for 2,105(88.4%) stations when these adjustments were made.

195 2.4 Spatial interpolation and cross validation

The erosivity maps were obtained using the method of Universal Kriging with the annual rainfall as a co-variable. The mean annual rainfall was computed using daily rainfall data and was interpolated using Ordinary Kriging, and interpolated mean

annual rainfall was then used to interpolate the R-factor value using Universal Kriging. Both the mean annual precipitation and the erosivity factor were interpolated first for each of the four regions separately (Fig. 1; Li et al., 2014), and then combined

200

to obtain annual precipitation and erosivity maps over China. Buffer areas were used to avoid discontinuity along region boundaries (Li et al., 2014).

To evaluate the efficiency of interpolation models, a leave-one-out cross-validation method was applied to each region. Symmetric mean absolute percentage error (sMAPE) and Nash-Sutcliffe coefficient of efficiency (NSE) were used for the assessment:

205
$$\text{sMAPE} = \frac{1}{n} \sum_{i=1}^{n} \left| \frac{F_i - A_i}{(F_i + A_i)/2} \right| \times 100\%,$$
 (9)

NSE =
$$1 - \frac{\sum_{i=1}^{n} (F_i - A_i)^2}{\sum_{i=1}^{n} (A_i - \bar{A}_i)^2},$$
 (10)

where *n* was the number of stations, F_i was the estimated value through Universal Kriging for the ith station using data from surrounding stations, A_i was the observed value at the ith station.

2.5 Accuracy assessment of erosivity maps

210 To evaluate the accuracy of the new erosivity maps, erosivity factors using 1-min data were assumed as the "true" values to calculate relative errors since they are most accurate. For the R-factor, 1-min data for 62 stations were used. For 1-in-10-year EI₃₀, 1-min data for 18 stations (No._1-18; Fig. 2) of the 62 stations with more than 22 years were used. The cross-validation results for these stations from the interpolation of the two erosivity maps were compared to the values from 1-min data to calculate relative errors. Since the relative error tends to be high for stations with small R-factor values, the overall relative error for erosivity maps was represented with the median of the absolute value of the relative error for all the stations.

2.6 <u>The eEvaluation of on the improvement of the new maps comparing with the current maps</u><u>Comparative evaluation</u> <u>of the existing and new erosivity maps</u>

Existing Current erosivity mapping at the national scale in mainland China usually uses daily rainfall data from about 500-800 stations. The R-factor and 1-in-10-year EI_{30} maps of Yin et al. (2019) were taken as references to evaluate the improvement in


220 the accuracy of the erosivity maps generated in this study. Their relative errors were also obtained with 1-min data as described above.

New erosivity maps in this study followed a procedure that is different from Yin et al. (2019) mainly in three <u>aspectsareas</u>: (1) temporal resolution (hourly vs. daily); (2) number of stations (2,381 stations vs. 744 stations); (3) interpolation method (Universal Kriging vs. Ordinary Kriging).

225 To evaluate the effect of the temporal resolution on R-factor and 1-in-10-year EI₃₀, data from the same set of stations were used, and the only difference was that in temporal resolution. Hourly and daily rainfall data with the same period as the 1-min data at the 62 stations were used to calculate R-factors and 1-in-10-year EI₃₀ respectively. Erosivity factors from 1-min data are regarded as the most accurate values. The relative errors of erosivity factors from daily and hourly data were computed for evaluating accuracy.

- To evaluate the effect of station density, maps were compared with the only difference in the number of stations. Hourly data from 774 stations (the same set of stations in Yin et al., 2019) and from 2,381 stations (used in this study) were used to generate two separate erosivity maps. R-factor and 1-in-10-year EI₃₀ values were compared using <u>a</u>leave-one-out cross validation method region by region. The sMAPE was calculated for <u>the</u> accuracy assessment.
- To evaluate the effect of interpolation methods, maps were compared with the only difference in interpolation methods. 235 Ordinary Kriging and Universal Kriging with the mean annual rainfall as the co-variable were applied for the R-factor and 1in-10-year EI₃₀ computed using hourly data from 2,381 stations. Both interpolation methods were applied to each of four different regions as shown in Fig. 1 and leave-one-out cross validation results were compared. The sMAPE was calculated to evaluate the accuracy of interpolated values.

The framework of this study is shown in Fig. 3.






Figure <u>3</u>: Framework of this study

3 Results

3.1 Accuracy evaluation on erosivity maps

With erosivity maps from Yin et al. (2019) as references, this study shows improvement in the accuracy of estimated R-factor and 1-in-10-year EI_{30} (Fig. 4 and Fig.5; Table 2). The spatial distribution of the absolute relative errors of the maps from this study is shown in Fig. 6.

The R-factor values in the map of Yin et al. (2019) were underestimated where the R-factor was relatively high, and overestimated where the R-factor was relatively low. The improvement was particularly noticeable for western China (R < 1,000 MJ mm ha⁻¹ h⁻¹ a⁻¹) and the south-eastern coastal region (R > 10,000 MJ mm ha⁻¹ h⁻¹ a⁻¹).

- 1,000 MJ mm ha⁻¹ h⁻¹ a⁻¹) and the south_eastern coastal region (R > 10,000 MJ mm ha⁻¹ h⁻¹ a⁻¹). Relative errors of erosivity factors at the stations from the two maps are shown in Fig. 5 (a) and (b). Those with the relative error of more than 100% were all in the Western (W) or Mid-western (MW) region. The absolute relative error for the R-factor in this study and Yin et al. (2019) was no more than 19% for Mid-western (MW), North_eastern (NE) and South_eastern (SE) regions (Table 2). However, there are some extremely high relative error values in Yin's map which were found to be located
- 255 in the MW region (Fig. 5(a)). The median values of the absolute relative error in the R-factor in Western (W) region were

16.2% and 161.6%, respectively for this study and Yin et al. (2019). For 1-in-10-year EI₃₀, the median values of the absolute relative error were 13.5% for this study and 20.6% for Yin et al. (2019), indicating a smaller improvement-in the mid-western and eastern regions_compared to the improvemented infor the R-factor mapvalues (Table 2, (Fig. 5(b)). The relative errors of the 1-in-10-year EI₃₀ in this study concentrated in the range of -10% ~ +10%, whereas those in Yin et al. (2019) concentrated in the range of -25% ~ -15% and +15% ~ +25% (Fig. 5(c)). The western region was excluded in the evaluation of the 1-in-10-year EI₃₀ map because the record length of the 1-min data was too short to estimate 1-in-10-year event erosivity.




Figure 4: Comparison of the R-factors and 1-in-10-year EI₃₀ of the cross-validation values at the station of the maps and the values from 1-min data. The graphs on the left were the evaluation of the maps generated in this study, and those on the right were the evaluation of the maps generated by Yin et al. (2019)

260





Figure 5: The relative errors of the R-factor (a for region MW, NE, SE; b for region W) and 1-in-10-year EI₃₀ (c for region ME, NE, SE) maps

270 Table 2: The statistical characteristics of the absolute relative errors of the erosivity factors from the maps

	R-factor				1-in-10-year EI ₃₀		
	MW, NE, SE		W		MW, NE, SE		
	This study	Yin et al. (2019)	This study	Yin et al. (2019)	This study	Yin et al. (2019)	
25th percentile	9.3%	8.8%	11.4%	23.1%	5.1%	13.0%	
Median	17.8%	18.1%	16.2%	161.6%	13.5%	20.6%	
75th percentile	32.8%	34.4%	45.9%	292.3%	31.6%	31.3%	
Mean	21.0%	24.7%	28.7%	184.8%	18.6%	22.3%	



(a) R-factor

(b) 1-in-10-year EI₃₀

Figure 66: Spatial distribution of the absolute relative errors in the map of R-factor for 62 stations (a) and in the map of 1-in-10-275 vear EI₃₀ for 18 stations (b) with 1-min observation data.

3.2 Erosivity maps and improvements over previous studies


The R-factor in China generally decreased from the south-eastern part to the north-western-part of China (Fig. 7a), ranging from 0 to 25,300 MJ mm ha⁻¹ h⁻¹ a⁻¹. The map of 1-in-10-year EI₃₀ shows a similar spatial pattern as that of the R-factor (Fig. 7b), ranging from 0 to 11,246 MJ mm ha⁻¹ h⁻¹. Zero R-factor value is found at Turpan, Xinjiang Uygur Autonomous Region, where the mean annual rainfall is only 7.8 mm. The maximum of the R-factor (more than 20,000 MJ mm $ha^{-1} h^{-1} a^{-1}$) is found in the southern part of the Guangxi and Guangdong provinces, along the South China Sea, where the mean annual rainfall is more than 2,500 mm.

In addition to the overall trend, some local scale characteristics could be identified. For the R-factor map, in the western region, the wetter region in north-western China was located in the west of Dzungaria Basin and along the Tianshan Mountain, which

285

280

has been captured on the map. Some statistical characteristics of the new maps of the erosivity factors are shown in Table 3 based for soil erosion and hydrological zones in China (Fig. 8).







Figure 7: R-factor(a) and 1-in-10-year EI₃₀(b) over mainland China based on hourly data from 2381 stations




(a) Soil erosion zoning

290

Figure 8: Zoning schemes

Table 3: Statistical characteristics of R-factor and 1-in-10-year EI₃₀ in soil erosion and hydrological zonings

arametersFac tors	Zones	Mean	Std.	5 th -percentile	25 th -percentile	50 th -percentile	75 th -percentile	95 th -percentil
R-factor	Mainland China	2200	3147	47	147	645	3503	8208
(MJ mm ha ⁻¹	NWE	208	192	30	70	144	276	614
h ⁻¹ a ⁻¹)	NWL	896	431	263	549	875	1239	1562
	NR	3637	1443	935	2780	3747	4577	5946
	NEB	1483	766	671	1041	1311	1611	3284
	SWR	4226	2079	841	2610	4324	5503	8060
	SR	8294	3370	4918	6140	7311	9141	16544
	Continental	138	130	25	62	92	174	424
	Haihe	2437	1169	719	1218	2717	3489	4042
	Huaihe	4744	948	3197	4062	4653	5466	6310
	SongLiao	1405	765	623	952	1235	1553	3220
	Yellow	920	754	214	402	749	1205	2199
	Yangtze	3933	2535	215	1355	4508	6052	7666
	Southwest	1318	2043	132	265	316	940	5998
	Southeast	7069	1292	4964	6014	7192	7916	9110
	Pearl	10280	3967	4450	7697	9354	12731	17594
1-in-10-year	Mainland China	1040	1259	99	166	435	1766	3206
EI30	NWE	189	101	84	125	165	220	415
MJ mm ha ⁻¹	NWL	635	254	226	438	635	825	1031
h ⁻¹)	NR	2199	770	556	1860	2422	2717	3123
	NEB	948	449	444	669	867	1044	2055
	SWR	1706	766	439	1098	1689	2308	2952
	SR	3273	1418	1953	2375	2846	3512	6814
	Continental	164	84	80	114	140	193	363
	Haihe	1595	794	459	718	1773	2350	2626
	Huaihe	2706	394	1999	2465	2723	2957	3337
	SongLiao	902	453	422	604	823	1026	1974
	Yellow	627	472	182	293	525	813	1430
	Yangtze	1706	1039	167	711	1959	2551	3194
	Southwest	496	533	184	212	232	389	1701
	Southeast	2814	881	1781	2160	2550	3262	4570
	Pearl	3846	1822	1564	2604	3320	4698	7512






Figure 9: Differences of the R-factor(a) and the 1-in-10-year EI₃₀(b) comparing with the previous study

300 Comparing with the maps in Yin et al. (2019), the new maps can be quite different at some local areas (Fig. 9a and 9b). The R-factor in the new map was higher for most of the south_eastern region, and lower for most of the middle and western regions, especially for the south_western area (Fig. 9a). While the 1-in-10-year EI₃₀ map shows a similar pattern as that of R-factor, and <u>the</u> overestimation in Yin et al. (2019) seems to be more pronounced for some hilly regions in south-eastern China (Fig. 9b).

305 **3.3 Evaluation on the improvement of the erosivity maps**

3.3.1 Effect of data temporal resolution

Figure 10 shows that the R-factor estimated from daily data (Eq. 6) is underestimated when the R value is higher than 10,000 MJ mm ha⁻¹ h⁻¹ a⁻¹, and slightly overestimated when the value is lower than 2,000 MJ mm ha⁻¹ h⁻¹ a⁻¹. The model using hourly data improved the accuracy by about 11.1% (median value of the relative error) compared to that from daily data (Fig. 10).

310 Estimated 1-in-10-year EI_{30} would be underestimated using hourly and daily data, and the underestimation is greater if daily data were used (Fig. 10). Unlike the R-factor, the 1-in-10-year EI_{30} was not noticeably improved with an increase in the temporal resolution from daily to hourly data, probably due to the fact that the 1-in-10-year EI_{30} values estimated using daily data in Yin et al. (2019) had already been multiplied by a conversion factor of 1.17 to correct the 1-in-10-year daily erosivity to approximate the 1-in-10-year EI_{30} from 1-min data.






Figure 10: Comparison of the R-factor (upper) and 1-in-10-year EI₃₀ (lower) estimated from hourly (left) and daily (right) rainfall data at the stations

3.3.2 Effect of the station density

Interpolation for the Western (W) region had the lowest NSE value compared to other regions, which may be caused by the low station density (Fig. 1) and the lower spatial correlation of rainfall. The fitted semivariogram for the R-factor in the Western region had a range of 35 km, whereas the ranges for Mid-western (MW), North_eastern (NE) and South_eastern (SE) regions were 288, 261 and 1,235 km, respectively. A comparison of cross-validation between the two maps with different station densities shows that the interpolation with denser stations can improve the accuracy by $2.6\% \sim 15.4\%$ for the R-factor based on the sMAPE index, and by $1.4\% \sim 31.8\%$ for 1-

in-10-year EI₃₀ (Table 4) when the station density increased. The NSE can increase by 0.016-013 to 0.109-110 for the R-factor.
 For the 1-in-10-year EI₃₀, the NSE decreased by 0.001 to 0.096 for Western (W), Mid-western (MW) and South_eastern (SE) regions, and increased by 0.038 for the North_eastern (NE) region.

For the R-factor, in the Western (W) region, the station density doubled (increased from 36, 600 to 21,200 km² per station), and the accuracy improved by 15.4%, whereas the sMAPE of 53.3% was still high with this increase in station density. In the

- 330 Mid-western (MW) region, the station density tripled (from 13,900 to 4,800 km² 1 station) and the accuracy was improved by 11.1% based on the sMAPE index from 30.7% to 19.6%. In North_eastern (NE) and South_eastern (SE) regions, the station density tripled and quadrupled, respectively, and the accuracy increased about 2.5%. For 1-in-10-year EI₃₀, the improvement was 31.8% in the Western (W) region and 19.6% in the Mid-western (MW) region. The improvement was mainly in western regions, and the station density in the eastern China before the increase is enough to describe the spatial variation of the R-
- factor and the 1-in-10-year EI_{30} . It can be inferred that when there were less than about 10,000 km² per station, the increasing of the site density has little impact on the improvement of the interpolation (Fig. 11).

Table 4: Comparison of cross-validation results for erosivity maps interpolated based on data from 774 and 2381 stations

Region	No. of the stations	Density of the stations (10^3 km^2)	R-facto	R-factor		1-in-10-year EI ₃₀	
Region		1 station)	sMAPE	NSE	sMAPE	NSE	
W	87	36.6	68.7%	0.489	63.7%	0.389	
	150	21.2	53.3%	0.599	31.8%	0.293	
MW	161	13.9	30.7%	0.938	44.0%	0.887	
	471	4.8	19.6%	0.951	24.5%	0.886	
NE	214	11.0	12.4%	0.946	17.0%	0.857	
	690	3.4	9.7%	0.962	14.9%	0.895	
SE	389	6.6	10.9%	0.942	15.5%	0.844	
	1362	1.9	8.3%	0.959	14.0%	0.824	




Figure 11: Improvement of the interpolation with the increase of station density. Data were from the 774 and 2381 stations in the 4 different regions

3.3.3 Effect of the interpolation method

For the R-factor, cross-validation of Ordinary Kriging and Universal Kriging with the mean annual rainfall as the co-variable (Table 5) shows that UK improved the interpolation accuracy by 2.3%-9.0% (sMAPE) compared to OK. In the Western (W) region, the NSE increased from 0.285_(OK) to 0.599_(UK). Therefore, it is better to use UK instead of OK when generating
the R-factor map, especially in <u>the western China where the station density was-is</u> low. For the 1-in-10-year EI₃₀, UK improved the accuracy by 0.4%-9.7% (sMAPE). In the Western (W) region, the accuracy improved by 9.7% and the NSE increased from 0.094_(OK) to 0.293_(UK).

Table 5: Cross-validation results of the interpolated ion of R-factor and 1-in-10-year event EI30 using OK and UK

Decien	Interpolation method	R-facto	or	1-in-10-year EI ₃₀		
Region		sMAPE	NSE	sMAPE	NSE	
W	OK	62.3%	0.285	41.5%	0.094	
	UK	53.3%	0.599	31.8%	0.293	
MW	OK	24.8%	0.861	24.9%	0.838	
	UK	19.6%	0.951	24.5%	0.886	
NE	OK	12.0%	0.926	16.5%	0.865	

Design	Interpolation method	R-facto	r	1-in-10-year EI ₃₀	
Region		sMAPE	NSE	sMAPE	NSE
	UK	9.7%	0.962	14.9%	0.895
SE	ОК	11.2%	0.911	14.8%	0.844
	UK	8.3%	0.959	14.0%	0.824

4 Discussion

- This study has produced quality R-factor and 1-in-10-year EI₃₀ maps with hourly data from 2,381 stations over mainland China, which are shown to be a noticeable improvement over the maps that are currently available for China (Yin et al., 2019; Table 1). The improvement of the R-factor map over previously published R-factor maps can be attributed to the increase in the temporal resolution from daily to hourly data, whereas that of 1-in-10-year EI₃₀ map to the increase of the station density in comparison with those of Yin et al. (2019). There are mainly two reasons for this. First, 1-in-10-year event EI₃₀ values estimated from the daily data had already been adjusted to those from the 1-min data by multiplying a conversion factor of 1.17 (Yin et al., 2019), which resulted in no obvious improvement from the daily data to the hourly data. Second, the 1-in-10-year event EI₃₀ associated with extreme rainfall event intrinsically has a high spatial variability in comparison to the R-factor as shown in Table 4. The accuracy of spatially interpolated rainfall erosivity was more sensitive to the station density when the station density is low. Hence the improvement of the map of the 1-in-10-year EI₃₀ was mainly a result of the increase of the station density.
- Comparison with maps from a world map of rainfall erosivity was also undertaken recent study on global mapping international study was also attempted conducted for over mainland China. Panagos et al. (2017) produced developed a Global Rainfall Erosivity Database with hourly and sub-hourly rainfall data from 3,625 stations fromover 63 countries. This, which has provided a good data base could be used for the comparison of rainfall erosivity among different regions in the world in the 365 world. In their study, hourly data from 387 stations in China were used. Figure 12 shows that the R-factor for China extracted from Panagos et al. (2017) is systematically underestimated by about 30% for most areas in China, whereas overestimated in the Tibetan Plateau (cf. Fig. 7a). The reason for the underestimation may be that the R-factor calculated from hourly data applied a conversion factor (CF_{30}) that was developed from the R-factor values computed estimated by with 60-min data to those with by 30-min data in Panagos et al. (2015b), rather than using an adjustment factor based on breakpoint data (CF_{bp}) or 370 1-min data (CF₁). Breakpoint data, which were used forin the USLE (Wischmeier and Smith, 1965; 1978), and RUSLE (Renard et al., 1997) and 1-min data for this study. Previous research has shown the difference between CF_{30} and CF_{bp} (CF_1) can result in an underestimation of R-factor by about 20% (Auerswald et al., 2015; Yue et al., 2020). Table 6 shows that the relative error of the map from Panagos et al. (2017) could reduce by about 6.2% after multiplying by a conversion factor of 1.253, which was calibrated by Yue et al. (2020) for converting the R-factor from 30-min data to 1-min data. Because the 375 cross-validation values from the map of Panagos et al. (2017) were not available, values extracted from the maps were used instead to compare with the values from 1-min data at the 62 stations. Erosivity values based on the adjusted maps are still

generally underestimated. The reason could be that the equation for estimating the storm energy (E) from rainfall intensity used in Panagos et al. (2017) was from the RUSLE (Renard et al., 1997), and the equation is known to cause underestimation of the storm energy up to 10% in previous studies (Mcgregor et al., 1995; Yin et al., 2017). Because of this, the equation for

380


385

395

estimating the storm energy (E) in RUSLE (Renard et al., 1997) was then modified in RUSLE2 (USDA-ARS, 2013), which was adopted in this study.

The R-factor in the Tibetan Plateau varies from 0 to 12,326 MJ mm ha⁻¹ h⁻¹ a⁻¹ in Panagos et al. (2017), and from 5 to 4,442 MJ mm ha⁻¹ h⁻¹ a⁻¹ in this study. The former was derived from a Gaussian Process Regression (GPR) model and a number of monthly climate variables from the WorldClim database, such as the mean monthly precipitation, mean minimum, average and maximum monthly temperature. The GPR model was calibrated using the site-specific R-factor values and these climate variables, which may not applicable for sites at high altitude, as none of the observation sites was located in the Tibetan Plateau

region. The GPR model might be the main reason for the overestimation of the R-factor in the Tibetan Plateau where the R-factor was expected to be underestimated just like any other regions.



390 Figure 12: R-factor map for China extracted from Panagos et al. (2017) and the evaluation of the map based on 62 stations with 1min data.

Table 6: Comparison of the statistical characteristics of the relative errors of the R-factor extracted from the map generated in this study and extracted from Panagos et al. (2017) (original and adjusted). The adjusted map of Panagos et al. (2017) was the original map multiplying by a conversion factors of 1.253, which was calibrated by Yue et al. (2020) for converting the R-factor from 30-min data to 1-min data.

This studyPanagos et al. (2017)Panagos et al. (2017) adjusted25th percentile7.1%14.8%10.4%

25

	This study	Panagos et al. (2017)	Panagos et al. (2017) adjusted
Median	16.1%	28.3%	22.1%
75 th percentile	28.0%	40.5%	43.2%
Mean	20.1%	33.8%	33.1%

Although this study provides improved erosvity maps in comparison with previous studies, errors remain inevitably. The uncertainty of the estimated R-factor and 1-in-10-year erosivity values from this study mainly comes from the following sources: First, KE-I model for estimating Kinetic Energy (KE) from the precipitation Intensity (I). KE-I model used in this study is from RUSLE2 (USDA-ARS, 2013) and raindrop disdrometer observation data need to be collected to calibrate the KE-I relationship. Second, estimation of the erosivity factors was based on hourly data, and conversion factors were developed based on 1-min rainfall data from 62 stations (Fig. 2). Hourly data brings information loss in the estimation of instant precipitation intensity comparing with breakpoint data. Third, the adjustment of the R-factor for the stations with a small number of effective years (Eq. 7). This was based on a power function relationship (Eq. 8) between the mean annual precipitation and rainfall erosivity using 1-min and daily rainfall data of 35 stations. The magnitude of uncertainty mainly depends on the variation of annual rainfall erosivity. Forth, station distribution and density. In western China, the stations were sparsely and unevenly distributed, which affect the interpolation accuracy. Finally, spatial interpolation technique (Universal Kriging in this study) and the interpolation procedures, i.e. the division of regions before the interpolation and the mergence

410 of regions after the interpolation. These five sources of uncertainty need to be addressed for any further improvement in erosivity estimation in China.

5 Conclusions

420

This study has generated <u>newthe</u> R-factor and 1-in-10-year EI_{30} maps using hourly and daily rainfall data for the period from 1951 to 2018 from 2,381 stations over mainland China. The improvement in the accuracy of these erosivity maps over what

415 are currently available was evaluated <u>in terms of the median absolute relative error, and was explained</u> in terms of temporal resolution of <u>data used</u> the rainfall data, the station density, and the interpolation methods. The following conclusions can be drawn from this study:

(1) Comparing with the <u>existing</u>eurrent maps for the 62 reference sites, the <u>mean-median</u> absolute <u>relative</u> error in the R-factor map generated in this study was reduced from 18.1% to 17.8% <u>forin</u> the mid-western and eastern regions, <u>from</u> 161.6% to

16.2% form the western region, and for the 1-in-10-year EI₃₀, from 20.6% to 13.5% in the mid-western and eastern regions.

(2) The R factor and the 1 in 10 year EI_{30} -increased from the northwestern to the southeastern China. The R-factor value varieds from 0 to 25,300 MJ mm ha⁻¹ h⁻¹ a⁻¹, and the 1-in-10-year EI_{30} value wwas from 0 to 11,246 MJ mm ha⁻¹ h⁻¹. In comparison with Comparing with the existing previous maps, new maps of the R-factor and 1-in-10-year event EI_{30} show a clear decreasing trend from south-eastern to north-eastern China. in the new maps were larger for most of the southeastern area,

425 and smaller for most of the middle and western areas.

(3) Improvement inof the R-factor map can be mainly attributed to an increase in the temporal resolution from daily to hourly, whereas that $\frac{1}{10}$ whereas that $\frac{1}{10}$ whereas the function $\frac{1}{10}$ whereas the station density has led to an increase of the station density. The increased station density has led to an improved R-factor and 1-in-10-year EI_{30} maps for the western regions primarily. The benefit from an increased station density is limited once the station density reached about 1 station per 10,000 km². As for the interpolation method, Universal Kriging with the mean annual rainfall as the co-variable performed better than Ordinary Kriging for all regions, especially for the western regions with sparse weather stations.

430

Data availability

The Rainfall erosivity (R-factor 1-in-10-year EI_{30}) available maps and are at: https://dx.doi.org/10.12275/bnu.clicia.rainfallerosivity.CN.001 (Yue et al., 2020)

435 **Competing interests**

The authors declare that they have no conflict of interest.

Acknowledgments

This work was supported by National Key R&D Program (no.2018YFC0507006) and the National Natural Science Foundation of China (no. 41877068). We also would like to thank the high-performance computing support from the Center for Geodata and Analysis, Faculty of Geographical Science, Beijing Normal University [https://gda.bnu.edu.cn/]

440

References

Alewell, C., Borelli, P., Meusburger, K., and Panagos, P.: Using the USLE: Chances, challenges and limitations of soil erosion modelling, International soil and water conservation research, 203-225, doi:10.1016/j.iswcr.2019.05.004, 2019.

Angulomart nez, M. and Beguer a, S.: Estimating rainfall erosivity from daily precipitation records: A comparison among 445 methods using data from the Ebro Basin (NE Spain), Journal of Hydrology, 379, 111-121, doi:10.1016/j.jhydrol.2009.09.051, 2009.

Arnoldus, H.: Methodology used to determine the maximum potential average annual soil loss due to sheet and rill erosion in Morocco, FAO Soils Bulletins (FAO), 34, 39-51, 1977.

Auerswald, K., Fiener, P., Gomez, J. A., Govers, G., Quinton, J. N., and Strauss, P.: Comment on "Rainfall erosivity in Europe"

450 by Panagos et al. (Sci. Total Environ., 511, 801-814, 2015), Science of the Total Environment, 532, 849-852, doi:10.1016/j.scitotenv.2015.05.019, 2015.

Bagarello, V. and D'Asaro, F.: Estimating single storm erosion index, Transactions of the ASAE, 37, 785-791, doi:10.13031/2013.28141, 1994.

Bonilla, C. A. and Vidal, K. L.: Rainfall erosivity in central Chile, Journal of Hydrology, 410, 126-133, 455 doi:10.1016/j.jhydrol.2011.09.022, 2011.

Borrelli, P., Diodato, N., and Panagos, P.: Rainfall erosivity in Italy: a national scale spatio-temporal assessment, International Journal of Digital Earth, 9, 835-850, doi:10.1080/17538947.2016.1148203, 2016.

Capolongo, D., Diodato, N., Mannaerts, C., Piccarreta, M., and Strobl, R.: Analyzing temporal changes in climate erosivity using a simplified rainfall erosivity model in Basilicata (southern Italy), Journal of Hydrology, 356, 119-130, doi:10.1016/j.jhydrol.2008.04.002, 2008.

460

475

480

Coles, S. G.: An introduction to statistical modeling of extreme values. - springer, Series in Statistics, doi:10.1007/978-1-4471-3675-0, 2001.

FAO: Soil erosion: the greatest challenge to sustainable soil management, Rome, 2019a.

FAO: Outcome document of the Global Symposium on Soil Erosion, Rome, 2019b.

Ferrari, R., Pasqui, M., Bottai, L., Esposito, S., and Di Giuseppe, E.: Assessment of soil erosion estimate based on a high 465 temporal resolution rainfall dataset, Proc. 7th European Conference on Applications of Meteorology (ECAM), Utrecht, Netherlands, 12-16,

Ferro, V., Giordano, G., and Iovino, M.: Isoerosivity and erosion risk map for Sicily, Hydrological Sciences Journal, 36, 549-564, doi:10.1080/02626669109492543, 1991.

Haith, D. A. and Merrill, D. E.: Evaluation of a daily rainfall erosivity model, Transactions of the ASAE, 30, 0090-0093, 470 doi:10.13031/2013.30407, 1987.

Hosking, J. R. M.: L-Moments: Analysis and Estimation of Distributions Using Linear Combinations of Order Statistics, Journal of the Royal Statistical Society, 52, 105-124, doi:10.2307/2345653, 1990.

Klik, A., Haas, K., Dvorackova, A., and Fuller, I. C.: Spatial and temporal distribution of rainfall erosivity in New Zealand, Soil Research, 53, 887-901, doi:10.1071/SR14363, 2015.

Lee, J. H. and Heo, J. H.: Evaluation of Estimation Methods for Rainfall Erosivity Based on Annual Precipitation in Korea, Journal of Hydrology, 409, 30-48, doi:10.1016/j.jhydrol.2011.07.031, 2011.

Li, T., Zheng, X., Dai, Y., Yang, C., Chen, Z., Zhang, S., Wu, G., Wang, Z., Huang, C., and Shen, Y.: Mapping near-surface air temperature, pressure, relative humidity and wind speed over Mainland China with high spatiotemporal resolution, Advances in Atmospheric Sciences, 31, 1127-1135, doi:10.1007/s00376-014-3190-8, 2014.

Liu, B., Tao, H., and Song, C.: Temporal and spatial variations of rainfall erosivity in China during 1960 to 2009, Geographical Research, 32, 245-256, doi:10.11821/yj2013020005, 2013.

Liu, Y., Zhao, W., Liu, Y., and Pereira, P.: Global rainfall erosivity changes between 1980 and 2017 based on an erosivity model using daily precipitation data, CATENA, 194, 104768, doi:10.1016/j.catena.2020.104768, 2020.

485 Lu, H. and Yu, B.: Spatial and seasonal distribution of rainfall erosivity in Australia, Soil Research, 40, 887-901, doi:10.1071/SR01117, 2002.
 McGreeger K. Birgerer B. Benrie A. and Fester C.: Encipite index subset for mother Mississipping Transactions of the

McGregor, K., Bingner, R., Bowie, A., and Foster, G.: Erosivity index values for northern Mississippi, Transactions of the ASAE, 38, 1039-1047, doi:10.13031/2013.27921, 1995.

Naipal, V., Reick, C. H., Pongratz, J., and Van Oost, K.: Improving the global applicability of the RUSLE model-adjustment

490 of the topographical and rainfall erosivity factors, Geoscientific Model Development Discussions, 8, 2991-3035, doi:10.5194/gmdd-8-2991-2015, 2015.

Oliveira, P. T. S., Rodrigues, D. B. B., Sobrinho, T. A., Carvalho, D. F. D., and Panachuki, E.: Spatial variability of the rainfall erosive potential in the State of Mato Grosso do Sul, Brazil, Engenharia Agr cola, 32, 69-79, doi:10.1590/S0100-69162012000100008, 2012.

- Panagos, P., Ballabio, C., Borrelli, P., and Meusburger, K.: Spatio-temporal analysis of rainfall erosivity and erosivity density in Greece, Catena, 137, 161-172, doi:10.1016/j.catena.2015.09.015, 2015a.
 Panagos, P., Ballabio, C., Borrelli, P., Meusburger, K., Klik, A., Rousseva, S., Tadić, M. P., Michaelides, S., and Hrabal Ková, M.: Rainfall erosivity in Europe, Science of the Total Environment, 511, 801-814, doi:10.1016/j.scitotenv.2015.01.008, 2015b.
 Panagos, P., Borrelli, P., Meusburger, K., Yu, B., Klik, A., Lim, K. J., Yang, J. E., Ni, J., Miao, C., and Chattopadhyay, N.:
- 500 Global rainfall erosivity assessment based on high-temporal resolution rainfall records, Scientific Reports, 7, 4175, doi:10.1038/s41598-017-04282-8, 2017.

Qin, W., Guo, Q., Zuo, C., Shan, Z., Ma, L., and Sun, G.: Spatial distribution and temporal trends of rainfall erosivity in mainland China for 1951–2010, Catena, 147, 177-186, doi:10.1016/j.catena.2016.07.006, 2016.

- Renard, K. G. and Freimund, J. R.: Using monthly precipitation data to estimate the R-factor in the revised USLE, Journal of
 Hydrology, 157, 287-306, doi:10.1016/0022-1694(94)90110-4, 1994.
- Renard, K. G., Foster, G. R., Weesies, G. A., Mccool, D. K., and Yoder, D. C.: Predicting soil erosion by water: a guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE), Agricultural Handbook, USDA-Agricultural Research Service, Washington, D.C.1997.

Richardson, C., Foster, G., and Wright, D.: Estimation of erosion index from daily rainfall amount, Transactions of the ASAE, 26, 0153-0156, doi:10.13031/2013.33893, 1983.

Riquetti, N. B., Mello, C. R., Beskow, S., and Viola, M. R.: Rainfall erosivity in South America: Current patterns and future perspectives, Science of The Total Environment, 724, 138315, doi:10.1016/j.scitotenv.2020.138315, 2020. Sadeghi, S. H., Zabihi, M., Vafakhah, M., and Hazbavi, Z.: Spatiotemporal mapping of rainfall erosivity index for different return periods in Iran, Natural Hazards, 87, 35-56, doi:10.1007/s11069-017-2752-3, 2017.

510

515 Selker, J. S., Haith, D. A., and Reynolds, J. E.: Calibration and testing of a daily rainfall erosivity model, Transactions of the ASAE, 33, 1612, doi:10.13031/2013.31516, 1990.

Sheridan, J., Davis, F., Hester, M., and Knisel, W.: Seasonal distribution of rainfall erosivity in peninsular Florida, Transactions of the ASAE, 32, 1555-1560, doi:10.13031/2013.31189, 1989.

Silva, R. M., Santos, C., Silva, J., Silva, A. M., and Neto, R.: Spatial distribution and estimation of rainfall trends and erosivity

in the Epitácio Pessoa reservoir catchment, Para ba, Brazil, Natural Hazards: Journal of the International Society for the Prevention and Mitigation of Natural Hazards, 102, doi:10.1007/s11069-020-03926-9, 2020.
 USDA-ARS: Science documentation: Revised Universal Soil Loss Equation Version 2 (RUSLE2), USDA-Agricultural Research Service, Washington, D.C., 2013.

Wang, W., Jiao, J., Hao, X., Zhang, X., and Lu, X.: Distribution of rainfall erosivity R value in China, Journal of Soil Erosion 325 and Soil Conservation, 29-39, 1996.

Wischmeier, W. H.: A Rainfall Erosion Index for a Universal Soil-Loss Equation 1, Soil Science Society of America Journal, 23, 246-249, doi:10.2136/sssaj1959.03615995002300030027x, 1959.

Wischmeier, W. H. and Smith, D. D.: Rainfall energy and its relationship to soil loss, Trans. Am. Geophys. Union, 39, 285-291, doi:10.1029/tr039i002p00285, 1958.

530 Wischmeier, W. H. and Smith, D. D.: Predicting rainfall-erosion losses from cropland east of the Rocky Mountains: Guide for selection of practices for soil and water conservation, Agricultural Handbook, USDA-Agricultural Research Service, Washington, D.C.1965.

Wischmeier, W. H. and Smith, D. D.: Predicting rainfall erosion losses - a guide to conservation planning, Agricultural Handbook, USDA-Agricultural Research Service, Washington, D.C.1978.

535 Xie, Y., Liu, B. Y., and Zhang, W. B.: Study on standard of erosive rainfall, Journal of Soil & Water Conservation, 14, 6-11, doi:10.13870/j.cnki.stbcxb.2000.04.002, 2000.

Xie, Y., Yin, S. Q., Liu, B. Y., Nearing, M. A., and Zhao, Y.: Models for estimating daily rainfall erosivity in China, Journal of Hydrology, 535, 547-558, doi:10.1016/j.jhydrol.2016.02.020, 2016.

Yin, S., Nearing, M. A., Borrelli, P., and Xue, X.: Rainfall Erosivity: An Overview of Methodologies and Applications, Vadose
Zone Journal, 16, doi:10.2136/vzj2017.06.0131, 2017.

Yin, S., Xie, Y., Liu, B., and Nearing, M. A.: Rainfall erosivity estimation based on rainfall data collected over a range of temporal resolutions, Hydrology and Earth System Sciences, 19, 4965-4996, doi:10.5194/hess-19-4113-2015, 2015.

Yin, S., Xue, X., Yue, T., Xie, Y., and Gao, G.: Spatiotemporal distribution and return period of rainfall erosivity in China, Transactions of the Chinese Society of Agricultural Engineering, 35, 105-113, doi:10.11975/j.issn.1002-6819.2019.09.013,
2019.

Yu, B. and Rosewell, C. J.: Technical notes: a robust estimator of the R-factor for the universal soil loss equation, Transactions of the ASAE, 39, 559-561, doi:10.13031/2013.27535, 1996a.

Yu, B. and Rosewell, C. J.: Rainfall erosivity estimation using daily rainfall amounts for South Australia, Soil Research, 34, 721-733, doi:10.1071/SR9960721, 1996b.

550 Yu, B. and Rosewell, C. J.: An assessment of a daily rainfall erosivity model for New South Wales, Australian Journal of Soil Research, 34, 139-152, doi:10.1071/SR9960139, 1996c. Yue, T., Xie, Y., Yin, S., Yu, B., Miao, C., and Wang, W.: Effect of time resolution of rainfall measurements on the erosivity factor in the USLE in China, International Soil and Water Conservation Research, 8, 373-382, doi:10.1016/j.iswcr.2020.06.001, 2020.

555 Zhang, W., Xie, Y., and Liu, B.: Rainfall Erosivity Estimation Using Daily Rainfall Amounts, Scientia Geographica Sinica, 22, 53-56, doi:10.13249/j.cnki.sgs.2002.06.012, 2002.

Zhang, W., Xie, Y., and Liu, B.: Spatial distribution of rainfall erosivity in China, Journal of Mountain Science, 21, 33-40, doi:10.16089/j.cnki.1008-2786.2003.01.005, 2003.

Zhu, Z. and Yu, B.: Validation of Rainfall Erosivity Estimators for Mainland China, Transactions of the ASABE, 58, 61-71, doi:10.13031/trans.58.10451, 2015.

560