



# The cooperative IGS RT-GIMs: a global and accurate estimation of the ionospheric electron content distribution in real-time

Qi Liu<sup>1</sup>, Manuel Hernández-Pajares<sup>1,2</sup>, Heng Yang<sup>3,1</sup>, Enric Monte-Moreno<sup>4</sup>, David Roma-Dollase<sup>2</sup>, Alberto García-Rigo<sup>1,2</sup>, Zishen Li<sup>5</sup>, Ningbo Wang<sup>5</sup>, Denis Laurichesse<sup>6</sup>, Alexis Blot<sup>6</sup>, Qile Zhao<sup>7,8</sup>, Qiang Zhang<sup>7</sup>, André Hauschild<sup>9</sup>, Loukis Agrotis<sup>10</sup>, Martin Schmitz<sup>11</sup>, Gerhard Wübbena<sup>11</sup>, Andrea Stürze<sup>12</sup>, Andrzej Krankowski<sup>13</sup>, Stefan Schaer<sup>14,15</sup>, Joachim Feltens<sup>16</sup>, Attila Komjathy<sup>17</sup>, and Reza Ghoddousi-Fard<sup>18</sup>

<sup>1</sup>Universitat Politècnica de Catalunya (UPC-IonSAT), Barcelona, Spain.

<sup>2</sup>Institut d'Estudis Espacials de Catalunya (IEEC), Barcelona, Spain.

<sup>3</sup>School of Electronic Information and Engineering, Yangtze Normal University, 408100 Chongqing, China.

<sup>4</sup>Department of Signal Theory and Communications, TALP, Universitat Politècnica de Catalunya, 08034 Barcelona, Spain.

<sup>5</sup>Aerospace Information Research Institute (AIR), Chinese Academy of Sciences (CAS), Beijing, China.

<sup>6</sup>Centre National d'Etudes Spatiales, Toulouse, France.

<sup>7</sup>GNSS Research Center, Wuhan University, No. 129 Luoyu Road, Wuhan 430079, China.

<sup>8</sup>Collaborative Innovation Center of Earth and Space Science, Wuhan University, No. 129 Luoyu Road, Wuhan 430079, China.

<sup>9</sup>German Aerospace Center (DLR), German Space Operations Center (GSOC), 82234 Wessling, Germany.

<sup>10</sup>European Space Operations Center, European Space Agency, Darmstadt, Germany.

<sup>11</sup>Geo++ GmbH, Steinriede 8, 30827 Garbsen, Germany.

<sup>12</sup>BKG, Federal Agency for Cartography and Geodesy, Frankfurt, Germany.

<sup>13</sup>Space Radio-Diagnostics Research Centre, University of Warmia and Mazury in Olsztyn, 10-719 Olsztyn, Poland.

<sup>14</sup>Astronomical Institute of the University of Bern, Sidlerstrasse 5, Bern 3012, Switzerland.

<sup>15</sup>Federal Office of Topography (swisstopo), Wabern, Switzerland.

<sup>16</sup>Navigation Support Office, Telespazio Germany GmbH c/o European Space Agency/European Space Operations Centre, Robert-Bosch-Strasse 5, 64293 Darmstadt, Germany

<sup>17</sup>Near Earth Tracking Systems Group (335S), NASA - Jet Propulsion Laboratory, California Institute of Technology, 4800 Oak Grove Drive, M/S 138-317, Pasadena, CA 91109, USA.

<sup>18</sup>Canadian Geodetic Survey, Natural Resources Canada, Ottawa, Canada.

**Correspondence:** Manuel Hernández-Pajares (manuel.hernandez@upc.edu)

**Abstract.** The Real-Time Working Group (RTWG) of the International GNSS Service (IGS) is dedicated to providing high-quality data, high-accuracy products for Global Navigation Satellite System (GNSS) positioning, navigation, timing, and Earth observations. As one part of real-time products, the IGS combined Real-Time Global Ionosphere Map (RT-GIM) has been generated by the real-time weighting of the RT-GIMs from IGS real-time ionosphere centers including the Chinese Academy of Sciences (CAS), Centre National d'Etudes Spatiales (CNES), Universitat Politècnica de Catalunya (UPC), and Wuhan University (WHU). The performance of global Vertical Total Electron Content (VTEC) representation in all of the RT-GIMs has been assessed by VTEC from Jason3-altimeter during one month over oceans and dSTEC-GPS technique with 2-day observations over continental regions. According to the Jason3-VTEC and dSTEC-GPS assessment, the real-time weighting technique is sensitive to the accuracy of RT-GIMs. Compared with the performance of post-processed rapid Global Ionosphere



10 Maps (GIMs) and IGS combined final GIM (igsf) during the testing period, the accuracy of UPC RT-GIM (after the transition  
of interpolation technique) and IGS combined RT-GIM (IRTG) is equivalent to the rapid GIMs and reaches around 2.7 and  
3.0 TECU (TEC Unit,  $10^{16} \text{eI/m}^2$ ) over oceans and continental regions, respectively. The accuracy of CAS RT-GIM and CNES  
RT-GIM is slightly worse than the rapid GIMs, while WHU RT-GIM requires a further upgrade to obtain similar performance.  
In addition, the strong response to the recent geomagnetic storms has been found in the Global Electron Content (GEC) of  
15 IGS RT-GIMs (especially UPC RT-GIM and IGS combined RT-GIM). The IGS RT-GIMs turn out to be reliable sources of  
real-time global VTEC information and have great potential for real-time applications including range error correction for  
transionospheric radio signals (such as GNSS positioning, search and rescue, air traffic, radar altimetry, and radioastronomy),  
the monitoring of space weather (such as geomagnetic and ionospheric storms, ionospheric disturbance) and detection of  
natural hazards on a global scale (such as hurricanes/typhoons, ionospheric anomalies associated with earthquakes). All the IGS  
20 combined RT-GIMs generated and analyzed during the testing period are available at <http://doi.org/10.5281/zenodo.4651445>  
(Liu et al., 2021b).

## 1 Introduction

The GIMs, containing VTEC information at given grid points (typically with a spatial resolution of 2.5 degrees in latitude  
and 5 degrees in longitude) have been widely used in both scientific and technological communities (Hernández-Pajares et al.,  
25 2009). Due to the good performance and global distribution of VTEC, GIM has been applied to investigating the behavior  
of the ionosphere, such as the climatology of mean Total Electron Content (TEC), ionospheric anomalies before earthquakes,  
semiannual variations of TEC in ionosphere, the VTEC structure of polar ionosphere under different cases, W-index for iono-  
spheric disturbance warning (e.g., Liu et al., 2009, 2006; Zhao et al., 2007; Hernández-Pajares et al., 2020; Gulyaeva et al.,  
2013). In addition, the high accuracy of GIM enables precise range corrections for transionospheric radio signals including  
30 radar altimetry, radio telescopes, and GNSS positioning (e.g., Komjathy and Born, 1999; Fernandes et al., 2014; Sotomayor-  
Beltran et al., 2013; Le and Tiberius, 2007; Lou et al., 2016). The Center for Orbit Determination in Europe (CODE), European  
Space Agency (ESA), Jet Propulsion Laboratory (JPL), and UPC agreed on the computation of individual GIMs in IONosphere  
map EXchange (IONEX) format, and created the Ionosphere Working Group (Iono-WG) of the International GNSS Service  
(IGS) at 1998 (Schaer et al., 1996, 1998; Feltens and Schaer, 1998; Feltens, 2007; Mannucci et al., 1998; Hernández-Pajares  
35 et al., 1998, 1999). In the IGS 2015 workshop, CAS, Canadian Geodetic Survey of Natural Resources Canada (NRCAN) and  
WHU, became new Ionospheric Associate Analysis Centers (IAACs) (Li et al., 2015; Ghoddousi-Fard, 2014; Zhang et al.,  
2013). Currently, there are three types of post-processed IGS GIMs at different latencies: final, rapid, and predicted GIMs.  
With the contribution from different IAACs, the final and rapid GIMs are assessed and combined by corresponding weights  
and uploaded to FTP or HTTP servers with the latency of 1-2 weeks and 1-2 days, respectively. The 1-day and 2-day predicted  
40 GIMs can provide valuable VTEC information in advance for ionospheric activities and corrections. However, the accuracy  
of predicted GIMs is limited due to the nonlinear variation of ionosphere and the lack of real-time ionospheric observations  
(Hernández-Pajares et al., 2009; García-Rigo et al., 2011; Li et al., 2018).



In order to satisfy the growing demand for real-time GNSS positioning and applications, RTWG of IGS was established in 2001 and officially started to provide Real Time Service (RTS) in 2013 (Caissy et al., 2012). Aside from multi-GNSS real-time  
45 (RT) data streams, the IGS-RTS also generates RT-GNSS products streams, including satellite orbits, clocks, code/phase biases, and GIM. These high-quality IGS-RTS products enable precise GNSS positioning, navigation, timing (PNT), ionosphere monitoring, and hazard detection. In RTCM Special Committee (SC-104), the State Space Representation (SSR) correction data format is defined as the standard message (RTCM-SSR) for real-time GNSS applications. In support of flexible multi-GNSS applications within current multi-constellation and multi-frequency environments, a new format (IGS-SSR) is developed. The  
50 dissemination of IGS RT-GIMs adopts spherical harmonic (SH) expansion to save the bandwidth in both RTCM-SSR and IGS-SSR format (IGS, 2020).

The accuracy of RT-GIMs is typically worse than post-processed GIMs due to the short span of ionospheric observations, sparse distribution of stations, higher noises in carrier-to-code leveling, or difficulty in carrier ambiguity estimation in real-time processing mode. While RT-GIMs perform slightly worse than post-processed GIMs, it is found that RT-GIMs are helpful  
55 to reduce the convergence time of dual-frequency Precise Point Positioning (PPP) and strengthen the solution (Li et al., 2013). With the corrections of RT-GIMs, the accuracy of single-frequency PPP reaches decimeter and meter level in horizontal and vertical directions (Ren et al., 2019), while the Real-Time Kinematic (RTK) Positioning over medium and long-baseline is able to achieve few centimeters level for rover stations (Tomaszewski et al., 2020). In addition, the feasibility of ionospheric storm monitoring based on RT-GIMs is tested (García Rigo et al., 2017). A first fusion of IGS-GIMs and ionosondes data from  
60 the Global Ionosphere Radio Observatory (GIRO) paves the way for the improvement of real-time International Reference Ionosphere (Froń et al., 2020). Currently, the routine RT-GIMs are available from CAS, CNES, German Aerospace Center in Neutrelitz (DLR-NZ), UPC, WHU, and JPL (Li et al., 2020; Laurichesse and Blot, 2015; Jakowski et al., 2011; Hoque et al., 2019; Roma Dollase et al., 2015; Komjathy et al., 2012). Individual RT-GIMs from different IGS centers can be gathered from IGS-RTS by means of Network Transportation of RTCM by Internet Protocol (NTRIP) (Weber et al., 2007). With the  
65 contribution of IGS RT-GIMs from CAS, CNES and UPC, a first IGS real-time combination of GIMs was generated in 2018 (Roma-Dollase et al., 2018).

Recently, one of the IGS RT-GIMs (UPC-IonSAT) has completely changed the RT-interpolation strategy, with a significant improvement. In addition, the number of contributing centers has been increased from 3 to 4, thanks to the participation of Wuhan University. A new version of IRTG has been developed to improve the performance and also adapt to the newly updated  
70 IGS-SSR format. In addition, the developed software has been further parallelized to decrease the latency of IRTG computation to a few minutes (Tange, 2011). This paper summarizes the computation methods of IGS RT-GIMs from different ionosphere centers and the generation of IRTG. In addition, the performance of different RT-GIMs and real-time weighting technique is shown and discussed. The conclusions and future improvements are given in the final section.



## 2 Data and methods

### 75 2.1 Real-time GNSS data processing

In order to generate RT-GIMs, the real-time GNSS observations from worldwide stations are received and transformed into Slant TEC (STEC). With the global distributed STEC, different strategies are chosen for the computation of RT-GIMs.

80 Currently, two methods are commonly used for the calculation of real-time STEC. The first method is the so-called Carrier-to-Code Levelling (CCL) as shown in Eq. 1. The geometry-free (GF) combination of pseudorange and carrier phase observations is formed to extract STEC within a continuous arc. Due to the typically shorter phase-arc length in real-time mode, the impact of multipath and thermal noise is higher than in post-processing mode (Li et al., 2020).

$$\begin{cases} P_{GF} \equiv P_2 - P_1 = \alpha \cdot STEC + D_r + D^s + \epsilon_M + \epsilon_T \\ L_{GF} \equiv L_1 - L_2 = \alpha \cdot STEC - \beta \cdot \phi + B_{GF} \\ \tilde{P}_{GF,k} \equiv L_{GF,k} - \frac{1}{k} \sum_{i=1}^k (L_{GF,i} - P_{GF,i}) \approx \alpha \cdot STEC + D_r + D^s - \beta \cdot \phi + \frac{1}{k} \sum_{i=1}^k (\beta \cdot \phi_i) \end{cases} \quad (1)$$

where  $P_1$  and  $P_2$  are the pseudorange observations at first and second frequency, respectively.  $\alpha \approx 40.3 \left( \frac{1}{f_2^2} - \frac{1}{f_1^2} \right)$ .  $f_1$  and  $f_2$  are the first and second frequency of observation.  $r$  is receiver and  $s$  is satellite.  $D_r$  and  $D^s$  are the receiver DCB and satellite  
 85 DCB.  $\epsilon_M$  and  $\epsilon_T$  are the code multipath error and thermal noise error.  $L_1$  and  $L_2$  are the carrier phase observations at first and second frequency.  $\beta = c \left( \frac{1}{f_2} - \frac{1}{f_1} \right)$ .  $\phi$  is the relative rotation between receiver and satellite antennas.  $B_{GF} = B_1 - B_2$ , while  $B_1$  and  $B_2$  are the carrier phase ambiguities including the corresponding phase bias at first and second frequency, respectively.  $P_{GF,i}$  and  $L_{GF,i}$  are the  $P_{GF}$  and  $L_{GF}$  at epoch  $i$  within continuous arc.  $k$  is the smoothing arc length. and  $\tilde{P}_{GF,k}$  represents the smoothed  $P_{GF}$  which is significantly affected by the pseudorange multipath in real-time mode than in post-processing.

90 The second method is the GF combination of phase-only observations, and the  $B_{GF}$  is estimated together with the real-time TEC model (for example, described in terms of tomographic voxel-based basis functions) in Eq. 2 (Hernández-Pajares et al., 1997, 1999). Although the STEC from the second method is accurate and free of code multipath and thermal noise in post-processing, the convergence time can affect the accuracy of the STEC, most likely in the isolated receivers.

$$L_{GF} \equiv L_1 - L_2 = \alpha \cdot STEC - \beta \cdot \phi + B_{GF} \quad (2)$$

95 In addition, the computation methods of RT-GIMs from different IGS real-time ionosphere centers were compared in detail at the next subsection and summarized in Table 1. Since the dissemination of RT-GIMs adopts spherical harmonic expansions, some ionosphere centers (CAS, CNES, WHU) directly estimate spherical harmonic coefficients in sun-fixed reference frame as Eq. 3 (RTCM-SC, 2014; Li et al., 2020), while UPC generates the RT-GIM in IONEX format and transforms RT-GIM into



**Table 1.** The brief summary of different IGS RT-GIMs

Agency /GIM	Runing date	Extra ionospheric information	DCB computation	GIM computation
CAS	Mid-2017 to present	2-day predicted GIM as background information	Estimated at the same time with local VTEC, and corrected by three-day aligned code bias	Observations with predicted GIMs generate 15-degree spherical harmonic expansion GIM in solar-geographic frame
CNES	End-2014 to present (with an evolution of the spherical harmonic degree)	No	Expected in a forthcoming version	12-degree spherical harmonic expansion GIM which is generated in solar-geographic frame
UPC /URTG	2011-02-06 to 2019-09-08	1-2 day rapid GIM UQRG as background information	optional	Tomographic model with kriging interpolation method and frozen rapid GIM (UQRG) as a priori model, which generates RT-GIM in sun-fixed geomagnetic frame
UPC /USRG	2019-09-08 to present	1-2 day rapid GIM UQRG as background information	optional	Tomographic model with spherical harmonic interpolation method and frozen rapid GIM (UQRG) as a priori model, which generates RT-GIM in sun-fixed geomagnetic frame
UPC /UADG	2021-01-04 to present	historical UQRG (since 1996) as database	optional	Tomographic model adopting atomic decomposition and LASSO solution for the global interpolation with the help of historical GIMs (UQRG), which generates GIM in sun-fixed geomagnetic frame
WHU	2020-09-09 to present	2-day predicted GIM as background information	Directly use the previous satellite and receiver DCB estimated simultaneously with WHU rapid GIM	Observations with predicted GIMs yield 15-degree spherical harmonic expansion GIM in solar-geomagnetic frame



spherical harmonic coefficients for the dissemination.

$$\begin{cases}
 M(z) = [1 - \sin^2 z / (1 + H_{ion}/R_E)^2]^{-\frac{1}{2}} \\
 VTEC(\varphi_I, \lambda_S) = STEC(\varphi_I, \lambda_S) / M(z) \\
 VTEC(\varphi_I, \lambda_S) = \sum_{n=0}^N \sum_{m=0}^{\min(n, M)} P_{n, m}(\sin \varphi_I) \cdot (C_{n, m} \cos(m\lambda_S) + S_{n, m} \sin(m\lambda_S)) \\
 \lambda_S = (\lambda_I + (t - t_0) * \pi / 43200) \text{ modulo } 2\pi
 \end{cases} \quad (3)$$

where  $z$  is the satellite zenith angle,  $M(z)$  is the mapping function between STEC and VTEC.  $H_{ion}$  is the height of ionospheric single-layer assumption, and  $R_E$  is the radius of earth.  $\varphi_I$  and  $\lambda_I$  are the geocentric latitude and longitude of Ionospheric Pierce Point (IPP).  $\lambda_S$  is the mean sun fixed and phase-shifted longitude of IPP (shifted by 2 hours to approximate TEC maximum at 14:00 in local time).  $t_0$  is a common reference of shifted hours, taken as 2 hours in the present broadcasting and gathering of RT-GIMs from the four corresponding IGS centers.  $VTEC(\varphi_I, \lambda_S)$  is the VTEC at IPP location.  $N$  is the max degree of spherical harmonic expansion, and  $M$  is the max order of spherical harmonic expansion.  $n, m$  are corresponding indices.  $P_{n, m}$  is the normalized associated Legendre functions.  $C_{n, m}, S_{n, m}$  are sine and cosine spherical harmonic coefficients.  $t$  is GPS time of computation epoch within the current day.

## 2.2 The computation of RT-GIMs by different IGS real-time ionosphere centers

The strategies for generating RT-GIMs differ between IGS RT ionospheric analysis centers (ACs). In this subsection, a brief introduction on the generation of RT-GIMs from individual ACs as well as the strategy comparison between different ACs are given.

### 2.2.1 Chinese Academy of Sciences

The post-processed GIM of CAS has been computed and uploaded to IGS since 2015. A predicting-plus-modeling approach is used by CAS for the computation of RT-GIM (Li et al., 2020). CAS RT-GIM is generated with multi-GNSS, GPS and GLONASS L1+L2, BeiDou B1+B2 and Galileo E1+E5a RT data streams, provided by the IGS and regional GNSS tracking network stations. The real-time differential code biases (DCB) are estimated as part of the local ionospheric VTEC modeling using a generalized trigonometric series (GTS) function as Eq. 4. And then three-day aligned biases are incorporated to increase the robustness of real-time DCBs (Wang et al., 2020).

$$\begin{cases}
 STEC_r^s(\varphi_d, \lambda_d, h, z) = M(z) \cdot VTEC_r^s(\varphi_d, \lambda_d, h) + c \cdot (D^s + D_r) \\
 VTEC_r^s(\varphi_d, \lambda_d, h) = \sum_{n=0}^{n_{max}} \sum_{m=0}^{m_{max}} \{E_{n, m} \cdot \varphi_d^n \cdot \lambda_d^m\} + \sum_{k=0}^{k_{max}} \{C_k \cos(k \cdot h) + S_k \sin(k \cdot h)\} \\
 h = 2\pi(t - 14)/T, \quad T = 24h \\
 n_{max} = m_{max} = 2 \\
 k_{max} = 4
 \end{cases} \quad (4)$$

where  $r$  is receiver and  $s$  is satellite.  $\varphi_d$  and  $\lambda_d$  are the difference between IPP and station in latitude and longitude, respectively.  $z$  is the satellite zenith angle,  $M(z)$  is the mapping function.  $n, m, k$  represent the degrees in the polynomials model and Fourier



series expansion.  $E_{n,m}, C_k, S_k$  are unknown parameters.

The Eq. 1 and Eq. 4 from 130 global stations are combined to calculate real-time line-of-sight STEC, which is then converted  
125 to VTEC with an ionospheric mapping function in single-layer assumption at 450 km. The VTEC is directly modeled in a  
solar-geographic reference frame as Eq. 3. To mitigate the impacts of the unstable real-time data streams, e.g. the sudden  
interruption of the data streams, CAS predicted TEC information is also included for RT-GIM computation (Li et al., 2020).

### 2.2.2 Centre National d'Etudes Spatiales

In the framework of the Real Time Service of the IGS, CNES computes global VTEC in real-time thanks to the CNES PPP-  
130 WIZARD project since 2014. The real-time VTEC is extracted by pseudorange and carrier phase GF combination as Eq. 1 with  
the help of mapping function. And the single-layer assumption in the mapping function adopts an altitude of 450 km above the  
Earth.

CNES also use spherical harmonic model for global VTEC representation, and the equation is the same as Eq. 3. Spherical  
harmonic coefficients are computed by means of a Kalman Filter and simultaneous STEC from 100 stations of the RT-IGS  
135 network. CNES started to broadcast RT-GIM at the end of 2014 and changed spherical harmonic degrees from 6 to 12 in May  
of 2017 (Laurichesse and Blot, 2015).

### 2.2.3 Universitat Politècnica de Catalunya

UPC has been providing daily GIMs in IONEX-format to IGS since 1998 (Hernández-Pajares et al., 1998, 1999). In order to  
meet the demand of real-time GIM, UPC developed the Real-Time TOMographic IONosphere model software (RT-TOMION)  
140 and started to generate the UPC RT-GIM on February 6 of 2011. The phase-only GF combination as Eq. 2, is used for obtaining  
real-time STEC from around 260 stations, and a 4-D voxel-based tomographic ionosphere model is adopted for global electron  
content modeling. The ionosphere is divided into two layers in the tomographic model and the electron density of each voxel is  
estimated together with the ambiguity term  $B_{GF}$  by means of a Kalman filter in the sun-fixed reference frame. The estimated  
electron density is condensed at a fixed effective height (450 km) for the generation of a single-layer VTEC map, and then the  
145 VTEC interpolation method is adopted in a sun-fixed geomagnetic reference frame for filling the data gap on a global scale.

From 2011 to 2019, the kriging technique is selected by UPC for real-time VTEC interpolation. And the spherical harmonic  
model has been adopted by UPC since September 08 of 2019. Recently, a new interpolation technique, denoted as Atomic  
Decomposition Interpolator of GIMs (ADIGIM), has been developed. ADIGIM, assuming that the global profile of ionospheric  
electron content performs spatial-temporal similarities, models the interpolation as the sparse representation of good-quality  
150 historical GIMs (e.g. UQRG) over last two solar cycles. Based on the atomic decomposition and the least absolute shrinkage  
and selection operator (LASSO), the modelling is to find a minimization problem regarding VTEC measurement and estimates  
which is a combination of an approximation error by norm  $\ell_2$ , along with a  $\ell_1$  penalization on the approximation coefficients  
inducing sparsity (Yang et al., 2021). The UPC RT-GIM with the new technique is denoted as UADG and generated by Eq. 5.  
Due to the improvement provided by the UADG, the broadcasted UPC-GIM was changed from USRG to UADG on January  
155 04 of 2021. In addition, the USRG and UADG are generated in real-time mode and saved in IONEX format at HTTP as shown



in Table 1.

$$\begin{cases} G_t = D_t \tilde{\alpha}_t \\ V(x, y) \approx D_t^I \alpha_t \\ \tilde{\alpha}_t = \arg \min_{\alpha_t} \frac{1}{2} \|V - D_t \alpha_t\|_{\ell_2} + \rho \|\alpha_t\|_{\ell_1} \end{cases} \quad (5)$$

where  $G_t$  is the generated RT-GIM.  $D_t$  is the dictionary matrix of historical UQRG database.  $\tilde{\alpha}_t$  is the estimated weight vector.  $V(x, y)$  is the observed VTEC at IPP.  $D_t^I$  is the VTEC extracted at IPP from historical GIM database.  $\alpha_t$  is the unknown weight  
160 vector of each historical GIM.  $\ell_2$  is the norm for minimizing the euclidean distance between current VTEC measurements and historic ones.  $\ell_1$  is the regularization norm for penalizing the approximation coefficients and  $\rho$  controls the sparsity of solution.

### 2.2.4 Wuhan University

The daily rapid and final GIM products have been generated with WHU new software named GNSS Ionosphere Monitoring and Analysis Software (GIMAS) since 21 June 2018 (Zhang and Zhao, 2018). At the end of the year 2020, WHU has also  
165 published a first RT-GIM product.

WHU uses the Spherical Harmonic Expansion (SHE) model and the formula is identical to Eq. 3. Currently, only the GPS real-time data streams from about 120 globally distributed IGS stations are used. The double frequency code and carrier phase observations with a cut-off angle of 10 degrees are used to gather precise geometry-free ionospheric data with the CCL method as Eq. 1 and ionospheric mapping function with the layer height of 450 km. In order to avoid the influence of satellite and  
170 receiver DCB on ionospheric parameters estimation, WHU directly uses the previous estimated DCB from WHU rapid GIM product. According to previous experience, the real-time data is not enough to model the ionosphere precisely on a global scale with SHE technique. Considering the lack and the uneven distribution of the GPS-derived ionospheric data, 2-day predicted GIM as external ionospheric information is also incorporated. It is important to balance the weight between the real-time data and the background information. Both the RT-GIM quality and the root mean square (RMS) map are influenced by the weight  
175 (Zhang and Zhao, 2019).

In the year 2021, WHU is going to focus on how to further improve the accuracy of RT-GIM and update the computation method. The precise WHU RT-GIMs with multi-GNSS data and the application of WHU RT-GIM in the GNSS positioning as well as space physics domain, are expected as next steps.

### 2.3 The combination of IGS RT-GIMs

180 Thanks to the contribution of the initial IGS real-time ionosphere centers (CAS, CNES, and UPC) and globally distributed real-time GNSS stations, the first experimental IRTG was generated by means of RT-dSTEC weighting technique (normalized inverse of the squared RMS of RT-dSTEC error) in October 2018 (Roma-Dollase et al., 2018; Li et al., 2020). Recently, WHU published the first WHU RT-GIM and UPC upgraded the real-time VTEC interpolation technique. A new version of IRTG has been developed and broadcasted since January 04 of 2021. The IGS combined RT-GIM is based on the weighted mean value





185 of VTEC from different IGS centers as Eq. 6.

$$\begin{cases} VTEC_{IRTG} = \sum_{i=1}^N (w_i \cdot VTEC_i) \\ w_i = t_i / \sum_{i=1}^N (t_i) \\ t_i = 1 / RMS_{\delta,i}^2 \\ RMS_{\delta,i} = \sqrt{\sum_{i=1}^N (\delta_i)^2 / N} \end{cases} \quad (6)$$


where  $VTEC_{IRTG}$  is the VTEC of IGS combined RT-GIM and  $VTEC_i$  is VTEC of RT-GIM from IGS center  $i$ .  $N$  is the number of IGS centers.  $w_i$  is the weight of corresponding RT-GIM (the sum of  $w_i$  is 1).  $t_i$  is the inverse of the squared RMS of RT-dSTEC error  $RMS_{\delta,i}^2$  and  $\delta_i$  is the RT-dSTEC error of IGS center  $i$  in the RT-dSTEC assessment.

190 In addition, the RT-dSTEC assessment is based on Root Mean Square (RMS) of the dSTEC error calculated by Eq. 7. In order to adapt to the real-time processing mode, the reference STEC ambiguous measurement  $L_{GF}(t_{E_{ref}})$  is set to be the first elevation angle higher than  $10^\circ$  within continuous phase-arc to enable the dSTEC calculation in the elevation-ascending arc.

$$\delta = \frac{1}{\alpha} (L_{GF}(t) - L_{GF}(t_{E_{ref}})) - (M(t) \cdot V(t)_{GIM} - M(t_{E_{ref}}) \cdot V(t_{E_{ref}})_{GIM}) \quad (7)$$

where  $\delta$  is the dSTEC error.  $t_{E_{ref}}$  is the epoch when reference elevation angle is stored.  $L_{GF}(t)$  is the difference between carrier phase observations at first and second frequency at epoch  $t$ .  $M(t)$  is the mapping function at epoch  $t$ , and  $V(t)_{GIM}$  is the VTEC from GIM at epoch  $t$ .


Due to the limited number of RT-stations, 25 common RT-stations that have been used by all the IGS real-time ionosphere centers are selected for allowing a fair RT-dSTEC assessment. The distribution can be seen as Fig. 1. Therefore, the RT-dSTEC



**Figure 1.** The 25 common RT-stations for RT-dSTEC assessment (in green color) and 50 external GNSS stations for dSTEC-GPS assessment (in red color)



is the measurement of "internal" post-fit residuals of RT-GIMs, and still sensitive to the accuracy of assessed GIMs. Every 20 minutes, the RT-dSTEC assessment is performed and used for the combination of different IGS RT-GIMs. The steps for the generation of IRTG can be seen as Fig. 2. The RTCM-SSR has been the standard message for real-time corrections, and the



**Figure 2.** Data flow for the IGS real-time combined GIM

IGS State Space Representation (SSR) Format Version 1.00 was published on October 05 of 2020 (IGS, 2020). The content of ISG-SSR is compatible with RTCM-SSR contents, while ISG-SSR supports more extensions. At present, both RTCM-SSR and IGS-SSR formats are used for the dissemination of RT-GIMs. In addition, IGS defines different reference for antenna correction: Average Phase Center (APC), and Center of Mass (CoM). The current status of RT-GIMs from different ionosphere centers can be seen as Table 2. It should be noted that "SSRA" means the SSR with APC reference, and "SSRC" means the SSR with CoM reference.

### 3 The performance of IGS RT-GIMs

In this section, the performance of IGS RT-GIMs was analyzed, and compared with IGS rapid GIMs as well as IGS combined final GIM (IGSG). It should be noted that the RT-GIMs were gathered with BKG Ntrip Client (BNC) software (Weber et al., 2016) and generated by received spherical harmonic coefficients from different centers as Table 2. And there were two kinds of temporal resolution for received RT-GIMs: the common temporal resolution of 20 minutes, and the full (original) temporal resolution. Since the IRTG is combined every 20 minutes, we will focus on such a common time resolution to compare the performance. The detail of compared RT-GIMs can be seen as Table 3. The influence of temporal resolution on RT-GIMs was also shown in this section.



**Table 2.** The current status of broadcasting IGS RT-GIMs

Agency	Temporal resolution	Broadcast frequency	Spherical harmonic degree	Mountpoints in NTRIP caster	Real-Time IONEX saved at FTP/HTTP
CAS	5 minutes	1 minute	15	123.56.176.228:2101/CAS05 <sup>a</sup> 59.110.42.14:2101/SSRA00CAS1 <sup>b</sup> 59.110.42.14:2101/SSRA00CAS0 <sup>a</sup> 59.110.42.14:2101/SSRC00CAS1 <sup>b</sup> 59.110.42.14:2101/SSRC00CAS0 <sup>a</sup> 182.92.166.182:2101/IONO00CAS1 <sup>b</sup> 182.92.166.182:2101/IONO00CAS0 <sup>a</sup>	ftp://ftp.gipp.org.cn/product/ionex/ (update at the end of day)
CNES	2 minutes	1 minute	12	products.igs-ip.net:2101/CLK91 <sup>a</sup> products.igs-ip.net:2101/SSRA00CNE1 <sup>b</sup> products.igs-ip.net:2101/SSRA00CNE0 <sup>a</sup> products.igs-ip.net:2101/SSRC00CNE1 <sup>b</sup> products.igs-ip.net:2101/SSRC00CNE0 <sup>a</sup>	No
UPC (only UADG)	15 minutes	15 seconds	15	products.igs-ip.net:2101/IONO00UPC1 <sup>b</sup>	http://chapman.upc.es/tomion/real-time/quick/ (UADG and USRG, update every 15 minutes)
WHU	5 minutes	1 minute	15	58.49.58.150:2106/IONO00WHU0 <sup>a</sup>	No
IGS	20 minutes	15 seconds	15	products.igs-ip.net:2101/IONO00IGS1 <sup>b</sup>	http://chapman.upc.es/irtg/ (update every 20 minutes)

<sup>a</sup> RTCM-SSR format

<sup>b</sup> IGS-SSR format

### 3.1 Jason3-VTEC assessment

The VTEC from the Jason3-altimeter was gathered as an external reference over oceans which were also the most challenging regions for GIMs (typically containing few nearby receivers in such regions). After applying a sliding window of 16 seconds to smooth the altimeter measurements, the typical standard deviation of Jason3-VTEC measurement error is around 1 TECU. Although the electron content above Jason3-altimeter (about 1300 km) is not available and the altimeter bias is around a few TECU, Jason3-VTEC has been proven to be a reliable reference of VTEC on a global scale (Hernández-Pajares et al., 2017). In this context, the daily standard deviation of the difference between Jason3-VTEC and GIM was selected as the statistic for



**Table 3.** The Id. of compared IGS RT-GIMs

Agency	20-minute RT-GIM	RT-GIM with full temporal resolution
CAS	crtg	crfg
CNES	cnes	cnfs
UPC	upc1	upf1
WHU	whu0	whf0
IGS	irtg	irfg <sup>a</sup>

<sup>a</sup> irfg and irtg are the same.

GIM assessment in Eq. 8.

$$\begin{cases} Bias = \sum_{i=1}^N (VTEC_{Jason3,i} - VTEC_{GIM,i}) / N \\ STD = \sqrt{\sum_{i=1}^N (VTEC_{Jason3,i} - VTEC_{GIM,i} - Bias)^2 / (N - 1)} \end{cases} \quad (8)$$


225 where  $VTEC_{Jason3,i}$  and  $VTEC_{GIM,i}$  are VTEC extracted from Jason3 and GIM observation  $i$ , respectively.  $N$  is the number of involved observations.

The recent one-month of data (January 03 to February 02 in 2021), containing the two significant events (new contributing GIM from WHU and the introduction of the new tomographic-atomic decomposition UPC-GIM (UADG) on Jan 04) has been selected to study the consistency and performance of the IGS RT-GIMs.

230 As can be seen in Fig. 3, the UPC RT-GIM (upc1) achieved a significant improvement after the transition from USRG to UADG on January 04. In addition, the accuracy of IGS experimental combined RT-GIM (irtg) also increased due to the better performance of upc1. Compared with IGS rapid GIMs (corg, ehrg, emrg, esrg, igrg, jprg, uhrg, uprg, uqrg, whrg) and IGS final combined GIM (igsg), the upc1 and irtg are equivalent to the post-processed GIMs and even better than some rapid GIMs. The accuracy of CAS RT-GIM (crtg) and CNES RT-GIM (cnes) are close to the post-processed GIMs, while WHU RT-GIM  
 235 (whu0) is slightly worse than the other GIMs. In order to investigate the influence of temporal resolution on RT-GIMs over oceans, different RT-GIMs with full temporal resolution were involved. The summary of Jason3-VTEC assessment can be seen in Table 4. The overall standard deviation of GIM-VTEC versus Jason3-VTEC is consistent with the Fig. 3 and the quality of 20-minute and full temporal resolution of RT-GIMs are similar over oceans.

### 3.2 dSTEC-GPS assessment

240 In addition, dSTEC-GPS assessment in post-processing mode was involved as a complementary tool with high accuracy (better than 0.1 TECU) over continental regions on a global scale. In the dSTEC-GPS assessment, the maximum elevation angle within a continuous arc was regarded as the reference angle in Eq. 7. The dSTEC-GPS assessment was performed by globally distributed GNSS stations as shown in Fig. 1 on January 03 (before the transition of UPC RT-GIM) and January 05 (after the transition) in 2021, with a focus on the transition of UPC RT-GIM. The RMS error and relative error were used for the




**Figure 3.** Daily standard deviation of GIM VTEC versus measured Jason3-VTEC (in TECU), from January 03 to February 02 in 2021.

245 assessment as Eq. 9.

$$\begin{cases} RMS_{\delta} = \sqrt{\sum_{i=1}^N (\delta_i)^2 / N} \\ Relative\ error = RMS_{\delta} / RMS_{\Delta_{GPS}} \end{cases} \quad (9)$$

where  $\delta_i$  is the dSTEC error as Eq. 7 at epoch  $i$ .  $RMS_{\Delta_{GPS}}$  is the RMS of observed dSTEC-GPS.

As shown in Table 4, the RMS error of most post-processed GIMs reaches around 2 or 3 TECU, while the RMS error ranges from 2.8 to 5.54 TECU for RT-GIMs. The transition of UPC RT-GIM (upf1) is apparent in the dSTEC-GPS assessment, and the RMS error of IGS RT-GIM (irtg) decreased from 4.11 to 3.37 TECU due to the improvement of UPC RT-GIM. After the transition of upf1, the performance of upf1 and irtg is comparable with most post-processed GIMs. Similar to the performance in Jason3-VTEC assessment, the accuracy of remaining RT-GIMs is close to post-processed GIMs. It should be pointed out that the performance of RT-GIMs with the full temporal resolution is slightly worse than 20-minute RT-GIMs. Furthermore, the full temporal resolution RT-GIM is even worse than the GIM obtained by linear interpolation of the 20-minute RT-GIM in a sun-fixed reference frame. This is coincident with a smaller number of ionospheric observations at shorter time scales. In Fig. 4, the performance of IGS RT-GIMs after the upgrade of UPC interpolation method in dSTEC-GPS assessment is represented. The higher values of RMS errors occur around the equator and southern hemisphere for all the RT-GIMs. And the higher values might be caused by the high electron density gradients at the equator and the sparse distribution of RT-stations in the southern hemisphere.



**Figure 4.** The distribution of dSTEC-GPS results on January 05 of 2021 (after the transition of UPC interpolation technique).



**Table 4.** Standard deviation of GIM-VTEC minus Jason3-VTEC from January 03 to February 02 of 2021 in Jason3-VTEC assessment (last column), and dSTEC-GPS assessment results of RT-GIMs on January 03 (second and third column) and January 05 (fourth and fifth column) in 2021.

GIM	RMS error of January 03 (TECU)	Relative error of January 03 (%)	RMS error of January 05 (TECU)	Relative error of January 05 (%)	Overall standard deviation in Jason3-VTEC assessment (TECU)
corg	6.63	103.22	6.08	89.28	2.8
ehrg	2.54	39.55	2.81	41.23	2.8
emrg	2.62	40.75	2.73	40.08	3.0
esrg	2.70	41.98	3.06	44.99	2.9
igrgr	2.60	40.40	3.06	44.99	2.7
jprgr	2.73	42.46	2.86	41.98	2.6
uhrgr	1.91	29.69	2.21	32.43	2.9
uprg	2.04	31.80	2.41	35.39	2.8
uqrg	1.89	29.44	2.19	32.24	2.9
whrg	2.42	37.63	2.65	38.94	2.7
igsg	2.33	36.25	2.57	37.74	2.4
crtg	3.36	52.25	3.86	56.67	3.2
crfg	4.29	66.67	3.92	57.56	3.2
cnes	<b>3.35</b>	52.13	3.74	54.86	3.3
cnfs	3.58	55.73	4.62	67.88	3.3
upcl	3.85	59.91	<b>2.80</b>	41.06	<b>2.7</b>
upfl	3.87	60.20	2.81	41.26	<b>2.7</b>
whu0	5.19	80.69	5.45	79.84	4.5
whf0	5.31	82.61	5.54	81.28	4.5
irtg	<u>4.11</u>	63.86	<u>3.37</u>	49.47	<b><u>2.7</u></b>

value in bold font means the corresponding RT-GIM has the best performance among the remaining RT-GIMs in each column, and values of irtg are underlined for comparison.

### 260 3.3 The sensibility of RT-weighting technique

RT-dSTEC assessment of RT-GIMs was automatically running in real-time mode, and used for RT-weighting in the combination of IGS RT-GIMs. In order to compare with the dSTEC-GPS assessment, the RT-dSTEC assessment with RT-stations in Fig. 1 was also performed on January 03 and January 05 in 2021. As can be seen in Table 5, the rank of RT-GIMs in RT-dSTEC assessment is similar to dSTEC-GPS assessment, but the RMS error values are larger. And the larger RMS error is coinciding with the much lower elevation angle of the observation reference in RT-dSTEC assessment. The real-time weights of RT-GIMs can be defined as the normalized inverse of the squared RMS of RT-dSTEC errors and represent the accuracy of RT-GIMs in



**Table 5.** RMS errors of RT-GIMs in RT-dSTEC assessment on January 03 and January 05 in 2021.

GIM	RMS error of January 03 (TECU)	RMS error of January 05 (TECU)
upc1	4.24	<b>3.91</b>
crtg	4.25	4.98
cnes	<b>3.98</b>	4.07
whu0	5.94	5.81

value in bold font means the corresponding RT-GIM has the best performance among the remaining RT-GIMs in each column.

the RT-dSTEC assessment. The evolution of real-time weights is consistent with the Jason3-VTEC assessment in the bottom figure of Fig. 5. The significant improvement of the transition in dSTEC-GPS and Jason3-VTEC assessment is obvious in the top figure of Fig. 5. In addition, the weight evolution and transition in Fig. 5 are consistent with the accuracy of RT-GIMs providing a combined RT-GIM which is one of the best RT-GIMs, as shown in the altimeter-based and dSTEC-based assessments. The good performance of the combination algorithm can be mainly explained from the point of view of the weights, i.e. the sensitivity of the dSTEC error to the quality of the RT-GIMs. But also from the point of view of the linear combination that can play a positive role under any potential negative correlation between the performance of pairs of involved RT-GIMs.


### 3.4 The response of GEC to recent minor geomagnetic storms in RT-GIMs

The GEC is defined as the total number of free electrons in the ionosphere. Hence the GEC can be estimated from the summation of the product of the VTEC value and the area of the corresponding GIM cell. In addition, GEC has been used as ionospheric index (Afraimovich et al., 2006; Hernández-Pajares et al., 2009). With the purpose of further checking the consistency of IGS RT-GIMs, the GEC of RT-GIMs was calculated and compared from January 24 to January 29 in 2021. It should be noted that the solar activity is low in January of 2021. During the selected period, several weak geomagnetic storms and one moderate geomagnetic storm occurred according to the classification of geomagnetic indices (Loewe and Pröls, 1997; Gonzalez et al., 1999), and the GEC evolution can be seen in Fig. 6. The GEC of CNES RT-GIM (cnfs) is slightly different from other RT-GIMs, and seems to be caused by the bias in CNES RT-GIM. There are some jumps in the GEC evolution of CAS RT-GIM (crfg) and WHU RT-GIM (whf0), and the jumps might be related to the handling of day boundary or unreal predicted GIM in certain cases. Compared with IGS final combined GIM (igsg), the good performance of global VTEC representation with upf1 and irfg can be seen in Fig. 6. In addition, the response of upf1 and irfg to the recent minor geomagnetic storms (detected by 3-hour ap and 1-hour Dst indices) is apparent and also similar to the post-processed IGS final combined GIM (igsg).


## 4 Data availability

The IGS real-time combined GIMs during the testing period are available from Zenodo at <http://doi.org/10.5281/zenodo.4651445> (Liu et al., 2021b) in IONEX format (Schaer et al., 1998). In addition, more archived IGS combined RT-GIMs





**Figure 5.** The evolution of real-time weights of RT-GIMs from January 03 to February 02 in 2021 (the top figure is a zoom of bottom figure).



**Figure 6.** The GEC, ap and Dst evolution of RT-GIMs from January 24 to January 29 of 2021 during the low solar activity period.

290 can be found at <http://chapman.upc.es/irtg/archive/> and the latest IGS combined RT-GIMs are available in real-time mode at [http://chapman.upc.es/irtg/last\\_results/](http://chapman.upc.es/irtg/last_results/).

## 5 Conclusions

In this paper, we have summarized the computation methods of RT-GIMs from four individual IGS ionosphere centers and introduced the new version of IGS combined RT-GIM. According to the results of Jason3-VTEC and dSTEC-GPS assessment,  
 295 it could be concluded as follows:



- The RT-weighting technique for the generation of IGS combined RT-GIM turns out to be effective when it is compared with Jason3-VTEC and dSTEC-GPS assessment.
- The transition of UPC RT-GIM is obvious in all involved assessments and also demonstrates the sensibility of the RT-weighting technique to RT-GIMs when the accuracy of RT-GIMs is increased.
- 300 – The quality of most IGS RT-GIMs is close to post-processed GIMs.
- The difference among RT-GIMs with 20-minute and full temporal resolution can be neglected over oceans in Jason3-VTEC assessment (see Fig. 3 and Table 4), while the difference is visible in some RT-GIMs over continental regions in dSTEC-GPS assessment (see Table 4). The lower accuracy of GIMs with full temporal resolution (2 or 5 minutes) might be related to the uneven distribution of ionospheric observations, the weight between predicted GIMs and real-time observations. Combined with the previous study (Liu et al., 2021a), it is suggested to find a more suitable temporal resolution for the generation of RT-GIM in sun-fixed reference frame.
- 305

In addition, the GEC evolution of UPC RT-GIM and IGS combined RT-GIM is close to the GEC evolution of IGS final combined GIM in post-processing mode, and has an obvious response to the geomagnetic storm during the low solar activity period. Future improvements might include:

- 310 – To broadcast real-time RMS maps that can be useful for the positioning users.
- To increase the accuracy of high temporal resolution RT-GIMs. In addition, higher maximum spherical harmonic degrees might be adopted to increase the accuracy and spatial resolution of RT-GIMs.
- Coinciding with a much larger number of RT-GNSS receivers in the future, the dSTEC weighting might be improved by replacing the "internal" by the "external" receivers, i.e. not used by any RT analysis centers. In this way the weighting would be sensitive as well to the interpolation/extrapolation error of the different RT ionospheric GIMs to be combined.
- 315 And the resulting combination might behave better.
- To increase the number of worldwide GNSS receivers used for the RT-dSTEC up to more than 100. In this way we will be able to study the potential upgrade of the present global weighting to a regional one.

*Author contributions.* QL wrote the manuscript. QL developed the updated combination software with contributions from DRD, HY and MHP. QL and MHP designed the research, with contributions from HY, EMM, DRD and AGR. QL, HY, EMM, MHP, ZL, NW, DL, AB, Q. Zhao and Q. Zhang provided the real-time GIMs of the corresponding IGS centers. AH, MS, GW and AS contributed in creating the framework of the real-time IGS service, the ionospheric message format and BNC open software updates. LA suggested the initial idea of this work. AK, SS, JF, AK, RGF and AGR contributed in the generation of rapid and final IGS GIMs used as additional reference in the manuscript.

- 320



325 *Competing interests.* The authors declare that they have not conflict of interest.

*Acknowledgements.* The first author is grateful for the financial support of the China Scholarship Council (CSC). The authors are thankful to the collaborative and friendly framework of the International GNSS Service, an organization providing first-class open data and open products (Johnston et al., 2017). The VTEC data from Jason3-altimeter were gathered from the NASA EOSDIS Physical Oceanography Distributed Active Archive Center (PO.DAAC) at the Jet Propulsion Laboratory, Pasadena, CA (<http://dx.doi.org/10.5067/GHGMR-4FJ01>) and the  
330 National Oceanic and Atmospheric Administration (NOAA). We are also thankful to the ap and Dst indexes from GeoForschungsZentrum (GFZ) and World Data Center (WDC) for Geomagnetism, Kyoto.



## References

- Afraimovich, E., Astafyeva, E., Oinats, A., Yasukevich, Y. V., and Zhivetiev, I.: Global electron content and solar activity: comparison with IRI modeling results, in: poster presentation at IGS Workshop, Darmstadt, Germany, 2006.
- 335 Caissy, M., Agrotis, L., Weber, G., Hernandez-Pajares, M., and Hugentobler, U.: Innovation: Coming Soon-The International GNSS Real-Time Service, <https://www.gpsworld.com/gnss-systemaugmentation-assistanceinnovation-coming-soon-13044/>, last access: March 21 2021, 2012.
- Feltens, J.: Development of a new three-dimensional mathematical ionosphere model at European Space Agency/European Space Operations Centre, *Space Weather*, 5, S12002, <https://doi.org/10.1029/2006SW000294>, 2007.
- 340 Feltens, J. and Schaer, S.: IGS Products for the Ionosphere, in: Proceedings of the 1998 IGS Analysis Center Workshop Darmstadt, Germany, pp. 3–5, 1998.
- Fernandes, M. J., Lázaro, C., Nunes, A. L., and Scharroo, R.: Atmospheric corrections for altimetry studies over inland water, *Remote Sensing*, 6, 4952–4997, <https://doi.org/10.3390/rs6064952>, 2014.
- Froń, A., Galkin, I., Krankowski, A., Bilitza, D., Hernández-Pajares, M., Reinisch, B., Li, Z., Kotulak, K., Zakharenkova, I., Cherniak, I.,  
345 et al.: Towards Cooperative Global Mapping of the Ionosphere: Fusion Feasibility for IGS and IRI with Global Climate VTEC Maps, *Remote Sensing*, 12, 3531, <https://doi.org/10.3390/rs12213531>, 2020.
- García-Rigo, A., Monte, E., Hernández-Pajares, M., Juan, J., Sanz, J., Aragón-Angel, A., and Salazar, D.: Global prediction of the vertical total electron content of the ionosphere based on GPS data, *Radio science*, 46, RS0D25, <https://doi.org/10.1029/2010RS004643>, 2011.
- García Rigo, A., Roma Dollase, D., Hernández Pajares, M., Li, Z., Terkildsen, M., Ghoddousi Fard, R., Dettmering, D., Erdogan, E., Haralambous, H., Beniguel, Y., et al.: St. Patrick's day 2015 geomagnetic storm analysis based on real time ionosphere monitoring, in: EGU 2017: European Geosciences Union General Assembly: Vienna, Austria: 23-28 April 2017: proceedings book, 2017.
- 350 Ghoddousi-Fard, R.: GPS ionospheric mapping at Natural Resources Canada, in: IGS workshop, Pasadena, 2014.
- Gonzalez, W. D., Tsurutani, B. T., and De Gonzalez, A. L. C.: Interplanetary origin of geomagnetic storms, *Space Science Reviews*, 88, 529–562, <https://doi.org/10.1023/A:1005160129098>, 1999.
- 355 Gulyaeva, T. L., Arikani, F., Hernandez-Pajares, M., and Stanislawski, I.: GIM-TEC adaptive ionospheric weather assessment and forecast system, *Journal of Atmospheric and Solar-Terrestrial Physics*, 102, 329–340, <https://doi.org/10.1016/j.jastp.2013.06.011>, 2013.
- Hernández-Pajares, M., Juan, J., and Sanz, J.: Neural network modeling of the ionospheric electron content at global scale using GPS data, *Radio Science*, 32, 1081–1089, <https://doi.org/10.1029/97RS00431>, 1997.
- Hernández-Pajares, M., Juan, J., Sanz, J., and Solé, J.: Global observation of the ionospheric electronic response to solar events using ground  
360 and LEO GPS data, *Journal of Geophysical Research: Space Physics*, 103, 20 789–20 796, <https://doi.org/10.1029/98JA01272>, 1998.
- Hernández-Pajares, M., Juan, J., and Sanz, J.: New approaches in global ionospheric determination using ground GPS data, *Journal of Atmospheric and Solar-Terrestrial Physics*, 61, 1237–1247, [https://doi.org/10.1016/S1364-6826\(99\)00054-1](https://doi.org/10.1016/S1364-6826(99)00054-1), 1999.
- Hernández-Pajares, M., Juan, J., Sanz, J., Orus, R., García-Rigo, A., Feltens, J., Komjathy, A., Schaer, S., and Krankowski, A.: The IGS VTEC maps: a reliable source of ionospheric information since 1998, *Journal of Geodesy*, 83, 263–275, <https://doi.org/10.1007/s00190-008-0266-1>, 2009.
- 365 Hernández-Pajares, M., Roma-Dollase, D., Krankowski, A., García-Rigo, A., and Orús-Pérez, R.: Methodology and consistency of slant and vertical assessments for ionospheric electron content models, *Journal of Geodesy*, 91, 1405–1414, <https://doi.org/10.1007/s00190-017-1032-z>, 2017.



- Hernández-Pajares, M., Lyu, H., Aragón-Ángel, À., Monte-Moreno, E., Liu, J., An, J., and Jiang, H.: Polar Electron Content From GPS  
370 Data-Based Global Ionospheric Maps: Assessment, Case Studies, and Climatology, *Journal of Geophysical Research: Space Physics*, 125,  
e2019JA027 677, <https://doi.org/10.1029/2019JA027677>, 2020.
- Hoque, M. M., Jakowski, N., and Orús-Pérez, R.: Fast ionospheric correction using Galileo Az coefficients and the NTCM model, *GPS  
Solutions*, 23, 41, <https://doi.org/10.1007/s10291-019-0833-3>, 2019.
- IGS: IGS State Space Representation (SSR) Format Version 1.00, [https://files.igs.org/pub/data/format/igs\\_ssr\\_v1.pdf](https://files.igs.org/pub/data/format/igs_ssr_v1.pdf), last access: March 21  
375 2021, 2020.
- Jakowski, N., Hoque, M., and Mayer, C.: A new global TEC model for estimating transionospheric radio wave propagation errors, *Journal  
of Geodesy*, 85, 965–974, <https://doi.org/10.1007/s00190-011-0455-1>, 2011.
- Johnston, G., Riddell, A., and Hausler, G.: The International GNSS Service, in: *Springer Handbook of Global Navigation Satellite Sys-  
tems* (1st ed., edited by Teunissen, P. J. and Montenbruck, O., pp. 967–982, Springer International Publishing, Cham, Switzerland,  
380 <https://doi.org/10.1007/978-3-319-42928-1>, 2017.
- Komjathy, A. and Born, G. H.: GPS-based ionospheric corrections for single frequency radar altimetry, *Journal of Atmospheric and Solar-  
Terrestrial Physics*, 61, 1197–1203, [https://doi.org/10.1016/S1364-6826\(99\)00051-6](https://doi.org/10.1016/S1364-6826(99)00051-6), 1999.
- Komjathy, A., Galvan, D., Stephens, P., Butala, M., Akopian, V., Wilson, B., Verkhoglyadova, O., Mannucci, A., and Hickey, M.: Detecting  
ionospheric TEC perturbations caused by natural hazards using a global network of GPS receivers: The Tohoku case study, *Earth, planets  
385 and space*, 64, 1287–1294, <https://doi.org/10.5047/eps.2012.08.003>, 2012.
- Laurichesse, D. and Blot, A.: New CNES real time products including BeiDou., <https://lists.igs.org/pipermail/igsmail/2015/001017.html>, last  
access: March 21 2021, 2015.
- Le, A. Q. and Tiberius, C.: Single-frequency precise point positioning with optimal filtering, *GPS solutions*, 11, 61–69,  
<https://doi.org/10.1007/s10291-006-0033-9>, 2007.
- 390 Li, M., Yuan, Y., Wang, N., Li, Z., and Huo, X.: Performance of various predicted GNSS global ionospheric maps relative to GPS and JASON  
TEC data, *GPS Solutions*, 22, 55, <https://doi.org/10.1007/s10291-018-0721-2>, 2018.
- Li, X., Ge, M., Zhang, H., and Wickert, J.: A method for improving uncalibrated phase delay estimation and ambiguity-fixing in real-time  
precise point positioning, *Journal of Geodesy*, 87, 405–416, <https://doi.org/10.1007/s00190-013-0611-x>, 2013.
- Li, Z., Yuan, Y., Wang, N., Hernandez-Pajares, M., and Huo, X.: SHPTS: towards a new method for generating precise global iono-  
395 spheric TEC map based on spherical harmonic and generalized trigonometric series functions, *Journal of Geodesy*, 89, 331–345,  
<https://doi.org/10.1007/s00190-014-0778-9>, 2015.
- Li, Z., Wang, N., Hernández Pajares, M., Yuan, Y., Krankowski, A., Liu, A., Zha, J., García Rigo, A., Roma-Dollase, D., Yang, H., et al.:  
IGS real-time service for global ionospheric total electron content modeling, *Journal of Geodesy*, 94, 32, [https://doi.org/10.1007/s00190-  
020-01360-0](https://doi.org/10.1007/s00190-<br/>020-01360-0), 2020.
- 400 Liu, J.-Y., Chen, Y., Chuo, Y., and Chen, C.-S.: A statistical investigation of preearthquake ionospheric anomaly, *Journal of Geophysical  
Research: Space Physics*, 111, A05 304, <https://doi.org/10.1029/2005JA011333>, 2006.
- Liu, L., Wan, W., Ning, B., and Zhang, M.-L.: Climatology of the mean total electron content derived from GPS global ionospheric maps,  
*Journal of Geophysical Research: Space Physics*, 114, A06 308, <https://doi.org/10.1029/2009JA014244>, 2009.
- Liu, Q., Hernández-Pajares, M., Lyu, H., and Goss, A.: Influence of temporal resolution on the performance of global ionospheric maps,  
405 *Journal of Geodesy*, 95, 34, <https://doi.org/10.1007/s00190-021-01483-y>, 2021a.



- Liu, Q., Hernández-Pajares, M., Yang, H., Monte-Moreno, E., Roma, D., García Rigo, A., Li, Z., Wang, N., Laurichesse, D., Blot, A., Zhao, Q., and Zhang, Q.: Global Ionosphere Maps of vertical electron content combined in real-time from the RT-GIMs of CAS, CNES, UPC-IonSAT, and WHU International GNSS Service (IGS) centers (from Jan 3 to Feb 2, 2021), <https://doi.org/10.5281/zenodo.4651445>, 2021b.
- 410 Loewe, C. and Pröls, G.: Classification and mean behavior of magnetic storms, *Journal of Geophysical Research: Space Physics*, 102, 14 209–14 213, <https://doi.org/10.1029/96JA04020>, 1997.
- Lou, Y., Zheng, F., Gu, S., Wang, C., Guo, H., and Feng, Y.: Multi-GNSS precise point positioning with raw single-frequency and dual-frequency measurement models, *Gps Solutions*, 20, 849–862, <https://doi.org/10.1007/s10291-015-0495-8>, 2016.
- Mannucci, A., Wilson, B., Yuan, D., Ho, C., Lindqwister, U., and Runge, T.: A global mapping technique for GPS-derived ionospheric total  
415 electron content measurements, *Radio science*, 33, 565–582, <https://doi.org/10.1029/97RS02707>, 1998.
- Ren, X., Chen, J., Li, X., Zhang, X., and Freeshah, M.: Performance evaluation of real-time global ionospheric maps provided by different IGS analysis centers, *GPS Solutions*, 23, 113, <https://doi.org/10.1007/s10291-019-0904-5>, 2019.
- Roma Dollase, D., López Cama, J. M., Hernández Pajares, M., García Rigo, A., et al.: Real-time Global Ionospheric modelling from GNSS data with RT-TOMION model, in: 5th International Colloquium Scientific and Fundamental Aspects of the Galileo Programme, pp.  
420 27–29, 2015.
- Roma-Dollase, D., Hernández-Pajares, M., García Rigo, A., Krankowski, A., Fron, A., Laurichesse, D., Blot, A., Orús-Pérez, R., Yuan, Y., Li, Z., Wang, N., Schmidt, M., and Erdogan, E.: Looking for optimal ways to combine global ionospheric maps in real-time, in: IGS workshop 2018, Oct 29-Nov2, Wuhan, 2018.
- RTCM-SC: Proposal of new RTCM SSR messages, SSR Stage 2: Vertical TEC (VTEC) for RTCM Standard 10403.2 Differential GNSS  
425 (global navigation satellite system) Services—Version 3, RTCM Special Committee 104, 2014.
- Schaer, S., Beutler, G., Rothacher, M., and Springer, T. A.: Daily global ionosphere maps based on GPS carrier phase data routinely produced by the CODE Analysis Center, in: Proceedings of the IGS AC Workshop, Silver Spring, MD, USA, March 19-21, 1996.
- Schaer, S., Gurtner, W., and Felten, J.: IONEX: The ionosphere map exchange format version 1, in: Proceedings of the IGS AC workshop, Darmstadt, Germany, vol. 9, 1998.
- 430 Sotomayor-Beltran, C., Sobey, C., Hessels, J., De Bruyn, G., Noutsos, A., Alexov, A., Anderson, J., Asgekar, A., Avruch, I., Beck, R., et al.: Calibrating high-precision Faraday rotation measurements for LOFAR and the next generation of low-frequency radio telescopes, *Astronomy & astrophysics*, 552, A58, <https://doi.org/10.1051/0004-6361/201220728>, 2013.
- Tange, O.: Gnu parallel-the command-line power tool, *The USENIX Magazine*, 36, 42–47, <https://doi.org/10.5281/zenodo.16303>, 2011.
- Tomaszewski, D., Wielgosz, P., Rapiński, J., Krypiak-Gregorczyk, A., Kaźmierczak, R., Hernández-Pajares, M., Yang, H., and OrúsPérez, R.:  
435 Assessment of Centre National d’Etudes Spatiales Real-Time Ionosphere Maps in Instantaneous Precise Real-Time Kinematic Positioning over Medium and Long Baselines, *Sensors*, 20, 2293, <https://doi.org/10.3390/s20082293>, 2020.
- Wang, N., Li, Z., Duan, B., Hugentobler, U., and Wang, L.: GPS and GLONASS observable-specific code bias estimation: comparison of solutions from the IGS and MGEX networks, *Journal of Geodesy*, 94, 74, <https://doi.org/https://doi.org/10.1007/s00190-020-01404-5>, 2020.
- 440 Weber, G., Mervart, L., Lukes, Z., Rocken, C., and Dousa, J.: Real-time clock and orbit corrections for improved point positioning via NTRIP, in: Proceedings of the 20th international technical meeting of the satellite division of the institute of navigation (ION GNSS 2007), pp. 1992–1998, 2007.



- Weber, G., Mervart, L., Stürze, A., Rülke, A., and Stöcker, D.: BKG Ntrip Client, Version 2.12, vol. 49 of *Mitteilungen des Bundesamtes für Kartographie und Geodäsie*, Verlag des Bundesamtes für Kartographie und Geodäsie, Frankfurt am Main, 2016.
- 445 Yang, H., Monte-Moreno, E., Hernández-Pajares, M., and David, R.-D.: Real-Time Interpolation of Global Ionospheric Maps by means of Sparse Representation, *Journal of Geodesy*, p. to be published, 2021.
- Zhang, H., Xu, P., Han, W., Ge, M., and Shi, C.: Eliminating negative VTEC in global ionosphere maps using inequality-constrained least squares, *Advances in Space Research*, 51, 988–1000, <https://doi.org/10.1016/j.asr.2012.06.026>, 2013.
- Zhang, Q. and Zhao, Q.: Global ionosphere mapping and differential code bias estimation during low and high solar activity periods with  
450 GIMAS software, *Remote Sensing*, 10, 705, <https://doi.org/10.3390/rs10050705>, 2018.
- Zhang, Q. and Zhao, Q.: Analysis of the data processing strategies of spherical harmonic expansion model on global ionosphere mapping for moderate solar activity, *Advances in Space Research*, 63, 1214–1226, <https://doi.org/10.1016/j.asr.2018.10.031>, 2019.
- Zhao, B., Wan, W., Liu, L., Mao, T., Ren, Z., Wang, M., and Christensen, A.: Features of annual and semiannual variations derived from the global ionospheric maps of total electron content, *Annales Geophysicae*, 25, 2513–2527, [https://doi.org/https://doi.org/10.5194/angeo-25-](https://doi.org/https://doi.org/10.5194/angeo-25-2513-2007)  
455 2513-2007, 2007.