



Canadian historical Snow Water Equivalent dataset (CanSWE, 1928-2020)

Vincent Vionnet¹, Colleen Mortimer², Mike Brady², Louise Arnal³, Ross Brown²

¹Meteorological Research Division, Environment and Climate Change Canada, Dorval, Canada

²Climate Research Division, Environment and Climate Change Canada, Toronto, Canada

³University of Saskatchewan Coldwater Laboratory, Canmore, Alberta, Canada

Correspondence to: Vincent Vionnet (vincent.vionnet@canada.ca)

Abstract.

10 In situ measurements of snow water equivalent (SWE) – the depth of water that would be produced if all the snow melted – are used in many applications including water management, flood forecasting, climate monitoring, and evaluation of hydrological and land surface models. The Canadian historical SWE dataset (CanSWE) combines manual and automated pan-Canadian SWE observations collected by national, provincial and territorial agencies as well as hydropower companies. Snow depth and derived bulk snow density are also included when available. This new dataset supersedes the previous
15 Canadian Historical Snow Survey (CHSSD) dataset published by Brown et al. (2019), and this paper describes the efforts made to correct metadata, remove duplicate observations, and quality control records. The CanSWE dataset was compiled from 15 different sources and includes SWE information for all provinces and territories that measure SWE. Data were updated to July 2020 and new historical data from the Government of Northwest Territories, Government of Newfoundland and Labrador, Saskatchewan Water Security Agency, and Hydro Quebec were included. CanSWE includes over one million
20 SWE measurements from 2607 different locations across Canada over the period 1928 – 2020. It is publicly available at <https://doi.org/10.5281/zenodo.4734372> (Vionnet et al., 2021).

1 Introduction

Reliable in situ information of snow water equivalent (SWE) – the equivalent amount of liquid water stored in the snowpack (Fierz et al., 2009) – is critical for flood and drought predictions (e.g., Jörg-Hess et al., 2015; Berghuijs et al., 2016; Vionnet
25 et al., 2020), streamflow management of water supply for hydropower generation (e.g., Magnusson et al., 2020), irrigation planning (e.g., Biemans et al., 2019) and is a key environmental variable for climate monitoring and understanding (e.g., Clark et al., 2001; Brown et al., 2019). In situ SWE measurements can be made manually or via automatic sensors (Kinar and Pomeroy, 2015). Manual SWE measurements typically consist of multi-point gravimetric snow surveys (also known as snow transects or snow courses) collected along a pre-determined transect (WMO, 2008). Manual snow surveys are
30 generally representative of the prevailing land cover and terrain but are time-consuming and expensive which limits their



temporal frequency, especially in remote locations. Automatic stations can overcome this limitation and provide SWE measurements at a higher temporal frequency but have the disadvantage of only measuring SWE at a single point. Snow pillows (Beaumont, 1965) and snow scales (Johnson, 2004) automatically measure SWE from the overlying pressure and weight of the snowpack, respectively. Indirect methods using passive radiation sensors installed below or above the snowpack have also been developed. They measure the attenuation by the snowpack of natural cosmic radiation (Kodoma et al., 1979; Paquet et al., 2008) or naturally emitted gamma radiation from the soil (Choquette et al., 2008). Finally, SWE can be automatically derived by analysis of the signal from Global Navigation Satellite System receivers (Henkel et al., 2018) or Global Positioning System receivers (Koch et al., 2019).

SWE observation networks using different measurements methods have been deployed at a national scale in various countries to provide valuable in situ information. Russia maintains a vast long-term network of manual snow survey transects located in the vicinity of meteorological stations (Bulygina et al., 2011). National SWE measurements relying on manual snow survey are also available in several European countries such as Finland, Estonia, Ukraine and Turkey (Haberkorn, 2019). In the Western United States (US), manual SWE measurements are collected along permanent snow courses maintained by the US Department of Agriculture (Natural Resources Conversation Services, 1988) and in the Northeast by various state departments (McKay et al., 1994). Another source of SWE information in the Western US and Alaska is the snowpack telemetry (SNOWTELE) network using automatic snow pillows (Serreze et al., 1999). In situ SWE data from several of these networks are used for many applications. For example, they serve as reference data for the evaluation of a variety of large-scale gridded SWE products (e.g., Mortimer et al., 2020) including (i) snowpack models driven by meteorological reanalysis (e.g., Brun et al., 2013) (ii) passive microwave estimates combined with surface snow depth observation such as the GlobSnow product (Pulliainen et al., 2020) and (iii) regional climate models (e.g., Rasmussen et al., 2011). Gridded snow products can also be derived from manual and automatic in situ SWE measurements (e.g., Brown et al., 2019). In a hydrological context, SWE measurements from large-scale networks can inform the calibration of snow-related parameters in hydrological models (Sun et al., 2019) and the hydrologic design in snow-dominated environments (Yan et al., 2018). Studies on the impact of climate variability and change on snowpack evolution can also rely on snow measurements from national networks (e.g., Clark et al., 2001; Musselman et al., 2017). Manual snow surveys and automatic SWE stations with collocated snow depth (SD) measurements can provide information on the bulk density of the snowpack. These data have been used to develop and evaluate methods to estimate bulk snow density from snow depth and different predictors (e.g., Sturm et al., 2010; Hill et al., 2019; Ntokas et al., 2020) and to correct biases in large-scale gridded SWE products (Pulliainen et al., 2020).

Snow covers almost 85% of Canada's landmass during winter (December–March mean monthly snow cover extent for 1976 – 2019: 8.40 million km²; ECCC, 2020). In Canada, the vast majority of in situ SWE measurements are collected by provincial or territorial governments and hydropower companies. Despite the importance of these measurements for pan-Canadian applications in hydrology, climate monitoring and applied research, there is no central agency tasked with the



ongoing coordination, maintenance, and archiving data collected from these various agencies. SWE is not measured by the 65 pan-Canadian network of manual and automatic stations operated by Environment and Climate Change Canada (ECCC), except at select stations in northern Canada. ECCC manual and automatic stations only report SD (Brown et al., 2021). Historically, the Government of Canada's Atmospheric Environment Service (AES, now the Meteorological Service of Canada (MSC), part of ECCC) coordinated the reporting and archiving of snow survey data from various agencies (including AES) between 1955 and 1985 in the form of yearly Snow Cover Data (SCD) bulletins (Braaten 1998). Since the mid 1980s, 70 there has been no ongoing coordinated effort to archive snow survey data from various reporting agencies across Canada. The Canadian Historical Snow Survey dataset (CHSSD) was borne out of a data recovery effort of the mid 1990s, led by AES, which aimed to digitize the AES SCD books and combine it with available data from other agencies. This digital dataset, which was released in 2000, combined seven datasets from six different agencies (Braaten 1998). Methods and quality control procedures are outlined in Braaten (1998). This database was updated for the first time in 2004 (Hill, 2004). 75 The most recent update, released in 2019 (Brown et al., 2019), contained data up to and including the 2016/17 snow season. It is referred in the rest of the text as the 2019 CHSSD update. With each database update, some agencies (and sites) are added while others are not updated. The 2019 update included new sites in Yukon Territory, Northwest Territories, British Columbia and northern Manitoba. Some regions, such as Saskatchewan, Newfoundland and Labrador, and Quebec were not updated, either because a data custodian could not be identified or because an agency ceased snow survey operations or did 80 not allow data sharing.

Researchers working with the 2019 CHSSD update have reported a number of errors in metadata (e.g., incorrect snow survey coordinates and elevations) and the presence of a large amount of duplicate data. These issues, combined with the need for coordinated regular updates of in situ SWE observations, highlighted a need for a reworking of the CHSSD. The 85 objective of this paper is to provide a detailed description of the development of the Canadian historical SWE dataset (CanSWE), which replaces the CHSSD. The dataset name was changed to reflect the inclusion of automated SWE data and to highlight SWE as the dataset's primary variable of interest. The methodology presented here will serve as a basis for future regular and coordinated updates of the CanSWE dataset. The paper is organized as follows. Section 2 describes the different steps involved in creating the CanSWE dataset, including quality control. Section 3 gives an overview of the spatial and temporal coverage of the dataset and provides details on the data and metadata included in this dataset. Finally, Sect. 4 90 describes the data availability and Sect. 5 offers concluding remarks and perspectives about future updates of CanSWE.

2 Creation of the CanSWE dataset

The creation of the new Canadian historical SWE (CanSWE) dataset from the most recent version of the CHSSD involved three main steps as detailed on Fig. 1: (i) correction and cleaning of the 2019 CHSSD update, (ii) update of this cleaned dataset to July 2020 and addition of snow data from new stations and agencies, and (iii) consistent quality control (QC) of 95 the final dataset. These steps are described in the next sections.




Figure 1: CanSWE dataset creation workflow.

2.1 Cleaning of the 2019 CHSSD update

2.1.1 Correction of erroneous metadata

100 The 2019 CHSSD update released by Brown et al. (2019) contained snow data from 3124 individual stations across Canada. Prior to adding new data, the existing data were scrutinized to identify and resolve several issues raised by researchers working with the 2019 update. A preliminary analysis consisted of identifying stations with erroneous or incomplete metadata: (i) blank station name, (ii) placeholder text for station name, (iii) missing latitude and/or longitude, (iv) obvious errors in latitude and/or longitude and/or elevation. 91 such stations were identified and were manually checked. Valid data for station name and/or coordinates were obtained from databases of the originating agencies for 28 stations and the corresponding changes were made to the CHSSD. The remaining 63 stations with erroneous/incomplete metadata and their corresponding records of snow data were excluded, leaving 3061 individual stations in the dataset.

105

2.1.2 Merging and removal of duplicates

110 A second analysis was then carried out to remove duplicates and improve the consistency of the database prior to adding any new data. Duplicates are defined as stations with different station IDs and potentially with different metadata (station name and/or coordinates and/or elevation) having the same SWE observation for multiple dates. Duplicates usually consist of a pair of stations but can also be formed of three or four stations. Duplicates were introduced in previous updates of the CHSSD when snow data from various agencies were added to the CHSSD without ensuring that incoming data were already present in the CHSSD under a different station ID. In particular, instances of data duplication were introduced when the SCD 115 books were digitized. Stations from these books were all assigned a unique ID (station with the prefix “SCD-”) which differs



from that of the agency of origin. This generated a substantial amount of duplicate data during the period 1956 – 1986. Duplicates were also introduced in transboundary situations where a single station is archived by multiple agencies but under different station names and IDs.

Duplicates were identified through a combination of automated station selection and manual inspection. For each station in 120 the CHSSD, all stations within a 5-km radius were identified. Each group of neighbouring stations was then manually inspected for similarities in (i) snow measurements for matching dates, (ii) station location and (iii) station name. In most cases, all three of the criteria were satisfied to trigger a decision on whether a duplicate was identified. When a duplicate was identified, the matching stations were assigned a unique merging key to be used in subsequent consolidation. If no similar 125 stations to a reference station were identified in a group of neighbouring stations, the reference station was assigned its own merging key to aid in future updates to the CHSSD. Isolated stations without neighbours in a 5-km radius and without having been assigned a merging key were then inspected. For these isolated stations, the five nearest stations – regardless of distance – were identified, and the same similarities criteria were applied within each group of stations. As before, a unique merging key was assigned to each set of identified duplicate stations, or only to the reference station itself in the case of no 130 duplicates being identified. As a final check, for each station, a query over the full list of station names was carried out using a shortened version of the station name to identify stations in the CHSSD with similar names. These stations were then manually inspected for similarities as described above. In total, 842 groups of duplicate sites were identified: among them, 788 were comprised of two stations, 52 had three stations and two had four stations.

The final step consisted of removing the duplicates. For each merging key associated with a set of duplicate stations, a single 135 reference station ID was identified. When duplicates occurred between one or several IDs from the SCD books and an ID from an originating agency, the reference ID was taken as that of the originating agency. When duplicates occurred between IDs from several agencies (typical of transboundary situations), the station ID belonging to the provincial or territorial agency where the station is located was selected as the reference ID. Finally, when duplicates occurred between IDs in the SCD books or IDs from the same agency, the ID associated with the longest SWE record was selected as the reference ID. Records of snow depth and SWE from the reference station were retained and records from the duplicate stations inserted on 140 dates when no data were present in the records from the reference station. The metadata (coordinates and elevation) were taken from the reference station. The station IDs and names of the duplicate sites were retained as alternative IDs and names to facilitate future data enquiries using IDs and names present in the previous versions of the CHSSD. The duplicates' metadata and data were then removed from the CHSSD, for a total of 898 stations removed. Duplicated data were mostly removed over the period 1956-1986 (Fig. 2) due to conflicts between the data from the SCD books and the data from the 145 agency of origin. The cleaned version of the CHSSD contains 2163 individual stations and was used as the basis for the update presented in this paper.




Figure 2: Number of manual snow survey sites reporting at least one measurement between 1 February and 30 April in the original 2019 CHSSD update before (blue) and after (orange) the removal of duplicate stations.

150

2.2 Update of the CHSSD

Agencies collecting SWE measurements across Canada were contacted to obtain access to snow data (SWE and SD). Table 1 lists the twelve different agencies that contributed snow data to the update leading to the CanSWE dataset. These agencies correspond to provincial and territorial agencies responsible for streamflow forecasting and/or environmental monitoring and 155 hydropower companies. All Canadian provinces and territories are covered by this update, with the exception of Nova Scotia and Prince Edward Island where no snow measurement program is currently active at the provincial level. Nunavut is included through the manual snow survey data collected at stations managed by ECCC. Snow survey data were also provided by the Government of Manitoba, but their format precluded inclusion in CanSWE at this time.



160

Table 1: Agencies that provided snow measurements used in this study. The table makes the distinction between manual and automatic snow measurement stations. *Updated* stations correspond to stations already present in the 2019 CHSSD update for which data for the recent years (2017-2020) have been added whereas *new* stations were not present in the 2019 update of the CHSSD.

Agency	Manual stations		Automatic stations	
	Updated	New	Updated	New
Yukon Water Resources Branch	56	1	0	0
Government of Northwest Territories	47	24	0	0
Meteorological Service of Canada (ECCC)	14	0	0	0
British Columbia Ministry of Environment	160	1	55	35
Alberta Environment and Parks	112	1	0	16
Saskatchewan Water Security Agency	0	172	0	0
Manitoba Hydro	24	11	0	0
Ontario Power Generation	42	0	0	0
Ontario Ministry of Natural Resources and Forestry	232	8	0	0
Hydro Québec	0	80	0	64
Government of New Brunswick	56	2	0	0
Government of Newfoundland and Labrador	0	25	0	4
Total	743	325	55	119

165

The snow data provided by the different agencies consist of two types of measurements: (i) manual gravimetric snow surveys and (ii) automatic stations. Manual snow survey data were provided by the twelve originating agencies (Table 1). These data are collected by field observers using snow corers typically at five to ten points along a pre-determined survey line of 150-300 m selected to be representative of the land cover and terrain, although the precise methodology varies by 170 agency (Brown et al., 2019). Manual snow surveys are collected irregularly in time and the sampling frequency varies from one agency to another (Fig. 3). A majority of agencies conduct snow surveys once or twice per month during the snow season (Fig 3b) but several (e.g., Saskatchewan, Newfoundland and Labrador, Northwest Territories, Fig. 3a) only conduct measurements close to the peak snow accumulation and during the melting period for hydrological purposes. Automatic SWE measurements from snow pillows were provided by the British Columbia Ministry of Environment (hourly 175 measurements) and Alberta Environment and Parks (daily measurements). Hydro Quebec and the Government of Newfoundland and Labrador also provided hourly automatic SWE measurements from passive gamma radiation sensors (Choquette et al., 2008). Most of these automatic stations are also equipped with automatic measurements of snow depth using ultrasonic sensors.



The snow data and the corresponding metadata from the different agencies were obtained by direct download from web
180 pages or ftp servers, from requests on web data servers, or directly via email. Data were most often provided as csv or Excel
files but were also received as text bulletins, zxrp files, and ESRI Shapefiles. Python routines specific to each agency and
corresponding data format were written to process the data and metadata and arrange them in a consistent NetCDF format.
Snow depth and SWE data were included at a daily frequency. Hourly time series from automatic stations were first pre-
185 processed with a 24-h median filter to remove noise (Stone, 1995), especially in the snow depth time series from ultra-sonic
sensors. The filtered data corresponding to 18 UTC was then extracted from the hourly time series to get a daily value. 18 UTC
was selected since it corresponds to daytime in Canada. When available, the quality control flags from the originating
agency were added (see Sect. 3.3 for more details on QC). Finally, a station metadata record was constructed for each snow
survey site including station ID, data source agency, station name, latitude, longitude and elevation. This list of metadata
variables corresponds to that used in the 2019 CHSSD update (Brown et al., 2019). When elevation was not present in the
190 metadata from the originating agency it was extracted from the United States Geological Survey's National Elevation
Dataset (USGS NED, Gesh et al., 2002) at the position corresponding to the location of the snow survey site. The USGS's
NED covers all Northern America at 30-m resolution (expect parts of Alaska). A new code was also added in the metadata to
describe the method of SWE measurements at each snow survey site. This code follows the standards of the World
195 Meteorological Organization (WMO, 2019) and is described in Table 2.

195

Table 2: WMO SWE measurement codes (WMO, 2019)

Code	Method of SWE measurement
0	Multi point manual snow survey
1	Single point manual SWE measurement
2	Snow pillow or snow scale
3	Passive gamma
4	Global Navigation Satellite System/ Global Positioning System methods
5	Cosmic ray attenuation
6	Time domain reflectometry

As a last step, snow data from the different agencies and the corresponding metadata were added to the NetCDF file
containing the cleaned 2019 CHSSD update (Sect. 2.1). For stations already present in this file, the new snow data (from the
200 beginning winter of 2016-2017 to the end of July 2020) were simply appended to the existing time series. Data from new
snow survey sites were also added (Table 1). They consisted of newly established snow survey sites over the period 2017-
2020 and of historical snow survey sites that were not included in the 2019 CHSSD update. For example, historical manual
snow survey data were added from Hydro Quebec, the Saskatchewan Water Agency, the Governments of Northwest



Territories and the Government of Newfoundland and Labrador. The full historical archive of the snow pillow data from 205 Alberta Environment and Parks was also added to CanSWE. Finally, new data from automated passive gamma radiation sensors from Hydro Quebec and the Government of Newfoundland and Labrador were added. This is significant because no data from automatic stations from Eastern Canada was present in any previous version of the CHSSD. Duplicates created by the addition of new stations were identified and removed following the methods described in Sect. 2.1.2. Overall, 798 stations from the cleaned 2019 CHSSD update were updated to 2020 and 444 new stations were added. The CanSWE dataset 210 contains snow data for 2607 sites across Canada (Table 1). Finally, where both SWE and SD measurements were available, derived bulk snow density was calculated from SWE and SD and included in the final database.

2.3 Quality control of the final dataset

Quality control of CanSWE involved two main steps: (i) homogenization of data quality flags from the various reporting agencies, (ii) QC of the manual and automated SWE and SD records. Each of the twelve reporting agencies have their own 215 data archiving and reporting system with many agencies using data flags to identify possibly erroneous or problematic measurements. For example, it is not always possible to accurately measure trace amounts of snow or to estimate SWE in patchy snow conditions. In these instances, the measurement may be reported as 0 but a flag of T (trace) or P (patches) assigned. Most, but not all, agencies conduct their own internal quality control prior to releasing their data. Instances where data have been revised by the originating agency are often flagged, as are cases when the originating agency estimated the 220 SWE or SD value, or when problems were encountered during sampling. It is important to note that not all agencies use internal data flags and not all agencies flag the same types of issues. For example, snow patches are only reported by four originating agencies and trace amounts of snow are reported by eight.

The publicly released dataset of Brown et al. (2019) did not include agency flags. This information is an important addition to CanSWE. For each agency, we identified all existing flag values and their respective definitions. This process highlighted 225 two key issues: (i) the same flag value had a different meaning depending on the reporting agency and/or type of measurement, (ii) the same meaning was represented by different flag values depending on the reporting agency and/or type of measurement. A conversion table was created to reassign flag values from the various agencies into a single set of standard values and definitions. New flag values were added where necessary. The final dataset contains 14 and 11 agency flags for SWE (data_flag_snw) and SD (data_flag_snd) (Table 3), respectively, compared to 18 and 15 before 230 homogenization.



Table 3: Agency data flags used in CanSWE (see Sect.2.3)

Data flag	Definition
A	Sampling problems
B	Early or late sampling
C	Combination of A and B
E	Estimate
G	Measurement location >1 km from station coordinates. This flag is specific to manual snow survey data provided by the Saskatchewan Water Security Agency beginning in 2011.
L	8AM measurement not available. Flag is specific to snow pillow data provided by British Columbia Ministry of Environment.
M	Missing
P	Patches
Q	8AM measurement available after L code. Flag is specific to snow pillow data provided by British Columbia Ministry of Environment.
R	Revised data
T	Trace
Y	Precise sampling date not available - set to April 1 st . Flag is specific to manual snow survey data provided by the Government of the Northwest Territories.

Quality control (QC) of SWE and SD measurements included range thresholding and automated outlier detection. SWE and 235 SD QC flag variables (qc_snw and qc_snd, respectively), which are separate and distinct from the agency flag variables were added to the dataset (Table 4). The set of QC procedures implemented here is self-contained, applicable to the full dataset, and does not rely on any auxiliary data. Researchers using a subset of CanSWE for a local region or specific years may wish to conduct their own independent QC that may consider available temperature and precipitation information (e.g., Johnson and Marks, 2004; Yan et al., 2018).


240

Table 4: QC flags used in CanSWE (see Sect. 2.3)

QC flag	Definition
H	SD > 3 m (>8 m west of -113° longitude). SD set to <i>NaN</i>
M	Data masked (set to <i>NaN</i>) in a previous CHSSD update
V	Automatic SD-SWE measurement identified as outlier using robust Mahalanobis distance. SD and SWE set to <i>NaN</i>
W	SWE > 3000 kg m ⁻² (>8000 kg m ⁻² west of -113° longitude). SWE set to <i>NaN</i>
D	Derived bulk snow density failed 25 - 700 kg m ⁻³ threshold. SD, SWE and derived bulk snow density set to <i>NaN</i>



Range thresholds were used to identify spurious records in both automated and manual measurements. We adopted the thresholds outlined in Brown et al. (2019) for SWE and SD (0 – 3000 mm, 0 – 8000 mm for mountain) but a slightly more stringent range of 25 – 700 kg m⁻³ (as opposed to 50 – 1000 kg m⁻³) for snow density. These ranges are based on common ranges for SWE, SD and density from the literature (see Braaten, 1998). To maintain consistency of the long-term database we used the same definition for *mountain* as Brown et al. (2019) where *mountain* is defined as all land west of -113° longitude. Measurements outside the specified ranges were set to *NaN* and QC flags assigned according to Table 5. When a record failed the SWE (SD) threshold but not the SD (SWE) threshold only the SWE (SD) value was set to *NaN*. When a record failed the density threshold SWE, SD and density were set to *NaN*. Together, these steps masked one or both of SWE and SD in 0.17% and 5.5% of the manual and automated records, respectively. Table 5 lists the number and percentage of records masked at each QC step. The available data before and after QC is shown in Fig. 3. The small number of records flagged using the range thresholds is not surprising given that much of the data underwent QC in previous updates. The SWE and SD ranges are unchanged from previous updates so only data added in the current update have the possibility of being flagged. The density range is slightly more conservative so both new and old data were removed. Consequently, the density range flagged the most records when compared to the SWE and SD thresholds. Finally, when SWE (SD) measurements were masked (set to *NaN*) in previous CHSSD updates for any reason, the corresponding QC flag (qc_snow/qc_snd) was set to *M* (missing) in CanSWE. 0.3% and 1.6% of the manual and automated records, respectively, have *M* flags.



260 **Figure 3: CanSWE data by measurement type before (red) and after (grey) quality control described in Section 2.3 and Table 5.**
Snow pillows are deployed in British Columbia and Alberta; passive gamma radiation sensors are used by Hydro Quebec and the Government of Newfoundland and Labrador (Sect. 2.2).



Table 5: Number of manual and automated records masked (set to *NaN*) at each quality control step. Percentage relative to final dataset that has 1,072,229 records: 312,551 manual and 759,678 automated.

QC step	QC flag	Number of records flagged		% of total	
		manual	auto	manual	auto
SD threshold: SD > 3 m, 8 m west of 113°W	H	1	343	<0.01%	0.05%
SWE threshold: SWE > 3000 kg m ⁻² , 8000 kg m ⁻² west of 113°W	W	7	4405	<0.01%	0.59%
Derived bulk snow density threshold: 25 - 700 kg m ⁻³	D	517	37140	0.17%	5.0%
RMD threshold (Sect. 2.3)	V	n/a	1177	n/a	0.16%
Data masked in previous CHSSD updates	M	824	12156	0.26%	1.62%

We applied additional quality control measures to the automated data. We used the robust sample Mahalanobis distance (RMD) (Leys et al. 2018) to identify spurious SWE – SD data pairs as in Hill et al (2019). The RMD method is based on the traditional Mahalanobis Distance (MD) (Mahalanobis, 1930) which is the distance of a point from the mean of a multivariate distribution. It relies on the mean and covariance matrix of the multivariate distribution which are affected by outliers. Conversely, the RMD uses the Minimum Covariance Determinant (Rousseeuw, 1984) and is less sensitive to outliers than the MD (Leys et al., 2018). Because this method relies on a multivariate dataset only automated data with both SWE and SD observations were assessed. For each site with a minimum of 20 records, the RMD was calculated for each SWE – SD data pair. Following Hill et al. (2019), outliers were defined as a square RMD larger than the upper 0.001 quantile of a chi-squared distribution with p degrees of freedom (χ^2_p ; where p = number of dimensions of the data) (Gnanadesikan and Kettenring, 1972). For these records SWE, SD, and density were set to *NaN* and QC flags (qc_flag_snw, qc_flag_snd) assigned V (Table 4). This step masked an additional 0.16% of automated records. This method was not applied to the manual data due to their low temporal sampling frequency.

3 Spatial and temporal coverage of the final dataset

Figure 4 shows the location of the 2607 sites included in the CanSWE dataset. It highlights the concentration of observations in the southern populated regions of Canada. The majority the manual data are from Ontario and British Columbia (Fig. 5). Importantly, there are large data gaps in Nunavut and in the northern regions of Quebec, Ontario and Saskatchewan. The



285 update of historical data in Yukon and the Northwest Territories and the establishment of new sites in the Northwest Territories improved the spatial and temporal coverage of CanSWE in the western part of the Canadian Arctic compared to the 2019 CHSSD update. A few snow survey sites are found in the USA close to the border with Alberta and British Columbia. These sites are in the headwater catchments of rivers flowing into Canada. Similarly, data from northern parts of the USA state of Maine are included in the data from New Brunswick.






Figure 4: Snow measurements sites (manual and automatic) contained in CanSWE. The distinction is made between new historical sites added during this update (New), those (Updated (Up.)) present in the 2019 CHSSD update for which 2017-2020 snow data have been added and those (Historical (Hist.)) present in the 2019 CHSSD update for which no data have been added.






310

Figure 6: Evolution of the number of stations reporting SWE measurement per snow season for Canada (upper left) and each province and territory. A snow season corresponding to year Y, is defined as starting on September 1st of year Y-1 and ending on August 31st of year Y. Note the changing maximal values on the y-axis of the different sub-figures.

315 The first automatic stations measuring SWE (snow pillows) in Western Canada were deployed in British Columbia in the late 60s and early 70s. In Eastern Canada, the installation of automatic GMON sensors is more recent and started in 2009 in Quebec. In the CanSWE dataset, measurements from automatic stations first outnumbered those from manual snow surveys in 1988 and accounted for 89% of total SWE records for snow season 2020 (Fig. 7). The higher proportion of automated data is largely due to their higher measurement frequency compared to manual snow surveys. Finally, the number and frequency 320 of manual snow survey observations varies over the course of the snow season and between reporting agencies (Fig. 5). The



number of snow surveys increases over the accumulation season reaching a maximum during the period of peak snow accumulation with February and March having the highest numbers of manual snow surveys. Peak SWE occurs later in the northern regions and in mountainous regions, but the seasonal peak shown in Fig. 5 reflects the concentration of observations in southern Canada.



325

Figure 7: Same as Fig. 6 for the number of SWE records per snow season. The order of the provinces and territories is the same as in Fig. 6. Note the changing maximal values on the y-axis of the different sub-figures.

4 Data availability

The CanSWE dataset is distributed as a single file in NetCDF format that follows the Climate and Forecasts (CF) Metadata 330 Conventions (Hassel et al., 2017). It is available at <https://doi.org/10.5281/zenodo.4734372> (Vionnet et al., 2021). Table 6



describes the data and metadata contained in this file. Readme files in English and French are also included in the Zenodo data repository.

Table 6: Description of the variables (dimensions, metadata, data and quality-control flags) present in the netcdf file containing the CanSWE dataset

335

Type of variable	Variable name	Description	Dimension	Units
Dimension	station_id	Station identification code	station_id	(-)
	time	Time	time	day
	lat	Station latitude	station_id	deg. north
	lon	Station longitude	station_id	deg. east
	elevation	Station elevation	station_id	m
Metadata	source	Data provider	station_id	(-)
	station_name	Primary station name	station_id	(-)
	station_name_sec	Secondary station name	station_id	(-)
	station_name_ter	Tertiary station name	station_id	(-)
	station_id_sec	Secondary station identification code	station_id	(-)
	station_id_ter	Tertiary station identification code	station_id	(-)
	type_mes	Method of measurement for SWE ¹	station_id	(-)
	snw	Snow water equivalent (SWE)	station_id, time	kg m ⁻²
	sd	Snow depth (SD)	station_id, time	m
Data	den	Snowpack bulk density	station_id, time	kg m ⁻³
	data_flag_snw	Agency data quality flag for SWE ²	station_id, time	(-)
	data_flag_sd	Agency data quality flag for SD ²	station_id, time	(-)
Quality-control	qc_flag_snw	CanSWE quality control flag for SWE ³	station_id, time	(-)
	qc_flag_sd	CanSWE quality control flag for SD ³	station_id, time	(-)

¹ see Table 2 for more details; ² see Table 3 for more details, ³ see Table 4 for more details.

5 Conclusion

The Canadian historical SWE dataset (CanSWE) contains measurements of snow water equivalent (SWE) and snow depth (SD) and derived bulk snow density for an ensemble of sites across Canada. This dataset includes the results of extensive cleaning and quality control of the existing Canadian Historical Snow Survey Dataset (CHSSD), the addition of new historical data sources, and an update to July 2020 with data from 12 organizations and their partners. New stations from Hydro Quebec, the government of Newfoundland and Labrador, the government of Northwest Territories and the

340



Saskatchewan Water Security Agency were added and improved the spatial coverage. A systematic quality control was applied to identify and remove outliers in SWE, SD and corresponding density. The CanSWE dataset presented in this paper 345 includes data from 2607 manual and automatic snow survey sites across Canada over the period 1928 – 2020. We anticipate that these data will be used for (i) climate monitoring and research, (ii) evaluation of land surface and hydrological models, (iii) development and evaluation of snow products, and (iv) other snow-related activities. Regular updates are required to make such datasets useful for the community. Ideally, these updates should be carried out on a yearly basis at the end of each snow season. The data ingestion routines and automated quality control procedures developed under this project will allow 350 future updates to be carried out in a timely and systematic fashion. We also hope that these efforts will provide opportunities to include new sources of in situ SWE information such as data collected at long-term experimental sites maintained by academic partners.

Author contribution

VV, CM and RB initiated the 2021 update of the CHSSD leading to CanSWE. VV coordinated the update effort. VV and 355 CM reached out partners agencies to obtain snow data and processed them. MB developed the routines for the automatic detection of duplicates and conducted systematic identification of duplicates. CM developed the quality control routines and data flag consolidation. LA identified duplicates in the 2019 update of the CHSSD and systematically tested the intermediate versions of CanSWE and identified remaining issues, that were then corrected. All authors contributed to the preparation of the manuscript.

360 Competing interest

The authors declare that they have no conflict of interest.

Acknowledgements

The following agencies are gratefully acknowledged for the high quality of their snow data collection programs and for providing historical data to the new CanSWE dataset: Alberta Environment and Parks, British Columbia Ministry of 365 Environment and partners, Environment New Brunswick, Government of Newfoundland and Labrador, Government of Northwest Territories, Manitoba Hydro, Meteorological Service of Canada (ECCC), Ontario Ministry of Natural Resources and Forestry and partners, Ontario Power Generation, Saskatchewan Water Security Agency and Yukon Water Resource Branch. Many thanks are expressed to the field observers collecting manual snow survey data across Canada and the persons in charge of the maintenance of automatic stations deployed across the country. Hydro Québec's 370 https://www.hydroquebec.com, last access: 19 April 2021) data are available under the terms of a Creative Commons



Attributions – Non Commercial – Share A Like 4.0 International License (<https://creativecommons.org/licenses/by-nc-sa/4.0/>, last access: 19 April 2021).

References

Beaumont, R. T.: Mt. Hood pressure pillow snow gage, *J. Appl. Meteorol.*, 4, 626–631, [https://doi.org/10.1175/1520-0450\(1965\)004<0626:MHPPSG>2.0.CO;2](https://doi.org/10.1175/1520-0450(1965)004<0626:MHPPSG>2.0.CO;2), 1965

375 Berghuijs, W. R., Woods, R. A., Hutton, C. J., and Sivapalan, M.: Dominant flood generating mechanisms across the United States. *Geophys. Res. Lett.*, 43, 4382-4390, <https://doi.org/10.1002/2016GL068070>, 2016

Biemans, H., Siderius, C., Lutz, A. F., Nepal, S., Ahmad, B., Hassan, T., von Bloh, W., Wijngaard, R. R., Wester, P., Shrestha, A. B., and Immerzeel, W. W.: Importance of snow and glacier meltwater for agriculture on the Indo-Gangetic Plain, *Nature Sustainability*, 2, 594-601, <https://doi.org/10.1038/s41893-019-0305-3>, 2019

380 Braaten, R.: Canadian Snow Water Equivalent Database Main Documentation. Environment Canada, Climate Processes and Earth Observation Division. Main Documentation, 25 p, http://data.ec.gc.ca/data/climate/systems/canadian-historical-snow-survey-data/Braaten_1998_Canadian_SWE_Database.pdf, 1998

Brown, R. D., Fang, B., and Mudryk, L.: Update of Canadian historical snow survey data and analysis of snow water equivalent trends, 1967–2016. *Atmos. Ocean*, 57, 149-156, <https://doi.org/10.1080/07055900.2019.1598843>, 2019

385 Brown, R. D., Smith, C., Derksen, C., and Mudryk, L.: Canadian in situ snow cover trends for 1955–2017 including an assessment of the impact of Automation. *Atmos. Ocean*, (in press), <https://doi.org/10.1080/07055900.2021.1911781>, 2021.

Bulygina, O., Groisman, P. Ya., Razuvaev, V., and Korshunova, N.: Changes in snow cover characteristics over Northern Eurasia since 1966, *Environ. Res. Lett.*, 6, 045204, <https://doi.org/10.1088/1748-9326/6/4/045204>, 2011

390 Clark, M. P., Serreze, M. C., and McCabe, G. J.: Historical effects of El Niño and La Niña events on the seasonal evolution of the montane snowpack in the Columbia and Colorado River Basins. *Wat. Resour. Res.*, 37, 741-757, <https://doi.org/10.1029/2000WR900305>, 2001

Choquette, Y., Lavigne, P., Nadeau, M., Ducharme, P., Martin, J. P., Houdayer, A., and Rogoza, J.: GMON, a new sensor for snow water equivalent via gamma monitoring. In Proceedings: Whistler 2008 International Snow Science Workshop (p. 802), 2008

395 ECCC (Environment and Climate Change Canada): Canadian Environmental Sustainability Indicators: Snow cover: www.canada.ca/en/environment-climate-change/services/environmental-indicators/snow-cover.html (last access: 23 March 2021), 2020

Fierz, C. R., Armstrong, R. L., Durand, Y., Etchevers, P., Greene, E., McClung, D. M., ... Sokratov, S. A.: The international classification for seasonal snow on the ground. Paris: UNESCO/IHP. Retrieved from <https://unesdoc.unesco.org/ark:/48223/pf0000186462>, 2009



Gesch, D., Oimoen, M., Greenlee, S., Nelson, C., Steuck, M., and Tyler, D.: The National Elevation Dataset. Photogramm. Eng. Rem. S., 68, 5-32, 2002

Gnanadesikan, R. and Kettenring, J: Robust estimates, residuals, and outlier detection with multiresponse data, Biometrics, 405 28, 81-214, <https://doi.org/10.2307/2528963>, 1972

Haberkorn, A. (Ed.): European Snow Booklet, 363 pp., <https://doi.org/10.16904/envidat.59>, 2019

Hassell, D., Gregory, J., Blower, J., Lawrence, B. N., and Taylor, K. E.: A data model of the Climate and Forecast metadata conventions (CF-1.6) with a software implementation (cf-python v2.1), Geosci. Model Dev., 10, 4619–4646, <https://doi.org/10.5194/gmd-10-4619-2017>, 2017.

410 Henkel, P., Koch, F., Appel, F., Bach, H., Prasch, M., Schmid, L., Schweizer, J., and Mauser, W.: Snow water equivalent of dry snow derived from GNSS carrier phases. IEEE T. Geosci. Remote, 56(6), 3561-3572, <https://doi.org/10.1109/TGRS.2018.2802494>, 2018

Hill, J. Snow CD Archive Update Journal. Environment Canada. Documentation, March 2004, 8 p, 2004

Hill, D. F., Burakowski, E. A., Crumley, R. L., Keon, J., Hu, J. M., Arendt, A. A., Wikstrom Jones, K., and Wolken, G. J.: 415 Converting snow depth to snow water equivalent using climatological variables, The Cryosphere, 13, 1767–1784, <https://doi.org/10.5194/tc-13-1767-2019>, 2019.

Hoyer, S. and Hamman, J.: xarray: N-D labeled Arrays and Datasets in Python. J. Open Res. Soft., 5, p.10, <https://doi.org/10.5334/jors.148>, 2017

Johnson, J. B.: A theory of pressure sensor performance in snow, Hydrol. Process., 18, 53–64, 420 <https://doi.org/10.1002/hyp.1310>, 2004

Johnson, J. B., and Marks, D.: The detection and correction of snow water equivalent pressure sensor errors. Hydrol. Process., 18, 3513-3525, <https://doi.org/10.1002/hyp.5795>, 2004

Kinar, N. J. and Pomeroy, J. W.: Measurements of the physical properties of the snowpack, Rev. Geophys., 53, 481–544, <https://doi.org/10.1002/2015RG000481>, 2015

425 Koch, F., Henkel, P., Appel, F., Schmid, L., Bach, H., Lamm, M., Prasch, M., Schweizer, J., and Mauser, W.: Retrieval of snow water equivalent, liquid water content, and snow height of dry and wet snow by combining GPS signal attenuation and time delay. Wat. Resour. Res., 55, 4465-4487, <https://doi.org/10.1029/2018WR024431>, 2019

Kodama, M., Nakai, K., Kawasaki, S., and Wada, M.: An application of cosmic-ray neutron measurements to the determination of the snow-water equivalent, J. Hydrol., 41, 85–92, 1979.

430 Leys, C., Klein, O., Dominicy, Y., and Ley, C.: Detecting multivariate outliers: Use a robust variant of the Mahalanobis distance, J. Exp. Soc. Psychol., 74, 150-156, <https://doi.org/10.1016/j.jesp.2017.09.011>, 2018.

McKay, M., Wilks, D. S. and Schmidlin, T. W.: Quality-controlled snow water equivalent data for the Northeastern United States. Northeast Regional Climate Center Data Set DS 93-1. 5 pp., 1994

Mahalanobis, P.C.: On tests and measures of groups divergence, Journal of Asiatic Sociology of Bengal, 26, 541–588, 1930.



435 Magnusson, J., Nævdal, G., Matt, F., Burkhart, J. F., and Winstral, A.: Improving hydropower inflow forecasts by assimilating snow data. *Hydrol. Res.*, 51, 226–237, <https://doi.org/10.2166/nh.2020.025>, 2020

Mortimer, C., Mudryk, L., Derksen, C., Luoju, K., Brown, R., Kelly, R., and Tedesco, M.: Evaluation of long-term Northern Hemisphere snow water equivalent products, *The Cryosphere*, 14, 1579–1594, <https://doi.org/10.5194/tc-14-1579-2020>, 2020.

440 Musselman, K. N., Clark, M. P., Liu, C., Ikeda, K., and Rasmussen, R: Slower snowmelt in a warmer world. *Nature Climate Change*, 7, 214-219, <https://doi.org/10.1038/nclimate3225>, 2017

Natural Resources Conservation Service (NRCS), Snow surveys and water supply forecasting, *Agric. Inf. Bull. U.S. Dep. Agric.*, 536, 1988

Ntokas, K. F. F., Odry, J., Boucher, M.-A., and Garnaud, C.: Using an ensemble of artificial neural networks to convert snow depth to snow water equivalent over Canada, *Hydrol. Earth Syst. Sci. Discuss.*, <https://doi.org/10.5194/hess-2020-566>, in review, 2020.

445 Paquet, E., Laval, M., Basalaev, L.M., Belov, A., Eroshenko, E., Kartyshov, V., Struminsky, A., and Yanke, V.: An Application of Cosmic-Ray Neutron Measurements to the Determination of the Snow Water Equivalent, *Proceedings of the 30th International Cosmic Ray Conference*, Merida, Mexico, 3–11 July, 2008.

450 Pulliainen, J., Luoju, K., Derksen, C., Mudryk, L., Lemmetyinen, J., Salminen, M., Ikonen, J., Takala, M., Cohen, J., Smolander, T., and Norberg, J.: Patterns and trends of Northern Hemisphere snow mass from 1980 to 2018. *Nature*, 581, 294-298, <https://doi.org/10.1038/s41586-020-2258-0>, 2020

Rasmussen, R., Liu, C., Ikeda, K., Gochis, D., Yates, D., Chen, F., Tewari, M., Barlage, M., Dudhia, J., Yu, W., Miller, K., Arsenault, K., Grubišić, V., Thompson, G., and Gutmann, E.: High-resolution coupled climate runoff simulations of seasonal snowfall over Colorado: A process study of current and warmer climate, *J. Climate*, 24, 3015–3048, <https://doi.org/10.1175/2010JCLI3985.1>, 2011

455 Serreze, M. C., Clark, M. P., Armstrong, R. L., McGinnis, D. A., and Pulwarty, R. S.: Characteristics of the western United States snowpack from snowpack telemetry (SNOWTELE) data. *Wat. Resour. Res.*, 35, 2145-2160, <https://doi.org/10.1029/1999WR900090>, 1999

460 Stone., D. C.: Application of median filtering to noisy data. *Can. J. Chem.*, 73, 1573-1581. <https://doi.org/10.1139/v95-195>, 1995

Sturm, M., Taras, B., Liston, G. E., Derksen, C., Jonas, T., and Lea, J.: Estimating snow water equivalent using snow depth data and climate classes, *J. Hydrometeorol.*, 11, 1380–1394, <https://doi.org/10.1175/2010JHM1202.1>, 2010.

Sun N, H Yan, M Wigmosta, R Skaggs, R Leung, and Z Hou. 2019. Regional snow parameters estimation for large-domain hydrological applications in the western United States. *J. Geophys. Res.-Atmos.*, <https://doi.org/10.1029/2018JD030140>, 2019



Vionnet, V., Fortin, V., Gaborit, E., Roy, G., Abrahamowicz, M., Gasset, N., and Pomeroy, J. W.: Assessing the factors governing the ability to predict late-spring flooding in cold-region mountain basins, *Hydrol. Earth Syst. Sci.*, 24, 2141–2165, <https://doi.org/10.5194/hess-24-2141-2020>, 2020.

Vionnet V., Mortimer C., Brady M., Arnal L. and Brown R., Canadian historical Snow Water Equivalent dataset (CanSWE, 470 1928–2020), Zenodo, <https://doi.org/10.5281/zenodo.4734372>, 2021

WMO (World Meteorological Organization): Guide to hydrological practices, Volume 1: Hydrology – From measurements to hydro-logical information, 6th Edn., WMO, Geneva, WMO-No. 168,296 pp., 2008.

WMO (World Meteorological Organization): Global Cryosphere Watch: Improvements in the international reporting of Snow Depth, WIGOS Newsletter, 5, 3-4, <https://community.wmo.int/wigos-newsletters-archive>, 2019

475 Yan H, N Sun, M Wigmosta, R Skaggs, Z Hou, and R Leung: Next-generation intensity-duration-frequency curves for hydrologic design in snow-dominated environments. *Wat. Resour. Res.*, 54, 1093–1108, <https://doi.org/10.1002/2017WR021290>, 2018