

One year of attenuation data from a commercial dual-polarized duplex microwave link with concurrent disdrometer, rain gauge and weather observations

Anna Špačková¹, Vojtěch Bareš¹, Martin Fenc¹, Marc Schleiss³, Joël Jaffrain⁴, Alexis Berne⁴, and Jörg Rieckermann²

¹Dept. of Hydraulics and Hydrology, Czech Technical University in Prague, Prague, the Czech Republic

²Dept. of Urban Water Management, Eawag: Swiss Federal Institute of Aquatic Science and Technology, Dübendorf, Switzerland

³Dept. of Geoscience and Remote Sensing, Delft University of Technology, Delft, Netherlands

⁴Environmental Remote Sensing Laboratory, EPFL, Lausanne, Switzerland

Correspondence: Anna Špačková (anna.spackova@cvut.cz)

Abstract. Commercial microwave links (CML) in telecommunication networks can provide relevant information for remote sensing of precipitation and other environmental variables, such as path-averaged drop size distribution, evaporation, or humidity. The CoMMon field experiment (COmmercial Microwave links for urban rainfall MONitoring) mainly focused on the rainfall observations by monitoring a 38-GHz dual-polarized CML of 1.85 km path length at a high temporal resolution (4 s), as well as a collocated array of five disdrometers and three rain gauges over one year. The dataset is complemented with observations from five nearby weather stations. Raw and pre-processed data, which can be explored with a custom static HTML viewer, are available at <https://doi.org/10.5281/zenodo.4923125> (Špačková et al., 2021). The data quality is generally satisfactory to the further analysis and potentially problematic measurements are flagged to help the analyst identify relevant periods for specific study purposes. ~~The analyses conducted so far suggest that the data are reliable and of satisfactory quality.~~ Finally, we encourage potential applications and discuss open issues regarding future remote sensing with CMLs.

1 Introduction

Accurate information on precipitation is important for many applications from agriculture to pluvial flooding (Chwala and Kunstmann, 2019). Commercial microwave links (CMLs) from telecommunication networks represent a promising source of information ([Graf et al., 2020](#); [Overeem et al., 2016](#)) as their signals are affected by both liquid and solid precipitation. Presently, there are an estimated 5 million CMLs (Ericsson, 2019) deployed around the world and the widespread coverage of mobile phone networks includes sparsely or completely ungauged areas. CMLs [can](#) observe precipitation close to the ground and can be queried remotely from network operation centres within a few seconds enabling operational applications such as precipitation nowcasting or hydrological forecasts and early flood warnings. Currently, only a small number of open datasets for studying the small-scale variability of rainfall and its relationship to CML attenuation data are available. In the Netherlands, Van Leth et al. (2018) provided measurements from three collocated microwave links near Wageningen. Gires et al. (2018)

published a dataset of two months of disdrometer data using three collocated devices and provided a dataset of disdrometer data collected during a measurement campaign testing a rainfall simulator (Gires et al., 2020). Unfortunately, datasets of CML attenuation and observations of precipitation microphysics with a high temporal resolution lack the ability to fully tap into this potential and identify current knowledge gaps (see below).

25 For example, the analysis of Chwala and Kunstmann (2019) suggests that operational datasets from real-world case studies and methods, e.g., for baseline removal, are not openly available. As telecommunication providers are reluctant to share the properties of CMLs, the majority of datasets and important meta information is available only to the research groups involved. However, openly available datasets of precipitation microphysics and CML attenuation, ideally with detailed weather information, are essential to test available theories and benchmark the prediction capabilities of developed methods, which were
30 mostly tuned and tested on non-public datasets. Nevertheless, there are openly available tools for CML rainfall information processing and mapping (e.g., Overeem et al., 2016; Chwala et al., 2020).

The goal of this paper is to publish the unique dataset and documentation of the "CoMMon" (Commercial Microwave links for rainfall MONitoring) experiment consisting of a 1-year-long field campaign in Dübendorf (CH), during which attenuation data from a 38-GHz dual-polarized CML were collected, together with precipitation observations from rain gauges and dis-
35 drometers deployed along the CML path in high temporal resolution (Fig. 1a). In addition, weather data, such as temperature, dew point, relative humidity, and wind speed from two nearby and three more distant weather stations, were acquired. Noteworthy features of the data are: i) a dual-polarized CML, rather than single-polarization; ii) an array of disdrometers in addition to rain gauges; and iii) outdoor units of the CML operated with weather-protecting shields (Fig. 2), to investigate the impact of antenna wetting, for approximately half of the experimental period.

40 This paper will, first, briefly describe the theory of rain retrieval and highlight the importance of drop size distribution. Second, we present the experimental set up, sensor specifications, experimental campaign ~~and~~, structure of the collected datafiles, and discuss data quality and reliability. The third section presents the database and the html viewer provided to explore the data efficiently. The fourth section discusses potential future applications of the CoMMon dataset.

2 Data and methods

45 2.1 The importance of drop size distribution for rain retrieval from commercial microwave links

The attenuation of a ~~microwave link~~ CML signal is related to the drop size distribution along ~~their path and the its path~~. The observed attenuation can be used to calculate the rain rate between the two end nodes of a CML. The observed total loss L_t (dB) is the difference of transmitted and received signal power. Rainfall-induced specific attenuation k (dB km⁻¹), due to raindrops passing the path of the microwave propagation, can be formulated as:

$$50 \quad k = \max\left(\frac{L_t - A_b - A_w}{l}, 0\right) \quad (1)$$

where k is the specific attenuation (in dB km⁻¹), A_b (dB) is background (baseline) attenuation (ITU-R, 2019), A_w (dB) is wet antenna attenuation and l (km) is path length. A_b is usually determined during dry weather periods (Fencl et al., 2017; Polz et

al., 2020) without dew or rain occurrence (cf. Fig. 7, Fig. 8) and is assumed to have the same level during rainfall. A_w describes the impact of radome wetting. The importance of accurate estimation of A_w increases in the case of short CMLs when its contribution to the observed attenuation is substantial (Pastorek et al., 2018).

The power-law relationship approximates the relation between attenuation caused by raindrops and rainfall intensity (Atlas and Ulbrich, 1977):

$$k = a \cdot R^b \quad (2)$$

where R is the rain rate in mm h^{-1} and parameters a and b are related to the ~~microwave link~~ CML characteristics (frequency, polarization) and drop size distribution (DSD) (Olsen et al., 1978). Value b is close to one for frequencies between 20 GHz and 40 GHz (ITU-R, 2005). While electromagnetic scattering for hydrometeors is generally complex (Eriksson, 2018), the specific attenuation for liquid precipitation can be estimated from the drop size distribution:

$$k(f) = 4.343 \times 10^3 \int_D C_{\text{ext}}(D, f) N(D) dD \quad (3)$$

where f is the frequency, D (mm) denotes equi-volumetric drop diameter, $N(D)$ ($\text{m}^{-3} \text{mm}^{-1}$) is the number of drops per unit volume in a drop diameter interval (drop size distribution, DSD) and $C_{\text{ext}}(D, f)$ is the extinction cross section at frequency f in m^2 which determines the attenuation from a single drop.

The accuracy of the power-law approximation (Eq. 2) can be assessed by comparing Eq. 3 to the rain rate R (Eq. 4) of the observed drop spectrum (Atlas and Ulbrich, 1977):

$$R = 0.6 \times 10^{-3} \pi \int_D v(D) D^3 N(D) dD \quad (4)$$

where $v(D)$ is the terminal fall velocity (in m s^{-1}) of a drop and D (mm) denotes equi-volumetric drop diameter.

2.2 Field campaign

The campaign took place in Dübendorf, Switzerland. Figure 1a presents the layout of the CoMMon field campaign with all sites (white pins) where the disdrometers and rain gauges were deployed. The two antennas were located at sites 1 (Dübendorf) and 5 (Wangen) and the ~~microwave link~~ CML was 1.85 km long (blue line). To assess wet antenna attenuation, antenna radomes and outdoor units were weather-protected by large custom-made PVC shields for approximately half of the experimental period (Fig. 2). The area between the antennas consists mainly of an airport, sport fields, agricultural fields, a shopping mall and a highway. Five laser optical disdrometers were placed at sites 2, 3, 4 and 5. The disdrometers at site 2 were collocated to enable quality control and the quantification of observation uncertainties. ~~For the campaign were also used three~~ Three tipping bucket rain gauges were also used at sites 2, 4 and 5 (Table 1). The location of each site was chosen based on a compromise between proximity to the ~~microwave link~~ CML path, accessibility, and protection against vandalism. The devices were situated as far as possible from roof edges to avoid wind disturbances. The instrument types and specifications are provided in section 2.3 below and in the metadata sheets in the Zenodo repository.




Figure 1. a) Layout of the CoMMon field campaign. The radio units are deployed at the end sites (site 1 and site 5). The path of the CML is in blue. Disdrometer (P - Parsivel) and rain gauge (RG - rain gauge) positions are indicated by white pins. Site 2 contained two collocated disdrometers for data quality control. Except for site 3, all rain gauges have a collocated disdrometer. The MeteoSwiss weather stations (yellow pins) are within 6 to 11 km away. Two additional weather stations (green) are located at the Dübendorf airport (site 11 and site 29). b) Longitudinal profile of terrain under the CML path.

The campaign was launched on 9 March 2011 when the disdrometers and tipping bucket rain gauges were deployed. On 17 March 2011 two radio units of the CML were installed. The collected dataset is enhanced by the meteorological data (MeteoSwiss, 2020) obtained from MeteoSwiss (the Federal Office for Meteorology and Climatology in Switzerland) for the duration of the campaign. The weather stations are located in Zürich within 6 to 10 km of the experimental area (Table 2). Moreover, observations from two other weather stations located at the airport (Table 3) provided additional data for the time period from 1 March 2011 to 26 September 2011. The campaign ended on 21 March 2012.




Figure 2. (top) Outdoor unit of the Dual-Pol [MiniLink-MINI-LINK](#) and the antenna radome without (left) and with custom shield (right). (bottom) Timeline of the operational period of the shielding of antenna radomes.

2.3 Instrumentation

90 2.3.1 Commercial microwave link

The CML consisted of two MINI-LINK outdoor units manufactured by Ericsson comprising a radio and a [Mini-Link-MINI-LINK](#) antenna (ANT20.3 38 HPX, Mod. No. UKY 210 75/DC15 SH) with a diameter of 30 cm. The MINI-LINK is a duplex dual-polarized link which has two communication channels with a horizontal and a vertical polarization. The resolution of the transmitted power (Tx) was 1 dBm and for received power (Rx) it was 1/3 dBm expressed to one decimal place. The horizontally polarized [EM-electromagnetic \(EM\)](#) waves were transmitted at frequencies of 38'657.5 MHz from site 1 and 37'397.5 MHz from site 5. The vertically polarized EM waves were transmitted at frequencies of 38'650.5 MHz from site 1 and 37'390.5 MHz from site 5. The length of the link was 1850 m. The antenna at site 1 was deployed 6 m above ground and the antenna at site 5 was deployed 5 m above ground. The [link-path-is-CML-path-was](#) not horizontal, the antennas at sites 1 and 5 were located 442 m AMSL and 491 m AMSL respectively (with 1.52° to the horizontal plane). Measurement intervals were changed from the original 15-min-setup to 4 s (instantaneous reading). Data were acquired by a software application based on Simple Network Management Protocol (Wang et al., 2012). During the measurement campaign, plastic shields were installed on the antennas on 6 October 2011 to avoid water films on the antenna radomes and to eliminate wet antenna attenuation due to rainfall. However, the wet antenna attenuation due to dew cannot be prevented.

The metadata sheets for the CML can be found in the Zenodo repository.

Table 1. Locations of the sites and deployed devices.

Site	Geographic coordinates	Devices and ID
1	47°24'4.800" N, 8°37'43.100" E 436 m AMSL	CML antenna
2	47°24'17.640"N, 8°37'47.640"E 446 m AMSL	PARSIVEL disdrometers ID: P40 and P41 Tipping bucket rain gauge ID: RG03
3	47°24'24.480"N, 8°37'57.720"E 455 m AMSL	PARSIVEL disdrometer* ID: P22
4	47°24'49.680"N, 8°38'8.520"E 435 m AMSL	PARSIVEL disdrometer ID: P21 Tipping bucket rain gauge ID: RG02
5	47°24'59.760"N, 8°38'16.800"E 486 m AMSL	PARSIVEL disdrometer ID: P20 Tipping bucket rain gauge ID: RG04 CML antenna

*Note: the only site with unrestricted access

105 2.3.2 Laser optical disdrometers

Raindrop information was collected by the 1st generation of the PARSIVEL optical disdrometer manufactured by OTT Hydromet and retrofitted by EPFL-LTE to allow for remote access and data transfer (Jaffrain et al., 2011). The horizontal laser beam had an area of 54 cm². The beam was oriented perpendicularly to the dominant wind direction in order to limit undersampling and splashing. The devices were deployed as far as possible from possible sources of turbulence and wake (roof edges and other obstacles). The cob webs were not specifically prevented and they were not observed during the field visits ~~were not observed~~. The measurement principle is based on the attenuation in received voltage and on the time required for the passage of a particle through the laser beam. From this, the terminal fall velocity and the equi-volumetric drop diameter can be estimated. The PARSIVEL rain rate (parameter 05 in Appendix C) retrieval is linked to the drop diameter. Drops larger than 1 mm are

Table 2. Location of the MeteoSwiss weather stations.

Weather station	Name	MeteoSwiss STN	Geographic coordinates [m]
ZH_Aff	Zürich Affoltern	83	47°25'39.780"N, 8°31'03.060"E 443 m AMSL
ZH_Flun	Zürich Fluntern	71	47°22'41.310"N, 8°33'57.030"E 556 m AMSL
ZH_Klo	Zürich Kloten	59	47°28'46.640"N, 8°32'09.890"E 436 m AMSL

Table 3. Location of the airport weather stations.

Weather station	Geographic coordinates [m]
Site 11	47°24'06.1194"N, 8°38'09.4164"E
Site 29	47°23'43.6158"N 8°39'34.2066"E

assumed to have an oblate shape with linearly decreasing axis ratio (i.e., the axis ratio between the vertical and horizontal dimensions of the drops) down to a value of 0.7 for 5 mm drops (Battaglia et al., 2010; Löffler-Mang and Joss, 2000). Data were categorized into 32 non-equidistant velocity classes and 32 non-equidistant diameter classes (see Appendix A and B). The first two diameter classes were always empty since they were outside the measurement range of the device. The sampling resolution was 30 s.

The metadata sheets for the laser optical disdrometers can be found in the Zenodo repository.

120 2.3.3 Tipping bucket rain gauges

The collocated tipping bucket rain gauges (3029-1, Précis Mécanique) were the same type of model and had been dynamically calibrated (Humphrey et al., 1997). The devices were deployed as far as possible from possible sources of turbulence and wake (roof edges and other structures). Deployed 50 cm from the ground (35 cm of the device itself and 15 cm of piece of wood and concrete), they had a sampling area of 400 cm². Their bucket content of 4 g corresponded to the resolution of 0.1 mm of rain. The rain gauges were equipped neither with wind protection shields nor with heating, but only 6 snow and 4 mixed

precipitation events were observed during the campaign. The loggers had a time resolution 0.1 s and their time drift was less than 2 min per month. The data were saved in the internal memory and downloaded on-site.

The metadata sheets for the tipping bucket rain gauges can be found in the Zenodo repository.

2.3.4 Weather stations

130 Comprehensive weather data are provided by three additional weather stations operated by MeteoSwiss and located 8.9 km (Affoltern), 5.9 km (Fluntern), and 10.9 km (Kloten) from the experimental site 3 (Fig. 1a) in azimuths 285°, 238°, and 318°, respectively. Data were extracted using CLIMAP software provided by MeteoSwiss. The metadata sheets for the MeteoSwiss stations can be found in the Zenodo repository.

In addition, there were two stations of the Automatic Weather Observation Systems (MIDAS IV, Vaisala) at the Dübendorf airport. The MIDAS IV system employed two sensors at both ends of the runway as these weather stations provide data primarily used for airport operations. The temporal resolution varied between 3 and 60 s depending on the weather parameter. Complete metadata sheets could ~~not be unfortunately~~ unfortunately not be compiled from an information provided by Dübendorf airport staff.

2.4 Measured variables

140 CML attenuation data are available between 18 March 2011 and 15 April 2012. The data are given "as is", without any processing or filtering. The columns of the microwave link datafiles are organised as described in Appendix E. The sampling interval of the instantaneous readings was 4 s. Missing observations are denoted by "NA". Figure 3 presents an example of the observed received power for 22 June 2011.

The disdrometers collected data from 11 March 2011 (for P41 from 16 April 2011) to 29 April 2012, and the disdrometer files provided raw data collected by PARSIVELs in 30 s resolutions (see Appendix C for details). The eight types of precipitation (parameter 07 and 08 correspond to precipitation codes according to SYNOP, see Appendix D) were classified based on a velocity-diameter relationship (Löffler-Mang and Joss, 2000). The code corresponds to the specific precipitation type and its intensity (OTT, 2006). Parameter 16 registered the status of the optical lenses. The raw spectrum of 32x32 drop counts is in parameter 21 (diameter classes x velocity classes). Figure 4 illustrates the observations of the disdrometers.

150 The tipping bucket rain gauges collected data from 12 March 2011 (for RG04 from 17 March 2011) to 21 March 2012 (for RG04 to 20 March 2012). The rain gauge data had been partly processed. The regular temporal sampling resolution was set to 1 min and the leap year (29 February 2012) had been accounted for. The columns of the datafiles were organised as described in Appendix F. Missing measurements are denoted by "NA".

The comparison of cumulative rain of the three rain gauges and five disdrometers for the whole period of the campaign is presented in Fig. 5. It can be seen that both types of devices are in general in good agreement.

The atmospheric variables of the MeteoSwiss weather stations, collected for the time period from 1 March 2011 to 22 April 2012, are presented in Appendix G. There are 14 parameters in total, including air temperature, air pressure, wind, precipitation, sun radiation, sunlight duration, and dew point. The variables were recorded with a 10-min time step resolution.

Received power (x10) [dBm] - 2011-06-22 - CML measurements without the shield




Figure 3. Example of measured received power for 22 June 2011 when antennas were not shielded. Green colours label the direction from site 1 to site 5 (D->W) and blue W->D. Light colours depict horizontal polarizations and dark colours vertical polarization. Red vertical lines indicate NA values (not present during this event).




Figure 4. Example of disdrometer data for 22 June 2011 at site 3 (disdrometer P22). (left) Scatterplot of the number of drops according to the velocity (terminal fall speed) and size (equi-volumetric drop diameter) classes. (right) Temporal evolution of the DSD.

The airport weather station data, collected for the time period from 1 March 2011 to 26 September 2011, contain monitored standard meteorological parameters such as temperature, dew point, relative humidity, pressure, rain intensity, wind speed and direction with columns organised as described in Appendix H.

All measured variables are recorded in UTC time.




Figure 5. Comparison of cumulative rain of the three rain gauges and five disdrometers. There were recorded several outages, suspicious measurements and technical issues, such periods are further described in the Data quality and reliability chapter. Despite this, both types of devices are, in general, in good agreement.

2.5 Data quality and reliability

Field visits were conducted on 15 April 2011, 6 July 2011, 19 October 2011, 1 November 2011 and 16 March 2012 to maintain the instruments. In general, very little maintenance was necessary on the instruments during the frequent field visits. On 15 April 2011, the minor levelling corrections and data collections for all the rain gauges were done. On 6 July 2011, the batteries were replaced in all the rain-gauge data loggers and the data were collected. On 19 October 2011, RG04 was inspected and no problems were found. On 1 November 2011, RG02 and RG04 were inspected with no reported issues. On 16 March 2012, RG02 was found blocked by a leaf and with empty batteries. The RG02 lagged laptop time by approximately 7 minutes. The difference between RG03 time and UTC was -00:05:31. The difference for RG04 was -00:02:28. Only the leap year had been corrected. The rain gauges were dynamically calibrated in the laboratory.

The CML had almost no technical issues causing problems with data collection. Nevertheless, the unit at site 1 (Dübendorf) was not working properly in the period between 16 September 2011 and 9 October 2011 where no data is available.

The disdrometers P20, P21 and P22 did not provide uninterrupted data between 14 October 2011 and 4 November 2011. All disdrometers partially malfunctioned between 7 December 2011 and 14 January 2012; and between 26 January 2012 and 3 February 2012 from the undersupplied solar panels during winter. A significant overestimation of rainfall occurred on 7 and 8 February 2012 when P22 measured around 300 mm of cumulative rainfall. Unfortunately, site 3 did not provide data from a collocated rain gauge for comparison. The filter presented in Jaffrain and Berne (2011) can be used to remove dubious measurements. Disdrometer locations and orientations were chosen to minimize wind disturbances, staying as far away from sharp corners and tall objects as possible. Cob webs were not observed during the field visits.

The rain gauges were deployed in adequate distance from trees and bushes to minimize the influence of wind whirling and clogging by leaves. However, one of the tipping bucket rain gauges faced technical issues that constrained the data collection. The greatest data availability gap, due to low batteries, happened at site 4 (RG02) between 6 July 2011 and 16 March 2012.

Figure 5 presents a comparison of cumulative rain collected by the rain gauges and disdrometers and shows a good temporal match of measured data. The outages of disdrometers between December and February, described above, caused the underestimation of rain amounts during this period. RG02 corresponds to RG03 for the entire time period when it was in operation. RG04 was blocked from the middle of June 2011 until the 6 July 2011. There was also unrealistic rainfall recorded by RG04 on 24 August 2011. In total, 139.7 mm of rainfall were measured within 2.5 h, probably an artefact due to vandalism. The collocated disdrometer (P20) also showed a dissimilar temporal evolution of rain rate to the other disdrometers. Both quality issues appeared at site 5 and were probably caused by the moving of the instrumentation during lawn mowing.

The data from weather stations of MeteoSwiss and the airport are rather continuous and consistent.

[The Appendix J presents the data availability of the devices during the campaign period.](#)

3 The database

3.1 Description of raw data

The raw data files are stored in various ASCII formats in folders based on the device/weather station and are available at daily resolutions. The files are organised as depicted in Fig. 6. The filename format examples are presented for each folder.

3.2 Tool/HTML viewer

To facilitate the efficient exploration of the data plots, the html file makes it possible to readily plot pre-defined views of one selected day. The folders are related to the main data sources: the CML, the disdrometers, the rain gauges, the MeteoSwiss and airport weather stations. The intensity of red colour in the campaign calendar describes the daily cumulative rainfall depth, based on RG03, which enables the user to choose the most interesting days and explore them further. Once the day is selected, the plots in each folder are displayed.

There are eight pre-defined views in the drop-down menu in the viewer. The first view plots CML data accompanied by data from RG03 from site 2 which is located in the middle of the link path. Views two and three present rainfall intensities from the disdrometers, missing values and drop size distributions. The fourth view displays rain gauge data and its missing values. Views five and six display the data and missing values from the airport weather stations and the last two views concern the data and missing values from the MeteoSwiss weather stations. Note that November 2012 was extremely dry, therefore no rainfall was recorded.

Table 4 summarizes the daily plots of measured quantities. All plotted quantities are accompanied by a plot of missing values. Each column in those figures represents one hour of the day. The proportional amount of missing values in each hour is displayed in red.




Figure 6. The organisation scheme of the files in folders.

4 Applications of the dataset and outlook

The following section contains a short review of important open issues related to rainfall estimation using microwave links for which the CoMMon field campaign provides relevant data and could give valuable input in future research.

215 4.1 Former applications

4.1.1 Dry/wet classification and baseline estimation

Based on the dataset, Wang et al. (2012) developed a new algorithm for classifying dry/wet periods and estimating baseline attenuation using a Markov switching model which outperformed a previous method based on the standard deviation of link attenuation over a moving time window by Schleiss and Berne (2010). Using factor graph theory and robust local linear regression, Reller et al. (2011) and Schatzmann et al. (2012) used the CoMMon dataset to develop two alternative baseline models with similar offline/online performances.

220

Table 4. Summary of quantities and their units displayed as daily plots in the html viewer.

CML	Received power (x10) [dBm] Transmitted power [dBm]
Disdrometers	Rain rate [mm h ⁻¹] Cumulative rainfall [mm] Drop diameter and fall velocity distribution Temporal evolution of drop diameter
Rain gauges	Rain rate [mm h ⁻¹] Cumulative rainfall [mm]
MeteoSwiss weather stations	Sun radiation (10 min mean) [W m ⁻²] Sunlight duration (10 min mean) [min] Temperature (10 min) [°C] Wind direction (10 min mean) [°] Wind speed (10 min mean) [m s ⁻¹]
Airport weather stations	Dew point [°C] Atmospheric pressure [hPa] Relative humidity [%] Rain intensity [mm h ⁻¹] Cumulative rainfall [mm] Temperature [°C] Wind direction (10 min mean) [°] Wind speed (10 min mean) [m s ⁻¹]

4.1.2 Wet antenna attenuation

Based on data collected during the CoMMon experiment, Schleiss et al. (2013) quantified the magnitude and dynamics of wet-antenna attenuation (WAA) affecting commercial microwave links at 38 GHz. They found WAA values in the order of 1-2 dB, with an upper bound at about 2.3 dB. Furthermore, WAA increased exponentially during the first 5-20 min of rain and decreased exponentially as soon as the rain stopped. Figure 7 presents an example of the attenuation pattern caused by a wet antenna. The rate at which WAA decreased after an event showed substantial variation, ranging from a few minutes to several hours depending on temperature, wind and humidity. In a follow-up study, Fencil et al. (2014) assessed the effectiveness of direct antenna shielding for mitigating WAA compared with post-processing techniques. They found that antenna shielding helps to substantially reduce bias in rainfall estimates. However, shielding did not outperform model-based corrections as signals from shielded antennas still experienced attenuation, even when the face of the radome was completely dry. Whether this is caused by the attenuation of side-lobes or whether these are effects caused by changes in the scattering and reflection behaviour of the




Figure 7. Wet antenna attenuation pattern. Rainfall causes signal resulting in residual wetness on the surface of the radomes. The return of baseline attenuation to previous dry-weather levels is attributed to the drying of the antenna radomes (Van Leth et al., 2018). The same behaviour was observed by new E-bands and reported recently in Fencel et al. (2020).

~~built environments~~surrounding buildings, such as nearby walls, roofs or impervious surfaces, during wet weather is currently unknown.

235 There are still several unresolved questions related to WAA, such as the effect of horizontal/vertical polarization on WAA magnitude or the quantification of WAA during fog and dew events (Fig. 8). For example, de Vos et al. (2019) showed that errors in CML quantitative precipitation estimates are the largest for observations during late night and early morning periods when dew is more likely to form on antennas. Van Leth et al. (2018) observed additional attenuation in the order of 3 dB during foggy weather conditions and whenever dew was present on the antennas. To be precise, Van Leth et al. (2018) explicitly
 240 mention that the theoretical upper limit for attenuation by fog droplets themselves is about 0.75 dB at 38 GHz for a 1 km path and a very high liquid water content of 0.8 g m^{-3} . Therefore, no more than 1.5 dB km^{-1} can be expected due to the fog itself and the rest is probably due WAA. So reasonable estimates of attenuation during heavy fog are in the order of 2-3 dB of WAA + 1-1.5 dB km^{-1} for the fog itself. ~~If we wanted to get more insight into this, we would need heated antennas~~ Heated antennas would be needed to prevent the formation of dew and/or air blowers ~~to would~~ blow away the water during fog events. However,
 245 modelling these effects remains challenging, since the dew-related wetting depends on the weather conditions, as well as on the condition/presence of hydrophobic radome cover. The CoMMon dataset could help gain new insight into these issues, for example, by further investigating WAA due to dew formation on antenna radomes (Fig. 8).

4.1.3 DSD retrieval and DSD related errors

Attenuation data of CMLs operating at different frequencies or polarizations could be, in theory, used for estimating path-
 250 averaged raindrop size distributions (e.g., Rincon and Lang, 2002). Research on this issue is still ongoing. Recently, Song et al. (2019) used a simulation study to illustrate how to retrieve DSDs from dual-frequency dual-polarization links. Another study




Figure 8. Wet antenna attenuation due to dew formation causes substantial attenuation from approx. 18:00 on 27 November 2011 to 7:00 on 28 November 2011.

by van Leth et al. (2020) based on a similar approach showed that reasonable performance on selected events and idealized conditions can be achieved. However, retrieved DSD parameters are not always reliable and large uncertainties remain due to quantization noise, baseline estimation and wet-antenna attenuation. These could possibly be reduced by using the data to update prior knowledge on empirical drop size distributions using Bayesian data analysis (Cao et al., 2010).

Also, the high-quality CoMMon dataset could provide the evidence base to test different retrieval techniques and to assess their strengths and limitations.

The data will be useful to design outage-free radio communication systems better. Detailed data on rainfall microphysics and microwave attenuation from operational devices can be extremely contributive to radio engineers (Kvicera et al., 2009).

260 4.2 Outlook

There are still many unsolved issues regarding how to effectively retrieve precipitation from the-CML attenuation in praxis. Given the high temporal resolution, the CoMMon data might be most useful in improving our understanding of antenna wetting, baseline dynamics and the impact of variable DSDs.

First, wet antenna attenuation and dew formation on antennas are phenomena that need to be described more precisely to avoid the overestimation of rainfall. Several studies have suggested that correcting for wet antenna attenuation can significantly enhance results (Leijnse et al., 2008; Pastorek et al., submitted). Most probably, corrections cannot be based on frequency and signal dynamics only, since the atmospheric state around the CML varies. In other words, temperature, relative humidity, radiation and wind probably have a more significant impact on the drying time of the antennas as well as the conditions prior to wetting. To what extent machine learning (Habi and Messer, 2018), trained on many CoMMon-type datasets, can provide an empirical solution remains to be seen.

Second, the baseline of transmitted minus received power is often approximated as constant, even though substantial variations during dry weather have been reported (Wang et al., 2012) and there is little evidence that the baseline remains stationary during wet periods. Different dry-wet weather classification approaches were presented in Schleiss and Berne (2010), Overeem et al. (2011) or Polz et al. (2020). A benchmarking activity with many datasets from different sites and climatic regions is still
275 lacking.

Scattering theory suggests that a larger variation of drop size distribution challenges more precise retrieval for longer links (Leijnse et al., 2010). The disdrometer observations in the CoMMon dataset can also be used to build simulators making it possible to better understand the attenuation-rainfall relation and assess CML rainfall retrieval uncertainties related to variable DSDs (Berne and Uijlenhoet, 2007; Schleiss et al., 2012). For example the assumption that the path-integrated DSD can be
280 represented by a simple unimodal distribution (e.g., a Gamma or exponential) might not be true for longer links, as rainfall rates and DSDs can exhibit significant heterogeneity along the path of the link. Similarly, for highly localized rain showers, only a small fraction of the link might actually experience rain and not all antennas might be equally wet/dry at a given time.

Variable DSDs also represent major uncertainties at CMLs with higher frequency bands. Although, to date, most CMLs use frequencies from 5 GHz to 40 GHz, the spectrum is currently further extended to 80 GHz. Recently, Fencel et al. (2020) used
285 PARSIVEL observations from the CoMMon dataset to simulate rainfall retrieval from an E-band CML which demonstrated that these may be promising tools for sensing light rainfall which is challenging for lower frequencies due to the quantization of the attenuation data (Berne and Schleiss, 2009). In a similar fashion, CMLs are "blind" regarding extremely high intensities as attenuation due to such high intensities drops below the receiver threshold of the hardware and causes outages of the CML (cf. event on 5 August 2011). How this can be solved by "inputtinginterpolating" missing observations based on signals from
290 nearby sensors (Mital et al., 2020), remains to be seen.

Melting snow causes large attenuation of EM waves at frequencies commonly used by CMLs (ITU-R, 2015). Upton et al. (2007) identified periods with melting snow by analysing attenuation data of dual-frequency microwave links operating at 12.8 GHz/17.6 GHz and 10.5 GHz/17.5 GHz. Ostrometzky et al. (2015) suggested using CMLs operating at multiple frequencies to distinguish between periods with snow, melting snow and rainfall and thus improve estimation of total accumulated
295 precipitation. Attenuation of EM waves by ice particles, however, remains challenging to simulate due to complex shapes of these hydrometeors. Moreover, ice particles containing liquid water interact with EM waves in substantially different manner (Eriksson, 2018).

5 Data accessibility

Data from CML, disdrometers and rain gauges, and nearby weather stations are available with data files stored in the Zenodo
300 repository at <https://doi.org/10.5281/zenodo.4923125> (Špačková et al., 2021). The citation should be used as follows:

- For the paper: Špačková, A., Bareš, V., Fencel, M., Schleiss, M., Jaffrain, J., Berne, A., and Rieckermann, J.: One year of attenuation data from a commercial dual-polarized duplex microwave link with concurrent disdrometer, rain gauge and weather observations, Earth Syst. Sci. Data, submitted.

- For the database: Špačková, A., Jaffrain, J., Wang, Z., Schleiss, M., Fencel, M., Bareš, V., Berne, A., and Rieckermann, J.:
305 One year of attenuation data from a commercial dual-polarized duplex microwave link with concurrent disdrometer, rain gauge
and weather observations, [Data set], Zenodo, <https://doi.org/10.5281/zenodo.4923125>, 2021.

The dataset is available for reuse under a CC BY 4.0 license. License terms apply.

6 Conclusions

The data from the CoMMon field campaign described in this paper is relevant for the remote sensing of rainfall, as well as for
310 the design of outage-free terrestrial wireless communication systems. The unique dataset provides a comprehensive package of
attenuation data from a 38 GHz dual-polarized [microwave link CML](#) with concurrent disdrometer and rain gauge measurements
in (sub-)minute resolution. In addition, meteorological data from the weather stations of MeteoSwiss and Dübendorf airport
were included. The main conclusions are:

- 315 – The remote sensing of precipitation and related atmospheric phenomena, such as dew, remains a relevant problem. Using
signals from commercial telecommunication microwave links to learn about these phenomena seems promising because
they cover sparsely or completely ungauged regions and can be queried remotely and fast. The open CoMMon dataset
makes a unique contribution by providing dual-polarized transmitted and received power levels, as well as ground-level
observations of precipitation microphysics and local weather. It fosters the interconnection of datasets which can be used
to better understand scattering phenomena and benchmark retrieval methods.
- 320 – The dataset represents a duration of one year and contains data from i) a single 38-GHZ dual polarized CML with a
length of 1.85 km; ii) collocated observations of five disdrometers; iii) three rain gauges; and iv) observations from five
nearby weather stations. Specific highlights are, first, that the antenna radomes were protected by custom shielding for
approximately half of the period of the campaign, thus making it possible to investigate the impact of antenna wetting
which is still considered a major disturbance for rainfall retrieval. Second, the data are provided in sub-minute resolutions
325 making it possible to investigate the detailed dynamics of the involved processes. Third, the dataset contains periods with
rain but also periods during which ice hydrometeors including snow and melting snow occurred (see Appendix I).
- Although the experimental campaign faced expected difficulties regarding sensor malfunctioning, data outages, etc.,
these episodes are well documented and, thus, do not compromise the ~~and~~-usefulness of the dataset (Appendix J). The
provided static HTML viewer also makes it easy to explore the data by pre-configured views of daily time series. For
330 example, by focusing on days with intense or little precipitation, typical dynamics of the observed processes can be
screened effortlessly.
- The dataset contains unique evidence regarding several processes such as the wetting and drying of antenna radomes
and outdoor units or the impact of temperature and wind. We encourage several applications, from investigating base-
line separation to wetting phenomena, such as dew, which had much slower dynamics in comparison to rain-induced
335 attenuation, to the retrieval of drop-size distributions from the joint analysis of horizontal and vertical polarizations.

- In the future, the CoMMon dataset can be used to further investigate challenging issues in the remote sensing of rainfall, such as the classification of dry/wet periods, space-time variability of DSDs or even the analysis of fade margins for better radio network design.

Appendix A: PARSIVEL drop diameter classes

Table A1. PARSIVEL drop diameter classes

Class number	Particle diameter classes	
	Class Average (mm)	Class Spread (mm)
1	0.062	0.125
2	0.187	0.125
3	0.312	0.125
4	0.437	0.125
5	0.562	0.125
6	0.687	0.125
7	0.812	0.125
8	0.937	0.125
9	1.062	0.125
10	1.187	0.125
11	1.375	0.250
12	1.625	0.250
13	1.875	0.250
14	2.125	0.250
15	2.375	0.250
16	2.750	0.500
17	3.250	0.500
18	3.750	0.500
19	4.250	0.500
20	4.750	0.500
21	5.500	1.000
22	6.500	1.000
23	7.500	1.000
24	8.500	1.000
25	9.500	1.000
26	11.000	2.000
27	13.000	2.000
28	15.000	2.000
29	17.000	2.000
30	19.000	2.000
31	21.500	3.000
32	24.500	3.000

Table B1. PARSIVEL drop velocity classes

Class number	Particle velocity classes	
	Class Average (m s ⁻¹)	Class Spread (m s ⁻¹)
1	0.050	0.100
2	0.150	0.100
3	0.250	0.100
4	0.350	0.100
5	0.450	0.100
6	0.550	0.100
7	0.650	0.100
8	0.750	0.100
9	0.850	0.100
10	0.950	0.100
11	1.100	0.200
12	1.300	0.200
13	1.500	0.200
14	1.700	0.200
15	1.900	0.200
16	2.200	0.400
17	2.600	0.400
18	3.000	0.400
19	3.400	0.400
20	3.800	0.400
21	4.400	0.800
22	5.200	0.800
23	6.000	0.800
24	6.800	0.800
25	7.600	0.800
26	8.800	1.600
27	10.400	1.600
28	12.000	1.600
29	13.600	1.600
30	15.200	1.600
31	17.600	3.200
32	20.800	3.200

Appendix C: PARSIVEL raw data parameters

Table C1. PARSIVEL raw data parameters

Position	Parameter	Format	Units
1	Date and Time	YYYY-MM-DD hh:mm:ss	UTC
2	Record number	-	-
3	Logger temperature	-	°C
4	Logger voltage	-	V
5	PARSIVEL rain rate	-	mm h ⁻¹
6	PARSIVEL rain amount	-	mm
7	Precipitation code 4680	-	-
8	Precipitation code 4677	-	-
9	PARSIVEL radar reflectivity	-	dBZ
10	Visibility in the precipitation	-	m
11	Laser amplitude	-	-
12	Number of particles detected	-	-
13	PARSIVEL temperature	-	°C
14	PARSIVEL heating current	-	A
15	PARSIVEL voltage	-	V
16	PARSIVEL status	-	-
17	Absolute amount	-	mm
18	Transmit time	-	-
19	Field N	Vector of 32 values	m ⁻³ mm ⁻¹
20	Field v	Vector of 32 values	m s ⁻¹
21	Raw data	Vector of 1024 values	-
22	Communication error	-	-

Parameter 16 registers the status of the optical lenses (0 – everything OK, 1 – laser protective glass is dirty, but measurements are still possible, 2 – laser protective glass is dirty, partially covered, no further usable measurements are possible, 3 – laser damaged).

Appendix D: Precipitation code according to SYNOP

Table D1. Precipitation code according to SYNOP

No precipitation		Tab. 4680	Tab. 4677
		00	00
Drizzle			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 0.1	51	51
moderate	$\geq 0.1 \dots < 0.5$	52	53
heavy	≥ 0.5	53	55
Drizzle with rain			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 2.5	57	58
moderate	$\geq 2.5 \dots < 10.0$	58	59
heavy	≥ 10.0	58	59
Rain			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 2.5	61	61
moderate	$\geq 2.5 \dots < 10.0$	62	63
heavy	≥ 10.0	63	65
Rain, drizzle with snow			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 2.5	67	68
moderate	$\geq 2.5 \dots < 10.0$	68	69
heavy	≥ 10.0	68	69
Snow			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 1.0	71	71
moderate	$\geq 1.0 \dots < 4.0$	72	73
heavy	≥ 4.0	73	75
Snow grains			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
₋₁₎	> 0	77	77
Soft hail			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 1.0	87	87
mod./heavy	≥ 1.0	88	88
Hail			
Intensity	Rain rate [mm/h]	Tab. 4680	Tab. 4677
light	< 2.5	89	89
mod./heavy	≥ 2.5	89	90

¹⁾ no classification made

Appendix E: CML: measured parameters

Table E1. CML: measured parameters

Column no.	Parameter	Units
1	Date and time, format YYYY-MM-DD hh:mm:ss	UTC
2	Tx W \rightarrow D, H	dBm
3	Rx x10 W \rightarrow D, H	dBm
4	Tx W \rightarrow D, V	dBm
5	Rx x10 W \rightarrow D, V	dBm
6	Tx D \rightarrow W, H	dBm
7	Rx x10 D \rightarrow W, H	dBm
8	Tx D \rightarrow W, V	dBm
9	Rx x10 D \rightarrow W, V	dBm

Transmitted power (Tx); Received power (Rx); Horizontal polarization (H); Vertical polarization (V); site 5 - Wangen (W); site 1 - Dübendorf (D); \rightarrow direction of the signal

Appendix F: Rain gauges: measured parameters

Table F1. Rain gauges: measured parameters

Column no.	Parameter	Units
1	Date and time, format YYYY-MM-DD hh:mm:ss	UTC
2	Number of tips per time step	-
3	Rain rate	mm h ⁻¹
4	Rain amount per time step	mm
5	Cumulative rain amount	mm

Table G1. MeteoSwiss weather station parameters

Column no.	MeteoSwiss name	Description	Measurement sampling
1	STN	MeteoSwiss station number	
2	time	Measurement time, format YYYY-MM-DD hh:mm:ss	
3	tre200s0	Air temperature 2 m above ground	Instantaneous (10 min resolution)
4	tko200ax	Air temperature 2 m above ground	Half-day max
5	tko200an	Air temperature 2 m above ground	Half-day min
6	presta0	Air pressure at the height of the station	Instantaneous (10 min resolution)
7	flk101z1	Gust wind speed	Maximum
8	rre150z0	Precipitation	10-min sum
9	rco150z0	Precipitation duration	10-min sum
10	sre000z0	Sunlight duration	10-min sum
11	dkl010z0	Wind direction	10-min mean
12	flk101z0	Wind speed	10-min mean
13	pp0qs0	Air pressure at sea level	Instantaneous (10 min resolution)
14	pp0qnhs0	Air pressure at sea level in standard atmosphere	Instantaneous (10 min resolution)
15	gre000z0	Sun radiation	10-min mean
16	tre005s0	Air temperature at 5 cm above grass	Instantaneous (10 min resolution)
17	tde200s0	Dew point at 2 m above ground	Instantaneous (10 min resolution)

Appendix H: Airport weather station parameters**Table H1.** Airport weather station parameters

Column no.	Parameter	Units
1	Date and time, format YYYY-MM-DD hh:mm:ss	UTC
2	Temperature	°C
3	Dew point	°C
4	Relative humidity	%
5	Pressure	hPa
6	Rain intensity	mm h ⁻¹
7	Wind speed	m s ⁻¹
8	Wind direction	°

Appendix I: Table of precipitation events

Table II. Example of precipitation event table. Complete table can be found in the Zenodo repository.

	[GMT]	Starting time	[GMT]					[mm h ⁻¹]					Peak mean R	[mm]			Predominant Prec. type (%)	
			Ending time	20	21	22	40	41	Mean amount	Max R	Sta max R	Min Ra		Sta min Ra	Max Ra	Sta max Ra		
1	17.03.2011	14:06:00	17.03.2011	18:46:30	x	x	x	-	-	-	4.11	5.22	21	3.25	20	4.38	21	Rain (100%)
2	19.03.2011	00:03:30	19.03.2011	16:20:00	x	x	x	-	-	-	5.29	6.50	20	6.38	40	14.43	21	Rain (99.8%)
3	28.03.2011	05:14:30	28.03.2011	10:54:30	x	x	x	-	-	-	3.95	7.95	21	3.18	40	4.46	21	Rain (99.3%)
4	31.03.2011	11:42:00	31.03.2011	17:07:30	-	-	-	x	x	-	6.39	6.39	40	4.39	40	4.39	40	Rain (100%)
5	04.04.2011	02:44:00	04.04.2011	09:51:00	x	x	x	-	-	-	9.42	15.62	40	14.97	20	19.14	21	Rain (99.8%)
6	04.04.2011	13:31:30	04.04.2011	15:30:00	x	x	x	-	-	-	3.62	10.96	22	1.32	20	2.82	21	Rain (100%)
7	27.04.2011	12:57:30	27.04.2011	15:42:30	x	x	x	-	-	-	31.50	72.52	21	2.74	40	5.05	20	Rain (97.9%)
8	28.04.2011	18:00:00	28.04.2011	19:55:00	x	x	x	-	-	-	15.34	35.32	40	0.70	20	3.21	40	Rain (99.4%)
9	03.05.2011	03:42:00	03.05.2011	07:02:30	x	x	x	-	-	-	21.62	39.87	21	6.80	40	8.90	21	Rain (98.7%)
10	11.05.2011	17:06:30	11.05.2011	18:16:00	x	x	x	-	-	-	19.73	43.20	21	1.30	20	3.77	41	Rain (100%)
11	12.05.2011	07:41:00	12.05.2011	10:27:30	-	x	-	x	x	-	19.45	53.20	21	0.08	22	7.13	21	Rain (99.6%)
12	12.05.2011	14:24:00	12.05.2011	18:14:30	x	x	x	-	-	-	57.53	80.91	20	11.76	22	16.73	21	Rain (96.7%)
13	14.05.2011	12:50:30	14.05.2011	14:47:00	x	x	x	-	-	-	3.63	4.82	22	0.87	20	1.17	21	Rain (100%)
14	14.05.2011	14:49:00	15.05.2011	02:02:30	x	x	x	-	-	-	5.48	10.56	40	13.53	20	16.70	21	Rain (99.9%)
15	15.05.2011	12:01:30	15.05.2011	13:20:30	x	x	x	-	-	-	10.83	35.22	20	2.30	40	4.45	20	Rain (91.2%)
16	15.05.2011	15:10:30	15.05.2011	16:17:30	x	x	x	-	-	-	10.16	14.78	21	2.74	40	3.79	21	Rain (98.9%)
...

Appendix J: Data availability scheme




Figure J1. Data availability scheme. Red: more than 30 % NAs. Blue: 10 % to 30 % NAs. Green: less than 10 % NAs.

Author contributions. AŠ processed the data, with support from JJ, plotted the results and wrote the manuscript with support from MS, JR, MF and VB. The section regarding the applications of the dataset and outlook was written by MS. JJ and AB provided valuable feedback on the manuscript. JJ, MS, ZW, JR and AB designed the experimental layout and installed and operated the CML, rain gauges and disdrometers. AB and JR conceived the study and were in charge of overall direction and planning.

Competing interests. The authors declare that they have no conflict of interest.

Acknowledgements. The authors greatly acknowledge financial support from the Eawag and the Czech Science Foundation (GACR) project SpraiLINK 20-14151J. We thank all the persons who helped to perform the campaign. We want to mention Zhe Wang, Tobias Doppler, Richard Fankhauser, Vahab Rostampour (Eawag), Paul Stump, Angelo di Boni (RUAG), Christoph Wirz (Dübendorf airport) and Andre Studzinski, (EPFL). We thank Martin Kryl for support with the implementation of the html viewer.

References

- Atlas, D. and Ulbrich, C. W.: Path- and Area-Integrated Rainfall Measurement by Microwave Attenuation in the 1–3 cm Band, *J. Appl. Meteor.*, 16(12), 1322–1331, doi:10.1175/1520-0450(1977)016<1322:PAAIRM>2.0.CO;2, 1977.
- 360 Battaglia, A., Rustemeier, E., Tokay, A., Blahak, U., and Simmer, C.: PARSIVEL Snow Observations: A Critical Assessment. *J. Atmos. Oceanic Technol.*, 27 (2), 333344, doi:10.1175/2009JTECHA1332.1, 2010.
- Berne, A., and Uijlenhoet, R.: Path-averaged rainfall estimation using microwave links: Uncertainty due to spatial rainfall variability, *Geophys. Res. Lett.*, 34, L07403, doi:10.1029/2007GL029409, 2007.
- 365 Berne, A., and Schleiss, M.: Retrieval of the rain drop size distribution using telecommunication dual-polarization microwave links. In the 34th conference on radar meteorology, American Meteorological Society, Boston, https://ams.confex.com/ams/34Radar/techprogram/paper_155668.htm, 2009.
- Cao, Q., Zhang, G., Brandes, E. A., and Schuur, T. J.: Polarimetric Radar Rain Estimation through Retrieval of Drop Size Distribution Using a Bayesian Approach, *Journal of Applied Meteorology and Climatology*, 49(5), 973-990, <https://journals.ametsoc.org/view/journals/apme/49/5/2009jamc2227.1.xml>, 2010.
- 370 Chwala, C., and Kunstmann, H.: Commercial microwave link networks for rainfall observation: Assessment of the current status and future challenges. *WIREs Water*. 2019;6:e1337. <https://doi.org/10.1002/wat2.1337>, 2019.
- Chwala, C., Keis, F., Graf, M., Sereb, D., and Boose, Y.: pycomlink software package, v0.2.5, available at: <https://github.com/pycomlink/pycomlink>, last access 6 March 2021, 2020.
- 375 de Vos, L. W., Overeem, A., Leijnse, H., and Uijlenhoet, R.: Rainfall Estimation Accuracy of a Nationwide Instantaneously Sampling Commercial Microwave Link Network: Error Dependency on Known Characteristics. *J. Atmos. Oceanic Technol.*, 36, 1267–1283, <https://doi.org/10.1175/JTECH-D-18-0197.1>, 2019.
- Ericsson. Ericsson microwave outlook. Retrieved from <https://www.ericsson.com/4a8c1f/assets/local/reports-papers/microwave-outlook/2019/ericsson-microwave-outlook-report-2019.pdf>, last access: 16. December 2020, 2019
- 380 Eriksson, P., Ekelund, R., Mendrok, J., Brath, M., Lemke, O., and Buehler, S. A.: A general database of hydrometeor single scattering properties at microwave and sub-millimetre wavelengths, *Earth Syst. Sci. Data*, 10, 1301–1326, <https://doi.org/10.5194/essd-10-1301-2018>, 2018.
- Fencl, M., Rieckermann, J., and Bareš, V.: Eliminating bias in rainfall estimates from microwave links due to antenna wetting, *EGU General Assembly 2014*, Geophysical Research Abstracts, Vol. 16, EGU2014-13107, Vienna, Austria, 2014.
- 385 Fencl, M., Dohnal, M., Rieckermann, J., and Bareš, V.: Gauge-adjusted rainfall estimates from commercial microwave links. *Hydrology and Earth System Sciences*, 21(1), 617–634. <https://doi.org/10.5194/hess-21-617-2017>, 2017.
- Fencl, M., Dohnal, M., Valtr, P., Grabner, M., and Bareš, V.: Atmospheric observations with E-band microwave links – challenges and opportunities, *Atmos. Meas. Tech. Discuss.*, <https://doi.org/10.5194/amt-2020-28>, 2020.
- Gires, A., Tchiguirinskaia, I., and Schertzer, D.: Two months of disdrometer data in the Paris area, *Earth Syst. Sci. Data*, 10, 941–950, <https://doi.org/10.5194/essd-10-941-2018>, 2018.
- 390 Gires, A., Bruley, P., Ruas, A., Schertzer, D., and Tchiguirinskaia, I.: Disdrometer measurements under Sense-City rainfall simulator, *Earth Syst. Sci. Data*, 12, 835–845, <https://doi.org/10.5194/essd-12-835-2020>, 2020.

- Graf, M., Chwala, C., Polz, J., and Kunstmann, H.: Rainfall estimation from a German-wide commercial microwave link network: Optimized processing and validation for 1 year of data. *Hydrology and Earth System Sciences*, 24(6), 2931–2950, <https://doi.org/10.5194/hess-24-2931-2020>, 2020.
- 395 Habi, H., and Messer, H.: Wet-Dry Classification Using LSTM and Commercial Microwave Links. 149-153. 10.1109/SAM.2018.8448679, 2018.
- Humphrey, M. D., Istok, J. D., Lee, J. Y., Hevesi J. A., and Flint, A. L.: A New Method for Automated Dynamic Calibration of Tipping-Bucket Rain Gauges. *J. Atmos. Oceanic Technol.*, 14, 1513–1519, [https://doi.org/10.1175/1520-0426\(1997\)014<1513:ANMFAD>2.0.CO;2](https://doi.org/10.1175/1520-0426(1997)014<1513:ANMFAD>2.0.CO;2), 1997.
- 400 ITU-R: Recommendation ITU-R P.838-3 - Specific attenuation model for rain for use in prediction methods, available at: http://www.itu.int/dms_pubrec/itu-r/rec/p/R-REC-P.838-3-200503-I!!PDF-E.pdf, last access: 6 March 2021, 2005.
- ITU-R: Recommendation ITU-R P.530-16 - Propagation data and prediction methods required for the design of terrestrial line-of-sight systems, available at: https://www.itu.int/dms_pubrec/itu-r/rec/p/R-REC-P.530-16-201507-S!!PDF-E.pdf, last access: 6 March 2021, 2015.
- 405 ITU-R: Recommendation ITU-R P.676-12 - Attenuation by atmospheric gases and related effects, available at: https://www.itu.int/dms_pubrec/itu-r/rec/p/R-REC-P.676-12-201908-I!!PDF-E.pdf, last access: 4 June 2021, 2019.
- Jaffrain, J., and Berne, A.: Experimental quantification of the sampling uncertainty associated with measurements from Parsivel disdrometers. *J. Hydrometeorol.*, 12 (3), doi:10.1175/2010JHM1244.1, 2011.
- Jaffrain, J., Studzinski, A., and Berne, A.: A network of disdrometers to quantify the small-scale variability of the raindrop size distribution, 410 *Water Resour. Res.*, 47, W00H06, doi:10.1029/2010WR009872, 2011.
- Kvicera, V., Grabner, M., and Fiser, O.: Frequency and path length scaling of rain attenuation from 38 GHz, 58 GHz and 93 GHz data obtained on terrestrial paths, 2009 3rd European Conference on Antennas and Propagation, Berlin, pp. 2648-2652, 2009.
- Leijnse, H., Uijlenhoet, R., and Stricker, J.: Microwave link rainfall estimation: Effects of link length and frequency, temporal sampling, power resolution, and wet antenna attenuation. *Advances in Water Resources*, 31(11), 1481–1493. <https://doi.org/10.1016/j.advwatres.2008.03.004>, 2008.
- 415 Leijnse, H., Uijlenhoet, R., and Berne, A.: Errors and Uncertainties in Microwave Link Rainfall Estimation Explored Using Drop Size Measurements and High-Resolution Radar Data. *Journal of Hydrometeorology* 11 (2010). 11. 10.1175/2010JHM1243.1, 2010.
- Löffler-Mang, M. and Joss J.: An optical disdrometer for measuring size and velocity of hydrometeors. *J. Atmos. Oceanic Technol.*, 17, 130-139, 2000.
- 420 MeteoSwiss: <https://www.meteoswiss.admin.ch/home/measurement-values.html?param=messwerte-lufttemperatur-10min&station=REH&chart=hour>, last access: 16 December 2020.
- Mital, U., Dwivedi, D., Brown, J. B., Faybishenko, B., Painter, S. L., and Steefel, C. I.: Sequential Imputation of Missing Spatio-Temporal Precipitation Data Using Random Forests. *Front. Water* 2:20.doi: 10.3389/frwa.2020.00020, 2020.
- Olsen, R., Rogers, D., and Hodge, D.: The aRb relation in the calculation of rain attenuation, *IEEE T. Anten. Propag.*, 26, 318–329, 425 doi:10.1109/TAP.1978.1141845, 1978.
- Ostrometzky, J., Cherkassky, D., and Messer H.: Accumulated Mixed Precipitation Estimation Using Measurements from Multiple Microwave Links, *Advances in Meteorology*, vol. 2015, Article ID 707646, 9 pages, <https://doi.org/10.1155/2015/707646>, 2015.
- OTT, Operating instructions: Present Weather Sensor Parsivel, 70.200.005.B.E 08-1008, 2006.
- Overeem, A., Leijnse, H., and Uijlenhoet, R.: Measuring urban rainfall using microwave links from commercial cellular communication 430 networks, *Water Resources Research*, 47(12), doi:10.1029/2010WR010350, 2011.

[Overeem, A., Leijnse, H., and Uijlenhoet, R.: Two and a half years of country-wide rainfall maps using radio links from commercial cellular telecommunication networks, *Water Resources Research*, 52\(10\), 8039–8065, <https://doi.org/10.1002/2016WR019412>, 2016.](#)

- Overeem, A., Leijnse, H., and Uijlenhoet, R.: Retrieval algorithm for rainfall mapping from microwave links in a cellular communication network, *Atmos. Meas. Tech.*, 9, 2425–2444, <https://doi.org/10.5194/amt-9-2425-2016>, 2016.
- 435 Pastorek, J., Fencl, M., Rieckermann, J., and Bareš, V.: The suitability of precipitation estimates from short CMLs for urban hydrological predictions, December 2018, International Workshop on Precipitation in Urban Areas (UrbanRain18), Pontresina, Switzerland, doi: 10.3929/ethz-b-000347556, 2018.
- Pastorek, J., Fencl, M., Rieckermann, J., and Bareš, V.: Precipitation Estimates from Commercial Microwave Links: Practical Approaches to Wet-antenna Correction, submitted to *Transactions on Geoscience and Remote Sensing (TGRS)*. Pre-print on engrXiv, submitted.
- 440 Polz, J., Chwala, C., Graf, M., and Kunstmann, H.: Rain event detection in commercial microwave link attenuation data using convolutional neural networks, *Atmos. Meas. Tech.*, 13, 3835–3853, <https://doi.org/10.5194/amt-13-3835-2020>, 2020.
- Reller, C., Loeliger, H., and Marín Díaz, J. P.: A model for quasi-periodic signals with application to rain estimation from microwave link gain, 19th European Signal Processing Conference, Barcelona, 2011, pp. 971-975, 2011.
- Rincon, R. F., and Lang, R. H.: Microwave link dual-wavelength measurements of path-average attenuation for the estimation of drop size distributions and rainfall, *IEEE Transactions on Geoscience and Remote Sensing*, vol. 40, no. 4, pp. 760-770, April 2002, doi: 10.1109/TGRS.2002.1006324, 2002.
- 445 Schatzmann, A., Scheidegger, A., Rieckermann, J., and Ruckstuhl, A.: Robust extraction of rain-induced attenuation from microwave link observations using local regression. In P. Molnar, P. Burlando, & T. Einfalt (Eds.), *Urban challenges in rainfall analysis* (pp. 1-5). Zurich: ETH Zurich, 2012.
- 450 Schleiss, M., and Berne A.: Identification of Dry and Rainy Periods Using Telecommunication Microwave Links, *IEEE Geoscience and Remote Sensing Letters*, vol. 7, no. 3, pp. 611-615, July 2010, doi: 10.1109/LGRS.2010.2043052, 2010.
- Schleiss, M., Jaffrain, J., and Berne, A.: Stochastic Simulation of Intermittent DSD Fields in Time, *Journal of Hydrometeorology*, 13(2), 621-637, 2012.
- Schleiss, M., Rieckermann, J., and Berne, A.: Quantification and Modeling of Wet-Antenna Attenuation for Commercial Microwave Links, *IEEE Geoscience and Remote Sensing Letters*, vol. 10, no. 5, pp. 1195-1199, Sept. 2013, doi: 10.1109/LGRS.2012.2236074, 2013.
- 455 Song, K., Liu, X., Gao, T., and He, B.: Raindrop Size Distribution Retrieval Using Joint Dual-Frequency and Dual-Polarization Microwave Links”, in *Advances in Meteorology*, doi: <https://doi.org/10.1155/2019/7251870>, 2019.
- Špačková, A., Jaffrain, J., Wang, Z., Schleiss, M., Fencl, M., Bareš, V., Berne, A., and Rieckermann, J.: One year of attenuation data from a commercial dual-polarized duplex microwave link with concurrent disdrometer, rain gauge and weather observations, [Data set], Zenodo, 460 <https://doi.org/10.5281/zenodo.4923125>, 2021.
- Upton, G.J.G., Cummings, R.J., and Holt, A.R.: Identification of melting snow using data from dual-frequency microwave links, *IET Microwaves, Antennas and Propagation*, 1, (2), p. 282-288, doi: 10.1049/iet-map:20050285, 2007
- van Leth, T. C., Overeem, A., Leijnse, H., and Uijlenhoet, R.: A measurement campaign to assess sources of error in microwave link rainfall estimation, *Atmos. Meas. Tech.*, 11, 4645–4669, <https://doi.org/10.5194/amt-11-4645-2018>, 2018.
- 465 van Leth, T. C., Leijnse, H., Overeem, A., and Uijlenhoet, R.: Estimating raindrop size distributions using microwave link measurements: potential and limitations, *Atmos. Meas. Tech.*, 13, 1797–1815, <https://doi.org/10.5194/amt-13-1797-2020>, 2020.
- Wang, Z., Schleiss, M., Jaffrain, J., Berne, A., and Rieckermann, J.: Using Markov switching models to infer dry and rainy periods from telecommunication microwave link signals, *Atmos. Meas. Tech.*, 5, 1847–1859, doi:10.5194/amt-5-1847-2012, 2012.