

Twelve years profile soil moisture and temperature measurements in Twente, the Netherlands

Rogier van der Velde^{1,2}, Harm-Jan F. Benninga^{1,3}, Bas Retsios¹, Paul C. Vermunt¹, Mhd. Suhyb Salama¹

1- Department of Water Resources, Faculty of ITC, University of Twente, Enschede, 7500 AE, The Netherlands

2- Waterexpertisecentrum, Vitens, Zwolle, 8019 BE, The Netherlands

3- Present affiliation: Witteveen+Bos Consulting Engineers, Deventer, 7400 AE, The Netherlands

Correspondence to: Rogier van der Velde (rogier.vandervelde@vitens.nl)

Abstract

Spread across Twente and its neighbouring regions in the east of the Netherlands, a network of 20 profile soil moisture and temperature (5 cm, 10 cm, 20 cm, 40 cm and 80 cm depths) monitoring stations was established in 2009. Field campaigns have been conducted covering the growing seasons of 2009, 2015, 2016 and 2017 during which soil sampling rings and handheld probes were used to measure the top 5 cm volumetric soil moisture content (VSM) of ~~in total of~~ 28 fields near 12 ~~different~~ monitoring stations. In this paper, we describe the design of the monitoring network and the field campaigns, adopted instrumentation, experimental setup, field sampling strategies, and the development of sensor calibration functions. Maintenance and quality control procedures and issues specific to the Twente network are discussed. Moreover, we provide an overview of open third-party datasets (i.e. land cover/use, soil information, elevation, groundwater and meteorological observations) that can support the use and analysis of the Twente soil moisture and temperature datasets beyond the scope of this contribution.

An indication for the spatial representativeness of the permanent monitoring stations is provided through comparisons of the 5 cm station measurements with the top 5 cm field-averaged VSM derived from the field campaign measurements. The results reveal in general reasonable agreements and root mean squared errors that are dominated by underestimations of the field-averaged VSM which is particularly apparent for the grass fields and strong after heavy rain. Further, we discuss the prospects the datasets offer to investigate i) the reliability of soil moisture references that serve the development and validation of soil moisture products, and ii) the water and energy exchanges across the groundwater-vadose zone – atmosphere continuum within a lowland environment in a changing climate.

The datasets discussed are publicly available at <https://doi.org/10.17026/dans-znj-wyg5> (Van der Velde et al. 2022) under the Creative Commons, CC BY 4.0 license.

1 Introduction

30 In virtually every hydrology textbook (e.g. Maidment 1993, Dingman 1993, Brutsaert 2005) one can read that water in the
unsaturated soil, hereafter soil moisture is needed for plants to grow, for groundwater to recharge, and for determining whether
rain infiltrates or runs off laterally and contributes to the production of streamflow. Moreover, the availability of soil moisture
for evapotranspiration controls heat and water exchanges between the land surface and atmosphere, affecting weather and
climate (Seneviratne et al. 2010). Since its foundation in 1992, the Global Climate Observing System (GCOS) acknowledges
the crucial role soil moisture plays in the Earth's climate system, supports the development of long-term global monitoring
35 programmes (GCOS, 2004) and has recognized soil moisture as an essential climate variable (GCOS 2010). Considerable
developments have taken place in global soil moisture monitoring with the launch of dedicated microwave satellites, e.g. Soil
Moisture and Ocean Salinity (SMOS, Kerr et al. 2010) [and](#) Soil Moisture Active Passive (SMAP, Entekhabi et al. 2010),
and long-term satellite-based data products have become available (Gruber et al. 2019). In addition, the International Soil Moisture
Network (ISMN) hosts in situ soil moisture measurements from across the globe (Dorigo et al. 2011, 2021).

40 The number of in situ soil moisture monitoring programmes dating back to the 1930s has been small and many relied on soil
sampling (Robock et al. 2000). Measurements obtained by weighing wet and dry soil are, however, destructive in nature and
labor-intensive. The gravimetric approach is, as such, unsuitable for monitoring purposes due to its inherent limitation in
collecting reproducible observations and has also become unfeasible for long-term monitoring as labor costs increased. Indirect
estimation of the soil [moisture](#) content has therefore been widely investigated (e.g. Vereecken et al. 2008). The large contrast
45 between the relative electric permittivity (ϵ_r) of dry soil (3-5) and water (80) as well as its relative insensitivity to variations in
salinity and soil texture have made electromagnetic field sensors operating at frequencies below 1 GHz the standard non-
destructive measurement technique used for regional-scale soil moisture monitoring networks (e.g. Martinez-Fernandez and
Cebalos 2005, Calvet et al. 2007, Su et al. 2011, Bircher et al. 2012, Smith et al. 2012, Benninga et al. 2018, Bogena et al.
2018, Caldwell et al. 2019, Tetlock et al. 2019). Despite technological advances facilitated a substantial increase in the
50 worldwide monitoring infrastructure, in situ monitoring networks providing long-term soil moisture data records are still very
scarce (GCOS, 2016).

In this manuscript, we report for the first time the complete in-situ soil moisture and soil temperature depth profile datasets
collected by a regional scale monitoring network composed of 20 permanent [monitoring](#) stations operated in and around the
Twente region situated in the east of the Netherlands as well as complementary surface soil moisture datasets collected during
55 field campaigns held in the growing seasons of 2009, 2015, 2016 and 2017. The installation of the monitoring stations of the
Twente network began in the fall of 2008 and was completed by the fall of 2009, and has witnessed continuous development
ever since. Dente et al. (2011) described the early development and the first scientific use of the data was the validation of
SMOS soil moisture products (Dente et al. 2012). Other studies performed with the datasets have focused on field scale soil
moisture retrieval (Van der Velde et al. 2015, Benninga et al. 2020, [Benninga et al. 2022](#)), upscaling of point measurements
60 to coarse satellite footprints (Van der Velde et al. 2021), agricultural and hydrological applications (Carranza et al. 2018, 2019,

Pezij et al. 2019, Buitink et al. 2020) and the Twente network has been used as one of the core international validation sites for the SMAP surface soil moisture products (Colliander et al. 2017, Chan et al. 2018, Chaubell et al. 2020).

The manuscript is organized as follows: Section 2 provides an overview of the study area and relevant open third-party datasets, i.e. land cover/use, soil information, elevation, groundwater and meteorological observations. The design of the monitoring network and the field campaigns, deployed instrumentation, experimental setup, field sampling strategies, and the development of sensor calibration functions are described in sections 3 and 4, respectively. In section 5, we discuss data uncertainties [related](#) to the sensor calibration as well as spatial representativeness of the permanent monitoring stations for individual fields and for the entire network. Section 6 highlights several exemplary research opportunities in the prospect of the disclosed dataset and section 7 presents details related to the processing, flagging and availability of the datasets. The manuscript closes with the summary and outlook in section 8.

2 Study area and open datasets

2.1. Regional characteristics

Twente is a 1500 km² region in the Netherlands directly bordering Germany towards the east and bound to the west by a glacial ridge known as the Sallandse Heuvelrug. The majority of the network is situated in Twente, other parts are located in the neighboring regions Salland and Achterhoek with similar characteristics. Glacial ridges formed in the second last glaciation period (Saalien) define the landscape. They have maximum elevations of around 80 m above mean sea level (a.m.s.l.) and consist mostly of fluvial sand deposits with glacial boulder clay sheets. This geomorphological feature in combination with a temperate oceanic climate (*Cfb* Köppen-Geiger climate classification; Beck et al. 2018) led to a drainage system composed of brooks and small unnavigable rivers flowing via larger rivers into the IJssel Lake. Although deeper groundwater levels of 6 m up to 10 m below the surface can be found on the glacial ridges, they are generally shallow and fluctuate from within 1 m [below the surface](#) during winters up to maximum depths of 2 m to 3 m in summers.

Twente and its surroundings are in the Netherlands considered rural areas with a few mid-sized and small cities, and several villages, and are known for their characteristic bocage landscape with small agricultural fields (1.63 hectares on average) separated by tree lines and bushes amidst gently rolling hills. The majority of agriculture has a focus on animal husbandry, whereby the available land is used to produce food for livestock via meadows and the cultivation of maize.

A large number of public datasets of the Netherlands is freely available and made accessible through various initiatives. The following sections describe datasets on topography, soil, groundwater, land cover and weather that can support the use of the Twente soil moisture and temperature dataset. Section [7](#) describes how these datasets can be accessed.

2.2 Topography, soils and groundwater

Detailed spatial elevation data is available from the AHN ('Actueel Hoogtebestand Nederland' in Dutch). AHN (2019) supplies 0.05 m accurate DTMs obtained via airborne laser altimetry. In 2019, the third version (AHN3) has been completed and made

available at spatial resolutions of 0.5 m and 5.0 m. The DTM for the area covered by the monitoring stations is shown in Fig. 1 with on top the locations of the monitoring stations. Soil information up to a depth of 1.2 m can be obtained from the soil physical units map of the Netherlands named BOFEK (‘Bodemfysische Eenheden Kaart’ in Dutch), which is a combination of the soil map of the Netherlands and the Dutch class pedotransfer function (Heinen et al. 2021). An extensive network of groundwater monitoring wells in the Netherlands is supported by various organisations, which are all contributing to a central database that is disseminated via DINOLoket (‘Data en Informatie van de Nederlandse Ondergrond’ in Dutch) and managed by the Geological Survey of the Netherlands (2021). Not all monitoring wells in the database have records that cover the observation period of the Twente network. The wells nearest to our monitoring stations with a matching temporal coverage are selected and displayed in Fig. 1. Table S1 in the supplement lists the well ID, coordinates, and distance to the associated soil moisture stations.

The DTM in Fig. 1 shows that the study area has little relief sloping gently from about 5 m a.m.s.l. in the west to 30 m a.m.s.l. in the east, with some glacial ridges up to an elevation of 80 m a.m.s.l.. Sand is with 76 % areal coverage the dominant soil type. Wind-blown loamy deposits have an areal coverage of almost 12% and are found near the surface on the eastern glacial ridge. Organic and peaty soils are present in 4 % of the study area in the parts where water naturally stagnates. The remainder of the region is classified as land cover types for which the soil type is undefined, such as built-up areas and water.

2.3 Land use

Land use information is publicly available from Statistics Netherlands and the Ministry of Economic Affairs and Climate Policy. Statistics Netherlands (2015) provides the main land use classes based on an interpretation of a 1:10.000 topographic map and is published every two to four years since 1989. The Ministry of Economic Affairs and Climate Policy (2021) is responsible for the crop parcel registry. Since 2009, every land owner in the Netherlands has to report each year the crop on each parcel in their possession.

In the 2015 land use map from Statistics Netherlands ~~can be deduced that~~ 70.2 % of the land is used for agricultural activities, 13 % is mixed coniferous and deciduous forest, 11.3 % is built-up and the remaining 5.5 % is classified as water, recreational, dry and wet nature. The larger forested areas are mainly found on the glacial ridges and the agricultural activities take mostly place on the post-glacial soils. From the crop parcel registry in 2015, we find that the agricultural land is covered 70.8% by grass meadows, 22.4 % by maize and the remaining 6.8% is used for potatoes, cereals, and other crops. The grass-growing season is generally from March to November during which the meadows are either grazed by cattle or cut four to six times per year (Benninga et al., 2022). Maize is planted in the months of April/May and harvested for silage in the period from September to November depending on the vehicle-bearing capacity of the land and growing conditions, in particular the dry matter content of the plants.

2.4. Weather

The locations of the 3 automated weather stations ([AWS](#)) and 29 rain gauges operated by the Royal Netherlands Meteorological Institute (‘Koninklijk Nederlands Meteorologisch Instituut’ in Dutch; KNMI 2021) in the study area are shown in Fig. 1. The rain gauges are part of a network of more than 300 voluntary observers in the Netherlands. The observers record manually with a 0.1 mm resolution the rainfall collected with a World Meteorological Organization (WMO) standard gauge around 9:00 CET in the morning and measure the snow depth with a ruler when applicable. The data are sent to the KNMI for validation in 10-day blocks and made available as daily values.

The three automated weather stations are situated near the villages Heino and Hupsel, and at Twenthe airport nearby Enschede. They measure wind speed and direction, air temperature at 1.5 m and 0.1 m above the surface, sunshine duration, shortwave incoming radiation, precipitation, air pressure, humidity, and cloud cover. The adopted instrumentation and measurement protocols are according to WMO standards, and the quality-controlled data are available as hourly and daily values. The daily set also holds the reference crop evapotranspiration (E_{ref}) calculated through the application of the modified Makkink method described in De Bruin (1987). In addition, radar-derived precipitation is available as approximately 1 km gridded files ~~for the Netherlands~~ as gauge-corrected accumulations for 5 min, 3 and 24 hours.

Figure 2 shows for the period 2008 – 2020 the monthly average of daily mean 1.5 m air temperature as well as monthly precipitation and E_{ref} sums derived as mean values for the three automated weather stations. The data in this figure supports that the soil moisture monitoring network is located in a temperate oceanic climate zone (*Cfb*). The coldest and warmest months have been January and July with mean monthly temperatures of 2.9 °C and 18.3 °C, respectively. Precipitation has been evenly distributed throughout the year according to the Köppen-Geiger classification, even though a difference of 53.3 mm exists in sums between the driest (April, 33.5 mm) and wettest (August, 86.8 mm) month.

In the past fourteen years, the annual precipitation and E_{ref} sums available for the three weather stations have been on average 757.1 mm and 611.3 mm, respectively, resulting in an annual surplus of 145.8 mm. In the years 2018, 2019 and 2020 north-western Europe has been struck by droughts (e.g. Buitink et al., 2020; Bakke et al., 2020; Buras et al., 2020) with below-normal precipitation and higher evaporative demands. The most extreme rain day occurred on 26 August 2010, with 49.6 mm, 142.3 mm and 106.4 mm collected at KNMI stations Heino, Hupsel and Twenthe, ~~while typically less than 50 mm of rain was recorded per day.~~

3. Monitoring network

3.1 Sites

The development of the soil moisture and temperature monitoring network started in November 2008 and was completed in November 2009, but 19 out of the 20 stations were installed already before July 2009. The ~~motivation for the development objective~~ of the measurement infrastructure was to serve as a reference for the validation and calibration of coarse-

resolution soil moisture products derived from active and passive microwave satellite observations (Dente et al. 2011). The measurement sites are spread over a roughly 45 km x 40 km area and the individual stations are 5 km to 13 km apart as shown in Fig. 1.

In the site selection care was taken to evenly distribute [monitoring stations](#) across the land covers and soil types in the study area. The majority of stations are found on sandy soils, two stations have been installed in sandy soils with a higher organic matter content, one in loamy soil and one in clayey soil according to the BOFEK soil map. [It should be noted that near the surface the organic matter content is higher than one would expect based on the texture class and that grasslands have a dense rooting system.](#) The land on which the monitoring took place is privately owned and actively used for farming. The instrumentation is, therefore, typically placed at the border of fields and preferably several tens of metres away from disturbing features (i.e. trees, roads [and](#) watercourses), as shown in Fig. 3, to minimize disturbance from recurring farming practices and optimize its representativeness for the adjacent fields, which is further discussed in section 5.2.

The monitoring network has been constantly subject to modifications, such as land cover changes as a result of crop rotation, and re-installations due to changes in land ownership or persistent equipment failures. Table S2 lists for each station the texture class derived from the soil map, land cover per year of the adjacent fields, percentage missing data, and changes made to the measurement setup. The location of the stations and their installation date are available as a list of geographic (datum: WGS84) and map projected (Amersfoort/RD New, EPSG: 28892) coordinates.

3.2 Instrumentation and measurement setup

The Twente soil moisture and temperature monitoring network is built with instrumentation manufactured by METER Group (formerly: Decagon Devices). The offline and remote versions of [the](#) EM50 data logger series have been deployed to perform measurements every minute with ECH₂O EC-TM and 5TM (firmware versions 2013 and 4.0) probes and were set to record readings at 15-minute intervals. The functionality of the probes was tested using measurements of water and air prior to deployment and the installed probe types are documented [along with the datasets'](#) as a quality flag within the datasets, see section [6.7](#). Equipment of METER Group has previously been used for the development of many monitoring networks, such as HOBE in Denmark (Bircher et al. 2012), TERENO in Germany (Bogena et al. 2018) and the Raam in the Netherlands (Benninga et al. 2018), and been evaluated in several intercomparison studies (e.g. Jackisch et al. 2020, Vaz et al. 2013, Robinson et al. 2008).

The ECH₂O probes estimate the volumetric soil moisture (VSM) by characterizing the apparent relative electric permittivity via the capacitance that is quantified as the charge needed to polarise the dielectric (soil-[water-air mixture](#)) surrounding the prongs and determined as a voltage (Bogena et al. 2007). Benninga et al. (2018) have shown under laboratory conditions that the 5TM probe is sensitive to about 3 cm to 4 cm of soil layer around the prongs. Readers are referred to the manuals for the details on the instrument design and [its-their](#) technical specifications (Decagon Devices 2008 and 2017).

Figure 3 illustrates typical measurement setups of the Twente network with probes installed at nominal depths of 5 cm, 10 cm, 20 cm, 40 cm and 80 cm. However, due to budget constraints, several stations are limited to the upper two, three or four

measurement depths. [Table S3 provides for each station the installed sensor types and installation depths.](#) At sites with a permanent grass cover, excavation of the installation pit started with cutting the grass sod of an area of approximately 40 cm by 40 cm after which the top 10 cm to 15 cm (soil layer including grass) was carefully removed and the pit was dug further until the required depth. The probes were installed in a lateral direction with the small sides of the prongs pointing upward to avoid water ponding, and with the printed text on the prongs in the upright direction to ensure consistency in the depth of the thermistor. After installation the pit was backfilled while compacting the soil several times during the filling process, the grass sod was placed back and a trench was dug to guide the cables to a pole on which the EM50 logger was mounted. The excess cables were buried near the pole. Typically a few months after installation, the plot ~~would have~~ returned to its original state. A similar installation procedure was adopted for cultivated land.

195 3.3 Capacitance probe calibration

Soil-specific calibrations of electromagnetic field sensors are needed to account for i) losses (the imaginary component of ϵ_r) due to the molecular relaxation and electric conductivity that alter the ϵ_r as it appears to a capacitance sensor (Robinson et al. 2008) and ii) the soil dependent dielectric response to VSM. Guidelines from the manufacturer (Cobos and Chambers 2010) were followed to develop soil-specific calibration functions for the EC-TM and 5TM probes using measurements made in the laboratory. With this approach, the sensor-to-sensor variability is assumed to be accounted for by the manufacturer's sensor calibration against known dielectric standards. This can be justified based on the small variability ($0.01 \text{ m}^3 \text{ m}^{-3}$) among sensors evaluated by Kizito et al. (2008) and Rosenbaum et al. (2010).

In Dente et al. (2011) the development of the calibration function for the EC-TM probe is described. They performed the calibration on soil collected from 10 sites and could identify three relationships, but at the same time could not attribute this to a specific soil feature. The conclusion was to use the following ~~generalized~~ calibration function,

$$\theta_{cp} = a + b\theta_p, \quad (1)$$

where θ stands for the VSM ($\text{m}^3 \text{ m}^{-3}$), a and b are the intercept ($\text{m}^3 \text{ m}^{-3}$) and slope (-) of the linear regression function, and subscripts p and cp indicate the native probe reading and calibrated probe value. The native probe reading is a direct sensor output obtained by applying the mineral soil calibration to the raw signal (Decagon Devices, 2008). Dente et al. (2011) report an a of $0.0706 \text{ m}^3 \text{ m}^{-3}$ and b of 0.7751 , yielding a root mean square error (RMSE) of $0.023 \text{ m}^3 \text{ m}^{-3}$.

210 The calibration of the 5TM probe was performed in 2015 for soil taken from three sites each belonging to one of three groups earlier identified by Dente et al. (2011). The selected sites were ITC_SM03, ITC_SM07 and ITC_SM08, for which 38, 32 and 29 pairs of gravimetrically determined VSM (GVSM) and probe VSM (~~VSM~~) measurements were collected, respectively. Figure 4a shows the GVSM against the 5TM VSM. Linear equations of the same type as Eq. (1) were fitted through the matchups for each soil individually and all together. [The leave-one-out cross-validation procedure is adopted for calculating the performance metrics because of the limited sample size and to provide an uncertainty estimate for coefficients \$a\$ and \$b\$.](#)

215 Table 1 lists the linear regression coefficients (a and b) obtained for the four sets of matchups along with the ~~ir~~ standard deviation (σ). The RMSE and mean error (ME) calculated from the matchups left for validation and the coefficient of

determination (R^2) obtained with the mean regression coefficients are provided as well. The listed metrics demonstrate that the performance of the 5TM sensor is in line with that of the EC-TM. Even though the regression coefficients differ among the analysed soils their point clouds in Fig. 4a have quite some overlap, which does not justify the use of different calibration functions. This is further supported by the fact that the σ is only a fraction of the magnitude of the regression coefficients when including all matchups. Notably, the obtained σ s are 4.8 % of the intercept and less than 0.5 % of slope relative to the magnitude, while it goes up to a respective 44 % and 2.4 % when using data from a single site. This suggests that the reliability of the function fitted through all matchups is higher. The ‘all soils’ calibration function is for this reason applied to every site of the Twente network, which is expected to provide an accuracy (RMSE) of 0.028 m³ m⁻³. Figure 4b presents the validation with the GVSM plotted against the 5TM VSM using the ‘all soils’ mean regression coefficients.

4 Field campaigns to observe surface soil moisture

Field campaigns were conducted in 2009, 2015, 2016 and 2017, during which soil moisture was measured in fields with handheld impedance probes and via soil samples taken for GVSM determination. The objective of the campaigns was the validation of soil moisture retrievals from satellite observations via estimates of the spatially aggregated top 5 cm soil moisture content, hereafter referred to as surface soil moisture. The general concept of each field campaign was similar, yet the execution differed every year. For instance, sampling days in 2009 and 2015 took place weekly from the end of summer in September until the beginning of November. In 2016 and 2017, the sampling days were held weekly or biweekly depending on weather and staff availability and covered the entire growing season from April/May till the end of fall in November. An overview of the field campaigns is provided in Table 2, which includes the time, the number of sampling days and the sampled stations. The following sections describe the sampling strategy, the instrumentation and the calibration of the probe readings.

4.1 Sampling strategy design

Sampling took place at up to five fields near a monitoring station with in total 28 sampled fields near 12 monitoring stations.

A maximum of six measurement locations were selected per field about 50 m to 100 m apart, which was reduced to a minimum of three locations when the size of the parcel was not big enough. The geographic position of the measurement locations have been determined using GPS with an accuracy typically better than 4 m.

Figure 5 illustrates the sampling at the measurement locations. The number of handheld impedance probe readings per sampling point varied from nine in the 2009 field campaign to five readings in 2015 and four in 2016-2017. At fields without crop rows, such as grass and wheat, surface soil moisture was measured with the impedance probe at four to nine points within a 1 m² plot and next to one of the probe readings a soil sample was taken for GVSM determination. In fields with crop rows, such as maize and potato, probe readings were taken along the transect perpendicular to the crop row with the soil sample taken in the middle of two rows. The collection of soil samples for GVSM determination was done during each field campaign to calibrate the probe readings and stopped when the covered dynamic range and number of matchups, ideally greater than 25,

were suitable to establish a calibration function. ~~We indicate in~~ The provided data sheets indicate which probes reading matches with the GVSM.

4.2 ThetaProbe and HydraProbe

The Delta-T ThetaProbe (Type ML2; Delta-T Devices, 1998) and Stevens HydraProbe (analog version; Stevens Water Monitoring Systems, 2020) are the two handheld probes that were used during field campaigns. Both instruments exploit the impedance mismatch between a coaxial transmission and a stainless steel pin inserted in the soil that acts as a waveguide and is electrically shielded by three similar pins (Seyfried and Murdock 2004). The ThetaProbe measures the amplitude difference of a standing sinusoidal wave between the start of a transmission line and the junction where the pins enter the soil as a result of the applied 100 MHz signal. The amplitude difference is used to determine the impedance from which the apparent ϵ_r is derived (Gaskin and Miller, 1996). The HydraProbe measures the complex ratio of the reflected and incident voltage of an applied 50 MHz signal to characterize the impedance of the soil to determine the complex ϵ_r (Campbell 1990, Kraft 1987). Both the ThetaProbe and HydraProbe data loggers have built-in software to convert the voltage output to a soil moisture content. In addition to soil moisture, the HydraProbe also provides bulk electric conductivity and temperature. Because the relationship between ϵ_r and VSM is affected by the soil type, calibration of impedance probe measurements is generally needed. In the case of the ThetaProbe, the calibration accounts also for conductive and molecular losses, which is less of an issue with the HydraProbe as it measures independently the real and imaginary components of the ϵ_r .

4.3 Impedance probe calibration

The measurements of the 2009 and 2015 field campaigns were collected with the ThetaProbe, during which a total of 93 and 166 matchups with GVSM were collected at fields near eight and six different stations, respectively. Figure 6 presents plots of GVSM against the ThetaProbe VSM with in the upper panels (Figs. 6a and 6b) the 2009 data and in the lower panels (Figs. 6c and 6d) ~~of~~ the 2015 data. The GVSM against the matching ThetaProbe readings is shown in Figs. 6a and 6c, and the GVSM values against the mean of the readings at a sampling point are shown in Figs. 6b and 6d.

In general, it can be noted that all plots show positive relationships and that the scatter among the data points is clearly less in 2015 ~~in comparison to~~ than in 2009. This is particularly the case for the matching ThetaProbe readings. The explanation for this difference in performance between the years is a combination of the larger number of stations sampled in 2009, the lower number of matchups available for 2009, and also the operator skills ~~that~~ could have played a role. Regardless of the scatter noted in the data points of 2009, it is difficult to identify distinct relationships for individual stations. Among the 2015 data points, clusters belonging to a single station are observed, but this is primarily due to the persistent soil moisture levels at specific stations. The attribution of a GVSM – ThetaProbe relationship to a specific soil type or station remains unclear. We have, therefore, chosen to develop the ThetaProbe calibration functions for the 2009 and 2015 field campaigns separately and not for individual stations or specific soil types. This also ensures a sufficient number of matchups and a larger soil moisture range.

The data collection of the 2016 and 2017 field campaigns was performed with the HydraProbe and took place near three stations (ITC_SM02, ITC_SM07, and ITC_SM10) in 2016, to which ITC_SM03 was added in 2017. A total of 285 pairs of GVSM and HydraProbe readings were acquired, with > 86 matchups for each station at which the measurements started in 2016 and 12 matchups for ITC_SM03. Figure 7a and 7b show the GVSM against the matching HydraProbe reading and the mean of the four readings collected at a sampling location, respectively.

From a comparison of Fig. 7 with Fig. 6, it is evident that the agreement between the HydraProbe readings and GVSM is equal to or better than the results obtained for the 2009 and 2015 ThetaProbe data. This could be explained by the deployed instruments, the different sets of fields sampled, the number of matchups collected per field and the extent of the dynamic soil moisture range covered by the matchups. However, it is beyond the scope of this manuscript to quantify their relative contributions. Also noticeable in Figs. 7 are the small differences among the relationships represented by the groups of the data points belonging to individual stations, which again may question the added value of station-specific calibration functions. However, because of the larger number of GVSM - HydraProbe pairs (> 86) and larger soil moisture range for individual stations, we decided to develop for the HydraProbe measurements station-specific calibration functions. Users of the dataset have the choice to apply the calibration function that suits their application best.

The development of calibration functions for the ThetaProbe and HydraProbe measurements consists of fitting linear regression coefficients (a and b) following the same procedure as described in section 3.3 for the 5TM probe. Table 3 provides the μ and σ of the coefficients for the ThetaProbe functions along with performance metrics. Table 4 lists the same information for the HydraProbe.

The performance metrics presented in Tables 3 and 4 show that the matching probe ('site') and GVSM measurements led to a better performance in terms of the R^2 except for the 2009 field campaign. The same holds when comparing the RMSEs with exception of the 2016-2017 results for ITC_SM02 in which case the mean of the probe readings leads to better performance. Of the field campaign calibrations, the calibration developed for the HydraProbe (2016-2017) led to the best results with an RMSE of $0.032 \text{ m}^3 \text{ m}^{-3}$ in comparison to RMSEs of $0.041 \text{ m}^3 \text{ m}^{-3}$ for 2015 and $0.048 \text{ m}^3 \text{ m}^{-3}$ for 2009 obtained for the ThetaProbes. A very good match of the HydraProbe with the GVSM is obtained for ITC_SM10 with an RMSE of $0.022 \text{ m}^3 \text{ m}^{-3}$. The explanation could be a combination of sandy soil and yearly cultivated land, which reduces disturbances due to soil clod and plant roots, and is favourable for reliable soil sampling. Under more difficult circumstances, such as the loamier soil with clods at ITC_SM07, the metrics are closer to yet still better than the ones obtained for the 2009 and 2015 field campaigns.

5. Data uncertainties

5.1 Sensor calibration

The soil moisture probes used for the monitoring network (EC-TM and 5TM) as well as the field campaigns (ThetaProbe and HydraProbe) estimate the ε_r through voltage measurements. Relationships between the voltage and ε_r are calibrated by the manufacturers using dielectric standards. A liquid with an ε_r of 40 is the highest for the METER group probes (Personal

communication METER Group, 21 April 2021), which means that the native EC-TM and 5TM probe readings above respectively $0.587 \text{ m}^3 \text{ m}^{-3}$ and $0.510 \text{ m}^3 \text{ m}^{-3}$ reach beyond the sensors' calibration domain. The ε_r is transformed into the VSM in the case of the 5TM probe using the empirical Topp et al. (1980) equation and for EC-TM probe using an equivalent third-order polynomial. The ThetaProbe and HydraProbe both determine the VSM through empirical linear relationships with the refractive index, $\sqrt{\varepsilon_r}$ (Gaskin and Miller 1996, Seyfried et al. 2005), which is equivalent to a second-order polynomial.

The difference in the shape of the probe-specific ε_r and VSM relationships may compromise the consistency among the probes calibrations that have been performed as the native probe VSM versus the GVSM in Sections 3.3 and 4.3. We have evaluated its theoretical implications by matching the mineral soil calibrations of the EC-TM, ThetaProbe and HydraProbe probes with the 5TM VSM through the application of linear fits. The results are ~~root mean squared differences (RMSDs)~~ RMSEs of respectively $0.004 \text{ m}^3 \text{ m}^{-3}$, $0.011 \text{ m}^3 \text{ m}^{-3}$ and $0.010 \text{ m}^3 \text{ m}^{-3}$ for the 5 – 40 ε_r range whereby the largest of differences of $0.025 \text{ m}^3 \text{ m}^{-3}$ are found for the ThetaProbe and HydraProbe in the wet limit. Yet, linear relationships have been found between the different native probe VSM and the independently determined GVSM in Sections 3.3 and 4.3. The other measurement uncertainties, such as spatial scale mismatch and sampling errors, are dominant over the uncertainty caused by the shape of the VSM and ε_r relationship.

Another point of attention is the inconsistency in the firmware of probes produced in 2013 with the latest version 4.0 and the earlier ones. In 2013, the manufacturer modified their calibration process to include two dielectric standards that turned out to overestimate the ε_r between 10 and 20 (Decagon customer notification 2014). We have applied the function supplied by the manufacturer to convert the 5TM readings and developed calibration functions for both probe versions. The 'all soils' calibration coefficients for firmware v4.0 are listed in Table 1 and applied accordingly.

5.2 Spatial representativeness ~~of observed surface soil moisture~~

Specific for the measurement setup of the Twente monitoring network is the placement of the instrumentation at the border of parcels, which inevitably has consequences for ~~the-its~~ representativeness ~~of-for~~ the field. Large differences in the meteorological inputs, e.g. precipitation and incoming solar radiation, are not expected, but small-scale topography, spatially variable soil texture, different land covers and degrees of soil compaction as a result of agricultural management practices, and ~~the~~ field-specific drainage infrastructure may cause discrepancies between the VSM at the border and inside of the field. ~~The~~ Field averages derived from the surface soil moisture measurements collected during the field campaigns described in (see section 4) Section 4 have been ~~conducted-used~~ to assess this issue. Table 5 lists the number of matchups and performance metrics computed between the field averages and matching station VSM. The metrics in the table have been developed based on crop type (grass, maize, fallow wheat and potato) and based on days during which more than one station was sampled whereby all field and matching station VSMs are averaged.

From the metrics in the table, the field VSM sampled in grass meadows near 9 permanent monitoring locations agrees, with a mean R^2 of 0.50, reasonably well with the station VSM. However, the station measurements systematically underestimate the field VSM by $0.0989 \text{ m}^3 \text{ m}^{-3}$, which ~~can~~ may be attributed to edge effects. ~~Those edge effects consist of a combination of~~

~~differences in elevation and exposure to agricultural practices.~~ The border of a meadow is typically a few centimeters higher than the field itself, and grass on the field is mown multiple times per year whereas the border is not, leading to more transpiration and interception of precipitation. Large variability in the agreements between the field and station VSM is, however, noted. The R^2 values ~~of the majority of the stations~~ range for six out of the nine stations from 0.516 to 0.793, while 350 R^2 values of 0.36 and 0.38 suggest that stations ITCSM_05 and ITCSM_18 are less representative of the fields. A poor agreement (R^2 of 0.06) with the field measurements is found for ITCSM_04, which was a motivation to relocate the measurement setup within the field.

In contrast, the station VSM overestimates the measurements of the ITCSM_09 fallow wheat fields with $0.14 \text{ m}^3 \text{ m}^{-3}$. However, the spread among the matchups around the linearly regressed line is fairly small resulting in a high R^2 of 0.794. The explanation 355 for the overestimation ~~is could be~~ that the field is virtually bare soil whereas the monitoring equipment is placed at the edge of the field ~~which is~~ covered by grass. ~~Since the soil surface of the field is directly exposed to the atmosphere, it will dry out faster than the grass-covered border where the instrumentation has been installed.~~

A systematic bias with the field VSM is not noticeable in the metrics obtained for maize. The matchups for maize, however, do suffer from a larger spread among the data points as indicated by the moderate to low R^2 values, 0.282 on average. On the 360 one hand, this may be ~~argued for because explained by~~ the large difference-variation in land cover ~~that varies~~ across seasons having has an impact on the transpiration and interception of precipitation. On the other hand, in particular, the low R^2 of the intensively measured ITCSM_10 is quite surprising and cannot only be explained by ~~the difference-variation~~ in land cover alone. Further analysis shows that a large part of this weaker performance-agreement stems from two days (19 October 2016 and 28 June 2017) with exceptionally large mismatches, which ~~both~~ have in common that on average -more than more than-27 365 mm of precipitation was recorded in total on the day itself and the day before. of antecedent precipitation in common. This led for 19 October to a $0.21 \text{ m}^3 \text{ m}^{-3}$ underestimation of the field's surface soil moisture -VSM and to a $0.08 \text{ m}^3 \text{ m}^{-3}$ underestimation for 28 June. The large rain volumes on those days ~~most likely~~ led to overland flow that accumulated in local depressions and led on those days to the partial flooding of fields as a result of small scale topography, whereas the instrumentation at ITCSM_10 is was installed in a slightly higher and, therefore, drier part of the field. Also, infiltration prior to a dry spell takes 370 time and the top soil was likely saturated whereas the infiltration front may not have reached the 5TM influence zone.

The metrics ~~computed-labelled per 'sampling day' are, whereby~~ based on matchups between the mean values of all field-averaged surface soil moisture and corresponding 5 cm station VSM measurements collected on a specific day. They, show how the biases found for individual fields propagate when aggregated over a number of fields and provide an indication for the bias of the entire network. In support, Fig. 8 shows the mean of the field-averaged surface soil moisture field campaign and the corresponding matching mean of the 5 cm station mean VSM for the years 2015, 2016 and 2017, along with the mean 375 5 cm VSM of the entire network VSM-mean plus and minus the standard deviation. ~~and~~ The time series shows that the field and station VSM match well with each other as well as the network mean. ~~In all three data sources (e.g. field campaign, corresponding station and network mean), a low VSM is found for dry episodes and a high VSM is obtained under wet conditions.~~

380 The agreement between the field and station VSM is fairly good with a R^2 of 0.770, while the RMSE of $0.0468 \text{ m}^3 \text{ m}^{-3}$ may seem somewhat disappointing given the $0.04 \text{ m}^3 \text{ m}^{-3}$ target accuracy for satellite-based soil moisture products (e.g. Entekhabi et al. 2010, Kerr et al. 2010). The ~~inflated-large~~ RMSE is for a part attributable to the $0.0303 \text{ m}^3 \text{ m}^{-3}$ underestimation of the field's surface soil moisture-VSM, which is specifically large after intensive rainfall, such as the events on 19 October 2016 and 28 June 2017. Also, the large dynamic range from $0.121 \text{ m}^3 \text{ m}^{-3}$ up to $0.414 \text{ m}^3 \text{ m}^{-3}$ covered by the field campaigns
385 contributes to the relatively large absolute error. Notably, a 16 % uncertainty level is obtained when performance is computed as an RMSE percentage with respect to the covered dynamic range, which is actually quite similar to previous reports (e.g. Jackson et al. 2010).

6. Research opportunities

The development of the network began in the fall of 2008 and in several studies subsets of its data records have been used
390 primarily for the development and validation of satellite-based soil moisture products, but also for agricultural and hydrometeorological studies. With this contribution, we disclose for the first time the complete, quality-checked, calibrated and validated records of the permanent monitoring stations as well as the datasets collected during campaigns held in the growing seasons of 2009, 2015, 2016 and 2017. The soil moisture and temperature depth profiles collected by the network and the surface soil moisture datasets collected during the campaigns offer ample research opportunities to serve, for instance, as
395 a reference for the development and validation of soil moisture data products and to investigate water and energy exchanges across the groundwater-vadose zone-atmosphere continuum of lowland ecosystem ~~in a changing climate~~.

6.1. Validation

The validation of both satellite and/or model-based soil moisture products requires the comparison of a satellite footprint/model grid cell/~~satellite footprint~~ with a reference constructed from in-situ point measurements. For optimal validation, attention
400 needs to be paid to the effects of weather (e.g. rain events, frozen soil) as well as the spatial and temporal representativeness of measurements. For instance, we previously reported (Van der Velde et al. 2021) that after filtering for frozen and precipitation conditions, the accuracy of a satellite soil moisture product (Soil Moisture Active/Passive, SMAP) improved from $0.059 \text{ m}^3 \text{ m}^{-3}$ to $0.043 \text{ m}^3 \text{ m}^{-3}$. The data record of the Twente network enables further investigation of these issues.

Figure 8 shows that the mean values of all field-averaged surface soil moisture and corresponding 5 cm station VSM measurements collected on a specific campaign day matches ~~fairly very~~ well with each other (R^2 of 0.770) as well as the mean of 5 cm station VSM of the entire network. These results ~~reflect-provide an indication for the bias of the entire network~~
405 ~~the network's overall performance~~, but the results presented in section 5.2 also demonstrates that further investigations should address the effect of spatial heterogeneity at field-scale. Such investigations could answer questions related to how soil moisture varies in space and how this spatial variability differs throughout the growing seasons and is affected by weather (e.g.
410 intensive rainfall, frozen soil, drought).

In addition, the presented data will enable research into the temporal representativeness of station VSM measured with probes installed at a depth of 5 cm for the top 5 cm soil moisture data measured with respect to the field data collected during the campaigns that are typically considered as reference in validation studies. We carried out a preliminary analysis and found that the best match least differences between between the surface soil moisture values measured during the field campaigns and is found with the 5 cm station VSM that is recorded several hours up to two days later. The presented network and datasets provide an opportunity to further investigate this and the underlying physical processes that affect the near surface soil moisture profile, in particular infiltration and evaporation.

6.2 Groundwater-vadose zone-Atmosphere nexus

As an illustration of the research prospects in the context of water and energy exchanges between the land and atmosphere, Fig. 9 presents soil moisture and temperature depth profiles measured at ITC_SM07 during the 2019 heatwave in Northwestern Europe. The figure shows that as the soil dries out, after the rain events on 1 1 and 13 July, the amplitude of the diurnal soil temperature cycle increases. Analysing these relationships between soil moisture, soil temperature and other essential climate variables, such as air temperature, incoming solar radiation, evapotranspiration, precipitation, and groundwater, could address research questions on the development and persistence of heat waves and droughts.

An example of the groundwater-vadose zone nexus is presented in Fig. 10, which shows the soil moisture measured at depths of 5 cm, 10 cm, 20 cm, 40 cm and 80 cm over the period from January 2016 to June 2020 for monitoring stations ITC_SM10 (Fig. 10b), ITC_SM14 (Fig. 10c) and ITC_SM17 (Fig. 10d). The groundwater level measured at the DINOLoket well closest to the respective soil moisture monitoring station (see supplement Table S1) is shown in the same plots and the upper panel presents the daily precipitation and daily air temperature as averages of the measurements collected at the three KNMI automated weather stations AWSs in the region.

Substantial differences can be noted between the three monitoring stations, which are situated 25 km to 30 km apart at elevations varying from 0-10 m to 15 m a.m.s.l. For instance, in Fig. 10c (ITC_SM14), the 80 cm soil moisture content remained at a high level even during the peak of the 2018 drought, whereas deep drops are observed in Figs. 10b (ITC_SM10) and 10d (ITC_SM17). These measurements demonstrate that the position within a catchment is an important factor for the impact drought has locally, even though drought may be seen as a regional-scale process. An improved understanding of the physical processes underlying such regional differences in hydrological behavior within lowland ecosystems could assist water managers with taking better informed decisions on drought mitigation measures.

The overall time series confirm the seasonal dynamics of wet soils and high groundwater levels in winters, and dry circumstances with lower groundwater levels during summers. Also expected is the stronger response to precipitation of the soil moisture contents measured closest to the surface, whereas at 80 cm mainly seasonal variations are noted. Specifically at a depth of 80 cm, the effects of the 2018, 2019 and 2020 droughts is-are visible, while the topsoil (5 and 10 cm) dries out nearly every summer during the summer period virtually every year.

Somewhat surprising in the plots is the response of the groundwater level to precipitation. In all three groundwater measurement_level series, ~~increments-increases~~ can be identified after large precipitation events, whereas the soil moisture at 80 cm primarily displays seasonal variations and individual events are hardly noticeable. ~~To take this a step further and explore the relationship with soil moisture, Table 6 presents the R² values computed between the measurements at specific depths and groundwater levels. Indeed, the R² values support the above observation. The shallower 40 cm soil moisture content yields the highest R², not the deeper 80 cm measurements.~~

Another interesting feature is that the soil moisture at 5 cm and 10 cm, ~~and the groundwater levels~~ are still reasonably correlated with the groundwater levels. This can likely be attributed to the shallow groundwater table in the study area that causes a naturally fast hydrological response. The groundwater table fluctuations match especially in winter well with the variations in soil moisture measured at 5 cm and 10 cm. The moisture contents measured at 80 cm are under those conditions less responsive to rain events because the surrounding soil is already saturated.

Hence, the disclosed datasets provide also an opportunity to further investigate the linkages between the water contents in the ~~unsaturated vadose~~ zone and the groundwater table. This knowledge may be used to provide soil moisture estimates in regions where groundwater monitoring wells are abundant or groundwater information based on surface soil moisture observed from space in countries where groundwater monitoring networks are absent. The latter has previously been conducted by Sutanudjaja et al. (2013), who estimated groundwater level across the Rhine-Meuse river basin using time series of soil water index retrieved from coarse resolution scatterometer data. The present dataset allows for more detailed investigations of the relationship between the phreatic groundwater and soil moisture, and how they behave in space and time. Moreover, the spatial measurement density of the Twente network as well as the field campaign data, the access to the other relevant data documented in this manuscript and the availability of higher resolution soil moisture products (e.g. Bauer-Marschallinger et al., 2019, Das et al. 2019) make it possible to ~~address study sub-catchment smaller~~ scale applications ~~than were addressed before~~.

7. Processing, flagging and availability of data

The datasets are made available at three processing levels referred to as raw, processed and calibrated data. The raw data ~~from the monitoring stations~~ are the native EM50 data logger files organized per monitoring station. These files are in the MS Excel 97-2003 format and have two worksheets, of which one includes the unprocessed data (digital numbers) and the other holds soil moisture and soil temperature measurements converted from the digital numbers using default calibration functions. For details, we refer to the EC-TM and 5TM manuals (METER Group, 2019) and the readme file provided together with the dataset. The processed data ~~is has been~~ developed from the raw ~~soil moisture and temperature~~ data and checked for missing time stamps, missing values ~~are have been~~ replaced with -99.999, time stamps ~~are hasve been~~ converted to a consistent date time format [dd-mm-yyyy hh:mm] and placed in a chronological order starting with January 1 of the year the station was installed till December 31 of the year operations were stopped or 2020. The resulting data files, one for each station, ~~are have~~

475 [been](#) converted into CSV files with suffix _pd. The calibrated data ~~is-has been~~ obtained through ~~the~~ application of the developed calibration functions (section 3.3) to the processed data and is included in the CSV files with suffix _cd.

DQ flags ~~are-have been~~ created, providing details related to the measurement setup and the reliability of the calibrated data in an automated manner. The DQ flags are documented in separate CSV files with suffix _fg. The files include 4 sets of flags indicative for the quality of ~~the~~-i) [the](#) soil moisture and ii) [the](#) soil temperature data, [and](#) iii) specifics related to the measurements setup and iv) probetype. The DQ flags start respectively with ‘SM’, ‘ST’, ‘MS’ and ‘PR’, followed by 5 integers each referring to one of the respective 5 ports of [the](#) EM50 data logger. The automated quality control procedure reported in Dorigo et al. (2013, 2021) ~~is-has been~~ adopted for i) and ii) except for the flags that require [external datasets](#). Table [67](#) lists the flags and ~~their-the~~ descriptions for the four [respective](#) flag types. Only the highest digit is visible within the dataset, implicating that the order of the flags is associated with an increase in concern for the data quality.

485 The raw data from the field campaigns are organized on a yearly basis. The processed data consists of soil moisture contents obtained through the application of the default calibration function to the native probe readings and the calibrated data are the processed soil moisture contents to which [the](#) field campaign-specific calibration functions have been applied. Details on the data processing can be found in the readme document accompanying the dataset. Both the processed and calibrated data are combined in a [single](#)-comma-separated values (CVS) formatted file with suffix _pd_cd for the stations where field campaigns took place.

490 The above-described datasets, [coordinates of the monitoring stations](#) and photos taken during field visits are publicly available at <https://doi.org/10.17026/dans-znj-wyg5> (Van der Velde et al. 2022). Folder and file structures as well as the processing steps are described in a readme file. ~~The measurement locations are given in geographic (WGS84) and map projected eordinates (Amersfoort/RD-new)~~. Table [8-7](#) lists the third-party datasets that are available for the study region.

8. Summary and outlook

495 Soil moisture and temperature profile measurements from 2008 to 2020 have been automatically collected at 15-minute intervals by a network of 20 permanent monitoring stations spread across the Twente region and neighbouring regions in the east of the Netherlands. The monitoring stations are mostly placed at the border of privately owned parcels used for agriculture with, in order of occurrence, grass, maize, cereals, potato and natural vegetation as land covers. The experimental setup includes METER Group (formerly: Decagon) EC-TM and its successor 5TM capacitance probes installed at nominal depths
500 of 5 cm, 10 cm, 20 cm, 40 cm and 80 cm. Soil-specific calibration functions have been developed under controlled laboratory conditions for both probe types yielding accuracies of $0.023 \text{ m}^3 \text{ m}^{-3}$ and $0.028 \text{ m}^3 \text{ m}^{-3}$ for the EC-TM and 5TM, respectively. In addition, field campaign data covering the growing seasons of 2009, 2015, 2016 and 2017 are described and disclosed, during which the top 5 cm soil moisture content was measured with handheld probes (Delta-T ThetaProbe, [Type ML2](#), and Stevens HydraProbe) and via soil sampling on a total of 28 fields near ~~twelve-12~~ different monitoring stations. Pairs of
505 gravimetrically determined soil moisture and probe readings were used to establish calibration functions for ~~both~~-the

ThetaProbe and HydraProbe. The ~~obtained~~ accuracies ~~obtained~~ for the probe calibrations varied from 0.048 m³ m⁻³ for the ThetaProbe measurements in 2009 up to 0.032 m³ m⁻³ for the HydraProbe measurements collected in 2016-2017.

The spatial representativeness of the permanent monitoring stations is investigated through comparisons with the in-situ measurements collected during the campaigns, which is found to result ~~at the network scale for the entire network~~ in a coefficient of determination (R²) of 0.770 and a root mean squared error (RMSE) of 0.0468 m³ m⁻³. An important part of the RMSE is attributable to a 0.0303 m³ m⁻³ underestimation, ~~which -of the field VSM- This underestimation-~~ is particularly apparent for individual grass fields ~~(0.0989 m³ m⁻²) as a result of edge effects~~ and is generally strong after heavy rainfall ~~due to the overland flow and the latency required for infiltration fronts to cross the complete sensor's influence zone.~~

~~Hence, t~~The soil moisture and temperature datasets offered by the network of permanent monitoring stations as well as the field campaign datasets provide opportunities to further study and quantify the uncertainties associated with the development of soil moisture references, for instance, ~~to develop and validate for the development and validation of~~ satellite and model-based soil moisture products ~~at both field and network the scale of footprints and grid cells scale~~. This ~~is may, for instance, also be particularly~~ relevant for ~~the development of calibration/validation plans for~~ upcoming Synthetic Aperture Radar (SAR) missions such as the NASA-ISRO SAR mission (NISAR; Kellogg et al., 2020) and the Radar Observing System of Europe L-band (ROSE-L; Davidson & Furnell, 2021), which ~~will feature L-band SAR sensors which are widely considered as suitable for have both~~ soil moisture ~~included as part of in their mission objectives retrieval (Entekhabi et al., 2010)~~. The datasets may further prove of value for investigations focused on the water and energy exchange across the groundwater-vadose zone-atmosphere continuum of lowland ecosystems, which is particularly relevant in a changing climate due to which these environments are expected to face more frequent occurrences of floods and droughts.

Scientists and professionals worldwide are invited to make free use of the datasets disclosed with this contribution for any purpose it may fit under a Creative Commons, CC BY 4.0 license. Descriptions of open third-party datasets are provided to support the use of the measurements ~~beyond the scope for which the network was originally established~~. We welcome any comments or suggestions that can help improve the quality and usability of the datasets. The data collected with the Twente network continues, but plans are underway to update the design of the network to contemporary societal and scientific needs. This may include flood and drought analyses, and high-resolution satellite product validation.

Author contribution

RV and HJB contributed to the fieldwork, data processing, data quality control, conceptualization and writing of the paper. HJB led the data quality control, BR assisted with the data analysis, SSA assisted with the data analysis and writing of the paper, PV assisted with writing and is responsible for the continuation of the monitoring network, and RV coordinated and led the writing of the paper.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

540 The authors thank the farmers who provided free access to the parcels where the monitoring stations have been installed. The
Royal Netherlands Academy of Arts and Sciences (KNAW) is acknowledged for the support via the small data project
(Klein Data Project) programme for making the dataset available through its DANS (Data Archiving and Networked
Services) platform, project number KDP002. Laura Dente, Zoltan Vekerdy, and Bob Su are acknowledged for their role in
the development and involvement of the monitoring network till 2012. Murat Ucer is mentioned for his contribution to field
545 data collection. Further, the authors would like to thank all the students and researchers who participated in the field data
collection over the years.

References

- Actueel Hoogtebestand Nederland (AHN): Actueel Hoogtebestand Nederland, [online] Available from: www.ahn.nl (last
access: 3 March 2022), 2019.
- 550 Bakke, S. J., Ionita, M., and Tallaksen, L. M.: The 2018 northern European hydrological drought and its drivers in a historical
perspective, *Hydrol. Earth Syst. Sci.*, 24, 5621–5653, <https://doi.org/10.5194/hess-24-5621-2020>, 2020.
- Bauer-Marschallinger, B., Paulik, C., Hochstöger, S., Mistelbauer, T., Modanesi, S., Ciabatta, L., Massari, C., Brocca, L.,
Wagner, W.: Soil Moisture from Fusion of Scatterometer and SAR: Closing the Scale Gap with Temporal Filtering, *Remote
Sens.*, 10, 1030. <https://doi.org/10.3390/rs10071030>, 2018.
- 555 Bauer-Marschallinger, B., Freeman, V., Cao, S., Paulik, C., Schauffer, S., Stachl, T., Modanesi, S., Massari, C., Ciabatta, L.,
Brocca, L., and Wagner, W.: Toward Global Soil Moisture Monitoring With Sentinel-1: Harnessing Assets and Overcoming
Obstacles, *IEEE Trans. Geosci. Remote Sens.*, 57, 520-539, doi: 10.1109/TGRS.2018.2858004, 2019.
- Benninga, H.-J. F., Carranza, C. D. U., Pezij, M., van Santen, P., van der Ploeg, M. J., Augustijn, D. C. M., and van der Velde,
R.: The Raam regional soil moisture monitoring network in the Netherlands, *Earth Syst. Sci. Data*, 10, 61-79, doi:10.5194/essd-
10-61-2018, 2018.
- 560 Benninga, H. F., van der Velde, R., and Su, Z.: Sentinel-1 soil moisture content and its uncertainty over sparsely vegetated
fields, *Journal of Hydrology X*, 9, 1-17, <https://doi.org/10.1016/j.hydroa.2020.100066>, 2020.
- Benninga, H.F., Van der Velde, R., and Su, Z.: Soil moisture content retrieval over meadows from Sentinel-1 and Sentinel-2
data using physically based scattering models, *Remote Sens. Environ.*, 280, <https://doi.org/10.1016/j.rse.2022.113191>, 2022.
- 565 Bircher, S., Skou, N., Jensen, K. H., Walker, J. P., and Rasmussen, L.: A soil moisture and temperature network for SMOS
validation in Western Denmark, *Hydrol. Earth Syst. Sci.*, 16, 1445–1463, <https://doi.org/10.5194/hess-16-1445-2012>, 2012.
- Bogena, H.R., Huisman, J.A., Oberdörster, C. and Vereecken, H.: Evaluation of a low-cost soil water content sensor for
wireless network applications, *Journal of Hydrology*, 344, 32-42, <https://doi.org/10.1016/j.jhydrol.2007.06.032>, 2007.
- Bogena, H., White, T., Bour, O., Li, X. and Jensen, K.: Toward Better Understanding of Terrestrial Processes through Long-
Term Hydrological Observatories, *Vadose Zone Journal*, 17, 1-10, <https://doi.org/10.2136/vzj2018.10.0194>, 2018.
- 570 Brutsaert, W.: *Hydrology – An Introduction*, Cambridge University Press, Cambridge, United Kingdom, 2005.

- Buitink, J., Swank, A. M., van der Ploeg, M., Smith, N. E., Benninga, H.-J. F., van der Bolt, F., Carranza, C. D. U., Koren, G., van der Velde, R., and Teuling, A. J.: Anatomy of the 2018 agricultural drought in the Netherlands using in situ soil moisture and satellite vegetation indices, *Hydrol. Earth Syst. Sci.*, 24, 6021–6031, <https://doi.org/10.5194/hess-24-6021-2020>, 2020.
- 575 Buras, A., Rammig, A., and Zang, C. S.: Quantifying impacts of the 2018 drought on European ecosystems in comparison to 2003, *Biogeosciences*, 17, 1655–1672, <https://doi.org/10.5194/bg-17-1655-2020>, 2020.
- Caldwell, T.G., Bongiovanni, T., Cosh, M.H., Jackson, T.J., Colliander, A., Abolt, C.J., Casteel, R., Larson, T., Scanlon, B.R. and Young, M.H.: The Texas Soil Observation Network: A Comprehensive Soil Moisture Dataset for Remote Sensing and Land Surface Model Validation. *Vadose Zone Journal*, 18: 1–20, <https://doi.org/10.2136/vzj2019.04.0034>, 2019.
- 580 Calvet, J.-C., Fritz, N., Froissard, F., Suquia, D., Petitpa, A., and Pignatelli, B.: In situ soil moisture observations for the CAL/VAL of SMOS: the SMOSMANIA network, *International Geoscience and Remote Sensing Symposium, IGARSS*, Barcelona, Spain, 23–28 July 2007, 1196–1199, doi:10.1109/IGARSS.2007.4423019, 2007.
- Campbell, J.E.: Dielectric Properties and Influence of Conductivity in Soils at One to Fifty Megahertz. *Soil Science Society of America Journal*, 54: 332–341. <https://doi.org/10.2136/sssaj1990.03615995005400020006x>, 1990.
- 585 Carranza, C. D. U., van der Ploeg, M. J., and Torfs, P. J. J. F.: Using lagged dependence to identify (de)coupled surface and subsurface soil moisture values, *Hydrol. Earth Syst. Sci.*, 22, 2255–2267, <https://doi.org/10.5194/hess-22-2255-2018>, 2018.
- Carranza, C., Benninga, H. J., van der Velde, R., & van der Ploeg, M. (2019). Monitoring agricultural field trafficability using Sentinel-1. *Agricultural water management*, 224, [105698]. <https://doi.org/10.1016/j.agwat.2019.105698>
- Chambers, C. and Crawford, L.: Customer Notification: attention 5TM, 5TE and GS3 calibrations, Decagon Devices, Pullman, United States of America, 2014.
- 590 Chan, S.K., Bindlish, R., O'Neill, P., Jackson, T., Njoku, E., Dunbar, R.S., Chaubell, J., Piepmeier, J., Yueh, S., Entekhabi, D., Colliander, A., Chen, F., Cosh, M.H., Caldwell, T.G., Walker, J., Berg, A.A., McNairn, H., Thibeault, M., Martínez-Fernández, J., Uldall, F., Seyfried, M., Bosch, D.D., Starks, P.J., Holfield-Collins, C.D., Prueger, J.H., van der Velde, R., Asanuma, J., Palecki, M., Small, E.E., Zreda, M., Calvet, J.C., Crow, W.T. and Kerr, Y.H.: Development and assessment of the SMAP enhanced passive soil moisture product, *Remote Sens. Environ.*, 204, 931–941, doi: 10.1016/j.rse.2017.08.025, 2018.
- 595 Chaubell, M. J., Yueh, S. H., Scott Dunbar, R., Colliander, A., Chen, F., Chan, S. K., Entekhabi, D., Bindlish, R., O'Neill, P. E., Asanuma, J., Berg, A. A., Bosch, D. D., Caldwell, T., Cosh, M. H., Collins, C. H., Martinez-Fernandez, J., Seyfried, M., Starks, P. J., Su, Z., Thibault, T., and Walker, J.: Improved SMAP Dual-Channel Algorithm for the Retrieval of Soil Moisture, *IEEE Trans. Geosci. Remote Sens.*, 58(6), 3894–3905, <https://doi.org/10.1109/TGRS.2019.2959239>, 2020.
- 600 Cobos, D. R. and Chambers, C.: Application Note: Calibrating ECH2O Soil Moisture Sensors, Pullman, WA USA. Decagon Devices, Inc. [online] Available from: <https://eu.ictinternational.com/content/uploads/2014/03/13393-04-CalibratingECH2OsoilMoistureProbes.pdf> (last access: 3 March 2022), 2010.
- 605 Colliander, A., Jackson, T.J., Bindlish, R., Chan, S., Das, N., Kim, S.B., Cosh, M.H., Dunbar, R.S., Dang, L., Pashaian, L., Asanuma, J., Aida, K., Berg, A., Rowlandson, T., Bosch, D.D., Caldwell, T., Caylor, K., Goodrich, D.C., Al Jassar, H., Lopez-Baeza, E., Martinez-Fernandez, J., Gonzalez-Zamora, A., Livingston, S., McNairn, H., Pacheco-Vega, A., Moghaddam, M., Montzka, C., Notarnicola, C., Niedrist, G., Pellarin, T., Prueger, J., Pulliainen, J., Rautiainen, K., Garcia-Ramos, J.V., Seyfried, M., Starks, P.J., Su, Z., Zeng, Y., van der Velde, R., Thibeault, M., Dorigo, W.A., Vreugdenhil, J.M., Walker, J.P., Wu, X., Monerris, A., O'Neill, P.E., Entekhabi, D., Njoku, E.G., and Yueh, S.: Validation of SMAP surface soil moisture products with core validation sites, *Remote Sens. Environ.*, 191, 215–231, <https://doi.org/10.1016/j.rse.2017.01.021>, 2017.

- 610 Das, N.N., Entekhabi, D., Dunbar, R.S., Chaubell, M.J., Colliander, A., Yueh, S., Jagdhuber, T., Chen, F., Crow, W., O'Neill, P.E., Walker, J.P., Berg, A., Bosch, D.D., Caldwell, T., Cosh, M.H., Collins, C.H.m Lopez-Baeza, E., and Thibeault, M.: The SMAP and Copernicus Sentinel 1A/B microwave active-passive high resolution surface soil moisture product, *Remote Sens. Environ.*, 233, 111380, doi:10.1016/j.rse.2019.111380, 2019.
- Davidson, M. W., & Furnell, R. (2021, July). ROSE-L: Copernicus L-band SAR mission. In 2021 IEEE International Geoscience and Remote Sensing Symposium IGARSS (pp. 872-873). IEEE.
- 615 De Bruin, H.A.R.: From Penman to Makkink, in: Evaporation and weather: Technical meeting 44, Ede, The Netherlands, 25 March 1987, Proceeding and Information/TNO Committee on Hydrological Research, no. 39, 1987.
- Decagon Devices: ECH2O-TE/EC-TM, Water Content, EC and Temperature Sensors: Operator's Manual version 7, Decagon Device Inc, Pullman, United States of America, 39 pp., 2008. Available at [http://manuals.decagon.com/Retired%20and%20Discontinued/Manuals/ECH2O-TEEC-TMv6-Operators-Manual-](http://manuals.decagon.com/Retired%20and%20Discontinued/Manuals/ECH2O-TEEC-TMv6-Operators-Manual-(discontinued).pdf) (discontinued).pdf (last access: 3 March 2022).
- 620 Decagon Devices: 5TM water content and temperature sensors version July 10 2017, Decagon Device Inc, Pullman, United States of America, 17 pp., 2017. Available at http://manuals.decagon.com/Retired%20and%20Discontinued/Manuals/13441_5TM_Web.pdf (last access: 3 March 2022).
- METER Group: Em50 version 2019, METER Group Inc, Pullman, United States of America, 55 pp., 2019. Available at http://publications.metergroup.com/Manuals/20452_Em50_Manual_Web.pdf (last access: 3 March 2022).
- 625 Delta-T Devices: User manual for the ML3 ThetaProbe version January 2017, Delta-T Devices Ltd, Cambridge, United Kingdom, 47 pp., 2017. Available at <https://delta-t.co.uk/wp-content/uploads/2017/02/ML3-user-manual-version-2.1.pdf> (last access: 3 March 2022).
- Dente, L., Vekerdy, Z., Su, Z. and Ucer, M.: Twente soil moisture and soil temperature monitoring network, University of Twente, Enschede, 19 pp., 2011.
- 630 Dente, L., Su, Z. and Wen, J.: Validation of SMOS Soil Moisture Products over the Maqu and Twente Regions, *Sensors*, 12(8), 9965–9986, doi:10.3390/s120809965, 2012.
- Dingman, S. L.: *Physical Hydrology* 3rd Edition, Waveland Press Inc., Long Grove, United States of America, 2015.
- Dorigo, W. A., Wagner, W., Hohensinn, R., Hahn, S., Paulik, C., Xaver, A., Gruber, A., Drusch, M., Mecklenburg, S., van Oevelen, P., Robock, A., and Jackson, T.: The International Soil Moisture Network: a data hosting facility for global in situ soil moisture measurements, *Hydrol. Earth Syst. Sci.*, 15, 1675–1698, <https://doi.org/10.5194/hess-15-1675-2011>, 2011.
- 635 Dorigo, W.A., Xaver, A., Vreugdenhil, M., Gruber, A., Hegyiova, Sanchis-Dufau, Zamojski, D., Cordes, C., Wagner, W., and Drusch, M.: Global automated quality control of in situ soil moisture data from the international soil moisture network. *Vadose Zone Journal*, 12, 1-22, <https://doi.org/10.2136/vzj2012.0097>, 2013.
- 640 Dorigo, W., Himmelbauer, I., Aberer, D., Schremmer, L., Petrakovic, I., Zappa, L., Preimesberger, W., Xaver, A., Annor, F., Ardö, J., Baldocchi, D., Blöschl, G., Bogaen, H., Brocca, L., Calvet, J.-C., Camarero, J. J., Capello, G., Choi, M., Cosh, M. C., Demarty, J., van de Giesen, N., Hajdu, I., Jensen, K. H., Kanniah, K. D., de Kat, I., Kirchengast, G., Rai, P. K., Kyrouac, J., Larson, K., Liu, S., Loew, A., Moghaddam, M., Martínez Fernández, J., Mattar Bader, C., Morbidelli, R., Musial, J. P., Osenga, E., Palecki, M. A., Pfeil, I., Powers, J., Ikonen, J., Robock, A., Rüdiger, C., Rummel, U., Strobel, M., Su, Z., Sullivan, R., Tagesson, T., Vreugdenhil, M., Walker, J., Wigneron, J. P., Woods, M., Yang, K., Zhang, X., Zreda, M., Dietrich, S., Gruber, A., van Oevelen, P., Wagner, W., Scipal, K., Drusch, M., and Sabia, R.: The International Soil Moisture Network:
- 645

- serving Earth system science for over a decade, *Hydrol. Earth Syst. Sci. Discuss.* [preprint], <https://doi.org/10.5194/hess-2021-2>, in review, 2021.
- 650 Entekhabi, D., Njoku, E.G., O'Neill, P.E., Kellog, K.H., Crow, W.T., Edelstein, W.N., Entin, J.K., Goodman, S.D., Jackson, T.J., Johnson, J., Kimball, J., Piepmeier, J.R., Koster, R.D., Martin, N., McDonald, K.C., Moghaddam, M., Moran, S., Reichle, R., Shi, J.C., Spencer, M.W., Thurman, S.W., Leung, T., and van Zyl, J.: The Soil Moisture Active Passive (SMAP) mission, *P. IEEE*, 98, 704-716, doi: 10.1109/JPROC.2010.2043918, 2010.
- Gaskin, G.J., and Miller, J.D.: Measurement of Soil Water Content Using a Simplified Impedance Measuring Technique, *J. Agric. Eng. Res.*, 63, 153-160, doi: 10.1006/jaer.1996.0017, 1996.
- 655 Geological Survey of the Netherlands (GDN): DINOLOKET - Ondergrondgegevens, [online] Available from: <https://www.dinoloket.nl/ondergrondgegevens> (last access: 3 March 2022), 2021.
- Global Climate Observing System (GCOS): Implementation plan for the global observing system for climate in support of the UNFCCC, World Meteorological Organization, Geneva, Switzerland, GCOS-No. 92, 136 pp., 2004. Available at https://library.wmo.int/doc_num.php?explnum_id=3943 (last access: 3 March 2022).
- 660 Global Climate Observing System (GCOS): Implementation plan for the global observing system for climate in support of the UNFCCC, World Meteorological Organization, Geneva, Switzerland, GCOS-No. 138, 180 pp., 2010. Available at https://library.wmo.int/doc_num.php?explnum_id=3851 (last access: 3 March 2022).
- Global Climate Observing System (GCOS): The global observing system for climate: implementation needs, World Meteorological Organization, Geneva, Switzerland, GCOS-No. 200, 315 pp., 2016. Available at https://library.wmo.int/doc_num.php?explnum_id=3417 (last access: 3 March 2022).
- 665 Havekes, H., Koster, M., Dekking, W., Uijterlinde, R., Wensink, W. and Walkier, R.: Water Governance – The Dutch Water Authority Model, Opmeer b.v., The Hague, The Netherlands, 61 pp., 2017. Available at <https://dutchwaterauthorities.com/wp-content/uploads/2021/05/The-Dutch-water-authority-model.pdf> (last access: 3 March 2022).
- 670 Heinen, M., Brouwer, F., Teuling, C., and Walvoort, D. J. J.: BOFEK2020 - Bodemfysische schematisatie van Nederland : update bodemfysische eenhedenkaart, Rapport/Wageningen Environmental Research No. 3056, Wageningen Environmental Research. <https://doi.org/10.18174/541544>, 2021.
- Heinen, M., Brouwer, F., Teuling, K. and Walvoort, D.: BOFEK2020 - Bodemfysische schematisatie van Nederland, Wageningen, the Netherlands. Wageningen Environmental Research, Rep. 3056. [online] Available from: <https://www.wur.nl/nl/show/Bodemfysische-Eenhedenkaart-BOFEK2020.htm> (last access: 3 March 2022), 2021.
- 675 Jackisch, C., Germer, K., Graeff, T., Andrä, I., Schulz, K., Schiedung, M., Haller-Jans, J., Schneider, J., Jaquemotte, J., Helmer, P., Lotz, L., Bauer, A., Hahn, I., Šanda, M., Kumpan, M., Dorner, J., de Rooij, G., Wessel-Bothe, S., Kottmann, L., Schittenhelm, S., and Durner, W.: Soil moisture and matric potential – an open field comparison of sensor systems, *Earth Syst. Sci. Data*, 12, 683–697, <https://doi.org/10.5194/essd-12-683-2020>, 2020.
- 680 Jackson, T.J., Cosh, M.H., Bindlish, R., Starks, P.J., Bosch, D.D., Seyfried, M., Goodrich, D.C., Moran, M.S, and Du, J.: Validation of advanced microwave scanning radiometer soil moisture products, *IEEE Trans. Geosci. Remote Sens.*, 48, 4256-4271, 539, doi: 10.1109/TGRS.2010.2051035, 2010.
- Kellogg, K., Hoffman, P., Standley, S., Shaffer, S., Rosen, P., Edelstein, W., ... & Sarma, C. V. H. S. (2020, March). NASA-ISRO synthetic aperture radar (NISAR) mission. In 2020 IEEE Aerospace Conference (pp. 1-21). IEEE

- 685 Kerr, Y.H., Waldteufel, P., Wigneron, J.-P., Delwart, S., Cabot, F., Boutin, J., Escorihuela, M.-J., Font, J., Reul, N., Gruhier, C., Juglea, S. E., Drinkwater, M.R., Hahne, A., Martin-Neira, M., and Mecklenburg, S.: The SMOS mission: New tool for monitoring key elements of the global water cycle, *P. IEEE*, 98, 666-687, doi: 10.1109/JPROC.2010.2043032, 2010.
- Kizito, F., Campbell, C. S., Campbell, G. S., Cobos, D. R., Teare, B. L., Carter, B., and Hopmans, J. W.: Frequency, electrical conductivity and temperature analysis of a low-cost capacitance soil moisture sensor, *J. Hydrol.*, 352, 367–378, 690 <https://doi.org/10.1016/j.jhydrol.2008.01.021>, 2008.
- Kraft, C.: Constitutive parameter measurements of fluids and soil between 500 kHz and 5 MHz using a transmission line technique, *J. Geophys. Res.*, 92(B10), 10650– 10656, doi:10.1029/JB092iB10p10650, 1987.
- Maidment, D.R. (Ed.): *Handbook of Hydrology*, McGraw-Hill Education, New York, United States of America, 1993.
- Martínez-Fernández, J., and Ceballos, A.: Mean soil moisture estimation using temporal stability analysis, *J Hydrol.*, 312, 28- 695 38, doi: 10.1016/j.jhydrol.2005.02.007, 2005.
- Ministry of Economic Affairs and Climate Policy: Basisregistratie Gewaspercelen (BRP), [online] Available from: <https://data.overheid.nl/dataset/10674-basisregistratie-gewaspercelen--brp> (last access: 3 March 2022), 2021.
- Pezij, M., Augustijn, D.C.M., Hendriks, D.M.D., Weerts, A.H., Hummel, S., van der Velde, R., and Hulscher, S.J.M.H.: State updating of root zone soil moisture estimates of an unsaturated zone metamodel for operational water resources management, *J. Hydrol. X*, doi: 10.1016/j.hydroa.219.100040, 2019. 700
- Robinson, D.A., Campbell, C.S., Hopmans, J.W., Hornbuckle, B.K., Jones, S.B., Knight, R., Ogden, F., Selker, J. and Wendroth, O.: Soil Moisture Measurement for Ecological and Hydrological Watershed-Scale Observatories: A Review, *Vadose Zone Journal*, 7, 358-389, <https://doi.org/10.2136/vzj2007.0143>, 2008
- Robock, A., Vinnikov, K. Y., Srinivasan, G., Entin, J. K., Hollinger, S. E., Speranskaya, N. A., Liu, S., and Namkhai, A.: The Global Soil Moisture Data Bank, *B. Am. Meteorol. Soc.*, 81, 1281–1299, 10.1175/1520- 705 0477(2000)081<1281:TGSMDB>2.3.CO;2, 2000.
- Rosenbaum, U., Huisman, J. A., Weuthen, A., Vereecken, H., and Bogaen, H. R.: Sensor-to-Sensor Variability of the ECH2O EC-5, TE, and 5TE Sensors in Dielectric Liquids, *Vadose Zo. J.*, 9, 181–186, <https://doi.org/10.2136/vzj2009.0036>, 2010.
- Royal Netherlands Meteorological Institute (KNMI): Klimatologie - Metingen en waarnemingen, [online] Available from: <https://www.knmi.nl/nederland-nu/klimatologie-metingen-en-waarnemingen> (last access: 3 March 2022), 2021. 710
- Seneviratne, S. I., Corti, T., Davin, E. L., Hirschi, M., Jaeger, E. B., Lehner, I., Orlowsky, B., and Teuling, A. J.: Investigating soil moisture-climate interactions in a changing climate: A review, *Earth-Science Rev.*, 99, 125–161, <https://doi.org/10.1016/j.earscirev.2010.02.004>, 2010.
- Smith, A. B., Walker, J.P., Western, A. W., Young, R. I., Ellett, K. M., Pipunic, R. C., Grayson, R. B., Siriwardena, L., Chiew, F. H. S., and Richter, H.: The Murrumbidgee soil moisture monitoring network data set, *Water Resour. Res.*, 48, W07701, 715 <https://doi.org/10.1029/2012WR011976>, 2012.
- Seyfried, M.S. and Murdock, M.D.: Measurement of Soil Water Content with a 50-MHz Soil Dielectric Sensor, *Soil Sci. Soc. Am. J.*, 68, 394-403, <https://doi.org/10.2136/sssaj2004.3940>, 2004.
- Seyfried, M.S., Grant, L.E., Du, E., and Humes, K.: Dielectric loss and calibration of the Hydra probe soil water sensor, *Vadose Zone Journal*, 4, 1070-1079, <https://doi.org/10.2136/vzj2004.0148>, 2005. 720

- Statistics Netherlands (CBS): Bestand bodemgebruik, [online] Available from: <https://www.cbs.nl/nl-nl/dossier/nederland-regionaal/geografische-data/natuur-en-milieu/bestand-bodemgebruik> (last access: 3 March 2022), 2015.
- 725 Stevens Water Monitoring Systems: HydraProbe (AKA Hydra Probe II) and HydraProbe Analog, Tech. rep., Stevens Water Monitoring Systems, Inc., Portland, OR USA, available online: <https://stevenswater.zendes.com/hc/en-us/articles/360034649013-HydraProbe-AKA-Hydra-Probe-II-and-HydraProbe-Analog> (last access: 3 March 2022), 2020.
- Su, Z., Wen, J., Dente, L., van der Velde, R., Wang, L., Ma, Y., Yang, K., and Hu, Z.: The Tibetan Plateau observatory of plateau scale soil moisture and soil temperature (Tibet-Obs) for quantifying uncertainties in coarse resolution satellite and model products, *Hydrol. Earth Syst. Sci.*, 15, 2303–2316, <https://doi.org/10.5194/hess-15-2303-2011>, 2011.
- 730 Sutanudjaja, E. H., de Jong, S. M., van Geer, F. C., and M. F. P. Bierkens: Using ERS spaceborne microwave soil moisture observations to predict groundwater head in space and time. *Remote Sens. Environ.*, 138, 172–188. <http://dx.doi.org/10.1016/j.rse.2013.07.022>, 2013.
- Tetlock, E., Toth, B., Berg, A., Rowlandson, T., and Ambadan, J. T.: An 11-year (2007–2017) soil moisture and precipitation dataset from the Kenaston Network in the Brightwater Creek basin, Saskatchewan, Canada, *Earth Syst. Sci. Data*, 11, 787–796, <https://doi.org/10.5194/essd-11-787-2019>, 2019.
- 735 Topp, G.C., Davis, J.L., and Annan, A.P.: Electromagnetic Determination of Soil Water Content Measurements in Coaxial transmission lines, *Water Res. Res.*, 16(3), 574–582, 1980.
- Van der Velde, R., Benninga, H.-J. F., V. Retsios, P.C. Vermunt, and M.S. Salama: Twelve years profile soil moisture and temperature measurements in Twente [data set], DANS, <https://doi.org/10.17026/dans-znj-wyg5>.
- 740 Van der Velde, R., Salama, M. S., Eweys, O. A., Wen, J., and Wang, Q.: Soil moisture mapping using combined active or passive microwave observations over the east of the Netherlands. *IEEE Journal of selected topics in applied earth observations and remote sensing*, 8(9), 4355–4372. <https://doi.org/10.1109/JSTARS.2014.2353692>, 2015.
- 745 Van der Velde, R., Colliander, A., Peziz, M., Benninga, H.-J. F., Bindlish, R., Chan, S. K., Jackson, T. J., Hendriks, D. M. D., Augustijn, D. C. M., and Su, Z.: Validation of SMAP L2 passive-only soil moisture products using upscaled in situ measurements collected in Twente, the Netherlands, *Hydrol. Earth Syst. Sci.*, 25, 473–495, <https://doi.org/10.5194/hess-25-473-2021>, 2021.
- Vaz, C. M. P., Jones, S., Meding, M., and Tuller, M.: Evaluation of Standard Calibration Functions for Eight Electromagnetic Soil Moisture Sensors, *Vadose Zo. J.*, 12, vjz2012.0160, <https://doi.org/10.2136/vzj2012.0160>, 2013.
- 750 Vereecken, H., Huisman, J. A., Bogaen, H., Vanderborght, J., Vrugt, J. A., and Hopmans, J.W.: On the value of soil moisture measurements in vadose zone hydrology: A review, *Water Resour. Res.*, 44, W00D06, <https://doi.org/10.1029/2008WR006829>, 2008.
- Wösten, H., de Vries, F., Hoogland, T., Massop, H., Veldhuizen, A., Vroon, H., Wesseling, J., Heijkers, J., and Bolman, A.: BOFEK2012, de nieuwe, bodemfysische schematisatie van Nederland (in: Dutch), Alterra Wageningen UR, Alterra-rapport 2387, 92 pp., 2013.

755

List of tables

Table 1: Mean (μ) regression coefficients and their standard deviations (σ) fitted through pairs of GVSM and 5TM VSM measured in the laboratory on soil collected at sites ITC_SM03, ITC_SM07 and ITC_SM08. Performance metrics, RMSE, ME and R^2 , follow from the validation. n stands for the number of matchups.

760 Table 2: Overview of the soil moisture field campaigns conducted at fields adjacent to monitoring stations. In the far right column, the number in parenthesis stands for the sampled field number and the letter represents the land cover at the start of the campaign (g = grassland, m = maize, f = forest, fw = fallow winter wheat, w = winter wheat, p = potato). In case of no letter, the field was not sampled during the field campaign.

765 Table 3: Mean (μ) and standard deviation (σ) of regression coefficients ([a and b](#)) obtained for pairs of GVSM and ThetaProbe VSM and associated performance metrics (RMSE, ME, R^2) for measurements taken during the 2009 and 2015 field campaigns. Two matching ThetaProbe values are used: i) a reading next to the soil sample (in the table: site), ii) the mean of all readings taken at the sampling point (in the table: mean). n stands for the number of matchups.

Table 4: Similar to Table 3, but for calibrations of 2016-2017 HydraProbe measurements. In this case, calibration functions were also developed for individual stations.

770 Table 5: The number of matchups, and performance metrics computed between the field ~~--averaged mean~~ and matching station VSM including the RMSE, ME, coefficients a and b of the linearly regressed line, R^2 and standard error of estimate (SEE).

~~Table 6: R^2 computed between soil moisture measured at specific depths and groundwater level at the well nearest to the soil moisture monitoring station available in DINOloket (see Supplement Table S2). The time series are shown in Figure 10. n stands for the number of groundwater and soil moisture data pairs.~~

775 Table ~~76~~: Soil moisture and temperature data quality, measurements setup and probe type flags included in the DQ files created based on the calibrated data files.

Table ~~87~~: Open third-party datasets available for the study region described in Section 2.

780

Table 1: Mean (μ) regression coefficients and their standard deviations (σ) fitted through pairs of GVSM and 5TM VSM measured in the laboratory on soil collected at sites ITC_SM03, ITC_SM07 and ITC_SM08. Performance metrics, RMSE, ME and R^2 , follow from the validation. n stands for the number of matchups.

<i>Set</i>	<i>n</i>	<i>a</i> ($m^3 m^{-3}$)		<i>b</i> (-)		<i>RMSE</i>	<i>ME</i>	<i>R</i> ²
		μ	σ	μ	σ	($m^3 m^{-3}$)	($m^3 m^{-3}$)	-
ITC_SM03	38	0.00423	0.00186	1.87	0.0165	0.0237	0.000	0.927
ITC_SM07	32	0.0214	0.00307	1.77	0.0208	0.0303	0.000	0.883
ITC_SM08	29	0.0546	0.00510	1.52	0.0369	0.0315	0.000	0.786
All soils*	99	0.0200 (-0.0217)	0.000958	1.76 (1.63)	0.00737	0.0277	0.000	0.884

* In parenthesis are the calibration coefficients for the 5TM probes with firmware v4.0.

Table 2: Overview of the soil moisture field campaigns conducted at fields adjacent to monitoring stations. In the far right column, the number in parenthesis stands for the sampled field number and the letter represents the land cover at the start of the campaign (g = grassland, m = maize, f = forest, fw = fallow winter wheat, w = winter wheat, p = potato). In case of no letter, the field was not sampled during the field campaign.

Year	Period	Days	Probe	Stations (field 1, field 2, field 3, field 4, field 5)
2009	22 Sept – 28 Oct	5	ThetaProbe	ITC_SM03 (1g, 2m), 05 (1g, 2g, 3m, 4), 07 (1m, 2m, 3m, 4), 08 (1g, 2m, 3f, 4), 11 (1g, 2g, 3f), 12 (1g, 2g, 3g, 4g), 17 (1g, 2g, 3g, 4g, 5g), 18 (1g, 2g, 3g, 4g)
2015	11 Sept – 3 Nov	11	ThetaProbe	ITC_SM03 (1g, 2), 04 (1g, 2g), 05 (1g, 2g, 3, 4g), 07 (1m, 2m, 3m, 4), 08 (1, 2m, 3, 4g), 09 (1fw, 2fw)
2016	25 May – 11 Nov	15	HydraProbe & ThetaProbe	ITC_SM02 (1g, 2m), 07 (1w, 2w, 3, 4m), 09 (1m, 2) 10 (1m, 2p)
2017/2018*	7 April – 16 Nov	14	HydraProbe	ITC_SM02 (1g, 2m), 03 (1g, 2), 05 (1g, 2g, 3, 4), 07 (1m, 2m), 10 (1m, 2m)

790 * In 2018 a limited number of fields were sampled on February 2nd and April 10th.

795

Table 3: Mean (μ) and standard deviation (σ) of regression coefficients ([a and b](#)) obtained for pairs of GVSM and ThetaProbe VSM and associated performance metrics (RMSE, ME, R^2) for measurements taken during the 2009 and 2015 field campaigns. Two matching ThetaProbe values are used: i) a reading next to the soil sample (in the table: site), ii) the mean of all readings taken at the sampling point (in the table: mean). n stands for the number of matchups.

Set	n	Matchup	a ($\text{m}^3 \text{ m}^{-3}$)		b (-)		RMSE	ME	R^2
			μ	σ	μ	σ	$\text{m}^3 \text{ m}^{-3}$	$\text{m}^3 \text{ m}^{-3}$	-
2009	93	site	0.0686	0.00139	0.920	0.00532	0.0522	-0.001	0.732
		mean	0.0498	0.00130	0.992	0.00484	0.0477	-0.001	0.780
2015	166	site	-0.0128	0.000735	1.09	0.00267	0.0411	0.000	0.875
		mean	-0.00899	0.000733	1.09	0.00277	0.0417	0.000	0.871

Table 4: Similar to Table 3, but for calibrations of 2016-2017 HydraProbe measurements. In this case, calibration functions were also developed for individual stations.

Set	n	Matchup	a ($\text{m}^3 \text{m}^{-3}$)		b (-)		$RMSE$	ME	R^2
			μ	σ	μ	σ	($\text{m}^3 \text{m}^{-3}$)	($\text{m}^3 \text{m}^{-3}$)	-
ITC_SM02	92	site	0.0738	0.000980	0.849	0.00670	0.0324	0.000	0.877
		mean	0.0550	0.000546	0.947	0.00352	0.0289	0.000	0.897
ITC_SM03	12	site	0.0875	0.00527	0.780	0.0196	0.0378	0.002	0.903
		mean	0.0923	0.00833	0.836	0.0405	0.0425	0.003	0.903
ITC_SM07	86	site	0.0797	0.00214	0.788	0.00988	0.0384	0.000	0.805
		mean	0.0865	0.00203	0.801	0.00956	0.0421	0.000	0.759
ITC_SM10	92	site	0.0420	0.000427	0.961	0.00388	0.0217	0.000	0.929
		mean	0.0621	0.000620	0.927	0.00453	0.0329	0.000	0.833
2016- 2017* all	285	site	0.0637	0.000319	0.860	0.00196	0.0323	0.000	0.881
		mean	0.0669	0.000311	0.890	0.00187	0.0351	0.000	0.858

* Three pairs collected on fields adjacent to ITC_SM05 were included in the regional calibration (2016-2017).

Table 5: The number of matchups, and performance metrics computed between the field -mean-averaged and matching station VSM including the RMSE, ME, coefficients a and b of the linearly regressed line, R^2 and standard error of estimate (SEE).

Crop	Station	n	a	b	R^2	ME	RMSE	MAE	SEE
Grass	ITC_SM02	28	1.088	-0.024	0.687	-0.00326	0.0653	0.0408	0.0672
	ITC_SM03	25	0.670	0.018	0.550	-0.0903	0.111	0.0936	0.0590
	ITC_SM04	13	-0.117	0.195	0.0637	-0.274	0.285	0.274	0.0314
	ITC_SM05	28	0.333	0.119	0.357	-0.0741	0.103	0.0853	0.0413
	ITC_SM08	10	0.945	-0.059	0.607	-0.0710	0.0800	0.0710	0.0410
	ITC_SM11	14	0.410	0.193	0.516	0.0370	0.0789	0.0673	0.0421
	ITC_SM12	15	0.390	0.089	0.576	-0.0777	0.0879	0.0781	0.0213
	ITC_SM17	13	0.285	0.002	0.793	-0.239	0.246	0.239	0.0124
	ITC_SM08	15	0.484	0.057	0.376	-0.0971	0.113	0.102	0.0485
	<i>mean</i>			<i>0.499</i>	<i>0.0656</i>	<i>0.503</i>	<i>-0.0989</i>	<i>0.130</i>	<i>0.117</i>
Maize	ITC_SM02	25	0.888	0.0536	0.308	0.0328	0.0767	0.0580	0.0721
	ITC_SM07	68	0.478	0.101	0.359	-0.320	0.0703	0.0494	0.0491
	ITC_SM08	13	0.511	0.0827	0.337	-0.0247	0.0587	0.0506	0.0478
	ITC_SM10	39	0.493	0.0892	0.125	0.00742	0.0681	0.0550	0.0648
	<i>mean</i>			<i>0.504</i>	<i>0.0675</i>	<i>0.282</i>	<i>-0.0041</i>	<i>0.0684</i>	<i>0.0532</i>
Fallow wheat	ITC_SM09	22	0.610	0.215	0.794	0.140	0.142	0.140	0.0170
Potato	ITC_SM10	14	1.032	-0.0192	0.457	-0.0141	0.0546	0.0476	0.0569
Sampling day		45	0.726	0.365	0.770	-0.0303	0.0468	0.0354	0.0300

Table 6: R² computed between soil moisture measured at specific depths and groundwater level at the well nearest to the soil moisture monitoring station available in DINOloket (see Supplement Table S2). The time series are shown in Figure 10. *n* stands for the number of groundwater and soil moisture data pairs.

<i>Station</i>	<i>n</i>	<i>Soil moisture measured at depth</i>				
		<i>5 cm</i>	<i>10 cm</i>	<i>20 cm</i>	<i>40 cm</i>	<i>80 cm</i>
<i>ITC_SM10</i>	1490	0.515	0.499	0.714	0.779	0.758
<i>ITC_SM14</i>	1338	0.722	0.575 ^a	0.709	0.782	0.527
<i>ITC_SM17</i>	1332	0.405	0.509	0.628	0.853	0.851

^aobtained for 1251 pairs.

Table 76: Soil moisture and temperature data quality, measurements setup and probe type flags included in the DQ files created based on the calibrated data files.

<i>Flag type</i>	<i>Flag</i>	<i>Method</i>	<i>Description</i>
Soil moisture (SM) and temperature (ST) data quality	0	n/a	Normal operations
	1	Range verification	Soil moisture below 0.0 m ³ m ⁻³ or soil temperature below -20°C
	2	Range verification	Soil moisture above 0.7 m ³ m ⁻³ or soil temperature above 50°C
	3	Spectrum based	Spike detected
	4	Spectrum based	Negative break (drop)
	5	Spectrum based	Positive break (jump)
	6	Spectrum based	Constant low values following a negative break
	7	Spectrum based	Saturated plateau following a positive break
	9	n/a	No data
Flag type	Flag	Description	
Measurement setup (MS)	0	Normal	
	1	Installation of the station	
	2	Replacement of the sensor	
	3	Relocation within the same field	
	4	Relocation to a different field	
	9	No measurements	
Flag type	Flag	Description	
Probe type (PR)	0	No probe	
	1	EC-TM	
	2	5TM firmware version 2013	
	3	5TM firmware v4.0	

Table 87: Open third-party datasets available for the study region described in Section 2.

<i>Name</i>	<i>Variable(s) of Interest</i>	<i>Responsible institute(s)</i>	<i>Data address and instructions</i>	<i>Available formats</i>
Actueel Hoogtebestand Nederland	Elevation	Regional water authorities WAs, provinces, Directorate-General for Public Works and Water Management	https://www.pdok.nl/introductie/-/article/actueel-hoogtebestand-nederland-ahn3- Under the tab ‘Downloads’ individual tiles can be obtained and under ‘Geo Services’ links to the entire dataset are provided.	GeoTIFF WMS WFS WMTS WCS
BOFEK (Heinen et al., 2021)	Soil texture, Soil physical parameterizations	Wageningen Environmental Research	https://www.wur.nl/nl/show/Bodemfysische-Eenhedenkaart-BOFEK2020.htm ; The map and report can be found under downloads both for BOFEK2020 and BOFEK2012.	.gdb .shp
Land use file (Bestand Bodemgebruik)	land use maps (2010 and 2015)	Statistics Netherlands	https://www.pdok.nl/introductie/-/article/cbs-bestand-bodemgebruik ; for the years 2010 and 2015 downloads as well as Geo Services are available.	.shp WMS WFS
Crop parcel registry (Basisregistratie Gewaspercelen)	Annually updated crop type map	Ministry of Economic Affairs and Climate Policy	https://data.overheid.nl/dataset/10674-basisregistratie-gewaspercelen-brp- ; for the years 2009 – 2020 downloads are available at the tab ‘Databronnen’ and under ‘INSPIRE Atom’ and from 2016 also view services are available.	.gdb WMS WFS WMTS
DINOloket	Groundwater	Geological Survey of the Netherlands	https://www.dinoloket.nl/en ; go to ‘Subsurface data’, apply a filter in the menu on the left and select one of the shapes in the menu on the right to order data for measurement locations.	.csv
Precipitation and weather	Precipitation, wind speed/direction, air temperature, sunshine	Royal Netherlands Meteorological Institute	https://www.knmi.nl/nederland-nu/klimatologie-metingen-en-	.txt

data	duration, shortwave incoming radiation, air pressure, humidity, and cloud cover.		waarnemingen ; for daily precipitation measurements select ‘Dagwaarden neerslagstations’ and for hourly weather data select ‘Dagwaarden van weerstations’.	
Precipitation – radar/gauge 5 min, 3_hr and 24 hr accumulations	Precipitation maps	Royal Netherlands Meteorological Institute	https://dataplatform.knmi.nl/ ; click on the ‘Precipitation’ tile, enter ‘radar/gauge’ in the search bar and select the dataset of choice to retrieve the API endpoint for data access.	.h5

List of figures

815 **Figure 1:** The topography of the study area (source: 5 m spatial resolution AHN3; AHN, 2019) and the locations of the soil moisture/temperature monitoring stations, KNMI automated weather stations (underlined with ID in parenthesis), KNMI precipitation stations and groundwater monitoring wells available in DINO Locket.

Figure 2: Monthly average of the daily mean 1.5 m air temperature, and monthly rainfall and E_{ref} sums derived as mean values from the measurements collected at the KNMI automated weather stations Heino, Hupsel and Twenthe.

820 **Figure 3:** Photos taken of (a and b) the reinstallation of ITC_SM03 on 2 May 2017, c) ITC_SM18 on 17 July 2019 and d) ITC_SM02 on 17 July 2019.

Figure 4: a) Measurements of GVSM against 5TM VSM on soil collected at sites ITC_SM03, ITC_SM07 and ITC_SM08 and b) calibrated 5TM VSM against GVSM measurements performed for the same soils as in a).

825 **Figure 5:** Schematization of impedance probe and GVSM sampling carried out at the sampling locations during the 2009, 2015, 2016 and 2017 field campaigns.


Figure 6: Scatter plots of the ThetaProbe VSM against GVSM collected during the 2009 (a and b) and 2015 (c and d) field campaigns. In subplots a) and c) are the ThetaProbe VSM readings taken next to a GVSM measurement. In subplots b) and d) are the mean of the ThetaProbe VSM readings taken at a sampling point.

830 **Figure 7:** Scatter plots with the HydraProbe VSM against the GVSM collected during the 2016 and 2017 field campaigns. In subplot a) is the HydraProbe VSM reading taken next to the GVSM measurement. In subplot b) is the mean of the HydraProbe VSM readings ~~matched up. s-taken at the sampling point.~~


835 **Figure 8:** Mean values of field-averaged surface soil moisture measured during the 2015, 2016, and 2017 field campaigns (marker: circle) and of 5 cm VSM measured at the matching monitoring stations (marker: square). The solid and dotted lines represent the mean 5 cm VSM of the entire network +/- the standard deviation. The precipitation shown on the secondary axis is derived as the arithmetic mean from the data collected by the three KNMI AWSs.

Figure 9: Soil moisture and temperature depth profiles measured at ITC_SM07 from 7 till 31 July covering a 2019 heatwave in Northwestern Europe.

840 **Figure 10:** The upper panel a) shows averages of the daily rainfall sum and the mean daily air temperature measured at the three KNMI automated weather stations. Profile soil moisture measured from January 2016 till June 2020 at b) ITC_SM10, c) ITC_SM14, and d) ITC_SM17 and groundwater level measured in the nearest well available in DINO Locket (see supplement Table S2).



845 **Figure 1: The topography of the study area (source: 5 m spatial resolution AHN3; AHN, 2019) and the locations of the soil moisture/temperature monitoring stations, KNMI automated weather stations (underlined with ID in parenthesis), KNMI precipitation stations and groundwater monitoring wells available in DINO Locket.**



850 **Figure 2: Monthly average of the daily mean 1.5 m air temperature, and monthly rainfall and E_{ref} sums derived as mean values from the measurements collected at the KNMI automated weather stations Heino, Hupsel and Twenthe.**



855 **Figure 3: Photos taken of (a and b) the reinstallation of ITC_SM03 on 2 May 2017, c) ITC_SM18 on 17 July 2019 and d) ITC_SM02 on 17 July 2019.**




Figure 4: a) Measurements of GVSM against 5TM VSM on soil collected at sites ITC_SM03, ITC_SM07 and ITC_SM08 and b) calibrated 5TM VSM against GVSM measurements performed for the same soils as in a).





Figure 5: Schematization of impedance probe and GVSM sampling carried out at the sampling locations during the 2009, 2015, 2016 and 2017 field campaigns.



865 | **Figure 6: Scatter plots of the ThetaProbe VSM against GVSM collected during the 2009 (a and b) and 2015 (c and d) field campaigns. In subplots a) and c) are the ThetaProbe VSM readings taken next to a GVSM measurement. In subplots b) and d) are the mean of the ThetaProbe VSM readings taken at a sampling point.**




Figure 7: Scatter plots with the HydraProbe VSM against the GVSM collected during the 2016 and 2017 field campaigns. In subplot a) is the HydraProbe VSM reading taken next to the GVSM measurement. In subplot b) is the mean of the HydraProbe VSM readings matched up, taken at the sampling point.

870




Figure 8: Mean values of field-averaged surface soil moisture measured during the 2015, 2016, and 2017 field campaigns (marker: circle) and of 5 cm VSM measured at the matching monitoring stations (marker: square). The solid and dotted lines represent the mean 5 cm VSM of the entire network +/- the standard deviation. The precipitation shown on the secondary axis is derived as the arithmetic mean from the data collected by the three KNMI AWSs.

875





Figure 9: Soil moisture and temperature depth profiles measured at ITC_SM07 from 7 till 31 July covering a 2019 heatwave in Northwestern Europe. The upper panel shows the hourly precipitation and air temperature measured the KNMI AWS Twenthe airport about 12 km southwest of ITC_SM07.

880



885

Figure 10: (a) Daily rainfall and daily air temperature as averages of the three KNMI automated weather stations. (b-d) Profile soil moisture measured at b) ITC_SM10, c) ITC_SM14, and d) ITC_SM17 and groundwater level measured in the nearest well available in DINOLoket (see supplement Table S2). -