

Multiyear surface waves dataset from the subsurface "DeepLev" Eastern Levantine moored station

Nir Haim¹, Vika Grigorieva¹, Rotem Soffer¹, Boaz Mayzel¹, Timor Katz², Ronen Alkalay^{2,3}, Eli Biton², Ayah Lazar², Hezi Gildor⁴, Ilana Berman-Frank⁵, Yishai Weinstein³, Barak Herut², and Yaron Toledo¹

¹School of Mechanical Engineering, Faculty of Engineering, Tel Aviv University, Tel-Aviv, 6997801, Israel

²Israel Oceanographic & Limnological Research, Tel Shikmona, Haifa, 31080, Israel

³Department of Geography and Environment, Bar-Ilan University, Ramat-Gan, 52900, Israel

⁴Institute of Earth Sciences, Hebrew University, Jerusalem, 91904, Israel

⁵Dept. of Marine Biology, Leon H. Charney School of Marine Sciences, University of Haifa, Haifa, 3498838, Israel

Correspondence: Yaron Toledo (toledo@tauex.tau.ac.il)

Abstract.

Processed and analyzed sea surface wave characteristics derived from an up-looking Acoustic Doppler Current Profiler (ADCP) for the period 2016-2022 are presented as a data set available from the public open-access repository of SEA scieNtific Open data Edition (SEANOE) at <https://doi.org/10.17882/96904> (Haim et al., 2022). The collected data include full two-dimensional wave fields along with computed bulk parameters, such as wave heights, periods, and directions of propagation. The ADCP was mounted on the submerged Deep Levantine mooring station located 50 km off the Israeli coast to the west of Haifa (bottom depth ~1470m). It meets the need for accurate and reliable in situ measurements in the Eastern Mediterranean Sea, as the area significantly lacks wave data compare to other Mediterranean sub-basins. The developed long-term timeseries of wave parameters contribute to monitoring and analysis of the region's wave climate, and the quality of wind-wave forecasting models.

1 Introduction

In the past decades ocean waves are being observed around the Mediterranean sea. In some cases providing prolonged records (Ntoumas et al., 2022; Vargas-Yáñez et al., 2023; Morucci et al., 2016). More recently, using High-Frequency radars (Lorente et al., 2022). While there are increasing efforts to gather measurements in the sub-basins of the Mediterranean sea (Tintoré et al., 2019) the Levantine basin is still comparably lacking in observations (Toomey et al., 2022). Monitoring ocean waves is crucial for support in making informed decisions related to the development, protection, and management of the marine and coastal environments. Accurate and regular wave measurements are also of great importance in numerous research fields, for example in studying air-sea and wave-current interactions (Wolf and Prandle, 1999), analysing climate changes or investigating the effects of waves dispersion of particles and oil slicks in the water (Fannelop and Waldman, 1972; Sobey and Barker, 1997; Röhrs et al., 2012). Furthermore, the renewable energy sectors seek to harness ocean waves for power generation, and precise wave monitoring is essential for optimizing the design and operation of wave energy converters (Aderinto and Li, 2018; Lira-

Loarca et al., 2021). Zodiatis et al. (2014, 2015) estimated the wave energy potential based on validated wave model in the East Levantine Basin (ELB).

The acquisition of a long series surface waves data was made possible with the establishment of the Deep Levantine (DeepLev) station that was deployed for the first time on November 2016 about 50 km off-shore Haifa, Israel, at $33^{\circ}00'N$, $34^{\circ}30'E$. It was the first of its kind deep ocean moored research station in the ELB conducting measurements across various fields of marine science. Katz et al. (2020) gives a full description of the mooring system and the large number of state-of-the-art measuring instruments installed on the platform. The mooring cable extended from the seabed at depth of approximately 1470 m up to a subsurface buoy (at a nominal depth of ~ 30 m) carrying an up-looking Acoustic Doppler Current Profiler (ADCP). In general, instruments for waves measurements are deployed at shallow and intermediate waters (20-40 m depth). A quite understandable practice considering the added complexity and hence increased costs involved in deep sea surveys. Nonetheless, long-term observations at deep waters are valuable for continuous monitoring of sea state. Moreover, avoiding the presence of nearshore bathymetry changes or shore reflections allows for a better accuracy evaluation of wave models and satellite measurements.

In this study, a multi-year open-source dataset of wave spectra and derived wave characteristics (i.e. heights, periods, directions) has been developed from DeepLev station measurements for the period 2016-2022. The paper is organized as follows. Section 2 is dedicated to a general description of the measuring instrument, its operation principles and evaluation of wave information. Section 3 deepens into the collected data, expanding about the processing, issues that emerged and their implications on quality. Conclusive Section 4 finalizes the paper by listing the main results and perspectives of deep sea measurements and wave monitoring in the ELB.

2 Methodology

2.1 Acoustic Doppler current profiler wave measurements

As it was mentioned above, the DeepLev station is a multi-functional platform equipped by numerous measuring systems for monitoring the sea state and marine environment. Throughout the whole campaign (2016-2022) the Norteks' Signature-500 ADCP was used to measure surface wave parameters thus the derived data are consistent and homogeneous (figure 1 shows the subsurface buoy and ADCP mounted on it). The practice of combining of the Nortek's ADCPs and subsurface buoys was found to be successful (Pedersen et al., 2007), though with possible data artifacts due to the buoy's wave induced movement. Compared to Pedersen et al. (2007), in this study the subsurface buoy was deeper therefore expected to be less responsive to surface waves' motion.

The Signature-500 has three types of sensors: a pressure sensor, four slanted acoustic beams, and a single vertical acoustic beam—which gives it an advantage over other types of ADCPs, allowing for several wave field evaluation approaches to be applied. The first method is solely relied on the slanted acoustic beams. The transmitted signals and received Doppler shifted back-scatter (Rowe and Young, 1979; McDaniel and Gorman, 1982) enable to estimate wave characteristics, including the directional wave spectrum, $S^{vel}(f, \theta)$ from the induced orbital velocities near the surface (Bowden and White, 1966). The

55 main limit of the "velocity-based" (hereinafter, VEL) method is its sensitivity to installation depth. In deep installations the horizontal spacing between the beams increases beyond the solution's validity. Within the DeepLev's settings, the theoretical upper cut-off at 30 meters depth is 3.85 sec for directional parameters and 1.15 sec for non-directional.

The second method uses the vertically oriented fifth beam for acoustic surface tracking (AST). The measurement of the surface elevation can be directly represented as a frequency spectrum $S^{ast}(f)$. Here, even short waves which cannot be detected
 60 by the slanted beams' array are visible to the AST. Pedersen et al. (2007) offered a way to expand the surface tracking information into directional spectrum, $S^{suw}(f, \theta)$, by combining correlated velocity measurements. This method is known as "SUV" suggesting the combination of surface tracking (S) with horizontal velocities (UV). The name references a third method, the established "PUV" technique (Panicker and Borgman, 1974) which applies similar calculations with pressure observations instead. In this study the depths of installation makes most of the wind-waves frequency range undetectable for the pressure
 65 sensor therefore the pressure fluctuations spectrum, $S^{puv}(f)$ is not further discussed though it is included in the dataset as it may be useful to those interested in the low-frequency end of the wind-wave spectrum.

Prior to each deployment the device's operation mode was configured balancing between the expected duration in the sea and available battery capacity. Table 1 summarizes details of the deployments including the configuration of the experiment, its duration, cycle intervals, and sampling frequency. Most of the time, the ADCP was configured to operate with a sampling
 70 frequency of 2 Hz, with the exception of the fourth deployment when the sampling frequency was 4Hz. The cycle intervals are regulated by two different modes of Signature-500 ("Burst" and "Continuous"). When set to "Burst mode", the device worked at intervals and collected only 2048 continuous samples withing a cycle (equivalent to about 17 min when using 2Hz). The intervals between cycles were also predetermined and are listed in Table 1. The third and fourth deployments measured in "Continuous" mode without any pauses. For the purpose of consistency, their measurements were analyzed to provide 17 min
 75 averages as the rest of the deployments.

2.2 Surface waves averages and directional properties extraction

The first stage of data processing was performed by Nortek's "Ocean Contour" Software, which synthesizes the primary binary files into wave information. The simplest type of analysis provided is by directly identifying individual waves in the surface elevation timeseries, $\eta(t)$. Then, wave characteristics are summarized into the maximal measured wave height H_{max} and period
 80 T_{max} , the mean height H_{mean} , mean zero-crossing T_z , averages over heights and periods of the highest 1/3 of the waves, H_3 and T_3 , and over the highest 1/10 of the waves, H_{10} and T_{10} .

Additionally, the timeseries signals are converted using fast Fourier transform into spectral variance density function $S(f)$ that indicates how much of the surface wave elevation variance is contained at the specific frequencies f . This spectral representation highlights the peak frequency f_p , the most energetic frequency inversely related to the peak period T_p . Other bulk
 85 parameters are calculated through the energy-spectrum's moments (Tucker, 1993), with the moment of order n defined as

$$m_n = \int_0^{\infty} f^n S(f) df, \quad (1)$$

where $S(f)$ is the directional-averaged density spectrum. The parameters calculated from the spectral moments are the significant wave height $H_{m0} = 4\sqrt{m_0}$, the mean wave period $T_{m02} = \sqrt{\frac{m_0}{m_2}}$, and the energy period $T_{energy} = m_{-1}/m_0$, a weighted mean period based on the spectral density which is useful in estimating wave energy potential. For directional data, the mean wave direction per wave frequency, $\theta_m(f)$, is obtained from the first harmonic Fourier coefficients of the power density spectrum function $S(f, \theta)$ and the corresponding Fourier coefficients $a_n(f)$, $b_n(f)$ as follows

$$\theta_m(f) = \arctan \frac{b_1(f)}{a_1(f)}, \quad a_n(f) = \frac{1}{S(f)} \int_0^{2\pi} S(f, \theta) \cos n\theta d\theta, \quad b_n(f) = \frac{1}{S(f)} \int_0^{2\pi} S(f, \theta) \sin n\theta d\theta. \quad (2)$$

The reported mean wave direction θ_m is a weighted average of $\theta_m(f)$ in each frequency bin according to its energy. The peak direction θ_p is the peak of the spread function constructed employing Fourier coefficients of all available harmonics ($n=2$) for the peak frequency. Both estimations are expressed here in meteorological conventions, i.e. the specified direction is the direction which the waves are coming from.

The applied methodology provides a complete set of standard wave characteristics and allows to compare the results with models, satellites, buoys, and visual wave observations on equal terms.

3 Results

100 The developed dataset presented in this paper includes processed, corrected and analyzed measurements from eight ADCP deployments for the period 2016-2022. In order to save maximum wave information we stored all measurements passed the original Norteks' software quality control. However, the data were complemented by quality indexes based on detailed analysis of observations.

3.1 Data integrity and correction

105 Overall, the observations presented here cover a period equivalent to 4.9 consecutive years, between 14-Nov-2016 and 30-Aug-2022. As to the writing of this paper, the DeepLev operation is still ongoing, carrying the ninth deployment of the wave monitoring ADCP which began on January 2023. Table 2 describes the data obtained from each deployment along with assigned quality indexes. Predictably, the majority of observations are of good quality and provide the full set of wave characteristics including directional information. (Soffer et al., 2020) previously compared wave parameters from the DeepLev's first deployment 110 Soffer et al. (2020) with a simultaneous measurement of a bottom-mounted ADCP which was located 48.5 km away at a depth of 26 meters. Both presented a stormy event with reasonable differences given the distance between the locations providing initial validation to the reliability of Signature-500 measurements from the subsurface buoy. However, in some of the later deployments we have faced several challenges during data processing and analysis. Some of them were resolved and others are yet to be explained.

115 The initial challenge we encountered was a considerable variability in the percentages of "Ambiguous" data indicating the inability of the system to determine a local maximum of the wave energy spectra. Naturally, The situation occurs more

frequently while the nominal depth of the buoy carrying the ADCP is higher. When installing a moored station with 1470 m long cable, it was difficult to ensure the precise depth of the sub-surface buoy. In practice, the nominal depths varied by 12 m (27-39 m), therefore some deployments retrieved higher percentages of directional data than others. The analysis showed that
120 for the specific wave characteristics measured, securing the instrument at 30 m bellow the sea surface would add another 10% of valid data to the gathered wave directional information.

Only a small portion of the measurements were found to be unreasonable or completely missing. Occasionally, if there is a problem with returning bursts or if the device has trouble detecting the surface it will lead to missing points after processing. Unfortunately, two of the deployments (the fourth and the eighth) had issues resulting in abnormal data loss. During the fourth
125 deployment, it seems like something obstructed the device as evidenced by notable deviations between the measured distance and pressure. A relatively short timeseries of the eighth deployment stem from an unexpected malfunction of the memory card.

Another problem was addressed after the initial processing. In both, the second and third deployments, the instrument returned without the ordinary temperature readings. Normally, this information is used to evaluate the water's sound velocity (SV) which is necessary to translate the return time of a burst to distance. As a consequence of the fault the initial processing
130 for these deployments was carried out with the Nortek's software default SV value of 1300 m/sec. In practice, the values suitable for the water properties in that area are around 1550 m/sec. This means that the calculations were performed with SV values lower by about 20% which led to similar deviations in computed length scales. To correct these values, the missing temperatures were replaced with records by a secondary temperature sensor attached to the pressure sensor. Using these data, the SV was recalculated with the Gibbs-SeaWater (GSW) Oceanographic Toolbox (McDougall and Barker, 2011). Then the
135 calculated parameters were adjusted according to the ratio between the new SV and the original ones. A good indication that the correction succeeded was to compare the adjusted distances from the AST measurement and to the pressures observations. After the adjustment the two series differed from each other in the same manner as in the remaining deployments. In this regard, one should consider that the SV used for calculations is constant even if the water column is strongly stratified. As it happened during the local summers when according to the temperature measurements the thermocline was located above the
140 ADCP. Then, the assumption that the measured values fitted the entire water column turns out to be inaccurate. In such a case the calculations are based on a temperature measured bellow the thermocline while the water column between the device and the surface are likely $8^{\circ}C - 10^{\circ}C$ warmer. As a result, the uncertainties in SV and wave height estimates could reach 2 – 3%.

Lastly, observing waves from a submerged subsurface buoy adds complexity since the measurements are caring out from a moving platform. The processing software uses records from the tilt sensors for corrections. But, to get a good reading from
145 the AST sensor the tilt must be lower than 10° . With specified DeepLev station mooring settings, there were no instances of angles exceeding this value with the maximal registered tilt reaching 8° . Additional variability manifests in the horizontal and vertical location of the subsurface buoy which mostly caused by the forces the flow applies on the entire mooring system. At the most extreme case the buoy descends by 30 meters in 6 hours meaning it does experience occasionally significant changes in depth even within the 17 minutes windows we use for analysis. These movements can have only a slight impact on the
150 quality of the measurement as the signal but for the most part is negligible since a linear detrend is performed prior to wave parameter extraction. Another type of buoy motion is expected which is a resonant response to the surface waves. According

to the instrument's accelerometers the natural period of the sub-surface buoy was around 8 seconds. Surface wave components around this period regularly induced sway in order of magnitude just a few to tens of centimeter which could add bias or random error to the directional estimates. Encouragingly, this motion is not substantial as appears in Pedersen et al. (2007), probably because the installation was deeper and the natural frequency was higher.

3.2 Data review

The developed dataset represents an open source of surface wave characteristics derived from ADCP measurements (<https://doi.org/10.17882/96904>). The number of files corresponds to the number of deployments which simplify the selection of the timeseries of interest. The used NetCDF4 format guarantees easy access and eliminates occasional reading errors. Each file contains the time varying spectra $S^{ast}(f)$, $S^{vel}(f, \theta)$ and $S^{suv}(f, \theta)$. In addition, it includes unified arrays of the aforementioned statistical wave parameters with preference to values derived from $S^{suv}(f, \theta)$. The frequency range for wave spectra is 0.02-0.45 Hz with the step of 0.005 Hz. A few isolated events led the ADCP to experience deepening of over 10 m. The maximal recorded depth was 54 m on Mar 20th 2022, thus lowering the frequency ambiguity limit to 0.195 Hz. A full description of the files with detailed specification of each wave parameter is available in the appendix.

Figure 2 shows a timeseries of H_{m0} and T_p reconstructed by two methods (VEL and AST) for a short period out of the 3rd deployment. This time frame includes the highest observed waves event of the entire campaign when H_{m0} reached 8 m. Apparently, when the surface waves are high and long there is a good agreement between the two methods. The preference of using the AST approach is eminent in young waves conditions (fig 2b). When it comes to directional spectra, the ability of ADCP is limited in very rough sea state, so the example for retrieved spectra is taken after the peak of the event (Figure 4). Both methods demonstrate a consistency in directional distributions. The incorporation of the AST in the SUV method adjusts the intensities and energy distribution between frequency bins.

Figure 3 displays the distributions of H_{m0} , H_{max} , T_p and T_{m02} among all the data collected. Though there are gaps between deployments, all months were sampled fairly evenly so the results are not expected to be strongly biased. The most probable wave statistics at the DeepLev location have H_{m0} between 0.5 m and 1 m and a T_p of 5-6 sec. Moreover, at least half the time the H_{m0} is over 0.8 m and finding it measuring up to 2.5 m with H_{max} of 4 m is common. To give additional overview of the measured wave distributions, the observed H_{m0} between 14-Nov-2016 and 30-Jun-2021 is compared with model results from the Copernicus Marine Environment Monitoring Service (CMEMS) which implements the WAM model (Günther et al., 1992) to simulate waves in the Mediterranean Sea¹. Similarly to Coppini et al. (2023), the correlation coefficient for H_{m0} is 0.957, but the bias and root mean square error are more significant, -0.025m and 0.256m correspondingly (See Figure 5a). This can be attributed to the bias of forcing winds in the Eastern Levant as seen in their comparison to satellite altimetry. Comparison of T_{m02} in figure 5 shows a general good trend along with a negative bias between modeled and observed representation. For lower values typical for young sea this is due to the instrument's limit of measuring short waves but deviations in the higher range must incorporate the bias originating in the discrepancies of modeling of longer swells as seen in the underestimation of high values of H_{m0} .

¹https://doi.org/10.25423/cmcc/medsea_multiyear_wav_006_012

Wind wave characteristics have been assembled together after multistage data processing, correction, and analysis for an extended period between 2016-2022. The developed dataset derived from an Acoustic Doppler Current Profiler is a part of the comprehensive DeepLev monitoring project in the Levantine basin off the Israeli shore. The analyzed data constitute a timeseries of full two-dimensional wave fields, calculated by two methods utilizing wave orbital velocities and surface tracking, along with conventional statistical parameters: wave heights, periods, and directions of propagation. Preliminary statistical analysis were performed to showcase the distributions, medians and maximal values of principle wave parameters. Finally, a comparison of observed significant wave heights and mean wave periods to parallel model values shows a gap in estimated periods and an underestimation in modeling of high waves.

Such a valuable add-on to the exploring of the Levantine Sea is of importance considering the deficiency of observations compared to other sub-basins of the Mediterranean Sea. The collected data can be effectively used for monitoring wave climate changes on seasonal and long term scales as well as for evaluation of extreme wave characteristics or wave energy in the Eastern Mediterranean. Beyond the importance of the dataset to this specific region it is an uncommon extensive time-series of deep water wave spectral measurements which can generally contribute to marine studies. Besides scientific findings, this experiment also have brought valuable insights on long exploitation of the ADCP Nortek “Signature 500” in deep waters.

To finalize the paper, we would like to stress the value and importance of a unique five year dataset of wave characteristics in the deep waters of the Eastern Mediterranean basin for sea state monitoring.

Data availability.

Described data are freely available through SEANOE (SEA scieNtific Open data Edition) open scientific data repository: <https://doi.org/10.17882/96904> (Haim et al., 2022).

205 *Author contributions.* NH managed processing and organization of data, NH, VG, and YT wrote the manuscript, analysed, evaluated and visualized the processed data. YT, RS and BM maintained the Signature 500 instrument and its operation. The authors TK, RA, EB, AL, HG, IB-F, YW and BH contributed via their labor in the long-term ongoing DeepLev project, its maintenance, operation and management. Funds were raised by IB-F, IW, BH and YT

Competing interests. none

210 *Acknowledgements.* This research was supported by the ISRAEL SCIENCE FOUNDATION [grant No. 25/2014 (IW); and 1940/14 and 1601/20 (YT)] in frame of the used equipment and the student grants. We are grateful to the Council for Higher Education in Israel and the Mediterranean Sea Research Centre of Israel (MERCİ), the Wolfson Foundation, the North American Friends of IOLR and Bar-Ilan University (BIU) for funding the construction and maintenance of DeepLev. This project was supported by the Israeli Ministries of Energy and Environmental Protection under the framework of the National Monitoring Program for Israeli Mediterranean Waters. We would like
215 to show our appreciations to the IOLR electronic, sea operations and marine physical departments for invaluable help with facilities and technical operations in establishing and running the DeepLev station, the captain and crew of R/V Bat-Galim, and the engineers of the machine shop at BIU for their help in the buildup of mooring.

References

- Aderinto, T. and Li, H.: Ocean wave energy converters: Status and challenges, *Energies*, 11, 1250, 2018.
- 220 Bowden, K. and White, R.: Measurements of the orbital velocities of sea waves and their use in determining the directional spectrum, *Geophysical Journal International*, 12, 33–54, 1966.
- Coppini, G., Clementi, E., Cossarini, G., Salon, S., Korres, G., Ravdas, M., Lecci, R., Pistoia, J., Goglio, A. C., Drudi, M., et al.: The Mediterranean Forecasting System–Part 1: Evolution and performance, *Ocean Science*, 19, 1483–1516, 2023.
- Fannelop, T. K. and Waldman, G. D.: Dynamics of oil slicks, *AIAA Journal*, 10, 506–510, 1972.
- 225 Günther, H., Hasselmann, S., and Janssen, P.: The WAM model Cycle 4 (revised version), 1992.
- Haim, N., Grigorieva, V., Soffer, R., Mayzel, B., Katz, T., Alkalay, R., Biton, E., Lazar, A., Gildor, H., Berman-Frank, I., Weinstein, Y., Herut, B., and Toledo, Y.: Surface waves data from a submerged ADCP in the "DeepLev" Eastern Levantine station, <https://doi.org/10.17882/96904>, "SEANOE", 2022.
- Katz, T., Weinstein, Y., Alkalay, R., Biton, E., Toledo, Y., Lazar, A., Zlatkin, O., Soffer, R., Rahav, E., Sisma-Ventura, G., et al.: The first
230 deep-sea mooring station in the eastern Levantine basin (DeepLev), outline and insights into regional sedimentological processes, *Deep Sea Research Part II: Topical Studies in Oceanography*, 171, 104 663, 2020.
- Lira-Loarca, A., Ferrari, F., Mazzino, A., and Besio, G.: Future wind and wave energy resources and exploitability in the Mediterranean Sea by 2100, *Applied Energy*, 302, 117 492, 2021.
- Lorente, P., Aguiar, E., Bondoni, M., Berta, M., Brandini, C., Cáceres-Euse, A., Capodici, F., Cianelli, D., Ciruolo, G., Corgnati, L., et al.:
235 Coastal high-frequency radars in the Mediterranean-Part 1: Status of operations and a framework for future development, *Ocean Science*, 18, 761–795, 2022.
- McDaniel, S. T. and Gorman, A. D.: Acoustic and radar sea surface backscatter, *Journal of Geophysical Research: Oceans*, 87, 4127–4136, 1982.
- McDougall, T. J. and Barker, P. M.: Getting started with TEOS-10 and the Gibbs Seawater (GSW) oceanographic toolbox, *Scor/lapso WG*,
240 127, 1–28, 2011.
- Morucci, S., Picone, M., Nardone, G., and Arena, G.: Tides and waves in the Central Mediterranean Sea, *Journal of Operational Oceanography*, 9, s10–s17, 2016.
- Ntoumas, M., Perivoliotis, L., Petihakis, G., Korres, G., Frangoulis, C., Ballas, D., Pagonis, P., Sotiropoulou, M., Pettas, M., Bourma, E., et al.:
245 The POSEIDON Ocean Observing System: Technological Development and Challenges, *Journal of Marine Science and Engineering*, 10, 1932, 2022.
- Panicker, N. N. and Borgman, L. E.: Enhancement of directional wave spectrum estimates, pp. 258–279, 1974.
- Pedersen, T., Siegel, E., and Wood, J.: Directional wave measurements from a subsurface buoy with an acoustic wave and current profiler (AWAC), in: *OCEANS 2007*, pp. 1–10, IEEE, 2007.
- Röhrs, J., Christensen, K. H., Hole, L. R., Broström, G., Drivdal, M., and Sundby, S.: Observation-based evaluation of surface wave effects
250 on currents and trajectory forecasts, *Ocean Dynamics*, 62, 1519–1533, 2012.
- Rowe, F. and Young, J.: An ocean current profiler using Doppler sonar, in: *OCEANS'79*, pp. 292–297, IEEE, 1979.
- Sobey, R. J. and Barker, C. H.: Wave-driven transport of surface oil, *Journal of Coastal Research*, pp. 490–496, 1997.
- Soffer, R., Vrecica, T., Kit, E., and Toledo, Y.: Observations, modeling, and inter-comparison of waves from deep to intermediate waters in the East Mediterranean basin, *Deep Sea Research Part II: Topical Studies in Oceanography*, 171, 104 646, 2020.

- 255 Tintoré, J., Pinardi, N., Álvarez-Fanjul, E., Aguiar, E., Álvarez-Berastegui, D., Bajo, M., Balbin, R., Bozzano, R., Nardelli, B. B., Cardin, V., et al.: Challenges for sustained observing and forecasting systems in the Mediterranean Sea, *Frontiers in Marine Science*, p. 568, 2019.
- Toomey, T., Amores, A., Marcos, M., and Orfila, A.: Coastal sea levels and wind-waves in the Mediterranean Sea since 1950 from a high-resolution ocean reanalysis, *Frontiers in Marine Science*, 9, 991 504, 2022.
- Tucker, M.: Recommended standard for wave data sampling and near-real-time processing, *Ocean engineering*, 20, 459–474, 1993.
- 260 Vargas-Yáñez, M., Moya, F., Serra, M., Juza, M., Jordà, G., Ballesteros, E., Alonso, C., Pascual, J., Salat, J., Moltó, V., et al.: Observations in the Spanish Mediterranean Waters: A Review and Update of Results of 30-Year Monitoring, *Journal of Marine Science and Engineering*, 11, 1284, 2023.
- Wolf, J. and Prandle, D.: Some observations of wave–current interaction, *Coastal Engineering*, 37, 471–485, 1999.
- Zodiatis, G., Galanis, G., Nikolaidis, A., Kalogeri, C., Hayes, D., Georgiou, G. C., Chu, P. C., and Kallos, G.: Wave energy potential in the Eastern Mediterranean Levantine Basin. An integrated 10-year study, *Renewable energy*, 69, 311–323, 2014.
- 265 Zodiatis, G., Galanis, G., Kallos, G., Nikolaidis, A., Kalogeri, C., Liakatas, A., and Stylianou, S.: The impact of sea surface currents in wave power potential modeling, *Ocean Dynamics*, 65, 1547–1565, 2015.

#	Deployment start	Deployment end	Duration [days]	Sampling Frequency [Hz]	Interval [min]
1	14-Nov-2016	12-May-2017	179	2	120
2	1-Jun-2017	25-Nov-2017	177	2	120
3	4-Dec-2017	28-Apr-2018	145	2	17*
4	31-Jul-2018	28-Mar-2019	240	4	17*
5	13-May-2019	18-Dec-2019	219	2	120
6	18-Feb-2020	16-Sep-2020	211	2	60
7	27-Oct-2020	3-Nov-2021	372	2	60
8	27-Dec-2021	30-Aug-2022	246	2	60

Table 1. Duration for each of the ADCP deployments with measuring configuration: Sampling frequency of sensors and interval of measurements in "Burst" mode. *"Continuous" mode measurements which were then processed in 17 min windows.

#	Nominal depth [m]	Time points	Valid [%]	Ambiguous [%]	Unreasonable [%]	Missing [%]
1	39	2153	82.86	15.00	1.90	0.23
2	31	2128	97.70	1.13	1.08	0.09
3	32	12235	88.39	7.61	3.95	0.06
4	28	20240	84.90	1.93	0.89	12.29
5	29	2621	92.79	4.85	2.37	0.00
6	39	5066	82.23	12.34	2.33	3.10
7	37	8921	84.92	12.70	0.91	1.47
8	27	5905	32.35	2.64	1.61	63.40

Table 2. Summary of quality of data collected at each deployment.



Figure 1. The wave measuring instrument, Nortek's "Signature 500", mounted on the top buoy of the "DeepLev" mooring system.




Figure 2. A short timeseries out of the 3rd deployment derived from velocity orbitals (red) or combined with AST (blue). Shown parameters are a) Significant wave heights and b) peak period. Vertical dashed line marks the date of measurements presented in figure 4




Figure 3. Histograms of combined data from the 8 deployments. a) significant wave heights H_{m0} b) maximal wave heights T_{max} c) peak wave periods T_p d) mean wave periods T_{m02} . Accompanied by approximated probability fits for comparison.




Figure 4. Directional energy density spectra observed on 2018-Jan-19 18:54 processed from a) velocity orbitals, $S^{vel}(\theta, f)$, or b) combined with AST, $S^{suv}(\theta, f)$.




Figure 5. Density scatter plots of the observed a) H_{m0} and b) T_{m02} values to modeled values from CMEMS WAM between 14-Nov-2016 and 30-Jun-2021.

Appendix A

Parameter Name	Notation	Dimensions	Description
Direction		frequency, time	Dominant direction of each frequency component
WaveSpectra AST	$S^{ast}(f, t)$	frequency, time	Spectral analysis of AST
WaveSpectra Pressure	$S^p(f, t)$	frequency, time	Spectral analysis of pressure
WaveSpectra Vel	$S^{vel}(f, t)$	frequency, time	Analysis of surface velocity magnitude
EnergySpectra		frequency, time	Compilation of S^{ast} , S^p and $S^{vel}(f, t)$
FrequencyAmbiguityLimit		time	Cut off frequency for directional analysis
VelocitySpectra_Energy	$S^{vel}(\theta, f, t)$	time, direction, frequency	VEL method, uses velocities
ASTSpectra_Energy	$S^{suv}(\theta, f, t)$	frequency, time	SUV method, uses AST and velocities
PressureSpectra_Energy	$S^{puv}(\theta, f, t)$	time, direction, frequency	PUV method, uses pressure and velocities
FullWaveDirectionalSpectra_Energy		time, direction, frequency	Compilation of S^{suv} , S^{puv} and $S^{vel}(\theta, f, t)$

Table A1. 1D and 2D spectral energy densities included in the Netcdf files. More details on the analysis methods can be found in Section 2.

Parameter Name	Notation	Description	Units
Temperature		averaged temperature	C
Tilt Pitch			degree
Tilt Roll			degree
Heading			degree
Pressure	P	averaged water column pressure	dbar
Distance		distance from surface measured by vertical acoustic beam (AST)	m
Current Direction			degree
Current Speed			m/sec
Direction DirTp	θ_p	Direction at peak wave period	degree
Direction MeanDir	θ_m	Mean Direction	degree
Direction SprTp		Spreading at peak wave period	degree
Height H10	H_{10}	mean height of the 10% largest waves (observed by AST)	m
Height H3	H_3	mean height of the 33% largest waves (observed by AST)	m
Height Hm0	H_{m0}	spectral significant wave height	m
Height Hmean	H_{mean}	mean height of all surface waves (observed by AST)	m
Height Hmax	H_{max}	Highest single wave height (observed by AST)	m
Period T10	T_{10}	mean period of the 10% largest waves (observed by AST)	sec
Period T3	T_3	mean period of the 33% largest waves (observed by AST)	sec
Period Tenergy	T_{energy}	m_{-1}/m_0	sec
Period Tm02	T_{m02}	$\sqrt{m_0/m_2}$: spectral mean wave period	sec
Period Tmax	T_{max}	wave period of single largest wave (observed by AST)	sec
Period Tp	T_p	$1/f_p$ wave period of peak wave frequency	sec
Period Tz	T_z	Mean zero-crossing wave period	sec
SpectrumType		origins of values in 1d spectral variables 0: Pressure 1:Velocity 3:AST	
ZeroCrossings		number of zero crossings	
QI		quality index as described in section 3. 1: valid, 2: ambiguous, 3: unreasonable, 4: fault	

Table A2. Timeseries of wave parameters and sensors records included in the Netcdf files. Parameter Names as appear in the files and notations as appear in the text.