



The German Small Lake and Pond Inventory

Alexander Wachholz¹, Susanne I. Schmidt², Jens Arle¹, Jeanette Völker¹

1 German Environment Agency (UBA), Department for Inland Waters, Wörlitzer Platz 1, 06844, Dessau-Roßlau, Germany

5 2 Helmholtz Center for Environmental Research (UFZ), Department for Lake Research, Brückstraße 3a, 39114, Magdeburg, Germany

Correspondence to: Alexander Wachholz (alexander.wachholz@uba.com)

Abstract. Small lakes and ponds are hotspots of biodiversity, biogeochemical reactions, and hydrological interactions in the landscape. While mostly providing the same functions as larger lakes, they often do so at higher rates per unit area. Exponentially more abundant than larger lakes, small lakes, and ponds contribute significantly to biodiversity, nutrient retention, and the water budget, even at large spatial scales. However, they are rarely considered in regional or larger-scale environmental studies, partly due to a lack of data. To alleviate this, we developed the German Small Lake and Pond Inventory (GSLPI), a comprehensive database of over 260.000 small lakes and ponds ranging in size from 10 to 500.000 m² (50 ha or 0.5 km²). Using only openly available data from Germany's federal states, we provide information on lake or pond location, shape, depth, volume, and connectivity. With this database, we aim to facilitate the integration of small lakes and ponds into environmental research and enhance understanding of their roles within changing landscapes.

1 Introduction

Lakes play a crucial role in supporting both natural environments and human well-being. While they cover only 2.2 % of the global land area (Pi et al., 2022), their contribution to biodiversity and ecosystem services is disproportionately high (Heino et al., 2021). Similar to river segments, smaller lakes occur exponentially more frequently than larger ones (Seekell et al., 2013). Here, we defined small lakes as those with mean surface areas < 0.5 km² (50 ha), as those do not have to be monitored and reported under the European Water Framework Directive ((EU, 2000), Annex II) - they are thus understudied and under-monitored. To further distinguish ponds from small lakes, we used the definition from Richardson et al. (2022), who found that standing water bodies < 5 ha and shallower than 5 meters substantially differ from larger and deeper ones. While large lakes are responsible for > 90 % of the global lake area (Pi et al., 2022), smaller lakes are exponentially more abundant (Seekell et al., 2013). The role that small lakes and ponds play in their surrounding landscape can hardly be overstated: Per area, smaller lakes and ponds contribute more to biodiversity (Biggs et al., 2017) and the retention of nutrients and sediments (Schmadel et al., 2019) than larger ones. During droughts, lakes and ponds can support their adjacent



ecosystems with water and thereby increase their resilience (Chen et al., 2023). In urban areas, lakes and ponds can
30 significantly contribute to mental health (Völker and Kistemann, 2011) and help to mitigate urban heat island effects by
evapotranspirative cooling (Targino et al., 2019). Small lakes and ponds can also be potent emitters of greenhouse gases like
CH₄ (Pi et al., 2022) and may thus contribute disproportionately to their area to global warming. This is especially true for
water bodies used for aquaculture (Rosentreter et al., 2021; Waldemer and Koschorreck, 2023).

However, the exact role that a small lake or pond plays for the adjacent ecosystems depends on its physical characteristics,
35 such as connection to the river network, connection to groundwater, depth, catchment land cover, and its use (Banas et al.,
2008; Richardson et al., 2022; Schmadel et al., 2019; Swartz and Miller, 2021). While such characteristics are easy to collect
for individual lakes, large sample studies, for example, can be assisted with the availability of such data (Meyer et al., 2024).
Furthermore, representative subsets of lakes, e.g. for large-scale sampling campaigns, can be created based on a database of
lake characteristics (Leech et al., 2018). An example of such a database is HydroLAKES (Messenger et al., 2016) which
40 globally describes lakes > 10 ha and their physical characteristics. A well-known national example is the LAGOS database
from the continental United States which contains lakes and ponds > 1 ha (Cheruvilil et al., 2021). LAGOS has been used in
a variety of large-scale studies and has been expanded multiple times (Hanly et al., 2024; King et al., 2021; Rodriguez et al.,
2023; Stachelek et al., 2022).

On the German national scale, however, no such database exists yet. The only dedicated inventory contains ~800 large lakes
45 and reservoirs (> 50 ha), which are monitored and reported according to the water framework directive (Völker et al. 2022).
The available global products (e.g. HydroLAKES (Messenger et al., 2016), Global Surface Water Explorer (Pekel et al.,
2016)) provide data on larger lakes and ponds (> 3 ha) (Ogilvie et al., 2018). Studies on lake size distributions have revealed
that the vast majority of lakes are smaller than that (Seekell et al., 2013). As small lakes are not just ecologically highly
relevant, but also seem to be strongly affected by climate and land use change (Pi et al., 2022; Pilla et al., 2020), we consider
50 a dedicated database on the national scale to be a stepping stone towards further understanding and protection of these
ecosystems.

To achieve this, we have combined publicly available data from all 16 German federal states to build a national scale
database of small lakes and ponds ranging from 1.000 (0.1 ha or 0.001 km²) to 500.000 m² (50 ha or 0.5 km²), the German
Small Lake and Pond Inventory (GSLPI) which contains more than 262.433 lakes and ponds. In addition to their location
55 and shape, we derived other highly relevant attributes such as relation to the river network, maximum depth and volume,
etc., for each lake and pond. For lakes and ponds with a surface area > 1 ha (n=27.210), we also delineated surface
catchments. We used the independent and publicly available data set OpenStreetMap to validate the German Small Lake and
Pond Inventory.

The GSLPI as well as the python scripts used to generate it are available via a Zenodo repository (Wachholz et al., 2024).



60 2 Data and methods

2.1 Lake geometries

The lake polygons, which are the basis of the GSLPI, were obtained from the official cadastral information systems digital landscape model (ATKIS Basis DLM, from here on referred to as DLM) of each federal state. This data is publicly available under the creative common's licenses CC BY 4.0, CC ZERO 2.0, or CC BY 2.0, depending on the federal state (see Table 65 S1 for details of data acquisition and licensing).

From each federal state's DLM, we retrieved all objects of the type 'Standing water bodies' (in German 'AX_Standgewässer'), which are defined as natural or artificial hollow forms of land surface filled with water and enclosed on all sides without any direct connection to the sea (BKG, 2024). In the DLM, harbors, which also fulfill this definition, are distinguished from other standing water bodies and were not considered in this work. Single standing water bodies often consist of multiple polygons in the DLM. To identify individual lakes, we added a one-meter buffer to all polygons and then combined all adjacent polygons. The geospatial operations were executed with the Python library GeoPandas (Jordahl et al., 2020) and the code is available together with the data. This resulted in a total of 262.433 individual lakes and ponds ranging from 10 m² to 500.000 m² (50 ha or 0.5 km²), which were each given a unique identifier (LakeID). While the federal states 75 DLMs should represent all standing water bodies > 1.000 m², some states include even small water bodies (Fig. 2). For example, in Bavaria, most derived lake polygons were smaller than 1.000 m². This heterogeneity between federal states had to be considered when national scale maps or lake density metrics were derived. For this study, we considered, as stated in the DLMs documentation, the lakes and ponds larger than 1.000 m² (n= 178.194) to be continuously mapped across Germany.

80 2.2 Lake attributes

The attributes we derived for the lakes and ponds are summarized in Table 1.

2.2.1 Geometry-related attributes

For each lake and pond, we derived some morphological attributes (area, shoreline length, aspect ratio, shoreline development index) based on their polygons. The shoreline development index (SDI) is defined as

$$85 \quad SDI = \frac{L}{2\sqrt{\pi A}} \quad (1)$$

Where L is the length of the lake's shoreline in meters (circumference of the polygon) and A is its area in square meters. In principle, the index indicates the complexity of the shorelines' form: a perfect circle has an SDI of 1. More complex forms lead to higher SDIs. As the SDI is scale-dependent, only lakes and ponds of similar size mapped at the same resolution should be compared unless some bias correction is applied (Seekell et al., 2022). The aspect ratio represents the ratio 90 between the lake's longest to its shortest axis. To identify these axes, we fitted rectangles to the lake's polygons' minimum



bounding geometries (Cheruvilil et al., 2021). While some lakes are poorly represented by rectangles, the aspect ratio nevertheless helps to identify elongated forms (high ratio) from square or round forms. We further derived the mean elevation of the lake and pond surfaces from the 10-meter national digital terrain model (BKG, 2016).

2.2.2 Connection to other water bodies

95 The connection between a standing water body and the river network is crucial when trying to understand its function in the surrounding landscape (Schmadel et al., 2019) and the landscape's water budget (Bizhanimanzar et al., 2024).

The river network used here also stems from the ATKIS Basis DLM. River segments with mean widths (during mean flow conditions) < 12 meters are represented as lines with a width class attribute (0-3, 3-6, 6-12 meters). The location of those lines is given with an accuracy of ± 3 meters (BKG, 2024). River segments with a mean width greater than 12 meters are
100 represented by polygons. To preserve the topological information, these large river polygons are further characterized by middle lines, which have been estimated by the respective federal authorities. Those middle lines have been supplemented by fictive connecting lines to connect tributaries or through standing water bodies ((BKG, 2024), Fig. S4).

If the closest river to a lake or pond was wider than 12 meters, we computed the Euclidean distance to the river's segments polygon center (Dist2RunningCenter) and to the rivers' segments' polygons edge (Dist2RunningEdge). If the closest river to
105 a lake or pond was narrower than 12 meters, we computed the distance to the river segment line (Dist2RunningCenter) and reported the width category (RunningWidth) of that segments line (see Figure S1 for details). This approach allows users of the database to judge the connectivity between standing water bodies and the river network based on their definitions. We furthermore reported the number of intersections (NRivIntersections) between lake polygon and river networks, as well as the width class of the intersecting river segment (WidthIntersection) and its flow direction (into or out of the lake;
110 FlowDirIntersection).

For the distance between standing water bodies, we derived two attributes. The first was the Euclidean distance to the next standing water body as listed in the new GLSPI (Dist2Standing). As only standing water bodies > 1000 m² are continuously mapped in the DLM across the national scale, we calculated a second attribute (Dist2Standing1000) which is the Euclidean
115 distance to the next standing water body ≥ 1000 m². The first metric cannot be mapped continuously for the entire area of Germany, but it can help, e.g., to identify clusters of lakes. However, since the lakes < 1000 m² are not mapped continuously, a Dist2Standing value > x meters cannot be interpreted as proof that there is indeed no standing water body within this range. The second metric (Dist2Standing1000) is only computed for lakes ≥ 1000 m² and only considers neighboring lakes ≥ 1000 m². It is therefore continuous for the entire Germany and can e.g. be used for map making (see Fig.
120 1). All distance metrics were computed with the sjoin_nearest function of the Python library GeoPandas (Jordahl et al., 2020).



We defined the attribute `IsInFloodplain` to distinguish lakes that are regularly flooded. For this, we used the River flood hazard maps for Europe and the Mediterranean Basin region (Dottori et al., 2021) with a 10-year return period.

125 **2.2.3 Small lake or pond depth and volume**

The depth of lakes and ponds is a key determinant of their ecological functioning. In deeper water bodies, the majority of primary production is more likely to be caused by phytoplankton, while in shallower water bodies submerged or emergent vegetation can play a major role (Richardson et al., 2022). Lake depth is furthermore a good predictor for other relevant lake attributes, such as mixing regime, timing of the seasonal ice cover, and water quality parameters (Ganz et al., 2024).

130 We estimated the lake or pond's maximal depth and volume by using the method from (Heathcote et al., 2015), who used the slope of the surrounding landscape. We derived the slope of the surrounding landscape for each lake from the national digital terrain model at 10 meters resolution (BKG, 2016). We validated the results by comparing estimated maximal depths with observations from ~1.600 bathymetric surveys for lakes provided by the federal state agency for environment, nature conservation and geology of Mecklenburg-Western Pomerania (LUNG) and the Bavarian state agency for the environment
135 (LfU).

2.3 Small lake or pond catchments

The composition of a lake's or pond's catchment can provide valuable information on its water quality and ecological state (Davies et al., 2008; Novikmec et al., 2016). For lakes and ponds with an area larger than 1 ha (10.000 m², $n \approx 27.200$) we derived the surface catchments based on the national digital terrain model at 10 meters resolution (BKG, 2016) using the
140 Python library `pysheds` (Bartos et al., 2024). For each 10 m x 10 m raster cell from the digital terrain model which was on the lake shoreline, we delineated a catchment and then combined all resulting catchments to get the entire catchment of the lake or pond. We used Corine Land Cover data (EEA, 2018) to estimate how much of the catchment is covered by agricultural, forest, and urban areas, etc.

145

150



155

Table 1: Short description of all attributes derived for the lake/ ponds, including their storage location in the database.

Attribute	Description	Unit/ data type	Filename
LakeID	Primary Key for each lake polygon	-	LakeGeometries
FedState	Name of the federal state in which the center of the lake or pond is located.	-	LakeGeometries
LakeArea	Size of the lake polygon.	[m ²]	LakeGeometries
LakeShore	Circumference of the lake polygon.	[m]	LakeGeometries
SDI	Shoreline development index.	[-]	LakeGeometries
AspctRatio	Ratio between the lake's or pond's longest and shortest axis.	[-]	LakeGeometries
LakeElevation	Elevation of the lake polygon above sea level.	[m]	LakeAttributes
SimZmax	Simulated maximal depth of the lake / pond.	[m]	LakeAttributes
SimZmean	Simulated maximal depth of the lake / pond divided by lake / pond area.	[m]	LakeAttributes
SimVolume	Simulated volume of the lake / pond.	[m ³]	LakeAttributes
Dist2RunningEdge	Distance to the edge of the next river. Only if next river is wider than 12 meters.	[m]	LakeAttributes
Dist2RunningCenter	Distance to the center of the next river.	[m]	LakeAttributes
WidthRunning	Width class (0-3 m as 3, 3-6 m as 6, 6-12 m as 12, >12 m as 13) of the next river.	[m]	LakeAttributes
IsInFloodplain	Is within the flooded area (return period 10 years).	Boolean	LakeAttributes
Dist2Standing	Distance to the next lake / pond.	[m]	LakeAttributes
Dist2Standing1000	See above, but only for lakes > 1.000 m ² .	[m]	LakeAttributes
CatchmentArea	For water bodies > 1 ha (10.000 m ²). Size of the catchment polygon.	[m ²]	CatchmentGeometries
f_clc_lvl3	Fraction of catchment covered by Corine level 3 land cover class.	[-]	CatchmentLandcover
NRivIntersections	Number of intersections between lake / pond and river network.		LakeAttributes
MaxWidthIntersection	Maximal width (see WidthRunning) from intersecting	[m]	LakeAttributes



	streams/ rivers.		
WidthIntersection	Width of each river – lake/ pond intersection.	[m]	LakeRivNetIntersectionStats
FlowDirIntersection	Flow direction of each river – lake/ pond intersection.	[in, out]	LakeRivNetIntersectionStats

160 2.4 Validation

The code used to retrieve OpenStreetMap (OSM) data is available together with the data. In our selection process, we queried the OSM API for features classified as ways and relations of the type "water," explicitly excluding those marked as rivers or streams. We then investigated the "type" of the resulting features and selected 'pond', 'reservoir', 'lake', 'drain', 'oxbow', 'lock', 'fishpond', 'moat', 'natural'. This approach yielded approximately 700,000 water bodies ranging in size from 165 to 500,000 m² which can be found add reference. We then analyzed the overall distribution of lake areas and identified lakes that are mapped in OSM but not included in the GSLPI.

3 Results and discussion

3.1 Lake geometries

In total, we were able to identify 262.433 small lakes and ponds in Germany, covering 1.2 % of the entire state. 178.194 of those are larger than 1.000 m². They show a characteristic distribution across Germany, with high densities occurring in 170 central and northern Bavaria, as well as Mecklenburg-Western Pomerania and Schleswig-Holstein (Fig. 1). High densities of lakes and ponds in northern Germany are associated with young moraine landscapes while those in northern Bavaria are largely artificial pond landscapes, created since medieval times by localized damming of small rivers for fish farming (Federal Ministry of the Environment, Nature Conservation and Nuclear Safety, 2003). Another prominent area of high land 175 and pond densities are the large river valleys of the Elbe and Danube rivers as well as their larger tributaries. These waterbodies are either oxbows formed through natural processes or during river straightening, or excavation lakes that have filled pits created by the mining of riverine deposits (Federal Ministry of the Environment, Nature Conservation and Nuclear Safety, 2003).

While the DLM aims to capture lakes larger than 1.000 m², some of the federal states report significant numbers of smaller 180 lakes and ponds (Fig. 2). In Bavaria for example, more than 50 % of all reported lakes and ponds are smaller than 1.000 m². In federal states with high numbers of lakes and ponds < 1.000 (Bavaria, Saxony, and Lower Saxony), we found a correlation between the occurrence of lakes and ponds < 1.000 m² with those ≥ 1.000 m². This indicates that, in areas of high lake and pond density, smaller lakes are more likely to be mapped (Fig. S2). Compared to lakes ≥ 500.000 m², the distribution of smaller lakes is highly heterogeneous across the federal states: in Mecklenburg-Western Pomerania, two



185 thirds of the total lake area are covered by these large lakes. In the Saarland, > 80 % of the total lake area consists of lakes < 500.000 m² (Fig. 2b).

This should be considered when national maps, e.g. of lake density, are created as lakes < 1.000 m² are not mapped over the entire area of Germany. The same applies to metrics such as lake-to-lake distances, which will be lower in the federal states that mapped lakes < 1.000 m².

190





Figure 1: Density of small lakes and ponds (between 1.000 and 500.000 m²) per square kilometer. A 5 x 5-kilometer grid was used to calculate the density.

195

200



205



210 **Figure 2: (a) Number and (b) share of federal state area covered by of lakes and ponds of different size classes per federal state. Lakes > 500.000 m² fall under the reporting obligation of the water framework directive and are not included in the GSLPI. As lakes of the size category > 500.000 m² are few in numbers, they are not visible in the bar chart of panel a.**

3.2 Lake attributes

3.2.1 Lake geometry attributes

215 The aspect ratio, which is the ratio between the longest and shortest axis of a geometric object, of lakes and ponds in the GSLPI varies between 1 and 7.3, with a median of 1.8 (Fig. 3b). This indicates that most lakes are slightly elongated. It has to be considered that the aspect ratio is calculated based on the longest and shortest axis of the water bodies minimum bounding geometries (Cheruvilil et al., 2021) and might not be appropriate for more complex geometries.

220 The shoreline development factor (SDF) ranges from 1 to 8 (data not shown), but cannot be interpreted across different water body sizes as it highly correlates with lake or pond area (Seekell et al., 2022).



Lake elevation shows a bi-modal distribution with peaks at 0 and 490 meters above sea level (Fig. 3c). This reflects the high density of lakes in the northern German lowlands, but also in the low mountain ranges of Bavaria, Saxony, and Thuringia.

3.2.1 Depth and volume

225 The simulated maximum depth of the GSLPI ranges from 0 to 170 meters, with a median of 1.5 meters (Fig. 3d). Predicting the depth of a lake from catchment attributes is however highly uncertain (Ganz et al., 2024). Testing our maximum depth, mean depth, and volume predictions against ~1.600 bathymetric maps affirmed this: While the prediction of maximum depth was only slightly biased (underestimation of 6.1 %, Fig. S3) the root mean square error (RMSE) was 7 meters. Predictions of mean depth and volume significantly underestimated the observed values (50 and 70 % respectively, Fig. S3).

3.2.2 Depth and volume

230 Overall, many lakes and ponds are closely associated with the river network. 32 % of the lakes and ponds are within the positional error (three meters, see Section 2.2.2) of the river network and could therefore have a direct connection to it (Figure 3f, g). Half of the lakes and ponds are within 15 meters of the river network (Figure 3f, g). Most of the lakes and ponds with direct connections to the river network have at least two intersections with the river network (see Fig. 3i) and can be considered “flow-through” lakes. 7 % of all lakes have outflows, but no inflows, and 2 % have in- but not outflows (data
235 not shown). It has to be acknowledged that those categorizations are only feasible for lakes and ponds that are directly connected to the river network. Also, note that lakes that are connected via groundwater will be missed with our methodology. Lakes and ponds within the positional error of the river network but with no connection to it (see Section 2.2.2) cannot be classified.

35 % of all lakes and ponds larger than 1.000 m² are within 50 meters of each other (Figure 3h). This attribute is likely to be
240 spatially very heterogeneous with low lake-lake distances in Bavaria (Fig. 1). 8 % of all small lakes and ponds are located within active floodplains (defined by areas flooded with a return period of 10 years), covering 7 % of the entire active floodplain area

3.2.3 Catchment area and land cover

Catchment area is expected to increase linearly or exponentially with lake area in logarithmic space (Walter et al., 2020),
245 which is congruent with the findings in this study (Fig. S5).

The land cover of the lake’s and pond’s catchments is heterogeneously distributed between forest, agriculture, and urban areas etc.: 55 % of the catchments have no urban areas, 38 % no forest areas while only 14 % have no share of agriculture within their catchment (Fig. S6). On average, the catchments are covered by 50 % agricultural areas, 39 % forested areas, 10 % urban areas, 2 % wetlands, and 6 % water bodies.

250



255




Figure 3: Normalized histograms (left y axis) and cumulative frequency distributions (right y-axis) for a selection of the derived lake attributes. Each histogram (except panel i) shows the data from the minimum value to the 99th percentile distributed across 20 bins.

260



265 3.3 Validation

To evaluate the accuracy of lake areas in the federal states' DLM, we compared it with waterbodies collected from OpenStreetMap (OSM). Although OSM is not peer-reviewed, it is compiled independently of the DLM and is thus unaffected by the federal system. This makes it a useful independent reference for identifying potential issues with the GSLPI.


- 270 Overall, the GLSPI has ca. 70.000 more lakes in the range of 1.000 – 500.000 m² than OSM (Fig. 4a). 85 % of the OSM lakes can be found in the GSLPI (Fig. 4c, d). The lakes and ponds that exist in both datasets tend to be larger in the GSLPI (Fig. 4b). This effect seems to decrease with increasing lake and pond size. The recovery rate (% of lakes from OSM found in GSLPI) increases with lake size in a non-linear fashion (Fig. 4c). A possible issue with the collected data could be different mapping practices between the federal states. While we could not exclude this, the fact that in most federal states 85
- 275 – 98 % of lakes could be recovered leads us to conclude that different mapping practices could be of minor concern. Only the city-state of Bremen has a lower recovery rate of 55 %, meaning that almost half the lakes and ponds from OSM were absent in the GSLPI. The fact that the federal state of Bremen only consists of two cities might hint towards an underrepresentation of small lakes and ponds in urban areas. Hamburg and Berlin, the other city-states, have however high recovery rates which indicate that this is a local issue.
- 280 Based on these findings, we consider the GSLPI to be the currently most comprehensive lake inventory for Germany. However, it remains unclear to what extent the small lakes and ponds are permanent. Usually, smaller ponds have a higher probability of being temporary, especially during droughts (Chumchal et al., 2016).

285

290



295



300

Figure 4: Results of the comparison between the German small lake and pond inventory (GSLPI) and the standing water bodies retrieved from openstreetmaps (OSM). (a) shows the log-log size abundance plot for both data sets. In (b) lake surface areas from both data sets are compared. The black line indicates perfect correlation. The recovery rate (c, d) is the share of lakes from OSM which also exist in the GSLPI shown as a function of lake area (c) and federal state (d).



305

4. Conclusions

Here we have compiled an open-access inventory of small lakes (< 500.000 m², 50 ha or 0.5 km²) and ponds (< 50.000 m² or 5 ha) at the national level for Germany. We used other publicly available data sets to add attributes such as depth, volume, and relationship to the river network. This data can be used by scientists, policymakers, or practitioners for various purposes. These can include selecting representative samples of lakes for field studies, improving hydrologic models, or public information. With the increasing availability of high-resolution remote sensing technology, this database can be the foundation of large-scale, low-cost monitoring programs helping to protect these vital ecosystems. Given the critical role small lakes and ponds play in providing ecosystem services and their vulnerability to climate change, this inventory offers crucial support for informed environmental management.

5. Data and code availability

The GSLPI as well as the python scripts used to generate it are available in a Zenodo repository at <https://doi.org/10.5281/zenodo.14228168> (Wachholz et al., 2024).

6. Competing interests

The authors declare that they have no conflict of interest.

References

- Banas, D., Masson, G., Leglize, L., Usseglio-Polatera, P., and Boyd, C. E.: Assessment of sediment concentration and nutrient loads in effluents drained from extensively managed fishponds in France, *Environmental Pollution*, 152, 679–685, <https://doi.org/10.1016/j.envpol.2007.06.058>, 2008.
- Biggs, J., Von Fumetti, S., and Kelly-Quinn, M.: The importance of small waterbodies for biodiversity and ecosystem services: implications for policy makers, *Hydrobiologia*, 793, 3–39, <https://doi.org/10.1007/s10750-016-3007-0>, 2017.
- Bizhanimanzar, M., Larocque, M., and Roux, M.: Improvement of SOIL WATER ASSESSMENT TOOL (SWAT) wetland module for modelling of ephemeral pond hydrology, *Hydrological Processes*, 38, e15114, <https://doi.org/10.1002/hyp.15114>, 2024.
- BKG: Digital terrain model grid width 10 m (DGM10), <https://www.bkg.bund.de/>, 2016.



- 335 BKG: Dokumentation Digitales Basis-Landschaftsmodell,
https://sg.geodatenzentrum.de/web_public/gdz/dokumentation/deu/ATKIS-OK%20Basis-DLM%206_0.pdf, last accessed on
the 4th of November, 2024, 2024.
- Chen, L., Sofia, G., Qiu, J., Wang, J., and Tarolli, P.: Grassland ecosystems resilience to drought: The role of surface water
340 ponds, *Land Degrad Dev*, 34, 1960–1972, <https://doi.org/10.1002/ldr.4581>, 2023.
- Cheruvilil, K. S., Soranno, P. A., McCullough, I. M., Webster, K. E., Rodriguez, L. K., and Smith, N. J.: LAGOS-US
LOCUS v1.0: Data module of location, identifiers, and physical characteristics of lakes and their watersheds in the
conterminous U.S., *Limnology and Oceanography Letters*, 6, 270–292, <https://doi.org/10.1002/lol2.10203>, 2021.
- 345 Chumchal, M., Drenner, R., and Adams, K.: Abundance and size distribution of permanent and temporary farm ponds in the
southeastern Great Plains, *IW*, 6, 258–264, <https://doi.org/10.5268/IW-6.2.954>, 2016.
- Davies, B. R., Biggs, J., Williams, P. J., Lee, J. T., and Thompson, S.: A comparison of the catchment sizes of rivers,
350 streams, ponds, ditches and lakes: implications for protecting aquatic biodiversity in an agricultural landscape,
Hydrobiologia, 597, 7–17, <https://doi.org/10.1007/s10750-007-9227-6>, 2008.
- Dottori, F., Alfieri, L., Bianchi, A., Skoien, J., and Salamon, P.: River flood hazard maps for Europe and the Mediterranean
Basin region, <https://doi.org/10.2905/1D128B6C-A4EE-4858-9E34-6210707F3C81>, 2021.
- 355 EEA: Corine land cover (CLC) 2018, <https://doi.org/10.2909/71c95a07-e296-44fc-b22b-415f42acdf0>, 2018.
- EU: Water framework directive, 2000. Accessed at <https://ec.europa.eu/environment/water/water-framework/> on the 4th of
August, 2021.
- 360 Federal Ministry of the Environment, Nature Conservation and Nuclear Safety: Hydrological Atlas of Germany,
<https://doi.org/10.2909/71c95a07-e296-44fc-b22b-415f42acdf0>, last accessed on the 1st of November, 2024, 2003.
- Ganz, K. J., Glines, M. R., and Rose, K. C.: The distribution of depth, volume, and basin shape for lakes in the conterminous
365 United States, *Limnology and Oceanography*, 69, 22–36, <https://doi.org/10.1002/lno.12475>, 2024.



- Hanly, P. J., Webster, K. E., and Soranno, P. A.: LAGOS-US LANDSAT: Remotely sensed water quality estimates for U.S. lakes over 4 ha from 1984 to 2020, <https://doi.org/10.1101/2024.05.10.593626>, 14 May 2024.
- 370 Heathcote, A. J., del Giorgio, P. A., and Prairie, Y. T.: Predicting bathymetric features of lakes from the topography of their surrounding landscape, *Can. J. Fish. Aquat. Sci.*, 72, 643–650, <https://doi.org/10.1139/cjfas-2014-0392>, 2015.
- Heino, J., Alahuhta, J., Bini, L. M., Cai, Y., Heiskanen, A., Hellsten, S., Kortelainen, P., Kotamäki, N., Tolonen, K. T., Vihervaara, P., Vilmi, A., and Angeler, D. G.: Lakes in the era of global change: moving beyond single-lake thinking in
375 maintaining biodiversity and ecosystem services, *Biological Reviews*, 96, 89–106, <https://doi.org/10.1111/brv.12647>, 2021.
- Jordahl, K., Bossche, J. V. D., Fleischmann, M., Wasserman, J., McBride, J., Gerard, J., Tratner, J., Perry, M., Badaracco, A. G., Farmer, C., Hjelle, G. A., Snow, A. D., Cochran, M., Gillies, S., Culbertson, L., Bartos, M., Eubank, N., Maxalbert, Bilogur, A., Rey, S., Ren, C., Arribas-Bel, D., Wasser, L., Wolf, L. J., Journois, M., Wilson, J., Greenhall, A., Holdgraf, C.,
380 Filipe, and Leblanc, F.: *geopandas/geopandas: v0.8.1*, <https://doi.org/10.5281/ZENODO.3946761>, 2020.
- King, K. B. S., Wang, Q., Rodriguez, L. K., and Cheruvilil, K. S.: Lake networks and connectivity metrics for the conterminous U.S. (LAGOS-US NETWORKS v1), *Limnology and Oceanography Letters*, 6, 293–307, <https://doi.org/10.1002/lol2.10204>, 2021.
- 385 Leech, D. M., Pollard, A. I., Labou, S. G., and Hampton, S. E.: Fewer blue lakes and more murky lakes across the continental U.S.: Implications for planktonic food webs, *Limnology and Oceanography*, 63, 2661–2680, <https://doi.org/10.1002/lno.10967>, 2018.
- Matt Bartos, Trevor James Smith, Ryan Grout, itati01, Rick Debbout, Philipp Kraft, Matthew Plough, David Huard, and
390 Jonathan King: *mdbartos/pysheds: 0.4*, <https://doi.org/10.5281/ZENODO.3822494>, 2024.
- Messenger, M. L., Lehner, B., Grill, G., Nedeva, I., and Schmitt, O.: Estimating the volume and age of water stored in global lakes using a geo-statistical approach, *Nat Commun*, 7, 13603, <https://doi.org/10.1038/ncomms13603>, 2016.
- 395 Meyer, M. F., Topp, S. N., King, T. V., Ladwig, R., Pilla, R. M., Dugan, H. A., Eggleston, J. R., Hampton, S. E., Leech, D. M., Oleksy, I. A., Ross, J. C., Ross, M. R. V., Woolway, R. I., Yang, X., Brousil, M. R., Fickas, K. C., Padowski, J. C., Pollard, A. I., Ren, J., and Zwart, J. A.: National-scale remotely sensed lake trophic state from 1984 through 2020, *Sci Data*, 11, 77, <https://doi.org/10.1038/s41597-024-02921-0>, 2024.



- 400 Novikmec, M., Hamerlík, L., Kočický, D., Hrivnák, R., Kochjarová, J., O'ahel'ová, H., Pa'ove-Balang, P., and Svitok, M.: Ponds and their catchments: size relationships and influence of land use across multiple spatial scales, *Hydrobiologia*, 774, 155–166, <https://doi.org/10.1007/s10750-015-2514-8>, 2016.
- Ogilvie, A., Belaud, G., Massuel, S., Mulligan, M., Le Goulven, P., and Calvez, R.: Surface water monitoring in small water
405 bodies: potential and limits of multi-sensor Landsat time series, *Hydrology and Earth System Sciences*, 22, 4349–4380, <https://doi.org/10.5194/hess-22-4349-2018>, 2018.
- Pekel, J.-F., Cottam, A., Gorelick, N., and Belward, A. S.: High-resolution mapping of global surface water and its long-term changes, *Nature*, 540, 418–422, <https://doi.org/10.1038/nature20584>, 2016.
- 410 Pi, X., Luo, Q., Feng, L., Xu, Y., Tang, J., Liang, X., Ma, E., Cheng, R., Fensholt, R., Brandt, M., Cai, X., Gibson, L., Liu, J., Zheng, C., Li, W., and Bryan, B. A.: Mapping global lake dynamics reveals the emerging roles of small lakes, *Nat Commun*, 13, 5777, <https://doi.org/10.1038/s41467-022-33239-3>, 2022.
- 415 Pilla, R. M., Williamson, C. E., Adamovich, B. V., Adrian, R., Anneville, O., Chandra, S., Colom-Montero, W., Devlin, S. P., Dix, M. A., Dokulil, M. T., Gaiser, E. E., Girdner, S. F., Hambright, K. D., Hamilton, D. P., Havens, K., Hessen, D. O., Higgins, S. N., Huttula, T. H., Huuskonen, H., Isles, P. D. F., Joehnk, K. D., Jones, I. D., Keller, W. B., Knoll, L. B., Korhonen, J., Kraemer, B. M., Leavitt, P. R., Lepori, F., Luger, M. S., Maberly, S. C., Melack, J. M., Melles, S. J., Müller-Navarra, D. C., Pierson, D. C., Pislegina, H. V., Plisnier, P.-D., Richardson, D. C., Rimmer, A., Rogora, M., Rusak, J. A.,
420 Sadro, S., Salmaso, N., Saros, J. E., Saulnier-Talbot, É., Schindler, D. E., Schmid, M., Shimaraeva, S. V., Silow, E. A., Sitoki, L. M., Sommaruga, R., Straile, D., Strock, K. E., Thiery, W., Timofeyev, M. A., Verburg, P., Vinebrooke, R. D., Weyhenmeyer, G. A., and Zadereev, E.: Deeper waters are changing less consistently than surface waters in a global analysis of 102 lakes, *Sci Rep*, 10, 20514, <https://doi.org/10.1038/s41598-020-76873-x>, 2020.
- 425 Richardson, D. C., Holgerson, M. A., Farragher, M. J., Hoffman, K. K., King, K. B. S., Alfonso, M. B., Andersen, M. R., Cheruveil, K. S., Coleman, K. A., Farruggia, M. J., Fernandez, R. L., Hondula, K. L., López Moreira Mazacotte, G. A., Paul, K., Peierls, B. L., Rabaey, J. S., Sadro, S., Sánchez, M. L., Smyth, R. L., and Sweetman, J. N.: A functional definition to distinguish ponds from lakes and wetlands, *Sci Rep*, 12, 10472, <https://doi.org/10.1038/s41598-022-14569-0>, 2022.
- 430 Rodriguez, L. K., Polus, S. M., Matuszak, D. I., Domka, M. R., Hanly, P. J., Wang, Q., Soranno, P. A., and Cheruvellil, K. S.: LAGOS-US RESERVOIR: A database classifying conterminous U.S. lakes 4 ha and larger as natural lakes or reservoir lakes, *Limnology and Oceanography Letters*, 8, 267–285, <https://doi.org/10.1002/lol2.10299>, 2023.



Rosentreter, J. A., Borges, A. V., Deemer, B. R., Holgerson, M. A., Liu, S., Song, C., Melack, J., Raymond, P. A., Duarte, C.
435 M., Allen, G. H., Olefeldt, D., Poulter, B., Battin, T. I., and Eyre, B. D.: Half of global methane emissions come from highly
variable aquatic ecosystem sources, *Nat. Geosci.*, 14, 225–230, <https://doi.org/10.1038/s41561-021-00715-2>, 2021.

Schmadel, N. M., Harvey, J. W., Schwarz, G. E., Alexander, R. B., Gomez-Velez, J. D., Scott, D., and Ator, S. W.: Small
Ponds in Headwater Catchments Are a Dominant Influence on Regional Nutrient and Sediment Budgets, *Geophys. Res.*
440 *Let.*, 46, 9669–9677, <https://doi.org/10.1029/2019GL083937>, 2019.

Seekell, D., Cael, B. B., and Byström, P.: Problems With the Shoreline Development Index—A Widely Used Metric of Lake
Shape, *Geophysical Research Letters*, 49, e2022GL098499, <https://doi.org/10.1029/2022GL098499>, 2022.

Seekell, D. A., Pace, M. L., Tranvik, L. J., and Verpoorter, C.: A fractal-based approach to lake size-distributions,
445 *Geophysical Research Letters*, 40, 517–521, <https://doi.org/10.1002/grl.50139>, 2013.

Stachelek, J., Hanly, P. J., and Soranno, P. A.: Imperfect slope measurements drive overestimation in a geometric cone
model of lake and reservoir depth, *Inland Waters*, 12, 283–293, <https://doi.org/10.1080/20442041.2021.2006553>, 2022.

450 Swartz, T. M. and Miller, J. R.: The American Pond Belt: an untold story of conservation challenges and opportunities,
Frontiers in Ecology and the Environment, 19, 501–509, <https://doi.org/10.1002/fee.2381>, 2021.

Targino, A. C., Coraiola, G. C., and Krecl, P.: Green or blue spaces? Assessment of the effectiveness and costs to mitigate
the urban heat island in a Latin American city, *Theor Appl Climatol*, 136, 971–984, [455
2534-1](https://doi.org/10.1007/s00704-018-), 2019.

Völker, S. and Kistemann, T.: The impact of blue space on human health and well-being – Salutogenetic health effects of
inland surface waters: A review, *International Journal of Hygiene and Environmental Health*, 214, 449–460,
<https://doi.org/10.1016/j.ijheh.2011.05.001>, 2011.

460

Wachholz, A.: [Data set] German small lake and pond inventory (GSLPI). Zenodo, doi: 10.5281/zenodo.14228168, 2024.

Waldemer, C. and Koschorreck, M.: Spatial and temporal variability of greenhouse gas ebullition from temperate freshwater
fish ponds, *Aquaculture*, 574, 739656, <https://doi.org/10.1016/j.aquaculture.2023.739656>, 2023.

465

Walter, J. A., Fleck, R., Pace, M. L., and Wilkinson, G. M.: Scaling relationships between lake surface area and catchment
area, *Aquat Sci*, 82, 47, <https://doi.org/10.1007/s00027-020-00726-y>, 2020.