

Capacity Building Enables Unique Near-Fault Observations of the destructive 2025 M_w 7.7 Myanmar Earthquake

Ssu-Ting Lai¹, Kyaw Moe Oo², Yin Myo Min Htwe², Tin Yi², Htay Htay Than², Oo Than², Zaw Min², Tun Minn Oo², Phyo Maung Maung³, Dino Bindi¹, Fabrice Cotton^{1,4}, Peter L. Evans¹, Andres Heinloo¹, Laura Hillmann¹, Joachim Saul¹, Christoph Sens-Schönfelder¹, Angelo Strollo¹, Frederik Tilmann^{1,5}, Graeme Weatherill¹, Ming-Hsuan Yen^{1,4}, Riccardo Zaccarelli¹, Thomas Zieke¹, and Claus Milkereit¹

¹GFZ Helmholtz Centre for Geosciences, Potsdam, Germany

²Department of Meteorology and Hydrology (DMH), Naypyitaw, Myanmar

³Nanyang Technological University (NTU), Singapore

⁴Institute of Geosciences, University of Potsdam, Potsdam, Germany

⁵Institute for Geological Sciences, Freie Universität Berlin, Germany

Correspondence: Dino Bindi (dino.bindi@gfz.de)

Abstract. We present an overview of station NPW, installed in Naypyitaw, Myanmar. The station is equipped with both strongmotion and broadband sensors and is situated 2.6 km from the Sagaing Fault, providing an exceptional near-fault recording of the M_w 7.7 earthquake that occurred on March 28, 2025. The installation and ongoing maintenance of NPW are the result of a collaborative effort between the Department of Meteorology and Hydrology in Naypyitaw and the GFZ Helmholtz Center for

- 5 Geosciences (GFZ) prompted by the GFZ International Training Course on seismology and seismic hazard assessment (ITC) in 2016. In this study, we provide background information about the collaborative effort that led to the installation of the only local station that provides on-scale measurements of the 2025, Myanmar earthquake. Given the widespread interest for data recorded by station, we describe the instrumental settings in detail, and how to access data and metadata for station NPW, which is part of the GEOFON (GE) network. Given the relevance of the near-fault recordings at NPW not only for constraining the
- 10 rupture process of the mainshock but also for engineering seismology applications, we analyze key features of the mainshock from an engineering seismology perspective. This includes an examination of ground motion amplitudes, frequency content, and response spectra, and near-fault effects such as fling effect and pulse-like motion. The high-quality near field data at NPW provide valuable information for seismic hazard assessment in the region and offer useful constraints for studies investigating the rupture characteristics of the mainshock, which preliminary findings suggest to have propagated at supershear speed.

15 1 Introduction

On March 28, 2025, a moment magnitude M_w 7.7 earthquake struck central Myanmar, exposing the second and third largest cities of Myanmar, Mandalay and Naypyitaw, respectively, to intensity IX shaking





and causing extensive damage and more than 3000 fatalities. The event occurred along the Sagaing Fault, a major right-lateral strike-slip fault that slips at ~2 cm/yr and accommodates about half of the transverse
motion between the Indian and Sunda plates (Socquet et al., 2006). Although Myanmar is a seismically active region with high seismic hazard (Yang et al., 2023) and specifically the fault segment between Mandalay and Naypyitaw had been identified as a seismic gap (Hurukawa and Maung Maung, 2011), its national seismic monitoring infrastructure remains relatively sparse (Thiam et al., 2017). As part of a long-term collaboration between the GFZ German Research Centre for Geosciences¹ (GFZ) and the
Department of Meteorology and Hydrology (DMH) of Myanmar, an effort that also includes capacity

- building, the NPW station was installed in Naypyitaw and integrated into the global GEOFON Seismic Network (GEOFON Data Centre, 1993). Station NPW provides the only near-fault, on-scale recordings of the mainshock and several large aftershocks, offering a unique dataset to constrain the source rupture characteristics. These data also enable the analysis of near-fault ground motion parameters that are
- 30 critical from an engineering seismology perspective. Furthermore, preliminary analysis of the Myanmar earthquake indicates that its rupture propagated at supershear velocities (F. Vera, pers. comm; manuscript in preparation); these data thus provide a rare on-scale near-fault record during the supershear phase of the rupture.

In this study, we start by outlining the ongoing collaborations that enabled the installation of station 35 NPW. We then provide detailed information on the station's metadata, data availability, and instrumental configuration, including a discussion of issues encountered in the immediate aftermath of the mainshock and the corresponding solutions. Finally, we present an engineering seismology analysis of the mainshock

- recordings, focusing on key parameters such as peak ground motion values, response spectra, spectral characteristics, and near-fault effects, specifically the identification of fling step and pulse-like motions. The analysis of near-source recordings highlights the uniqueness of the data set constructed with the
- 40 The analysis of near-source recordings highlights the uniqueness of the data set constructed with th recordings of station NPW.

2 Background collaboration

For more than a decade, the GFZ and the DMH of Myanmar have been developing a long-term partnership to strengthen seismic monitoring, hazard assessment and scientific capacity building in Myanmar. The first

¹Current name: GFZ Helmholtz Centre for Geosciences





- 45 contacts were established in 2010 with initial cooperation within joint regional seismological initiatives. In 2016, GFZ and DMH jointly organized the International Training Course on seismology and seismic hazard assessment (ITC) in Naypyitaw (https://www.gfz.de/fileadmin/gfz/sec21/pdf/ITKurse/2016M yanmar/web_programme.pdf); also see (Milkereit et al., 2023). During the training course, scientists from Myanmar and the wider Southeast-Asia region were trained in Seismology, Seismic Data Analysis,
- 50 Hazard Assessment and Risk Mitigation. For the first time, installation of a permanent seismic station (NPW) and a SeisComP system for acquisition and analysis (Helmholtz Centre Potsdam GFZ German Research Centre for Geosciences and GEMPA GmbH, 2008) were added as additional components to the training program and handed over to the local hosting institution at the end of the training (Figure 1). The standard programme of the ITC was thus complemented with transfer not only of hardware, but more
- of additional technical know-how, building on the lessons learned from establishing and maintaining the GEOFON network (Quinteros et al., 2021; GEOFON Data Centre, 1993). During the ITC, general introductory lectures on SeisComP introduced all participants to the basic use and focused on how to obtain relevant metadata and waveform data from other data archives operated by EIDA (Strollo et al., 2021) and EarthScope IRIS; the participants also practised interactive event location using the SeisComP
- 60 graphic user interface with simulated playbacks. The later part, dedicated to DMH staff only, went into more detail on the practicalities of installing SeisComP and integrating into the real-time workflow the new seismic station NPW at DMH, other Myanmar National Seismic Network (FDSN network code MM) stations (Department of Meteorology and Hydrology - National Earthquake Data Center, 2016), which are acquired from a separate local acquisition server, as well as stations from other networks in Southeast Asia
- ⁶⁵ and the rest of the world. The availability of high-quality strong-motion recordings, particularly from nearfault stations such as NPW, provides valuable data for advancing our understanding of seismic hazard and for informing future engineering design and mitigation efforts in the region.

As a further outcome of the deeper cooperation fostered during the workshop, a temporary seismic array consisting of 30 broadband stations was deployed in northern Myanmar (Tilmann et al., 2021), in close cooperation with other international activities from the US (Eric Sandvol et al., 2018) and Singapore (Wang et al., 2019), and with consideration of the temporary Chinese experiments conducted in Myanmar shortly before (Mon et al., 2020). During the preparation and deployment of the array, additional spare hardware was handed over to DMH, and maintenance and capacity-building activities were also carried out at the NPW co-operated station.







Figure 1. NPW station at DMH: a) location of station NPW with respect to the main rupture plane of the 2025, Mw 7.7 Myanmar earthquake as depicted by coherence analysis of Sentinel 1 (https://sentiwiki.copernicus.eu/web/s1-mission) and Digital Image Correlation analysis of Sentinel 2 (https://sentiwiki.copernicus.eu/web/sentinel-2) data (courtesy of M. Motagh and the Remote Sensing for Geohazards group, GFZ Helmholtz Centre for Geosciences; Map data [©]2025 Google); b) view of the shelter housing the NPW instruments; c) broadband (before being covered by thermal insulation) and d) accelerometer; fixed to the floor of the shelter without thermal insulation; e) the SeisComP system used during the 2016 training course, integrating all regional stations and a subset of global stations.

75 **3** Instrumental settings

The DMH/GEOFON seismic station in Naypyitaw (NPW) is the first station in the GE network that was established during an ITC event. The operation of this station, like that of nearly all the other GE stations, is based on a clear commitment from the partners, in this case, DMH, to commit to long-term joint operation and ownership by providing local facilities and technical expertise in case of maintenance

actions being needed. In return, GEOFON provides hardware as needed, capacity building (in this case embedded in the ITC), data curation and preservation, and a long-term commitment to joint operations, which includes remote support during maintenance actions, if required, and the shipping of replacement parts that cannot be obtained locally. The NPW station is situated in Naypyitaw, Myanmar, within the





facilities of the DMH at 19.78°N and 96.14°E, with an elevation of 158 m, only 2.6 km from the rupture plane (Figure 1a) and 246 km from the epicentre.

To prepare for the installation, DMH provided a shelter (Figure 1b) with a 2 m deep vault adjacent to it. They further contributed an existing Güralp CMG-3ESPC 30 sec sensor, a continuous power supply and connectivity via the local network of the seismology department building. During the preparatory work, which took place in early 2016, GFZ provided additional Güralp hardware, including a Fortis accelerom-

- 90 eter, a DM24 digitizer and an EAM local computer unit, which enables direct seedlink streaming (Figure 1). In addition to the seismological hardware, GFZ provided a mobile router for backup communication via a protected Virtual Private Network (VPN) link and a power control module. The station is powered by the local mains power with an additional under-voltage protected battery as buffer, to keep the station running for a few days in case there would be a power outage. As the vault was flooded just before in-
- 95 stallation, the broadband sensor, the accelerometer, and all the other hardware were housed in the shelter (Figures 1b,c). The sensor showed reasonable noise levels for the wide band sensor for periods longer than 1 s (Figure 2), so it was decided to leave the sensors in the shelter rather than move them to the vault and risk damage from repeated floodings. Considering the conditions in which the station operates, NPW can be considered a good-quality station at intermediate and long periods (Figure 2). In our view,
- it represents a good compromise between quality and availability in a region with sparse coverage; the setup was discussed and agreed upon with the local partners and adapted to the actual capacity and needs of long-term operation. In fact, since its installation, the station has been operating with several intervals where the data flow was interrupted, but always restored by DMH staff with only remote support from the GEOFON maintenance team. The overall data availability since installation is $\sim 80\%$. Figure 2c shows
- the availability for the last 4 years (since 01.01.2021) with a large gap between 13 October 2024 and 10 February 2025 with an overall average availability of 82% for the given period (90% since January 2025 and 100% since 28/03/2025 (day of the mainshock) to 07/04/2025). The station's timing quality has been unstable since installation, however, despite attempts to change parts of the GPS hardware. For users of these data, we further note that the timing quality reported by the data logger seems to be consistent
- 110 with the time since last lock until the beginning of the large gap in October 2024 (Figure 2d), but when data flow was restored in February 2025, the timing quality was no longer consistently reported, and can no longer be considered a reliable indicator. Nevertheless, sporadic GPS locks occurred every few days, with the last known GPS lock before the mainshock on 23 March 2025. Triggered by the observations







Figure 2. Power Spectral Density (PSD) of the vertical components of both sensors for the data available in 2025; note that the colour scale was reversed compared to ObsPy default in order to enhance visibility of the mode line, a) broadband sensor, b) strong-motion sensor (see Data Availability section for links to corresponding plots for all components and user-defined time spans); c) daily availability for the last 4 years (since 01.01.2021), d) timing quality as stored in the file headers for one year time span.

of growing residuals in arrival times we investigated the timing of NPW using ambient seismic noise
cross-correlation (Sens-Schönfelder, 2008) of the HH channels with the neighboring stations MM.NGU,
MM.TGI, and TM.MHIT. Correlations of NPW's HHZ and HHN channels with NGU provide most stable
estimates of the clock offset, as illustrated in Figure 3. We find that NPW lost GPS synchronization on
March 19 at 4am (±18h) when the clock starts to drift linearly with a rate of 1.14 × 10⁻⁶ ± 6.6 × 10⁻⁸, i.e.
98.6 ± 5.7ms/d (regression coefficient r² = 0.87). At the time of the mainshock, the accumulated clock
error was 775 ± 40 ms. Observations with other stations confirm these findings, however, with less accuracy.

In terms of noise level, the station is well suited for local, regional and teleseismic monitoring, despite its location in an area of urban activity. The broadband sensor allows clear identification of the primary and secondary microseismic peaks. The increasing local anthropic noise is clearly visible for periods







Figure 3. Timing of NPW recordings from earthquake picks and ambient noise correlation. Stable timing is confirmed until March 19th (red dot) when the internal clock starts to drift with about 0.1s per day. Orange dots show independent estimates of ambient noise correlations from the north and vertical components with all components of station MM.NGU (Sens-Schönfelder et al., 2014). Blue dots represent the joint estimate from all components. Stars indicate the clock offset inferred from earthquake arrival time picks. Red line with black confidence limits indicates the least squares fit of the clock drift. The main shock is indicated by the vertical line.

shorter than 1 s. The strong-motion sensor performed as expected for periods shorter than 1 s, enabling the dynamic range extension to record large near-fault events up to 2g, which is the full scale to which it is set.

The NPW station plays a crucial role in regional and global seismic monitoring, providing valuable data for seismological research and contributing to earthquake hazard studies by improving the completeness

130 of earthquake catalogs. The station is in the International Registry of Seismograph Stations and has contributed to more than 3000 P-phase observations at the ISC (International Seismological Centre, 2025), see https://www.isc.ac.uk/cgi-bin/stations?stacode=NPW.

In April 2025, immediately following the M_W 7.7 earthquake on 28 March 2025, the contact was initially lost a few seconds after the P onset, and the condition of the station was unknown to GEOFON staff at this time. The station started transmitting data again on 1 April 2025, 4 days after the earthquake.



By remote connection, it was confirmed that the station had continued recording throughout, and just data transmission was lost during the data gap, such that it was possible to backfill the data holdings. Given the amount of damage incurred to the power and communications infrastructure, the continuous operation of the station and quick restoration of connectivity are remarkable.

- 140
- Given low prior usage of the strong motion data, GEOFON staff identified a serious metadata issue affecting three strong motion components; in the wake of clarifying this issue, a more subtle issue was also identified with the metadata of the broadband instruments. As a result, a public warning to data users was put out immediately (https://geofon.gfz.de/forum/t/metadata-for-ge-npw/32635). As soon as the open questions could be clarified, which needed checking with the manufacturer, the metadata were updated and a notification was put out to warn users to re-download the metadata. 145

The station proved to be instrumental in recording this seismic event, as it was the only open strongmotion station operating during the earthquake adjacent to the rupture, providing critical data for the rapid understanding of some basic characteristics of the earthquake, as presented in the following sections of this article.

150 4 Data quality and parameters of engineering interest

Station NPW is the only station in Myanmar that recorded on-scale the 28 March mainshock and its larger aftershocks. In order to evaluate the quality of both data and metadata, and to characterize these unique near-fault recordings of the 2025 sequence from the engineering seismology perspective, we use the stream2segment software (Zaccarelli et al., 2019) to download seismic waveform data from the GE-155 OFON node (https://geofon.gfz.de/fdsnws/dataselect/1/) of EIDA (https://www.orfeus-eu.org/data/eida/) and populate a local PostgreSQL database. Station metadata are retrieved from GEOFON station service (https://geofon.gfz.de/fdsnws/station/1/). Event metadata are retrieved from the EMSC event web service (http://www.seismicportal.eu/fdsnws/event/1/) to compile a catalog of earthquakes with magnitude greater than 3, occurring since 2021, within a radius of 5.5° from station NPW. From the continuous waveform

160

To assess the quality of the data and evaluate their potential for both seismological applications, such as constraining the spatial and temporal evolution of the rupture process, and engineering seismology studies, we conducted a series of analyses based on the mainshock recordings:

data, we extract 5-minute windows centered on the theoretical P arrival of each event.







Figure 4. Displacement time histories of the M_w 7.7 mainshock recorded at station NPW, obtained through double integration and baseline corrections of the instrument corrected acceleration.

165

170

- Broad band displacement and static offset. The NPW recording of the M_w 7.7 mainshock provides the rare opportunity to investigate near-fault ground motion data. Figure 4 shows the static displacement obtained through double integration of the unfiltered, instrument-corrected acceleration. Before each integration, a linear trend was removed from the entire time window. The trend was based on straight-line fitting of 5 minutes of noise immediately preceding the P onset. To determine the static offset and to flatten the coda trace, a simple quadratic function was fit to first 2 minute of the double-integrated data after the displacement stabilized. The linear and quadratic terms were then removed from the data. The retrieved static displacement on the north-south (NS) compo-







Figure 5. Time series of the processed mainshock acceleration and velocity for all three components at station NPW.

nent, which is almost parallel to the fault strike, is 1.6 m, whereas on the east-west (EW), it is about -0.13 m. The static displacement offset measured along the fault parallel component (i.e., the NS one), which corresponds to unidirectional long-period velocity pulse, is known in the engineering seismology context as fling-step, or fling velocity-pulse (e.g., Hisada and Tanaka, 2021).

For the following analysis each trace is detrended and 5% tapered at both ends before being band-pass filtered using a zero-phase (acausal), fourth-order Butterworth filter. For the mainshock, the high-pass corner frequency is fixed at 0.02 Hz, while for aftershocks, it is adapted based on magnitude. The low-pass corner frequency is set to 40 Hz. The instrumental response is removed, and the resulting acceleration time series are integrated to obtain velocity. Finally, acceleration and velocity response spectra are computed assuming 5% critical damping.

– Peak ground acceleration and velocity. To analyze the earthquake recordings from an engineering seismology perspective, Figure 5 presents the high-pass filtered acceleration and velocity time histories. The peak ground accelerations (PGAs) for the vertical (Z), NS (fault-parallel), and EW (fault-normal) components are 10.53, 4.82, and 5.63 m/s², respectively. Notably, the vertical component exhibits the highest PGA, exceeding those of both horizontal components.

175







Figure 6. Acceleration response spectra for the mainshock recorded at station NPW. Spectra are shown for all three components individually (see legend), as well as for the RotD50 horizontal combination (black), see text. Observed spectra are compared with the median predictions from the Chiou and Youngs (2014) ground motion model.

- Acceleration response spectra. The acceleration response spectra shown in Figure 6 further highlight the significant vertical accelerations during the mainshock, especially for short-period oscillators. The short-period spectral amplitudes for the two horizontal components are comparable, with a pronounced spectral peak observed around 0.15 s (i.e., ~ 6.5 Hz, relevant for one- or two-story buildings), at which the fault-parallel (NS) component exhibits approximately twice the amplitudes of the fault-normal component (EW). The horizontal ground motion is compared against a ground motion prediction model (GMPM) appropriate for the region in question, namely Chiou and Youngs (2014). In this case we first define the horizontal ground motion in terms of RotD50, the median







Figure 7. Vertical-to-horizontal (V/H) response spectral ratios as a function of period, considering the RotD50 horizontal combination. The V/H computed for the mainshock (black line) is compared with the median predictions \pm two standard deviations from the Bozorgnia and Campbell (2016) model. Ratios for peak ground acceleration (PGA) and peak ground velocity (PGV) are also shown.

values of the response spectra of the two horizontal components projected onto all non-redundant azimuths (Boore, 2010), which is shown in the black line in Figure 6. For comparison with the GMPM, we first calculate the distance to the finite-fault rupture, which is taken from the USGS Shakemap (https://earthquake.usgs.gov/earthquakes/eventpage/us7000pn9s/finite-fault, updated on 2025-04-02 at 14:19:57). The site condition for the station is assumed as V_{S30} (the time-average shear-wave velocity up to 30 m depth) 360 m/s, while the required basin depth parameters $Z_{1.0}$ (depth to the $V_S = 1$ km/s velocity layer) and $Z_{2.5}$ (depth to the $V_S = 2.5$ km/s velocity layer) are predicted from the V_{S30} using empirical relations proposed by Chiou and Youngs (2014) and Campbell and Bozorgnia (2014), respectively. As seen in Figure 6 for these assumed parameters, the observed response spectra for RotD50 fall well within the aleatory variability of the ground motion prediction model across the 0.01 s to 10.0 s period range.







Figure 8. Stockwell transform analysis of the velocity pulse (fault normal component), see text. The marginal plot on top is the time series; the marginal plot on the left is the Fourier amplitude spectrum (integral over time for each frequency of the Stockwell transform).

- Vertical to Horizontal response spectra ratio. Although vertical-to-horizontal spectral ratios (V/H) greater than 1 are often observed in near-fault recordings of large earthquakes on soft sites, Figure 7 shows that the V/H ratios computed for the mainshock exceed the median predictions by Bozorgnia and Campbell (2016) across all periods. However, the observed ratios generally remain within two standard deviation above the median. A particularly pronounced peak at 0.07 s (approximately 15 Hz) stands out and warrants further investigation.
- Fault-normal velocity pulse. Figure 8 shows the amplitude of the Stockwell transform (Stockwell et al., 1996) for the EW velocity component of the mainshock. The dominant frequency associated with the main velocity pulse is approximately 0.3 Hz, followed by higher-frequency shaking centered around 0.8 Hz. A comparison with previously published observations, shown in Figure 9, indicates that the pulse period is consistent with the general trends reported for other earthquakes (Shahi and Baker, 2014; Türker et al., 2023; Yen et al., 2021, 2024), although it lies near the lower end of the observed range. The temporal evolution of the instantaneous frequency (IF), shown in Figure 8 and defined as the time derivative of the complex phase, provides valuable insight into the non-







Figure 9. Comparison of the pulse period, Tp of the Myanmar earthquake with literature values (compiled by Yen et al. (2024), as a function of earthquake moment magnitude. Red stars represent the strongest pulse of 2025 Myanmar earthquake. Note that the pulse periods published by Yen et al. (2024) have been computed using the Shahi and Baker (2014) method but the pulse period of the Myanmar earthquake has been measured based on the Stockwell transform of the fault normal component, see Figure 8. The lines show the regressions of Shahi and Baker (2014) (black solid line), Chioccarelli and Iervolino (2010) (gray dotted line), and Somerville (2003) (gray dashed-dotted-dashed line). Black dots represent the pulses identified from the NGA-West2 database (Ancheta et al., 2014) in the study of Shahi and Baker (2014). Open circles represent the fling-step pulses published by Kamai et al. (2014). Blue triangles represent the pulses identified in Taiwan, Japan, and New Zealand (Yen et al., 2021). Colored diamonds represent 2023 Türkiye doublet (Yen et al., 2024) and 2022 Düzce earthquake (Türker et al., 2023). Figure modified and adapted from Yen et al. (2024).

- stationary characteristics of the ground motion. At the onset of strong motion, the IF exhibits a sharp increase, marking the transition from background noise to significant energy input. During the large velocity pulse, the IF decreases from an early peak consistent with the dominance of lower frequencies during this interval. After the pulse, the IF shows increases gradually, suggesting the presence of higher-frequency energy in the later part of the signal.
- Comparison of engineering seismology parameters with the 2023, Türkiye earthquake. When comparing the computed PGAs and peak ground velocities (PGVs), calculated as ROTD50, with those recorded during the 2023 Türkiye earthquake, no significant anomalies are observed (Figure 10). The comparison with predictions from the Boore et al. (2014) ground motion model is shown



230



Figure 10. Comparison of peak ground acceleration (PGA, left) and peak ground velocity (PGV, right) recorded at station NPW during the M_w 7.7 Myanmar mainshock (large red circle) with the median predictions (solid line) and ±1 standard deviation bounds (shaded area) of the Boore et al. (2014) ground motion model. For reference, peak values recorded during the M_w 7.7, 2023 Türkiye earthquake (Luzi et al., 2020) are also shown.

in Figure 10, using the linear site amplification term corresponding to V_{S30} =360 m/s. The good agreement between observed and predicted values suggests that the actual V_{S30} at station NPW is likely close to, or possibly lower than, 360 m/s, consistent with the topography-based estimate of 302 m/s.

Finally, since station NPW has been continuously recording since the onset of the seismic sequence, numerous high-quality aftershock recordings are now available in the archive. Figure 11 presents the EMSC (European-Mediterranean Seismological Centre) locations of the mainshock and 61 aftershocks with magnitudes greater than 3.0, recorded up to April 7, 2025. Among these, Figure 11 also shows the processed acceleration and velocity time histories of a well-recorded M_w 6.7 aftershock that occurred just 12 minutes after the mainshock, at 06:20:54 UTC, approximately 220 km from station NPW. Another example is the m_b 5.1 aftershock recorded on March 29, 2025, at 09:20:47 UTC, located only 12.3 km from the station. These events highlight the value of the NPW station for capturing both near-fault and far-field ground motions throughout the sequence. The 61 events are part of the data set used to investigate the site resonances following the approach by Lai et al. (2025).







Figure 11. The mainshock and 61 selected earthquakes with magnitudes greater than 3 recorded up to 7 April 2025. The focal mechanisms of the M_w 7.7 mainshock and the M_w 6.7 aftershock are obtained from the Global Centroid Moment Tensor Project (https://www.global cmt.org/). Active faults (shown in dark red) are sourced from the GEM Global Active Faults Database (Styron and Pagani, 2020). On the right, the processed acceleration and velocity waveforms of the M_w 6.7 and m_b 5.1 aftershocks, recorded by the accelerometer installed in NPW, are shown. The m_b 5.1 aftershock is located approximately 12.3 km from station NPW. Map is produced with Generic Mapping Tool software (Wessel et al., 2019), with topography generated using the ETOPO1 global relief model (Amante and Eakins, 2009).

- Site resonance frequencies. Figure 12 shows the broadband resonance curves at station NPW, computed using the time-frequency resonance analysis method adapted from Lai et al. (2025). We selected aftershock records with PGA ranging from 1 to 10 cm/s², recorded by accelerometers up to 7 April 2025, resulting in a dataset of 20 events with magnitudes between 3.5 and 6.7. For each event, we applied a time window of 15 s for magnitudes ≤ 6.0 and 20 s for magnitudes > 6.0, beginning 20% of the window duration before the PGA time and extending 80% beyond it. The Stockwell transform was then applied to the windowed time series of the derivative of acceleration, acceleration, velocity, and displacement. The squared spectral amplitudes, representing signal energy over time, were normalized between 0 and 1. We then computed three percentiles along the time axis to obtain a smooth representation of energy distribution in the frequency domain, referred to as the resonance curve. The peaks of the curves serve as proxies for the frequencies of linear site amplifi-

245







Figure 12. Resonance curves at station NPW, computed from the radial and transverse components of aftershock records using the time-frequency resonance analysis method adapted from Lai et al. (2025), see text for further details.

255

cation. The station has a predominant resonance frequency around 12-13 Hz. Although this peak is dominant, a secondary peak around 7–8 Hz is also present in the resonance curve, albeit somewhat obscured by the taller primary peak. Additionally, relatively smaller and less prominent peaks are observed at 2.5-3 Hz, 1.4-2 Hz, and approximately 0.9-1.1 Hz. The peaks around 0.13 s and 1.3 s in the response spectra of the mainshock for the NS, EW, and Z components in Figure 6 are therefore likely associated with site effects.

260 5 Code and data availability

Software and processed data are available at Zenodo under https://doi.org/10.5281/zenodo.15228691
 (Bindi et al., 2025).



265

270

275

280



- Waveform data and metadata for the GEOFON seismic network (GEOFON Data Centre, 1993) with its station NPW are available via standard FDSN web services and formats (https://www.fdsn.org/s ervices) alongside with other custom services and products.
- Station metadata, including instrument responses for NPW, are available through the FDSN Station Web Service. StationXML format metadata can be obtained using the following query: https://geof on.gfz.de/fdsnws/station/1/query?level=response&net=GE&station=NPW. On April 3, 2025, issues with the timing quality and metadata of all channels at NPW were detected. The metadata have been updated to address these issues, and users should ensure they have the most recent metadata when analyzing data from this station.
- Waveform data from NPW can be retrieved from GEOFON using the FDSN fdsnws-dataselect Web Service http://fdsn.org/webservices/. To request specific time windows of data, one queries the service, providing parameters such as network code (net), station code (sta), channel (cha), start time (starttime), and end time (endtime). For example for a 10 minutes time window around the mainshock including only the 20 Hz broadband vertical channel: https://geofon.gfz.de/fdsnws/datas elect/1/query?net=GE&sta=NPW&cha=BHZ&starttime=2025-03-28T06:15:00&endtime=2025-0 3-28T06:25:00

Due to instability of the internet connection to Myanmar data gaps are present in the continuous recordings and efforts are ongoing to back-filling gaps when data are available locally at Myanmar and bandwidth allows.

Additional data access tools

- Live seismogram (browsable daily plots of the broadband vertical component): https://geofon.gfz.d e/waveform/liveseis.php?station=NPW&date=2025-03-28
- Interactive availability calendar view (2025): https://geofon.gfz.de/waveform/archive/data.php?nc
 ode=GE&year=2025
 - fdsnws-availability (average availability 01.01 07.04.2025 90%): https://geofon.gfz.de/fdsnws/ava ilability/1/query?network=GE&station=NPW&start=2025-01-01T00:00:00&end=2025-04-07T00: 00:00



- 200 2025 WFcatalog quality metrics: availability, RMS, gaps, overlaps, records, timing quality (2025): https://geofon.gfz.de/eidaws/wfcatalog/1/query?net=GE&station=NPW&channel=HHZ,HNZ&star t=2025-01-01T00:00:00.000Z&end=2025-04-07T23:59:59.999Z&include=all

The Power Spectral Density PSD (Figure 2)

The PSD for the period from 01.01.2025 to date for all components at 100 Hz can be retrieved as follows for the vertical strong motion channel:

- https://geofon.gfz.de/eidaws/seedpsd/1/histogram?&cmap=viridis&fontsize=12&grid=true&mod e=true&noise=true&percentiles=false&&dpi=600&network=GE&station=NPW&location=*&ch annel=HNZ&nodata=404&start=2025-01-01&end=2025-12-31

Replace HNZ in above by HNN, HNE for the horizontal strong motion, and by HHZ, HHN, HHE for the broadband PSDs. The channel naming follows the SEED standard (https://www.fdsn.org/pdf/SEEDMan ual_V2.4_Appendix-A.pdf).

Additional software used

- Computations are done in Python (Van Rossum and Drake, 2009) and R (R Core Team, 2024), using ObsPy (Beyreuther et al., 2010)
- The stream2segment software used to download and process the waveform is available by Zaccarelli (2018). Templates for the data download and process are provided with the distribution.
 - The eGSIM software used to compare ground motion model predictions and observation is available by Zaccarelli and Weatherill (2020).

6 Concluding remarks

The installation of station NPW was made possible through a collaborative effort between the Department of Meteorology and Hydrology (DMH) in Napyitaw and the GFZ Helmholtz Centre for Geosciences. This collaboration underscores the critical role of capacity building in supporting the development of highquality, open-access seismic data that can serve both national monitoring efforts and the global scientific community. By strengthening local expertise, infrastructure, and collaborative networks, such initiatives





help establish and sustain robust seismic monitoring systems that provide valuable observations for advancing earthquake science and hazard assessment. In the case of the M_w 7.7 Myanmar earthquake sequence in 2025, NPW is the only station to provide near-fault, on-scale recordings of the mainshock and the largest aftershocks. It thus adds a rare example of a near-fault record of a supershear rupture to the global strong motion databases. As such, the NPW near-fault data set presented in this study not only support fundamental research aimed at improving our understanding of earthquake processes and seismic hazard, but also informs practical strategies for risk mitigation, urban planning, and resilient infrastructure design in vulnerable regions.

Author contributions. All authors provided contributions to the conceptualization and finalization of the article, coordinated by DB and FT. Regarding the figures: AS prepared Figures 1 and 2; CSS prepared Figure 3; JS prepared Figure 4; DB prepared Figures 5, 8 and 10; GW
 prepared Figures 6 and 7; STL prepared Figures 11 and 12; MHY prepared Figure 9. The 2016 training course was organized and managed by CM.

Competing interests. The authors declare no competing interests.

Acknowledgements. The 2016 International training course on Seismology, Seismic data analysis, Hazard assessment and Risk mitigation (Naypyitaw, 26 September-21 October, 2016) had been organized and sponsored by the GFZ Helmholtz Centre for Geosciences (GFZ) and the Department of Meteorology and Hydrology in Naypyitaw (Myanmar), and co-sponsored by the German Federal Foreign Office (FFO),

330 the Department of Meteorology and Hydrology in Naypyitaw (Myanmar), and co-sponsored by the German Federal Foreign Office (FFO), Berlin, Germany. We thank D. Kroll for her support in the organization of the training. We thank M. Motagh and the Remote Sensing for Geohazards group (GFZ) for sharing Figure 1a. The article processing charges for this open-access publication were covered by the GFZ.



References

335

Amante, C. and Eakins, B. W.: ETOPO1 1 Arc-Minute Global Relief Model: Procedures, Data Sources and Analysis, NOAA Technical Memorandum NESDIS NGDC-24. National Geophysical Data Center, NOAA, 2009.

- Ancheta, T. D., Darragh, R. B., Stewart, J. P., Seyhan, E., Silva, W. J., Chiou, B. S.-J., Wooddell, K. E., Graves, R. W., Kottke, A. R., Boore, D. M., Kishida, T., and Donahue, J. L.: NGA-West2 Database, Earthquake Spectra, 30, 989–1005, https://doi.org/10.1193/070913EQS197M, 2014.
- Beyreuther, M., Barsch, R., Krischer, L., Megies, T., Behr, Y., and Wassermann, J.: ObsPy: A Python Toolbox for Seismology, Seismological
 Research Letters, 81, 530–533, https://doi.org/10.1785/gssrl.81.3.530, 2010.
- Bindi, D., Lai, S.-T., Strollo, A., Zaccarelli, R., and Tilmann, F.: Software and data products for "Capacity Building Enables Unique Near-Fault Observations of the destructive 2025 Mw 7.7 Myanmar Earthquake", Zenodo, 10.5281/zenodo.15228691, https://doi.org/10.5281/zenodo.15228691, 2025.

Boore, D. M.: Orientation-Independent, Nongeometric-Mean Measures of Seismic Intensity from Two Horizontal Components of Motion,

- Bulletin of the Seismological Society of America, 100, 1830–1835, https://doi.org/10.1785/0120090400, 2010.
 - Boore, D. M., Stewart, J. P., Seyhan, E., and Atkinson, G. M.: NGA-West2 Equations for Predicting PGA, PGV, and 5% Damped PSA for Shallow Crustal Earthquakes, Earthquake Spectra, 30, 1057–1085, https://doi.org/10.1193/070113EQS184M, 2014.
 - Bozorgnia, Y. and Campbell, K. W.: Ground Motion Model for the Vertical-to-Horizontal (V/H) Ratios of PGA, PGV, and Response Spectra, Earthquake Spectra, 32, 951–978, https://doi.org/10.1193/100614eqs151m, 2016.
- 350 Campbell, K. W. and Bozorgnia, Y.: NGA-West2 Ground Motion Model for the Average Horizontal Components of PGA, PGV, and 5% Damped Linear Acceleration Response Spectra, Earthquake Spectra, 30, 1087–1115, https://doi.org/10.1193/062913EQS175M, 2014.
 - Chioccarelli, E. and Iervolino, I.: Near-source seismic demand and pulse-like records: A discussion for L'Aquila earthquake, Earthquake Engineering & Structural Dynamics, 39, 1039–1062, https://doi.org/https://doi.org/10.1002/eqe.987, 2010.

Chiou, B. S.-J. and Youngs, R. R.: Update of the Chiou and Youngs NGA Model for the Average Horizontal Component of Peak Ground
 Motion and Response Spectra, Earthquake Spectra, 30, 1117–1153, https://doi.org/10.1193/072813EQS219M, 2014.

- Department of Meteorology and Hydrology National Earthquake Data Center: Myanmar National Seismic Network. International Federation of Digital Seismograph Networks., https://doi.org/10.7914/SN/MM, 2016.
 - Eric Sandvol, Jim Gaherty, Michael Steckler, and Patricia Persaud: Tripartite-BIMA (Bangladesh-India-Myanmar Array), https://doi.org/10.7914/SN/XR_2018, 2018.
- 360 GEOFON Data Centre: GEOFON Seismic Network, https://doi.org/10.14470/TR560404, 1993.
 - Helmholtz Centre Potsdam GFZ German Research Centre for Geosciences and GEMPA GmbH: The SeisComP seismological software package. GFZ Data Services, https://doi.org/10.5880/GFZ.2.4.2020.003, 2008.
 - Hisada, Y. and Tanaka, S.: What Is Fling Step? Its Theory, Simulation Method, and Applications to Strong Ground Motion near Surface Fault Ruptures, Bulletin of the Seismological Society of America, 111, 2486–2506, https://doi.org/10.1785/0120210046, 2021.
- 365 Hurukawa, N. and Maung Maung, P.: Two seismic gaps on the Sagaing Fault, Myanmar, derived from relocation of historical earthquakes since 1918, Geophysical Research Letters, 38, https://doi.org/10.1029/2010gl046099, 2011.
 - International Seismological Centre : International Seismograph Station Registry (IR), https://doi.org/https://doi.org/10.31905/EL3FQQ40, 2025.



370

Kamai, R., Abrahamson, N., and Graves, R.: Adding Fling Effects to Processed Ground-Motion Time Histories, Bulletin of the Seismological Society of America, 104, 1914–1929, https://doi.org/10.1785/0120130272, 2014.

Lai, S.-T., Schibuola, A., and Bonilla, L. F.: Unveiling nonlinear site response through time-frequency analysis of earthquake records, Geophysical Journal International, p. ggaf098, https://doi.org/10.1093/gji/ggaf098, 2025.

Luzi, L., Lanzano, G., Felicetta, C., D'Amico, M., Russo, E., Sgobba, S., Pacor, F., and ORFEUS, W.: Engineering Strong Motion Database (ESM) (Version 2.0). Istituto Nazionale di Geofisica e Vulcanologia (INGV)., https://doi.org/https://doi.org/10.13127/ESM.2, 2020.

- 375 Milkereit, C., Dahm, T., Cesca, S., Cotton, F., bindi, d., Strollo, A., Tilmann, F., and Participants, T. C.: International Training Courses on "Seismology, Seismic Hazard Assessment and Risk Mitigation", XXVIII General Assembly of the International Union of Geodesy and Geophysics (IUGG) (Berlin), https://doi.org/10.57757/IUGG23-2629, 2023.
- Mon, C. T., Gong, X., Wen, Y., Jiang, M., Chen, Q.-F., Zhang, M., Hou, G., Thant, M., Sein, K., and He, Y.: Insight Into Major Active Faults in Central Myanmar and the Related Geodynamic Sources, Geophysical Research Letters, 47, e2019GL086236, https://doi.org/https://doi.org/10.1029/2019GL086236, 2020.
- Quinteros, J., Strollo, A., Evans, P. L., Hanka, W., Heinloo, A., Hemmleb, S., Hillmann, L., Jaeckel, K., Kind, R., Saul, J., Zieke, T., and Tilmann, F.: The GEOFON Program in 2020, Seismological Research Letters, 92, 1610–1622, https://doi.org/10.1785/0220200415, 2021.
 R Core Team: R: A Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria, https://www.R-project.org/, 2024.
- 385 Sens-Schönfelder, C.: Synchronizing seismic networks with ambient noise, Geophys. J. Int., 174, 966–970, https://doi.org/10.1111/j.1365-246X.2008.03842.x, 2008.
 - Sens-Schönfelder, C., Pomponi, E., and Peltier, A.: Dynamics of Piton de la Fournaise Volcano Observed by Passive Image Interferometry with Multiple References, J. Volcanol. Geotherm. Res., 276, 32–45, https://doi.org/10.1016/j.jvolgeores.2014.02.012, 2014.
- Shahi, S. K. and Baker, J. W.: An Efficient Algorithm to Identify Strong-Velocity Pulses in Multicomponent Ground Motions, Bulletin of the
 Seismological Society of America, 104, 2456–2466, https://doi.org/10.1785/0120130191, 2014.
 - Socquet, A., Vigny, C., Chamot-Rooke, N., Simons, W., Rangin, C., and Ambrosius, B.: India and Sunda plates motion and deformation along their boundary in Myanmar determined by GPS, Journal of Geophysical Research: Solid Earth, 111, https://doi.org/10.1029/2005jb003877, 2006.
- Somerville, P. G.: Magnitude scaling of the near fault rupture directivity pulse, Physics of the Earth and Planetary Interiors, 137, 201–212, https://doi.org/https://doi.org/10.1016/S0031-9201(03)00015-3, the quantitative prediction of strong-motion and the physics of earthquake
 - sources, 2003.
 - Stockwell, R., Mansinha, L., and Lowe, R.: Localization of the complex spectrum: the S transform, IEEE Transactions on Signal Processing, 44, 998–1001, https://doi.org/10.1109/78.492555, 1996.
 - Strollo, A., Cambaz, D., Clinton, J., Danecek, P., Evangelidis, C. P., Marmureanu, A., Ottemöller, L., Pedersen, H., Sleeman, R., Stammler,
- K., Armbruster, D., Bienkowski, J., Boukouras, K., Evans, P. L., Fares, M., Neagoe, C., Heimers, S., Heinloo, A., Hoffmann, M., Kaestli, P., Lauciani, V., Michalek, J., Odon Muhire, E., Ozer, M., Palangeanu, L., Pardo, C., Quinteros, J., Quintiliani, M., Antonio Jara-Salvador, J., Schaeffer, J., Schloemer, A., and Triantafyllis, N.: EIDA: The European Integrated Data Archive and Service Infrastructure within ORFEUS, Seismological Research Letters, 92, 1788–1795, https://doi.org/10.1785/0220200413, 2021.

Styron, R. and Pagani, M.: The GEM Global Active Faults Database, Earthquake Spectra, 36, 160–180, https://doi.org/10.1177/8755293020944182, 2020.



410

- Thiam, H. N., Htwe, Y. M. M., Kyaw, T. L., Tun, P. P., Min, Z., Htwe, S. H., Aung, T. M., Lin, K. K., Aung, M. M., Cristofaro, J. d., Franke, M., Radman, S., Lepiten, E., Wolin, E., and Hough, S. E.: A Report on Upgraded Seismic Monitoring Stations in Myanmar: Station Performance and Site Response, Seismological Research Letters, 88, 926–934, https://doi.org/10.1785/0220160168, 2017.
- Tilmann, F., Schurr, B., Yuan, X., and Than, O.: Myanmar subduction to collision imaging array (MySCOLAR).GFZ Data Services. Dataset/-Seismic Network, https://doi.org/https://doi.org/10.14470/1P7564636194, 2021.
- Türker, E., Yen, M., Pilz, M., and Cotton, F.: Significance of Pulse-Like Ground Motions and Directivity Effects in Moderate Earthquakes: The Example of the Mw 6.1 Gölyaka-Düzce Earthquake on 23 November 2022, Bulletin of the Seismological Society of America, https://doi.org/10.1785/0120230043, 2023.

Van Rossum, G. and Drake, F. L.: Python 3 Reference Manual, CreateSpace, Scotts Valley, CA, 2009.

- 415 Wang, X., Wei, S., Wang, Y., Maung Maung, P., Hubbard, J., Banerjee, P., Huang, B.-S., Moe Oo, K., Bodin, T., Foster, A., and Almeida, R.: A 3-D Shear Wave Velocity Model for Myanmar Region, Journal of Geophysical Research: Solid Earth, 124, 504–526, https://doi.org/10.1029/2018jb016622, 2019.
 - Wessel, P., Luis, J. F., Uieda, L., Scharroo, R., Wobbe, F., Smith, W. H. F., and Tian, D.: The Generic Mapping Tools Version 6, Geochemistry, Geophysics, Geosystems, 20, 5556–5564, https://doi.org/10.1029/2019GC008515, 2019.
- 420 Yang, H.-B., Chang, Y.-K., Liu, W., Sung, G.-Y., Gao, J.-C., Thant, M., Maung Maung, P., and Chan, C.-H.: Probabilistic seismic hazard assessments for Myanmar and its metropolitan areas, Geoscience Letters, 10, 48, https://doi.org/10.1186/s40562-023-00301-x, 2023.
 - Yen, M.-H., Specht, S., Lin, Y.-Y., Cotton, F., and Ma, K.-F.: Within- and Between-Event Variabilities of Strong-Velocity Pulses of Moderate Earthquakes within Dense Seismic Arrays, Bulletin of the Seismological Society of America, 112, https://doi.org/10.1785/0120200376, 2021.
- 425 Yen, M.-H., Türker, E., Ulrich, T., Marchandon, M., Gabriel, A.-A., and Cotton, F.: An analysis of directivity pulses using empirical data and dynamic rupture simulations of the 2023 Kahramanmaras earthquake doublet, Earthquake Spectra, 2024.

Zaccarelli, R.: Stream2segment: a tool to download, process and visualize event-based seismic waveform data (Version 2.7.3), GFZ Data Services., https://doi.org/10.5880/GFZ.2.4.2019.002, 2018.

Zaccarelli, R. and Weatherill, G.: eGSIM - a Python library and web application to select and test Ground Motion models, GFZ Data 430 Services., https://doi.org/https://doi.org/10.5880/GFZ.2.6.2023.007, 2020.

Zaccarelli, R., Bindi, D., Strollo, A., Quinteros, J., and Cotton, F.: Stream2segment: An Open-Source Tool for Downloading, Processing, and Visualizing Massive Event-Based Seismic Waveform Datasets, Seismological Research Letters, 90, 2028–2038, https://doi.org/10.1785/0220180314, 2019.