

Regional Oceanographic Database (BaRDO) for the Argentine Continental Shelf

Ana G. Baldoni¹, Graciela N. Molinari¹, Raúl A. Guerrero²

¹Instituto Nacional de Investigación y Desarrollo Pesquero (INIDEP). Paseo Victoria Ocampo N°1, Esollera Norte (B7602HSA), Mar del Plata, Argentina

²Laboratory example, city, postal code, country

Correspondence to: Ana Baldoni (baldoni@inidep.edu.ar)

Abstract. The Regional Oceanographic Data Base (BaRDO) contains 25,845 quality-controlled oceanographic stations acquired by INIDEP research vessels in the Southwest Atlantic. This paper describes the operability of the data management system, the characteristics and accuracy of the dataset, the quality-control procedures, and the main errors detected and corrected during the flagging process. In addition, we present information on the geographical and temporal distribution of the data, the evolution of the dataset in response to technological advances, and recommendations for its use. BaRDO contains two main data types: quasi-continuous CTD profiles (conductivity, temperature, and depth) and discrete, low-resolution OSD (Ocean Station Data) profiles. The majority of observations comprise temperature and salinity, while fluorometry, oxygen, and turbidity are also available when measured. Cruise listings and data access covering the period up to 2012 are provided at <https://catalogo.inidep.edu.ar/geonetwork/>.

1 Introduction

In the Southwest Atlantic, the total extension of the Argentine Continental Margin—comprising the continental shelf, slope, and rise, as well as the Malvinas Plateau and the Scotia Arc—covers an area of around 2×10^6 km² (Violante et al., 2014).

This extent was significantly increased after the 2017 recognition of the outer limits of the Argentine continental shelf, which added approximately 1.7×10^6 km² beyond 200 nautical miles (COPLA, 2017).

The Argentine Continental Shelf (ACS) is one of the world’s largest, spanning about 9.6×10^5 km². It extends north–south for about 2,400 km, from the Río de la Plata (35°30’ S) to Cape Horn (57° S), with an average width of 400 km.

The area is a highly productive marine ecosystem (Acha et al., 2004, 2018; Lutz et al., 2010; Diaz et al., 2018; Gil et al., 2019; Cepeda et al., 2024) and plays an important role in the regional heat and global carbon cycle (Bianchi et al., 2005, 2009; Kahl et al., 2017). A variety of fishery resources of economic significance (Villasante et al., 2015; Marrari et al, 2013; Alemany et al, 2009, 2021; Bogazzi et al., 2005) are primarily located along the coastal sector of the ACS, from the mouth of the Río de La Plata (34°S) to the southern tip of South America (55°S), including the Argentine-Uruguayan Common Fishing Zone (ZCP, between 34° - 39°30’ S).

30 Oceanographic surveys in the Southwest Atlantic began in the early 20th century with the German Antarctic expedition aboard R/V *Deutschland* (1911–1912), which operated in the Brazil–Malvinas Confluence región (around 38°S off the continental shelf, Schmid and Garzoli, 2009). Subsequent missions by R/V *Meteor* expedition (1925–1927), R/V *W. Scoresby* (1927–1932), and R/V *Discovery I and II* (1931–1936) made significant contributions to the oceanographic understanding of the ACS. In the 1960s, the Argentine government, in cooperation with the United Nations Development Programme (UNDP) and the

35 Food and Agriculture Organization (FAO), launched the Fishery Development Project. This initiative included eleven cruises under the *Pesquerías* program (1966–1969) (PDP, 1968–1971). The research developed as part of this project provided relevant data that contributed to a better understanding of the Argentine Sea’s fishery resources, including their spatiotemporal distribution, bioproductive capacity, and economic potential.

In 1977, the routine evaluations of fishery resources in the ACS were initiated, following the establishment of the National

40 Institute for Fisheries Research and Development (INIDEP) and the signing of international cooperation agreements with Japan (Japan Marine Fishery Resource Research Center – JAMARC) and Germany (Federal Research Center for Fisheries – BFAFi). The first cruises under this collaboration were carried out in 1978 aboard the R/V *Walter Herwig* (Germany) (Ciechomski, et.al. 1979) and R/V *Shinkai Maru* (Japan) (Cousseau, et al. 1979).

With the acquisition of its own research vessels—R/V *Dr. Eduardo Holmberg* (Japan, 1980), R/V *Cap. Oca Balda* (Germany,

45 1983), and the adaptation of a coastal fishing vessel later renamed R/V *Capitán Cánepa* (1979)—INIDEP began regular sampling of oceanographic variables, primarily associated with fisheries research. More recently, INIDEP acquired two modern fisheries and oceanographic vessels: R/V *Víctor Angelescu* in 2017 and R/V *Mar Argentino* in 2020, both designed and built to comply with rigorous technical standards.

Over the past 47 years, continuous operations of INIDEP research vessels have constituted the primary source of physical

50 oceanographic data for the region. The spatial distribution of the stations (Figure 1) illustrates the scope of this effort and the extensive coverage achieved across the Argentine Continental Shelf (ACS).

In 2005, the INIDEP Physical Oceanography group, with support from the Global Environment Facility (GEF) Patagonia Program, began developing an oceanographic database to provide a complete quality-controlled physical dataset of the Southwest Atlantic with special focus on the ACS region. The creation of the *Base Regional de Datos Oceanográficos* (BaRDO

55 - Regional Oceanographic DataBase) enabled the development of improved temperature and salinity climatologies (Baldoni et al, 2015) and provide a baseline information for oceanographic and ecosystem studies (Simionato et al., 2010; Delgado et al., 2014; Lomovasky et al, 2011; Kahl et al., 2017; Palma et al., 2020; Pisoni et al., 2020; Risoli et al., 2020; Temperoni et al, 2020; Temperoni et al., 2021;).

Even though BaRDO incorporates external data from public databases and individual researchers, this work specifically

60 describes the data structure and management system of the oceanographic stations exclusively collected by INIDEP between 1981 and 2024.




Figure 1: Geographical distribution of BaRDO stations carried out by INIDEP (ZCP: Argentine-Uruguayan Common Fishing Zone).

Comentado [U1]: AM_2



65 2 Data origin

At the time of submitting this paper, BaRDO holds and manages 25,845 quality-controlled oceanographic stations from 872 research cruises. Most (93%) of the stations were carried out onboard INIDEP R/Vs, while the rest were developed on small ships or fishing vessels, and a small proportion (less than 2%) were measured from the coast. The database comprises two distinct types of data: 93% of the stations were collected using quasi-continuous CTD profilers, the remaining 7% comes from

70 discrete water sample observations (OSD), primarily acquired before 1993. The annual distribution of oceanographic stations, by type of instrument – OSD, CTD - is shown in Figure 2. Data collected before 1999 were incorporated into the World Ocean Database (WOD- accession numbers 0089784, 0020559, 0115150, and 0143331) (Mishonov et al., 2024). During the first few years, all measurements correspond to OSD profiles; the first CTD was acquired in 1984, and with the incorporation of new equipment from 1993 onwards, the average number of stations per year increased from 193 to 981 until 2006. Since 2007, the average number of stations per year has been around 540, with a period of low activity between 2014 and 2017, during which the annual average dropped to 237 stations.

75

Comentado [U2]: AM_1



Comentado [U3]:

Comentado [U4R3]: AM_3

Figure 2: Number of yearly stations stored in BaRDO

Approximately 80% of the stations were conducted in shallow waters (< 200 m depth), with temperature and salinity measurements available in 98.5% and 97.4% of cases, respectively. Additional parameters such as fluorometry (32%), oxygen (2.4%), and turbidity (6%) were recorded at a smaller subset of stations.

2.1. OSD

The first measurements of physical variables were carried out in 1981 using Knudsen inversion bottles and initially constituted the only source of temperature and salinity data for fisheries studies. Temperature was measured with reversing thermometers, and salinity was determined using laboratory salinometers. However, there is a lack of information on the specific salinometers used and on the algorithms and standards used for salinity determination.

In 1984, with the deployment of the first CTD, bottle sampling became an alternative used only when the CTD was unavailable; consequently, the annual percentage of OSD profiles decreased significantly (Fig. 2) with a maximum of 187 stations in 1993. From 1984 onward, sampling was conducted using Niskin-type bottles, and salinity determinations were performed in the laboratory using Beckman and Tsurumi-Seiki salinometers between 1987 and 1994, applying different salinity algorithms and non-systematic use of seawater standards. Since then, a Guildline Autosol 8400B salinometer (accuracy ± 0.003 PSU; precision 0.0003 PSU), calibrated with IAPSO Standard Seawater (Ocean Scientific International OSIL, P106 to P167), has been used.

2.2. CTD

~~From 1984 to 1993, CTD measurements were carried out using a single ME Meerestechnik Elektronik instrument. The data obtained during this initial stage represent only 13% of the total dataset. This instrument remained in operation until 2010, and 40% of the data collected between 1993 and 2010 correspond to it. Furthermore, during this initial period, the CTD NBIII-III/V, although not part of INIDEP's equipment, was used in several cruises between 1993 and 1997 on loan from the SHN (National Hydrographic Service). Until 1993, the only CTD available was the ME Meerestechnik Elektronik instrument. This CTD remained operational until 2010, and the stations sampled with it represent 13% of the total dataset. Furthermore, between 1993 and 1997, the CTD NBIII-III/V, although not part of INIDEP's equipment, was used in several cruises on loan from the SHN (National Hydrographic Service).~~

The ME CTD system was gradually phased out as Sea-Bird Electronics (SBE) profilers became the operational standard. INIDEP progressively acquired different CTD models from this manufacturer: SBE 19 in 1993 (SN1268), 1995 (SN1683), 1996 (SN1806), and 2001 (SN3030); SBE 911plus (SN09P8073-0359) in 1994 and later in 2017 (SN09P63966-1045); SBE 25 (SN2542135-0412) in 2007; and finally, SBE 25plus (SN1219) in 2021.

Until 2017, water samples for CTD *in situ* calibration were collected using a Niskin bottle attached to an oceanographic cable and closed by a messenger. Since then, sampling with a rosette system (General Oceanic GO1015; SBE32; SBE55) has been used to improve the collection of water samples at defined depths.

Comentado [U5]: AR_1

115 The characteristics of each CTD model used and their operating periods are summarized in Table 1. Figure 3 shows the percentage of oceanographic stations carried out by each CTD model, along with the corresponding proportion of OSD profiles.

CTD MODEL		NBIII-III/V	ME	Citadel NV	SBE 19	SBE25	SBE25plus	SBE 911
Sampling rate [Hz]		30	10	1 to 15	2	2 to 8	0.5 to 8 RT 16	24
Range	C [S/m]	0 to 6.5/7.0	0 - 6	0 - 7	0 - 7	0 - 7	0-7	0 - 7
	T [°C]	-2 to - 32	- 2 to 32	-2 to +35	-5 to +35	-5 to +35	-5 to +35	-5 to +35
	P [db]	6500/6850	6000	500	Paine 680/ 3400; Digiquartz 6800	Strain gage 1000/2000	7000	Digiquartz 6800
Accuracy	C [S/m]	0.0005	0.001	0.0002	0.001	0.0003	0.0003	0.0003
	T [°C]	0.005-0.001	0.005	0.002	0.01	0.002	0.001	0.001
	P [% Full scale]	0.1 -0.02	0.25	0.2	0.25	0.1	0.1	0.015
Resolution	C [S/m]	0.0001	0.0001	0.00001	0.0001	0.00004	0.00004	0.00004
	T [°C]	0.0005	0.001	0.0001	0.001	0.0003	0.0003	0.0002
	P [% Full scale]	0.0015	0.0015	0.001	Paine 0.015 Digiquartz 0.001	0.015	0.002	0.001
Operational period		1993-1997	1984-2000	2010-2019	SN1268 1993-2007	SN2542135- 0412 2008-present	SN1219 2021-present	SN09P8073- 0359 1996-present
					SN1806 1996-present			SN09P63966- 1045 2017- present
					SN1683 1995-1996			
					SN3030 2001-present			

Table 1: Technical characteristics of CTD models.








Figure 3: Oceanographic data distribution by instrument type and model.

The largest share (57%) corresponds to the SBE19 model, followed by the ME (13%), which remained in use until 2000. The data were collected in real-time using a conducting oceanographic cable, except for 20% of the stations collected with SBE19 profilers and for all measurements from the Citadel NV, which were operated in internal recording mode.

To illustrate differences in the performance of CTD models, Figure 4 illustrates temperature and salinity profiles recorded by different SBE CTD models under two typical vertical stratification conditions over the ACS during the warm season.






Figure 4: Temperature and salinity profiles versus pressure from different CTD models: SBE19 (left) vs SBE9plus (right). Solid lines indicate the downcast and dashed lines indicate the upcast.

Temperature and salinity profiles from different CTD models: SBE19 (left) vs SBE9plus (right).

135

For SBE19 data, although a pump is employed to minimize sensor response lag, residual mismatches may result in spurious salinity and density signals at the zone of thermal gradient. In contrast, the SBE9 model—with higher sample rates, faster-response sensors, and a Temperature–Conductivity (TC) duct assembly ([Seabird Application Note 38](#))—produces less noisy salinity and density measurements. Some of these differences between CTD models can be resolved through appropriate signal processing; however, a significant number of flagged salinity data points should be expected at the thermocline level under stratification conditions, depending on the instrument used.

140

3 Data management system

Figure 5 illustrates the flow diagram developed to manage physical data measured onboard INIDEP research vessels, including their acquisition, storage, and availability for user access. The system was developed considering the specific working conditions onboard and its evolution over time. Since 1993, the significant increase in the number of oceanographic stations—associated with the incorporation of new CTDs—has led to a high demand for onboard technical personnel. Initially, this requirement was met by INIDEP-trained staff, although turnover rates were high. At that time, despite the availability of working protocols, the lack of automated storage systems for key variables, including position, bottom depth, and meteorological parameters on INIDEP vessels, together with the participation of many different operators, considerably increased the likelihood of human error. To address this issue, it became necessary to design an automated data acquisition process that incorporated navigation data and provided an organized structure to minimize data entry errors. The objective was to ensure accurate recording and transfer of information, and to enable the application of quality-control procedures for error identification and correction. With this aim, the SIAVO system (*Sistema Integral de Almacenamiento de Variables Oceanográficas* – Integral System for the Storage of Oceanographic Variables) was developed. SIAVO manages onboard data acquisition, processing, and storage of oceanographic data in an MS Access database. After each cruise, SIAVO exports the onboard database to a staging database for verification and basic quality control of the raw data. Once salinity correction (Section 3.2) and station profile quality control procedures (Section 3.3) have been completed, the final dataset is stored in BaRDO (Microsoft SQL Server) for further use and distribution to end users.




Figure 5: Data management system flow diagram

3.1 Database design and principles

Both SIAVO and BaRDO databases share a similar logical structure, organized around three main tables:

- **Cruise:** stores general information about each survey (vessel, year, cruise number).
- **Station:** compiles station-specific information (station number, cast, starting position and UTC date/time, time zone, bottom depth, temperature scale, instrument, and meteorological variables).
- **Profile:** contains the vertical distribution of the observed variables: temperature, salinity, oxygen, etc. Derived variables (e.g., potential temperature, density, buoyancy, sound velocity) can be computed dynamically by built-in functions based on EOS-80 algorithms (UNESCO, 1980, 1981; Fofonoff et al., 1983; Millero et al., 1981) integrated into the database for this purpose.

The structure of the database tables enables easy expansion to include new vessels, sampling instruments, and parameters, and facilitates data search with diverse criteria (spatial area, time, ship, project, instrument, etc.).

The general entity-relationship model of BaRDO is shown in Figure 6. Some of the tables included are: *Vessel*, *Cruise*, *Instrument*, *Data Source*, *Institutions*, *Project*, *Station*, and *Profile*. The identification key for each oceanographic station results from the unique field combination of *CruiseID*+ *Station number* + *Cast number*; relationships between the cruise, station, and profile tables are one-to-many. Each record in the Cruise table is related by the primary key *CruiseID* to several records in *Station* table, which equals to the number of casts in the cruise. Similarly, in the *Station* table, the composite primary key (*CruiseID*+ *Station number* + *Cast number*), becomes a foreign key in the Profile table, where measurement levels for each cast are stored.

Comentado [U7]: AR_4




Figure 6: Regional Oceanographic Data Base (BaRDO) entity relation model.

3.2 Data processing and calibration

Data acquisition was performed using calibration coefficients from the manufacturer's certificates (static calibration). For fluorescence measurements, a blank reading is taken before each oceanographic cruise, and an offset correction is applied to the data. This section describes the temperature monitoring and the corrections applied to salinity data. Oxygen and turbidity data are reported exclusively using the manufacturer's coefficients.

CTD data were processed using Sea-Bird Data Processing software, available for free at seabird.com. In the case of non SBE instruments, the data were previously converted to an ASCII format and then incorporated into the standard Sea-Bird Data Processing software steps.

190 Obtaining accurate salinity estimates from CTD measurements requires extensive processing and multiple corrections to account for sensor response characteristics (McTaggart et al., 2010). The routines and parameters depend on the CTD model, with their final selection determined by factors such as water column stratification, lowering speed, sea state, and the time allowed for surface stabilization. However, in highly stratified waters and depending on the CTD model used, it is not possible to eliminate spikes in the profile, even after adjusting the parameter values in each routine.

195 For calibration purposes, it is important to note that manufacturer-provided CTD calibrations were limited, as shown in Table 2, largely due to the cost and bureaucratic challenges associated with temporary exports. Consequently, sensor stability between calibrations has been monitored over time by comparing paired instruments/sensors, paying particular attention to temperature sensors, since no *in situ* calibrations were applied during processing.

CTD Model	Serial Number		Calibration dates
ME	-		- 1984
NB III/V	-		1976 -1989
SBE 19	1268		Jan 1993 -Dec 1997
	1806		Nov 1995 -Aug 2010
	1683		Nov 1994
	3030		Nov 2000 -Jan 2011
Citadel RV	2275		Mar 2010
	SBE3-Temp	SBE4-Cond	
SBE 25 SBE 911plus SBE 25plus	4727	3330	Jul 2007- Oct 2014
	1689	1381	Nov 1994 - Jan 2001 - Dec 2023
	1691	1382	Nov 1994 - Dec 2010 - Feb 2024
	6210	4660	Jun 2017
	6214	4682	Jun 2017 - Feb 2024
	6218	4684	Jun 2017
	6604	5065	May 2021

CTD Model	Serial Number		Calibration date
ME	-		-1984
NB III/V	-		1976-1989
SBE 19	1268		Jan 1993 -Dec 1997
	1806		Nov 1995 -Aug 2010
	1683		Nov 1994
	3030		Nov 2000 -Jan 2011

Citadel-RV	2275		Mar-2010
	SBE3-Temp	SBE4-Cond	
SBE-25 SBE-911plus SBE-25plus	4727	3330	Jul-2007 – Oct-2014
	1689	1381	Nov-1994 – Jan-2001
	1691	1382	Nov-1994 – Dec-2010
	6210	4660	Jan-2017
	6214	4682	
	6218	4684	
	6604	5065	May-2021

Comentado [U8]: AR_7; AM_5

Table 2: Manufacturer calibration dates by instrument.

3.2.1. Temperature

Monitoring of temperature sensors between manufacturer calibrations is shown in box plots of temperature differences in Figure 7. The boxes represent the interquartile range (Q1–Q3), the solid lines indicate the median, the crosses denote the mean, and the whiskers extend to the minimum and maximum values, excluding outliers.

Until 2017, sampling was carried out using CTDs with a single pair of sensors; therefore, temperature sensor monitoring was only performed when paired instruments were available. These comparisons were made between: ME vs SBE 19 (SN: 1268 and 1806); different SBE 19s (SN: 1268, 1806, 3030); SBE 911plus (SN: 1689, 1691, 6214) vs SBE 19 (SN: 1268, 1806, 3030) and SBE 25 (SN: 4727) vs SBE 19s (SN: 1806 and 3030) (Figure 7a). From then on, it was possible to optimize the control for modular sensors mounted as primary and secondary sensors on the same SBE 911plus CTD (SN: 4727, 1689, 1691, 6210, 6214, 6218, and 2230) (Figure 7b).

It's important to note that, when working in shallow waters (mostly < 200 m), even within homogeneous layers, the accuracy of estimated differences is inherently limited due to their high natural variability. In addition, when sensors are mounted on different CTD fish, their relative position on the carousel may introduce further uncertainty. Even taking these factors into account, the maximum temperature differences calculated between distinct instruments remain below ± 0.02 °C, whereas comparisons between sensors mounted on the same fish show differences of less than ± 0.005 °C.




Figure 7: Temperature differences comparisons between different paired CTD models (a) and different sensors mounted in the same SBE 911plus fish (b)

3.2.2. Salinity

225 In the case of conductivity sensors, instrumental drift represents a more significant problem when CTDs are not regularly
 calibrated by the manufacturer to ensure stability and accuracy. To mitigate this, strict protocols are followed to keep the
 conductivity cells clean and uncontaminated, and a systematic salinity sampling program is implemented for subsequent
 adjustments. Comparisons between bottle-sample salinities and CTD-derived measurements enable the detection and
 correction of errors due to sensor drift or calibration offsets. Salinity samples for in situ calibration have been collected since
 230 1987, and the methods and instruments used to measure them have evolved (see Section 2.1).

These water samples for salinity correction are collected in the most stable part of the water column; however, this condition
 is not met at all stations. Additionally, given that most measurements are conducted in waters shallower than 200 m, salinity

samples are often collected at a single pressure level. Consequently, only a limited number of salinity samples are available per cruise for calibration purposes, and in most cases, a temporal analysis by instrument is performed.

235 Salinity corrections are based on a linear adjustment using the least squares method. The fitting equation and its basic statistics - correlation coefficient, standard error of the regression, and number of observations- are stored in BaRDO (not shown), along with the type of analysis performed -by cruise or by instrument over a defined period.

Figure 8 follows the same box-plot format as Figure 7 and shows regression standard errors by instrument, to assess the accuracy of different CTDs' salinity correction models and inform users about the precision of the reported salinity values.

240 The lowest regression standard errors are observed for the SBE 911 and SBE 25 CTD models (<0.005). The highest errors are found for the ME CTD, reflecting the limited availability of bottle data for corrections, the use of different salinometers, and the scarcity of calibration standards. For the NV instrument records, the greater dispersion is mainly associated with its use in shallow, low-salinity coastal waters ($\approx 70\%$ at depths of less than 25 m). Within the SBE19 group, error magnitudes vary among individual instruments. Unit SN1806 exhibits the highest mean error (~ 0.01) and the largest standard deviation during
245 the period before 2010 (SBE19_1806a in Figure 8), whereas after that date (SBE19_1806b in Figure 8) the values fall below 0.005. This behavior may be explained by the original configuration of this CTD, which included a pack of six batteries and an associated pump that, during some cruises, was replaced by a higher-power pump. This change likely affected pump performance, causing it to operate more slowly or intermittently and thereby degrading data quality. Although it is not possible to determine the exact period during which the instrument operated with the high-consumption pump, since 2010, the CTD
250 has been modified to include a pack of nine batteries, allowing the use of both pump models.

255




Figure 8: Standard error from salinity regression analysis by instrument.

3.3 Quality-control

Quality-control (QC) procedures described here have been developed in accordance with the IOC (International Oceanographic Commission) recommendations (IOC, 1993; UNESCO-IOC, 2010). QC routines are run on individual stations and cruise groups. The controls are classified as: station data (QC0), profile data (QC1) and climatological comparisons (QC2). The quality-control codes assigned are listed in Table 3.

Comentado [U9]: AR_10; AM_6

Flag	Quality	Description
0	NoQC done	They have not yet been quality-controlled.
1	Good data	The data passes all quality control processes. Good data.
2	Inconsistent data	The data is inconsistent with other data. The data are probably good, although some features are present with uncertain validity.
3	Doubtful data	Suspect data in which unusual, and probably erroneous, features are observed.
4	Bad data	Erroneous values are observed.
5	Changed	The data have been changed. The original values (before the change) are preserved in the database.
6 - 7	Reserved	Flags 6 - 7 are reserved for future use.
8	Out of climatology	The data is anomalous compared with local climatology.
9	QC flag missing	Flag 9 data indicate that the element is missing.

Table 3: Data quality codes.

QC0 is performed within the SIAVO environment on station data, verifying both the identification fields (vessel name, cruise number, station number, position, and date/time) and the associated meteorological information. The operator may accept or modify the assigned quality-control flag and correct the data as needed. When a variable is modified, the original value is saved, and the field is marked as “changed” (QC=5), and all quality-control checks associated with the changed field are rerun using the new value. This QC0 level includes routines to check data format, date/time, sequential station numbers, ship’s speed between stations, global and regional ranges (cruise, station, east number, latitude/longitude, depth, and meteorological data), and the consistency between the bottom depth and the maximum depth of the measurement.

The QC1 and QC2 level control groups are associated with profile observations in each oceanographic station. This task is performed using the Data Quality Cruise Editor (QCEd) software (original version 1.5-<http://www.nodc.noaa.gov/GTSPP/software/qced/index.html>) provided by the Global Temperature-Salinity Profile Program (GTSPP / NODC / NOAA).

The program performs a suite of automated data quality tests to detect constant profiles, spikes, gradients, and density inversions when both temperature and salinity are available, or temperature inversions when only temperature is present. It displays “trouble lights” to alert the operator to questionable data. At this stage, only QC flags can be edited; observed temperature or salinity values cannot be modified. Thresholds implemented by QCEd V1.5 are summarized in Table 4, with

gradient thresholds expressed in units per dbar.

Comentado [U10]: AR_13

ROUTINE	Temperature [°]	Salinity	Density [kg m⁻³] [kg/m3]
Spike	2,0	0,3	
Surface/Bottom Spikes	10,0	5,0	
Gradient	10,0	5,0	
Inversion			> 0,1

Comentado [U11]: AM_7

300 Table 4: Thresholds of QC routines.


First, automatic quality controls are executed. Then, an analyst conducts a visual examination to validate or manually adjust the flags based on overall data consistency. Regarding modifications to automatic flagging, it is important to note that if data pass the thresholds set by automatic control, no changes are made. The original flag is retained even when analysts may consider the data suspicious. When in doubt, analysts adopt this conservative approach to avoid incorrectly flagging good data as suspicious. This protocol minimizes subjective flagging, ensuring uniform criteria consistent with the current thresholds across the entire dataset.

4 Results

4.1 Spatial and temporal coverage of the database

310 In Figure 9, the geographical coverage of INIDEP oceanographic stations displays a sampling strategy directly linked to the evaluation of specific fishery resources. The observational effort is focused on the continental shelf, within the 200 m isobath. Most stations are located in the Argentine–Uruguayan Common Fishing Zone (box A) and the San Jorge Gulf (box B), which together account for 64% of the stations in the database. Data from latitudes south of 47°S were especially sparse. Temporal coverage of data - inside graphs - was also uneven, as sampling was related to the months of stock evaluation mainly for red shrimp (*Pleoticusmuelleri*) and Argentine hake (*Merluccius hubbsi*). Both species are monitored in box B in January, while from October to December, the hake hubbsi biomass is estimated in box A. Overall, the temporal distribution of total dataset of observations across the ACS (Figure 9, bottom right-hand corner) is relatively homogeneous, with higher coverage percentages in November and January, while June and April are somewhat less well sampled.

Comentado [U12]: AM_8






Figure 9: Geographical and monthly distribution of BaRDO stations.

4.2 Results of the quality control

Stations flagged as inconsistent, doubtful, or poor-quality represent less than 6% of the total. This condition is primarily influenced by the instrument type, time of year, sampling region (stratified or non-stratified profiles), and water-column depth. The flagged levels represent only 0.07 % of the total number of temperature observations and 0.31 % of salinity observations.

Figure 10 shows, for each month, the percentage of total sampled levels relative to the complete dataset (black dots), together with the percentage of flagged temperature and salinity levels relative to the total number of observations in that month. Figure 10 represents the relationship between the percentage of total data collected each month and the corresponding percentage of flagged temperature and salinity data with respect to the sampled data in each month. The highest proportion of flagged



levels relative to the total number of observations occurs in February and November, mainly in temperature in November and in salinity in February. On the other hand, during cold months (June to October), when the vertical stratification substantially

Comentado [U13]: AM_8

Comentado [U14]: AR_12

decreases the percentage of flagged levels relative to the total number of observations is considerably lower than during the warm months., the percentage of levels marked is less than the total % of levels for each month.

Comentado [U15]: AR_11; AM_9



Comentado [U16]: AR_12

Figure 10: Monthly percentage of sampled data and proportion of flagged ones within each month.

340 Considering the different instruments, the highest proportion of flagged levels is associated with the SBE 19, which accounts for 57% of the stations (Fig. 3) and 75.1% of all flagged levels. In contrast, the SBE 9plus, which represents 10% of the stations (Fig. 3), accounts for only 6.6% of the flagged levels. To illustrate the types of flags present in the dataset, Figure 11 shows typical stratified profiles over the continental shelf, with flagged points (crosses) identified during the quality-control. The

spiky salinity is to be expected across these intense thermoclines, and it will be considered that not all the suspicious data has been marked with the established thresholds. In the case of climatological tests (QC2 level), comparison with global climatology (Levitus, 2005) does not yield reliable results for the region due to the limited number of observations used in its development. Therefore, based on knowledge of the local distribution of properties, most automatic “inconsistent” flags were discarded.




Figure 11. Quality control flags in a stratified profile

5 Data availability

The dataset covering the period up to 2012 is published through the institutional GeoNetwork catalogue maintained by the Instituto Nacional de Investigación y Desarrollo Pesquero (INIDEP). The CTD dataset is openly accessible at <https://doi.org/10.47193/ctd.inidep.1984-2012.v1> (Baldoni, 2026), and the discrete water sample observations are available at <https://doi.org/10.47193/bottle.temp-sal.1969-2012.v1> (Baldoni, 2026a). The DOIs resolve to the exact versions of the datasets

Comentado [U17]: AM_10

used in this publication. Both datasets are provided in CSV format under the Creative Commons Attribution 4.0 International (CC BY 4.0) license.

Work is currently ongoing to publish the extended dataset covering the period up to 2020. Data from the most recent five years are currently subject to restricted access.

6 Summary and perspectives

This paper introduces the physical oceanographic dataset collected by INIDEP over the past 47 years. The organization of these data within BaRDO, an updated database, has improved accessibility and facilitated the use of ACS data, a region of high environmental, biogeochemical, and economic significance. This resource has already supported numerous scientific studies and is expected to advance understanding of the physical and biogeochemical variability of this marine environment. All data records include an associated quality flag. It should be noted that, in the thermocline, some salinity spikes and density inversions may remain unflagged due to the thresholds applied. To identify all potentially doubtful values, a new dataset version could be generated using more stringent thresholds (e.g., density inversions $<- 0.01 \text{ kg m}^{-3}$ and salinity spikes of 0.03). The development of a new regional climatology incorporating the present dataset would improve future quality-control procedures by providing more reliable reference fields for assessing temporal and spatial consistency at annual, seasonal, and monthly scales.

It should also be noted that the lack of regular CTD calibration under controlled conditions may affect overall data accuracy, particularly given the challenges of conducting field calibration in shallow, highly variable waters. This limitation is partially mitigated by careful cleaning and maintenance of the instruments, complemented by rigorous adjustment using water samples.

Following delayed-mode corrections and checks, the accuracy of salinity is estimated at approximately 0.03, while temperature measurements, based on paired instruments, achieve accuracies better than 0.01–0.005 °C depending on the CTD model.

Acknowledgements

We thank all those who have participated in INIDEP research cruises over the years, including scientists, technicians, vessel crews, and especially the staff of the Physical Oceanography Department. Their work and dedication enabled the compilation of the data that now form the Regional Oceanographic Database (BaRDO) presented here. We also gratefully acknowledge

Enzo Mastroliberto and Pablo Rosales for their technical support in the publication and dissemination of the dataset through the institutional GeoNetwork catalogue.

References

- Acha, E., Mianzan, H., Guerrero, R., Favero, M., and Bava, J.: Marine fronts at the continental shelves of austral South America. *J. Mar. Syst.* 44, 83–105. doi: 10.1016/j.jmarsys.2003.09.005, 2004.
- Acha, E., Ehrlich, M., Muelbert, J., Pájaro, M., Bruno, D., Machinandarena, L., and Cadaveira, M.: Ichthyoplankton Associated to the Frontal Regions of the Southwestern Atlantic. M. S. Hoffmeyer et al. (eds.), *Plankton Ecology of the Southwestern Atlantic*. doi: 10.1007/978-3-319-77869-3_11, 2018.
- Alemaný, D., Rico, M. R., Lagos, N., Martos, P., Mendiolar, M., and Carozza, C.: Temporal evolution of diversity, abundance and structure of the coastal fish assemblage in ‘El Rincón’ area (39° S–41° 30' S), Argentina. *Marine and Fishery Sciences (MAFIS)*, 34(2), 143–180. doi: 10.47193/mafis.3422021010602, 2021.
- Alemaný, D., Acha, E.M., and Iribarne, O.: The relationship between marine fronts and fish diversity in the patagonian shelf large marine ecosystem. *J Biogeogr.* 36 (11): 2111–2124, 2009.
- Baldoni, A.; Molinari, G.; Reta, R., y Guerrero, R.: Atlas de temperatura y salinidad de la Plataforma Continental en el Atlántico Sudoccidental: períodos cálido y frío. Mar del Plata: Instituto Nacional de Investigación y Desarrollo Pesquero INIDEP. 85 p., 2015.
- Baldoni, A.: Datos CTD - Campañas INIDEP 1984–2012 [data set], <https://doi.org/10.47193/ctd.inidep.1984-2012.v1>, 2026.
- Baldoni, A.: Datos discretos de temperatura y salinidad - 1969 – 2012 [data set], <https://doi.org/10.47193/bottle.temp-sal.1969-2012.v1>, 2026a.
- Bianchi, A., Bianucci, L., Piola, A., Ruiz Pino, D., Schloss, I., and Poisson, A.: Vertical stratification and air–sea CO₂ fluxes in the Patagonian shelf. *J. Geophys. Res.* 110:C07003. doi: 10.1029/2004JC002488, 2005.
- Bianchi, A., Ruiz Pino, D., Isbert Perlender, H., Osiroff, A., Segura, V., Lutz, V., Luz Clara, M., Balestrini, C., and Piola, A.: Annual balance and seasonal variability of sea–air CO₂ fluxes in the Patagonian Sea: their relationship with fronts and chlorophyll distribution. *J. Geophys. Res.* 114:C03018. doi: 10.1029/2008JC004854, 2009.
- Bogazzi, E., Baldoni, A., Rivas, A., Martos, P., Reta, R., Orenzan, J., Lasta, M. dell’Arciprete, P., and Werner, P. 2005: Spatial correspondence between areas of concentration of Patagonian scallop (*Zygochlamys patagonica*) and frontal systems in the southwestern Atlantic. *Fish. Oceanogr.* 14:5, 359–376. doi: 10.1111/j.1365-2419.2005.00340, 2009.
- Cepeda, G., Ehrlich, M., Deriso, C., Severo, A., Machinandarena, L., Cadaveira, M., Betti, P., Do Souto, M., Pantano, C., and Acha, M.: Zooplanktonic Crustacea and Ichthyoplankton of the Patagonian Shelf-Break Front. In book: The Patagonian Shelfbreak Front. doi: 10.1007/978-3-031-71190-9_4, 2024.

Ciechomsky, J., Ehrlich, M., Lasta, C., y Sánchez, R.: Campañas realizadas por el buque de investigación “WaltherHerwig” en el Mar Argentino, desde mayo hasta noviembre de 1978. Organización y reseña de datos básicos obtenidos. INIDEP, Mar del Plata, Contribución N° 374, 311 p., 1979.

Commission of the European Communities and Intergovernmental Oceanographic Commission: UNESCO- [IOC Manuals and guides No. 26: Manual of quality control procedures for validation of oceanographic data.](#), 436p, 1993.

COPLA (2017): *Outer limit of the Argentine continental shelf*. National Commission on the Outer Limit of the Continental Shelf (COPLA), Ministry of Foreign Affairs, Argentina. Available at: <https://www.argentina.gob.ar/cancilleria/copla>

Cousseau, M., Hansen, J., y Gru, D.: Campañas realizadas por el buque de investigación “Shinkai Maru” en el Mar Argentino, desde Abril de 1978 hasta abril de 1979. Organización y reseña de datos básicos obtenidos. INIDEP, Contribución N° 373, Mar del Plata, 625p., 1979.

Delgado, A., Jamet, C., Loisel, H., Vantrepotte, V., Perillo, G., and Piccolo, M. C.: Evaluation of the MODIS-Aqua Sea-Surface Temperature product in the inner and mid-shelves of southwest Buenos Aires Province, Argentina. *International Journal of Remote Sensing*. Volume 35, Issue 1doi: 10.1080/01431161.2013.870680, 2014.

Díaz, M., Marrari, M., Casa, V., Gattás, F., Pájaro, M., and Macchi, G.: Evaluating environmental forcing on nutritional condition of *Engraulis anchoita* larvae in a productive area of the Southwestern Atlantic Ocean. *Prog. Oceanogr.* 168, 13–22. doi: 10.1016/j.pocean.2018.09.007, 2018.

Fofonoff, N., and Millard, R.: Algorithms for computation of fundamental properties of seawater. UNESCO Tech. Pap. Mar. Sci. 44 1-53, 1983.

Gil, M., Giarratano, E., Barros, V., Bortolus, A., Codignotto, J., Delfino Schenke, Góngora, M., Lovrich, G., Monti, A., Pascual, M., Rivas, A., and Tagliorette, A.: Southern Argentina: The Patagonian Continental Shelf. *World Seas: An Environmental Evaluation*. Ed. Shepard, C. Elsevier Academic Press Inc; 1; 2019; 783-811, 2019.

Kahl, L., Bianchi, A., Osiroff, A., Ruiz Pino, D., and Piola, A.: Distribution of sea-air CO₂ fluxes in the Patagonian Sea: Seasonal, biological and thermal effects, *Continental Shelf Research*, Volume 143, Pages 18-28, ISSN 0278-4343, doi: 10.1016/j.csr.2017.05.011, 2017.

Locarnini, RA, AV Mishonov, JI Antonov, TP Boyer, and HE Garcia, 2006. *World Ocean Atlas 2005, Volume 1: Temperature*. S. Levitus, Ed. NOAA Atlas NESDIS 61, U.S. Gov. Printing Office, Washington, D.C., 182 pp https://repository.library.noaa.gov/view/noaa/1126/noaa_1126_DS1.pdf

Levitus, S. Ed. *World Ocean Atlas 2005*. Locarnini, R., Mishonov, A., Antonov, J., Boyer, T., García, H. Volume 1: *Temperature*. Amato, J., Locarnini, R., Boyer, T., Mishonov, A., García, H. Volume 2: *Salinity*. NOAA Atlas NESDIS 62, U.S. Government Printing Office, Washington, D.C., 182 p., 2005.

Lomovasky, B.; Baldoni, A.; Ribeiro, P.; Lasta, M.; Campodónico, S., and Iribarne, O.: Exploring the causes of differences in growth rate of the Patagonian scallop *Zygochlamys patagonica* along their SW Atlantic distribution range, *Journal of Sea Research*. Volume 66, Issue 2, 162–171. doi: 10.1016/j.seares.2011.05.010, 2011.

Comentado [U18]: AM_12

- Lutz, V., Segura, V., Dobliotti, A., Gagliardini, D., Bianchi, A., and Balestrini, C.: Primary production in the Argentine Sea during spring estimated by field and satellite models. *J. Plankton Res.* 32, 181–195. doi: 10.1093/plankt/fbp117, 2010.
- Marrari, M., Signorini, S., Mc Clain, C., Pájaro, M., Martos, P., Viñas, M. D., Hansen, J., Dimauro, R., Cepeda, G., and Buratti, C.: Reproductive success of the Argentine anchovy, *Engraulis anchoita*, in relation to environmental variability at a mid-shelf front (Southwestern Atlantic Ocean). *Fish. Oceanogr.* 22, 247–261. doi: 10.1111/fog.12019, 2013.
- Mc Taggart, K., Johnson, G., Johnson, M., Delahoyde, F., and Swift, J.: Notes on CTD/O2 data acquisition and processing using Seabird hardware and software (as available), in *GO-SHIP Repeat Hydrography Manual: A Collection of Expert Reports and Guidelines*, eds E. M. Hood, C. L. Sabine, and B. M. Sloyan (IOCCP), 1–10, 2010.
- Millero, F., Poisson, A., Chen, C. T., Bradshaw, A., and Schleicher, K.: Background papers and supporting data on the International Equation of State of Seawater, 1980. *Unesco technical papers in marine science* N°38 –1981, 192 p. <http://unesdoc.unesco.org/images/0004/000473/047363eb.pdf>, 1981.
- Mishonov AV, TP Boyer, OK Baranova, CN Bouchard, S Cross, HE Garcia, RA Locarnini, CR Paver, JR Reagan, Z Wang, D Seidov, AI Grodsky, JG Beauchamp: *World Ocean Database 2023*. C. Bouchard, Technical Ed., NOAA Atlas NESDIS 97, 206 pp., doi.org/10.25923/z885-h264, 2024.
- Palma, E., Matano, R., Tonini, M., Martos, P., and Combes, V.: Dynamical analysis of the oceanic circulation in the Gulf of San Jorge, Argentina, *Journal of Marine Systems*, Volume 203, 2020, 103261, ISSN 0924-7963, doi:10.1016/j.jmarsys.2019.103261, 2020.
- Pisoni, J., Glembocky, N., Romero, S., and Tonini, M.: Internal solitary waves from L-band SAR over the Argentine inner Patagonian shelf, *Remote Sensing Letters*, 11:6, 525–534, doi: 10.1080/2150704X.2020.1736725, 2020.
- Proyecto de Desarrollo Pesquero: Datos y resultados de las campañas Pesquerías. 1968–1971. Mar del Plata. Publicación. Serie informes técnicos. p.v. vol.10/ I al XI.
- Risoli, M., Baldoni, A., Gimenez, J., and Lomovasky, B.: Age and growth variability of the yellow clam *Mesodesmumactroides* Reeve, 1854 in two populations of Argentina: implications under climate change. *Canadian Journal of Zoology*, 98, 481 – 494.
- Simionato, C., Luz Clara Tejedor, M., Campetella, C., Guerrero, R., and Moreira, D.: Patterns of sea surface temperature variability on seasonal to sub-annual scales at and offshore the Río de la Plata estuary. *Cont. Shelf Res.* 30 (19), 1983–1997, ISSN 0278-4343, doi: 10.1016/j.csr.2010.09.012, 2020, 2010.
- Schmid, C., and Garzoli, S.: New observations of the spreading and variability of the Antarctic Intermediate Water in the Atlantic. *Journal of Marine Research*. 67. 815–843, doi:10.1357/002224009792006151, 2009.
- Temperoni, B., Massa, A., Martos, P., Marrari, M.: Seasonal and spatial variability in condition of age-0+ Argentine hake *Merluccius hubbsi* Marini, 1933, in the San Jorge Gulf (Argentina): A bottom-up perspective. *Fisheries oceanography*, 29 (6), 597–611, 2020.
- Temperoni, B., Luz Clara, M., Berghoff, C., Derisio, C., and Massa, A.E.: The effect of physical and biological variables upon condition of *Merluccius hubbsi* (age-0+) of the northern stock (argentine shelf, SW Atlantic Ocean), *Journal of Marine Systems*, 224, 103620, ISSN 0924-7963, doi:10.1016/j.jmarsys.2021.103620, 2021.

Comentado [U19]: AM_1;

UNESCO: Tenth report of the Joint Panel on Oceanographic Tables and Standards. UNESCO Tech. Pap. Mar. Sci. No. 36, 25 p. , 1980.

480 UNESCO: International oceanographic tables. UNESCO Tech. Pap. Mar. Sci. No. 39, 111 p., 1981.

UNESCO: Algorithms for computation of fundamental properties of seawater.UNESCOTech. Pap. Mar. Sci. No. 44, 53p. , 1983.

UNESCO-IOC. GTSPP Real-Time Quality Control Manual, First Revised Edition. (IOC Manuals and Guides No. 22, Revised Edition.) (IOC/2010/MG/22Rev.) 145 p. [https://www.ncei.noaa.gov/sites/default/files/2020-11/GTSPP%20Real-](https://www.ncei.noaa.gov/sites/default/files/2020-11/GTSPP%20Real-Time%20Quality%20Control%20Manual.pdf)

485 [Time%20Quality%20Control%20Manual.pdf](https://www.ncei.noaa.gov/sites/default/files/2020-11/GTSPP%20Real-Time%20Quality%20Control%20Manual.pdf) , 2010.

Villasante, S., Macho, G., De Rivero, J. I., Divovich, E., Zylich, K., Harper, S., Zeller, D., and Pauly, D.: Reconstruction of Marine Fisheries Catches in Argentina (1950–2010). Working Paper #2015-50, Fisheries Centre, University of British Columbia: Vancouver, 2015.

Violante, R., Paterlini, C., Marcolini, S., Costa, I., Cavalotto, J., Laprida, C., Dragani, W., García Chaporí, N., Watanabe, S.,

490 Totah, V., Rovere, E., and Osterrieth, M.: The Argentine continental shelf: Morphology, sediments, processes and evolution since the last glacial maximum. Geological Society Memoir. 41(1):55-68, 2014.

Villasante, S., Macho, G., Isusu de Rivero, J., Divovich, E., Zylich, K., Harper, S., Zeller, D., and Pauly, D.: Reconstruction of marine fisheries catches in Argentina (1950–2010). Working Paper Series #50. Fisheries Centre- University of British Columbia, Canada, 2015.

Comentado [U20]: AR_10; AM_6